



# FCC RF Test Report

**APPLICANT** : ZTE CORPORATION  
**EQUIPMENT** : LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone  
**BRAND NAME** : ZTE  
**MODEL NAME** : Z971  
**FCC ID** : SRQ-Z971  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on Dec. 29, 2016 and testing was completed on Feb. 13, 2017. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China**



# TABLE OF CONTENTS

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 5

    1.5 Modification of EUT ..... 6

    1.6 Testing Location ..... 6

    1.7 Applicable Standards..... 6

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7**

    2.1 Descriptions of Test Mode ..... 7

    2.2 Test Mode ..... 7

    2.3 Connection Diagram of Test System ..... 8

    2.4 Support Unit used in test configuration and system ..... 9

    2.5 EUT Operation Test Setup ..... 9

    2.6 Measurement Results Explanation Example..... 9

**3 TEST RESULT ..... 10**

    3.1 6dB Bandwidth Measurement ..... 10

    3.2 Peak Output Power Measurement ..... 14

    3.3 Power Spectral Density Measurement ..... 15

    3.4 Conducted Band Edges and Spurious Emission Measurement ..... 22

    3.5 Radiated Band Edges and Spurious Emission Measurement ..... 31

    3.6 AC Conducted Emission Measurement..... 35

**4 LIST OF MEASURING EQUIPMENT..... 40**

**5 UNCERTAINTY OF EVALUATION..... 41**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. RADIATED SPURIOUS EMISSION**

**APPENDIX C. DUTY CYCLE PLOTS**

**APPENDIX D. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.50 dB at 46.490 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.36 dB at 0.466 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

## 1.2 Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone
<b>Brand Name</b>	ZTE
<b>Model Name</b>	Z971
<b>FCC ID</b>	SRQ-Z971
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0 + EDR Bluetooth v4.0 LE/Bluetooth v4.1 LE/Bluetooth v4.2 LE
<b>IMEI Code</b>	Conducted: 863727030004422 Radiation: 863727030004604 Conduction: 863727030004471
<b>HW Version</b>	Z971HW1.0
<b>SW Version</b>	Z971V1.0.0B07
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	40
<b>Carrier Frequency of Each Channel</b>	40 Channel(37 hopping + 3 advertising channel)
<b>Maximum Output Power to Antenna</b>	2.85 dBm (0.0019 W) for Bluetooth v4.0 LE 13.40 dBm (0.0219 W) for Bluetooth v4.2 LE
<b>Antenna Type / Gain</b>	IFA Antenna with gain 1.20 dBi
<b>Type of Modulation</b>	Bluetooth LE : GFSK



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.	
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-KS	CO01-KS

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH03-SZ	565805

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Data Rate / Modulation	
		GFSK	
		1Mbps	
		Bluetooth v4.0 LE RF Output Power	Bluetooth v4.2 LE RF Output Power
Ch00	2402MHz	2.45 dBm	12.86 dBm
Ch19	2440MHz	2.85 dBm	13.40 dBm
Ch39	2480MHz	1.42 dBm	11.48 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.


### 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)
<b>Remark:</b> For Radiated TCs, The tests were performed with Adapter, Earphone and USB Cable.	

## 2.3 Connection Diagram of Test System

### <Bluetooth LE Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
5.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2m	N/A
6.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 5.8 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.8 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB Bandwidth Measurement

##### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.


For Bluetooth v4.0

#### 6 dB Bandwidth Plot on Channel 00



Date: 19.JAN.2017 06:44:57


#### 6 dB Bandwidth Plot on Channel 19



Date: 19.JAN.2017 06:57:23



### 6 dB Bandwidth Plot on Channel 39



Date: 19.JAN.2017 07:00:14

### For Bluetooth v4.2


### 6 dB Bandwidth Plot on Channel 00



Date: 19.JAN.2017 07:13:06




6 dB Bandwidth Plot on Channel 19



Date: 19.JAN.2017 07:23:55

6 dB Bandwidth Plot on Channel 39



Date: 19.JAN.2017 07:31:52

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Power Spectral Density


Test data refers to Appendix A.



### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


For Bluetooth v4.0

PSD 100kHz Plot on Channel 00



Date: 13.FEB.2017 16:40:45


PSD 100kHz Plot on Channel 19



Date: 13.FEB.2017 16:45:56




PSD 100kHz Plot on Channel 39



Date: 13.FEB.2017 16:48:50

For Bluetooth v4.2


PSD 100kHz Plot on Channel 00



Date: 13.FEB.2017 18:27:07




PSD 100kHz Plot on Channel 19



Date: 13.FEB.2017 18:39:40

PSD 100kHz Plot on Channel 39




Date: 13.FEB.2017 18:46:36




### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

For Bluetooth v4.0

PSD 3kHz Plot on Channel 00




PSD 3kHz Plot on Channel 19






PSD 3kHz Plot on Channel 39



Date: 19.JAN.2017 07:00:36

For Bluetooth v4.2


PSD 3kHz Plot on Channel 00



Date: 19.JAN.2017 07:13:35




PSD 3kHz Plot on Channel 19



Date: 19.JAN.2017 07:24:20

PSD 3kHz Plot on Channel 39



Date: 19.JAN.2017 07:32:08

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges Plots


For Bluetooth v4.0

#### Low Band Edge Plot on Channel 00



Date: 13.FEB.2017 16:41:57

#### High Band Edge Plot on Channel 39




Date: 13.FEB.2017 16:49:37




For Bluetooth v4.2

Low Band Edge Plot on Channel 00



Date: 13.FEB.2017 18:29:23

High Band Edge Plot on Channel 39



Date: 13.FEB.2017 18:47:17




### 3.4.6 Test Result of Conducted Spurious Emission Plots

For Bluetooth v4.0


#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

##### GFSK Channel 00




#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

##### GFSK Channel 00






Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 13.FEB.2017 16:46:27


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 13.FEB.2017 16:46:35




### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 13.FEB.2017 16:49:54

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 13.FEB.2017 16:50:02




For Bluetooth v4.2

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 00



Date: 13.FEB.2017 18:29:55


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 00



Date: 13.FEB.2017 18:30:03




### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 13.FEB.2017 18:42:56


### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 13.FEB.2017 18:44:37




### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 13.FEB.2017 18:49:32

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 13.FEB.2017 18:51:09



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




### 3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

### 3.5.7 Duty Cycle

Please refer to Appendix C.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~28°C
Test Engineer :	Jeff Yao	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS  
 Condition : FCC PART 15C LISN-L-20151024 LINE  
 mode : Mode 1  
 IMEI : 863727030004471  
 : #16

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.152	41.10	-24.77	65.87	30.20	0.51	10.39	QP
2	0.152	37.00	-18.87	55.87	26.10	0.51	10.39	Average
3	0.466	40.52	-16.06	56.58	30.10	0.23	10.19	QP
4 *	0.466	32.22	-14.36	46.58	21.80	0.23	10.19	Average
5	1.242	36.52	-19.48	56.00	26.10	0.23	10.19	QP
6	1.242	29.02	-16.98	46.00	18.60	0.23	10.19	Average
7	2.273	37.48	-18.52	56.00	27.10	0.18	10.20	QP
8	2.273	29.88	-16.12	46.00	19.50	0.18	10.20	Average
9	2.487	38.59	-17.41	56.00	28.21	0.18	10.20	QP
10	2.487	30.99	-15.01	46.00	20.61	0.18	10.20	Average
11	15.552	37.27	-22.73	60.00	26.50	0.26	10.51	QP
12	15.552	28.57	-21.43	50.00	17.80	0.26	10.51	Average



Test Mode :	Mode 1	Temperature :	23~28°C
Test Engineer :	Jeff Yao	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS  
 Condition : FCC PART 15C LISN-N-20151024 NEUTRAL

mode : Mode 1  
 IMEI : 863727030004471  
 : #16

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.150	37.09	-28.91	66.00	26.40	0.30	10.39	QP
2	0.150	29.59	-26.41	56.00	18.90	0.30	10.39	Average
3	0.161	35.78	-29.65	65.43	25.10	0.30	10.38	QP
4	0.161	24.58	-30.85	55.43	13.90	0.30	10.38	Average
5	0.474	33.11	-23.34	56.45	22.60	0.32	10.19	QP
6 *	0.474	25.91	-20.54	46.45	15.40	0.32	10.19	Average
7	1.032	30.66	-25.34	56.00	20.10	0.37	10.19	QP
8	1.032	22.46	-23.54	46.00	11.90	0.37	10.19	Average
9	2.409	31.68	-24.32	56.00	21.10	0.38	10.20	QP
10	2.409	23.48	-22.52	46.00	12.90	0.38	10.20	Average
11	9.352	30.71	-29.29	60.00	20.10	0.28	10.33	QP
12	9.352	20.81	-29.19	50.00	10.20	0.28	10.33	Average



### **3.6.6 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.6.7 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.6.8 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Jan. 17, 2017~ Feb. 13, 2017	Aug. 08, 2017	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Jan. 17, 2017~ Jan. 18, 2017	Jan. 19, 2017	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Jan. 19, 2017~ Feb. 13, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Jan. 17, 2017~ Jan. 18, 2017	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Jan. 19, 2017~ Feb. 13, 2017	Jan. 18, 2018	Conducted (TH01-KS)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	May 07, 2016	Jan. 17, 2017~ Feb. 08, 2017	May 06, 2017	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz	May 07, 2016	Jan. 17, 2017~ Feb. 08, 2017	May 06, 2017	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Jan. 17, 2017~ Feb. 08, 2017	May 06, 2017	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 21, 2016	Jan. 17, 2017~ Feb. 08, 2017	May 20, 2017	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	May 07, 2016	Jan. 17, 2017~ Feb. 08, 2017	May 06, 2017	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	Jan. 17, 2017~ Feb. 08, 2017	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 11, 2016	Jan. 17, 2017~ Feb. 08, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 11, 2016	Jan. 17, 2017~ Feb. 08, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 06, 2017	Jan. 17, 2017~ Feb. 08, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jan. 17, 2017~ Feb. 08, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 17, 2017~ Feb. 08, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 17, 2017~ Feb. 08, 2017	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Apr. 29, 2016	Jan. 24, 2017	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Jan. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Jan. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Jan. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
---	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
---	-------



## **Appendix A. Conducted Test Results**

**Bluetooth Low Energy (for Bluetooth v4.0 LE)**

Test Engineer:	Ivan Zhang	Temperature:	24~25	°C
Test Date:	2017/01/17~2017/02/13	Relative Humidity:	50~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.05	0.67	0.50	Pass
BLE	1Mbps	1	19	2440	1.05	0.68	0.50	Pass
BLE	1Mbps	1	39	2480	1.05	0.68	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	2.45	30.00	1.20	3.65	36.00	Pass
BLE	1Mbps	1	19	2440	2.85	30.00	1.20	4.05	36.00	Pass
BLE	1Mbps	1	39	2480	1.42	30.00	1.20	2.62	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
**(Reporting Only)**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.04	2.19
BLE	1Mbps	1	19	2440	2.04	2.52
BLE	1Mbps	1	39	2480	2.04	1.27

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	2.29	-12.58	1.20	8.00	Pass
BLE	1Mbps	1	19	2440	2.54	-12.12	1.20	8.00	Pass
BLE	1Mbps	1	39	2480	1.07	-13.54	1.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

**Bluetooth Low Energy (for Bluetooth v4.2 LE)**

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.05	0.68	0.50	Pass
BLE	1Mbps	1	19	2440	1.05	0.68	0.50	Pass
BLE	1Mbps	1	39	2480	1.05	0.68	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	12.86	30.00	1.20	14.06	36.00	Pass
BLE	1Mbps	1	19	2440	13.40	30.00	1.20	14.60	36.00	Pass
BLE	1Mbps	1	39	2480	11.48	30.00	1.20	12.68	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
**(Reporting Only)**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.04	12.62
BLE	1Mbps	1	19	2440	2.04	13.16
BLE	1Mbps	1	39	2480	2.04	11.30

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	12.85	-2.15	1.20	8.00	Pass
BLE	1Mbps	1	19	2440	13.21	-1.71	1.20	8.00	Pass
BLE	1Mbps	1	39	2480	11.41	-3.35	1.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



## Appendix B. Radiated Spurious Emission

For Bluetooth v4.0

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2367.225	47.18	-26.82	74	50.16	27.22	4.82	35.02	173	324	P	H
		2344.86	37.96	-16.04	54	41	27.19	4.82	35.05	173	324	A	H
	*	2402	89.25	-	-	92.1	27.29	4.86	35	173	324	P	H
	*	2402	88.21	-	-	91.06	27.29	4.86	35	173	324	A	H
		2383.92	46.68	-27.32	74	49.58	27.26	4.86	35.02	193	245	P	V
		2370.69	37.7	-16.30	54	40.6	27.26	4.86	35.02	193	245	A	V
	*	2402	88.09	-	-	90.94	27.29	4.86	35	193	245	P	V
	*	2402	87.16	-	-	90.01	27.29	4.86	35	193	245	A	V
BLE CH 19 2440MHz		2356.34	47.43	-26.57	74	50.44	27.22	4.82	35.05	195	321	P	H
		2357.88	37.93	-16.07	54	40.94	27.22	4.82	35.05	195	321	A	H
	*	2440	89.85	-	-	92.54	27.4	4.88	34.97	195	321	P	H
	*	2440	89.12	-	-	91.81	27.4	4.88	34.97	195	321	A	H
		2490.9	46.9	-27.10	74	49.4	27.5	4.92	34.92	195	321	P	H
		2492.37	37.83	-16.17	54	40.31	27.5	4.92	34.9	195	321	A	H
		2355.64	46.83	-27.17	74	49.84	27.22	4.82	35.05	152	221	P	V
		2374.26	37.72	-16.28	54	40.62	27.26	4.86	35.02	152	221	A	V
	*	2440	88.96	-	-	91.65	27.4	4.88	34.97	152	221	P	V
	*	2440	87.89	-	-	90.58	27.4	4.88	34.97	152	221	A	V
		2492.79	47.52	-26.48	74	50	27.5	4.92	34.9	152	221	P	V
		2497.55	38.26	-15.74	54	40.74	27.5	4.92	34.9	152	221	A	V



BLE CH 39 2480MHz	*	2480	87.34	-	-	89.89	27.47	4.9	34.92	245	319	P	H
	*	2480	86.42	-	-	88.97	27.47	4.9	34.92	245	319	A	H
		2483.8	47.1	-26.90	74	49.65	27.47	4.9	34.92	245	319	P	H
		2499.64	37.99	-16.01	54	40.47	27.5	4.92	34.9	245	319	A	H
	*	2480	87.36	-	-	89.91	27.47	4.9	34.92	158	222	P	V
	*	2480	86.46	-	-	89.01	27.47	4.9	34.92	158	222	A	V
		2489.2	46.81	-27.19	74	49.31	27.5	4.92	34.92	158	222	P	V
		2492.52	38.16	-15.84	54	40.64	27.5	4.92	34.9	158	222	A	V
Remark	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against Peak and Average limit line.</li> </ol>												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4804	40.16	-33.84	74	58.98	32.52	6.96	58.3	250	0	P	H
		4804	40.87	-33.13	74	59.69	32.52	6.96	58.3	250	0	P	V
BLE CH 19 2440MHz		4880	39.87	-34.13	74	58.88	32.66	6.99	58.66	250	0	P	H
		7320	48.08	-25.92	74	60.08	37.67	8.93	58.6	150	0	P	H
		4880	39.31	-34.69	74	58.32	32.66	6.99	58.66	250	0	P	V
BLE CH 39 2480MHz		7320	48.05	-25.95	74	60.05	37.67	8.93	58.6	150	0	P	V
		4960	41.16	-32.84	74	59.56	32.83	7.07	58.3	150	135	P	H
		7440	48.24	-25.76	74	59.85	37.69	9.15	58.45	175	260	P	H
		4960	41.76	-32.24	74	60.16	32.83	7.07	58.3	150	135	P	V
		7440	48.86	-25.14	74	60.47	37.69	9.15	58.45	175	260	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BLE LF		30	27.16	-12.84	40	31.24	26.7	1	31.78	100	80	P	H
		98.87	20.62	-22.88	43.5	32.15	18.7	1.38	31.61	-	-	P	H
		207.51	20.58	-22.92	43.5	34.35	15.97	1.57	31.31	-	-	P	H
		402.48	28.19	-17.81	46	31.37	25.94	2.12	31.24	-	-	P	H
		712.88	30.42	-15.58	46	31.51	27.6	2.75	31.44	-	-	P	H
		955.38	32.19	-13.81	46	30.87	29.52	3.15	31.35	-	-	P	H
		30	29.59	-10.41	40	33.67	26.7	1	31.78	-	-	P	V
		46.49	30.5	-9.50	40	42.74	18.5	1	31.74	120	300	P	V
		74.62	23.57	-16.43	40	39.99	14.1	1.14	31.66	-	-	P	V
		409.27	28.32	-17.68	46	31.64	25.79	2.12	31.23	-	-	P	V
		773.02	30.94	-15.06	46	31.92	27.35	2.91	31.24	-	-	P	V
		997.09	34.47	-19.53	54	32.34	30.34	3.18	31.39	-	-	P	V
Remark	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against limit line.</li> </ol>												



For Bluetooth v4.2

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2389.485	47.6	-26.4	74	50.47	27.29	4.86	35.02	150	228	P	H
		2365.44	37.66	-16.34	54	40.64	27.22	4.82	35.02	150	228	A	H
	*	2402	99.09	-	-	101.94	27.29	4.86	35	150	228	P	H
	*	2402	98.19	-	-	101.04	27.29	4.86	35	150	228	A	H
		2382.66	46.51	-27.49	74	49.41	27.26	4.86	35.02	150	264	P	V
		2334.255	37.89	-16.11	54	40.98	27.16	4.82	35.07	150	264	A	V
	*	2402	99.94	-	-	102.79	27.29	4.86	35	150	264	P	V
	*	2402	99.2	-	-	102.05	27.29	4.86	35	150	264	A	V
BLE CH 19 2440MHz		2343.32	46.74	-27.26	74	49.78	27.19	4.82	35.05	153	229	P	H
		2332.26	37.96	-16.04	54	41.05	27.16	4.82	35.07	153	229	A	H
	*	2440	100.63	-	-	103.32	27.4	4.88	34.97	153	229	P	H
	*	2440	99.75	-	-	102.44	27.4	4.88	34.97	153	229	A	H
		2493.35	47.04	-26.96	74	49.52	27.5	4.92	34.9	153	229	P	H
		2494.68	37.93	-16.07	54	40.41	27.5	4.92	34.9	153	229	A	H
		2328.48	47.19	-26.81	74	50.28	27.16	4.82	35.07	150	265	P	V
		2388.26	37.79	-16.21	54	40.66	27.29	4.86	35.02	150	265	A	V
	*	2440	100.38	-	-	103.07	27.4	4.88	34.97	150	265	P	V
	*	2440	99.45	-	-	102.14	27.4	4.88	34.97	150	265	A	V
		2495.59	46.92	-27.08	74	49.4	27.5	4.92	34.9	150	265	P	V
		2496.15	38.06	-15.94	54	40.54	27.5	4.92	34.9	150	265	A	V



BLE CH 39 2480MHz	*	2480	98.19	-	-	100.74	27.47	4.9	34.92	150	229	P	H
	*	2480	97.19	-	-	99.74	27.47	4.9	34.92	150	229	A	H
		2483.56	47.03	-26.97	74	49.58	27.47	4.9	34.92	150	229	P	H
		2483.52	38.49	-15.51	54	41.04	27.47	4.9	34.92	150	229	A	H
	*	2480	97.6	-	-	100.15	27.47	4.9	34.92	163	277	P	V
	*	2480	96.77	-	-	99.32	27.47	4.9	34.92	163	277	A	V
		2486.88	47.05	-26.95	74	49.6	27.47	4.9	34.92	163	277	P	V
		2491.24	38.05	-15.95	54	40.55	27.5	4.92	34.92	163	277	A	V
Remark	<p>3. No other spurious found.</p> <p>4. All results are PASS against Peak and Average limit line.</p>												



2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4804	40.16	-33.84	74	58.98	32.52	6.96	58.3	250	0	P	H
		4804	40.87	-33.13	74	59.69	32.52	6.96	58.3	250	0	P	V
BLE CH 19 2440MHz		4880	41.6	-32.40	74	60.61	32.66	6.99	58.66	250	0	P	H
		7320	47.58	-26.42	74	59.58	37.67	8.93	58.6	150	0	P	H
		4880	43.33	-30.67	74	62.34	32.66	6.99	58.66	250	0	P	V
BLE CH 39 2480MHz		7320	47.27	-26.73	74	59.27	37.67	8.93	58.6	150	0	P	V
		4960	43.56	-30.44	74	61.96	32.83	7.07	58.3	150	135	P	H
		7440	48.52	-25.48	74	60.13	37.69	9.15	58.45	175	260	P	H
		4960	42.11	-31.89	74	60.51	32.83	7.07	58.3	150	135	P	V
		7440	48.61	-25.39	74	60.22	37.69	9.15	58.45	175	260	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BLE LF		30.97	26.5	-13.50	40	31	26.28	1	31.78	110	200	P	H
		208.48	20.6	-22.90	43.5	34.32	16.02	1.57	31.31	-	-	P	H
		317.12	22.14	-23.86	46	32.01	19.55	1.94	31.36	-	-	P	H
		408.3	27.82	-18.18	46	31.12	25.81	2.12	31.23	-	-	P	H
		698.33	30.54	-15.46	46	31.66	27.61	2.75	31.48	-	-	P	H
		976.72	32.98	-21.02	54	31.23	29.94	3.18	31.37	-	-	P	H
		30	29.14	-10.86	40	33.22	26.7	1	31.78	-	-	P	V
		47.46	29.57	-10.43	40	42.4	17.9	1	31.73	100	50	P	V
		74.62	21.59	-18.41	40	38.01	14.1	1.14	31.66	-	-	P	V
		421.88	28.27	-17.73	46	31.78	25.51	2.22	31.24	-	-	P	V
		700.27	30.44	-15.56	46	31.47	27.7	2.75	31.48	-	-	P	V
		878.75	31.34	-14.66	46	31.38	28.33	3.03	31.4	-	-	P	V
Remark	3. No other spurious found. 4. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.




## Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth v4.0 LE	62.50	0.391	2.558	3kHz
Bluetooth v4.2 LE	62.50	0.391	2.558	3kHz




Bluetooth v4.0 LE



Date: 17.JAN.2017 03:32:54

Bluetooth v4.2 LE



Date: 17.JAN.2017 03:52:08