



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA/ LTE Multi-Mode Digital
Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z982
FCC ID : SRQ-Z982
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 07, 2017 and testing was completed on May 01, 2017. We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



Sporton International (KunShan) INC.
No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	30
3.6 AC Conducted Emission Measurement.....	34
3.7 Antenna Requirements.....	39
4 LIST OF MEASURING EQUIPMENT	40
5 UNCERTAINTY OF EVALUATION	41
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR740701C	Rev. 01	Initial issue of report	May 26, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.58 dB at 34.850 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.08 dB at 0.415 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA/ LTE Multi-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z982
FCC ID	SRQ-Z982
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/ Bluetooth v4.1 LE/Bluetooth v4.2 LE
IMEI Code	Conducted: 864650030004110 Radiation: 864650030004052 Conduction: 864650030003963
HW Version	Z982HW1.0
SW Version	Z982V1.0.0B01
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 17.52 dBm (0.0565 W) 802.11g : 22.13 dBm (0.1633 W) 802.11n HT20 : 20.28 dBm (0.1067 W) 802.11n HT40 : 20.63 dBm (0.1156 W)
Antenna Type / Gain	PIFA Antenna with gain 0.09 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	Sporton International (KunShan) INC.			
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH03-KS	CO01-KS	306251

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performed with Adapter, Earphone and USB Cable.	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	Earphone	Lenovo	LH102	N/A	N/A	Unshielded, 1.2m

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.8 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.8 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Start Xu







Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Start Xu

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz







Spurious Emission 2GHz~25GHz





Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Start Xu


WLAN 802.11b Channel 11**100kHz PSD reference Level****High Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Start Xu

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz






Spurious Emission 2GHz~25GHz





Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Start Xu


WLAN 802.11g Channel 06**100kHz PSD reference Level****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Start Xu

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Start Xu

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Start Xu

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Start Xu

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	03	Test Engineer :	Start Xu

WLAN 802.11n HT40 Channel 03


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Start Xu

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	09	Test Engineer :	Start Xu



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
Condition : FCC PART 15C LISN-L-161017-060103 LINE
mode : Mode 1
: 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.400	47.27	-10.59	57.86	36.80	0.27	10.20	QP
2 *	0.400	40.77	-7.09	47.86	30.30	0.27	10.20	Average
3	0.491	42.66	-13.48	56.14	32.20	0.27	10.19	QP
4	0.491	37.26	-8.88	46.14	26.80	0.27	10.19	Average
5	0.532	39.75	-16.25	56.00	29.29	0.27	10.19	QP
6	0.532	32.65	-13.35	46.00	22.19	0.27	10.19	Average
7	0.579	39.04	-16.96	56.00	28.60	0.26	10.18	QP
8	0.579	32.74	-13.26	46.00	22.30	0.26	10.18	Average
9	2.779	39.72	-16.28	56.00	29.30	0.21	10.21	QP
10	2.779	33.72	-12.28	46.00	23.30	0.21	10.21	Average
11	3.058	39.63	-16.37	56.00	29.20	0.21	10.22	QP
12	3.058	34.03	-11.97	46.00	23.60	0.21	10.22	Average
13	4.006	40.05	-15.95	56.00	29.60	0.21	10.24	QP
14	4.006	33.75	-12.25	46.00	23.30	0.21	10.24	Average
15	4.338	40.05	-15.95	56.00	29.60	0.21	10.24	QP
16	4.338	34.05	-11.95	46.00	23.60	0.21	10.24	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
 Condition : FCC PART 15C LISN-N-161017-060103 NEUTRAL
 Project : (FR) 740701
 mode : Mode 1
 : 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.415	52.17	-5.38	57.55	41.60	0.37	10.20	QP
2 *	0.415	43.47	-4.08	47.55	32.90	0.37	10.20	Average
3	0.466	46.17	-10.41	56.58	35.60	0.38	10.19	QP
4	0.466	36.87	-9.71	46.58	26.30	0.38	10.19	Average
5	0.549	47.16	-8.84	56.00	36.60	0.38	10.18	QP
6	0.549	37.86	-8.14	46.00	27.30	0.38	10.18	Average
7	0.601	42.76	-13.24	56.00	32.20	0.38	10.18	QP
8	0.601	34.16	-11.84	46.00	23.60	0.38	10.18	Average
9	0.665	40.16	-15.84	56.00	29.60	0.38	10.18	QP
10	0.665	31.86	-14.14	46.00	21.30	0.38	10.18	Average
11	1.049	41.19	-14.81	56.00	30.60	0.40	10.19	QP
12	1.049	32.89	-13.11	46.00	22.30	0.40	10.19	Average
13	1.242	41.19	-14.81	56.00	30.60	0.40	10.19	QP
14	1.242	32.49	-13.51	46.00	21.90	0.40	10.19	Average
15	1.593	41.69	-14.31	56.00	31.09	0.41	10.19	QP
16	1.593	33.19	-12.81	46.00	22.59	0.41	10.19	Average
17	1.790	42.20	-13.80	56.00	31.60	0.41	10.19	QP
18	1.790	33.80	-12.20	46.00	23.20	0.41	10.19	Average
19	2.055	42.20	-13.80	56.00	31.60	0.41	10.19	QP
20	2.055	33.80	-12.20	46.00	23.20	0.41	10.19	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4G) Link + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS
Condition : FCC PART 15C LISN-N-161017-060103 NEUTRAL

mode : Mode 1
: 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
21	2.487	42.81	-13.19	56.00	32.21	0.40	10.20	QP
22	2.487	33.91	-12.09	46.00	23.31	0.40	10.20	Average
23	2.707	42.91	-13.09	56.00	32.30	0.40	10.21	QP
24	2.707	33.91	-12.09	46.00	23.30	0.40	10.21	Average
25	3.140	42.92	-13.08	56.00	32.30	0.40	10.22	QP
26	3.140	34.22	-11.78	46.00	23.60	0.40	10.22	Average
27	3.509	43.92	-12.08	56.00	33.30	0.39	10.23	QP
28	3.509	35.22	-10.78	46.00	24.60	0.39	10.23	Average
29	4.247	44.23	-11.77	56.00	33.60	0.39	10.24	QP
30	4.247	35.23	-10.77	46.00	24.60	0.39	10.24	Average
31	4.574	44.23	-11.77	56.00	33.61	0.38	10.24	QP
32	4.574	35.23	-10.77	46.00	24.61	0.38	10.24	Average
33	5.390	44.82	-15.18	60.00	34.20	0.37	10.25	QP
34	5.390	36.22	-13.78	50.00	25.60	0.37	10.25	Average
35	5.929	45.21	-14.79	60.00	34.59	0.36	10.26	QP
36	5.929	36.21	-13.79	50.00	25.59	0.36	10.26	Average
37	6.698	44.81	-15.19	60.00	34.19	0.34	10.28	QP
38	6.698	35.91	-14.09	50.00	25.29	0.34	10.28	Average
39	7.566	44.82	-15.18	60.00	34.20	0.32	10.30	QP
40	7.566	35.82	-14.18	50.00	25.20	0.32	10.30	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	Apr. 22, 2016	Apr. 14, 2017~ Apr. 20, 2017	Apr. 21, 2017	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Apr. 14, 2017~ Apr. 20, 2017	Aug. 08, 2017	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Apr. 14, 2017~ Apr. 20, 2017	Jan. 19, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Apr. 14, 2017~ Apr. 20, 2017	Jan. 19, 2018	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 22, 2016	Apr. 27, 2017	Oct. 21, 2017	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Apr. 27, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Apr. 27, 2017	Nov. 22, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Apr. 27, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Apr. 27, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Oct. 19, 2016	Apr. 27, 2017	Oct. 18, 2017	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1000MHz / 32dB	Apr. 18, 2017	Apr. 27, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	1Ghz-18Ghz	Apr. 18, 2017	Apr. 27, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Oct. 13, 2016	Apr. 27, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 27, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 27, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 27, 2017	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	May 01, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	May 01, 2017	Oct. 13, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	May 01, 2017	Oct. 13, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	May 01, 2017	Oct. 13, 2017	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.6dB
--	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.5dB
--	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.7dB
--	-------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Start Xu	Temperature:	21~25	°C
Test Date:	2017/4/14~2017/4/20	Relative Humidity:	51~55	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.19	9.55	0.50	Pass
11b	1Mbps	1	6	2437	14.29	10.05	0.50	Pass
11b	1Mbps	1	11	2462	14.29	10.03	0.50	Pass
11g	6Mbps	1	1	2412	18.08	16.32	0.50	Pass
11g	6Mbps	1	6	2437	18.58	16.34	0.50	Pass
11g	6Mbps	1	11	2462	18.63	16.34	0.50	Pass
HT20	MCS0	1	1	2412	18.98	17.56	0.50	Pass
HT20	MCS0	1	6	2437	19.18	17.58	0.50	Pass
HT20	MCS0	1	11	2462	19.13	17.58	0.50	Pass
HT40	MCS0	1	3	2422	36.56	35.13	0.50	Pass
HT40	MCS0	1	6	2437	36.66	35.45	0.50	Pass
HT40	MCS0	1	9	2452	36.66	35.13	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.23	30.00	0.09	17.32	36.00	Pass
11b	1Mbps	1	6	2437	17.36	30.00	0.09	17.45	36.00	Pass
11b	1Mbps	1	11	2462	17.52	30.00	0.09	17.61	36.00	Pass
11g	6Mbps	1	1	2412	21.69	30.00	0.09	21.78	36.00	Pass
11g	6Mbps	1	6	2437	22.13	30.00	0.09	22.22	36.00	Pass
11g	6Mbps	1	11	2462	22.08	30.00	0.09	22.17	36.00	Pass
HT20	MCS0	1	1	2412	19.94	30.00	0.09	20.03	36.00	Pass
HT20	MCS0	1	6	2437	20.22	30.00	0.09	20.31	36.00	Pass
HT20	MCS0	1	11	2462	20.28	30.00	0.09	20.37	36.00	Pass
HT40	MCS0	1	3	2422	20.45	30.00	0.09	20.54	36.00	Pass
HT40	MCS0	1	6	2437	20.63	30.00	0.09	20.72	36.00	Pass
HT40	MCS0	1	9	2452	19.07	30.00	0.09	19.16	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.11	14.74
11b	1Mbps	1	6	2437	0.11	14.66
11b	1Mbps	1	11	2462	0.11	14.81
11g	6Mbps	1	1	2412	0.58	12.53
11g	6Mbps	1	6	2437	0.58	12.87
11g	6Mbps	1	11	2462	0.58	12.92
HT20	MCS0	1	1	2412	0.66	10.11
HT20	MCS0	1	6	2437	0.66	10.57
HT20	MCS0	1	11	2462	0.66	10.64
HT40	MCS0	1	3	2422	0.66	10.35
HT40	MCS0	1	6	2437	0.66	10.57
HT40	MCS0	1	9	2452	0.66	9.21

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-8.17	0.09	8.00	Pass
11b	1Mbps	1	6	2437	-7.26	0.09	8.00	Pass
11b	1Mbps	1	11	2462	-8.09	0.09	8.00	Pass
11g	6Mbps	1	1	2412	-12.39	0.09	8.00	Pass
11g	6Mbps	1	6	2437	-11.90	0.09	8.00	Pass
11g	6Mbps	1	11	2462	-9.25	0.09	8.00	Pass
HT20	MCS0	1	1	2412	-14.94	0.09	8.00	Pass
HT20	MCS0	1	6	2437	-13.80	0.09	8.00	Pass
HT20	MCS0	1	11	2462	-14.67	0.09	8.00	Pass
HT40	MCS0	1	3	2422	-16.81	0.09	8.00	Pass
HT40	MCS0	1	6	2437	-17.10	0.09	8.00	Pass
HT40	MCS0	1	9	2452	-17.22	0.09	8.00	Pass



Appendix B. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preampl	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2382.28	55.08	-18.92	74	54.93	31.16	5.45	36.46	311	60	P	H
		2389.95	44.05	-9.95	54	43.8	31.2	5.47	36.42	311	60	A	H
	*	2410	96.71	-	-	96.46	31.21	5.47	36.43	311	60	P	H
	*	2410	93.43	-	-	93.18	31.21	5.47	36.43	311	60	A	H
		2373.05	54.8	-19.20	74	54.65	31.16	5.45	36.46	100	117	P	V
		2386.57	44.24	-9.76	54	43.99	31.2	5.47	36.42	100	117	A	V
	*	2412	98.91	-	-	98.66	31.21	5.47	36.43	100	117	P	V
	*	2410	95.62	-	-	95.37	31.21	5.47	36.43	100	117	A	V
802.11b CH 06 2437MHz		2346.79	55.11	-18.89	74	55.16	31.09	5.41	36.55	368	139	P	H
		2385.92	43.98	-10.02	54	43.73	31.2	5.47	36.42	368	139	A	H
	*	2436	98.19	-	-	97.92	31.23	5.48	36.44	368	139	P	H
	*	2436	95.03	-	-	94.76	31.23	5.48	36.44	368	139	A	H
		2485.06	54.87	-19.13	74	54.56	31.27	5.51	36.47	368	139	P	H
		2485.84	43.96	-10.04	54	43.65	31.27	5.51	36.47	368	139	A	H
		2347.57	54.77	-19.23	74	54.82	31.09	5.41	36.55	100	107	P	V
		2389.17	44.03	-9.97	54	43.78	31.2	5.47	36.42	100	107	A	V
	*	2436	100.42	-	-	100.15	31.23	5.48	36.44	100	107	P	V
	*	2436	97.05	-	-	96.78	31.23	5.48	36.44	100	107	A	V
		2485.48	55.15	-18.85	74	54.84	31.27	5.51	36.47	100	107	P	V
		2484.88	43.9	-10.10	54	43.59	31.27	5.51	36.47	100	107	A	V



802.11b CH 11 2462MHz	*	2464	95.04	-	-	94.74	31.26	5.5	36.46	382	148	P	H
	*	2464	91.99	-	-	91.69	31.26	5.5	36.46	382	148	A	H
		2486.74	54.35	-19.65	74	54.04	31.27	5.51	36.47	382	148	P	H
		2486.56	43.93	-10.07	54	43.62	31.27	5.51	36.47	382	148	A	H
	*	2462	96.98	-	-	96.68	31.26	5.5	36.46	100	72	P	V
	*	2464	93.83	-	-	93.53	31.26	5.5	36.46	100	72	A	V
		2486.14	54.52	-19.48	74	54.21	31.27	5.51	36.47	100	72	P	V
		2483.68	43.99	-10.01	54	43.68	31.27	5.51	36.47	100	72	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		4824	45.2	-28.80	74	38.64	35.35	7.72	36.51	100	360	P	H
CH 01		4824	44.34	-29.66	74	37.78	35.35	7.72	36.51	100	360	P	V
2412MHz													
802.11b		4872	45.7	-28.30	74	39.16	35.31	7.76	36.53	100	360	P	H
CH 06		7308	48.49	-25.51	74	39.29	35.69	9.76	36.25	100	360	P	H
2437MHz		4872	46.41	-27.59	74	39.87	35.31	7.76	36.53	100	360	P	V
		7308	49.37	-24.63	74	40.17	35.69	9.76	36.25	100	360	P	V
802.11b		4926	47.35	-26.65	74	40.84	35.27	7.8	36.56	100	360	P	H
CH 11		7386	47.41	-26.59	74	38.09	35.74	9.86	36.28	100	360	P	H
2462MHz		4926	45.58	-28.42	74	39.07	35.27	7.8	36.56	100	360	P	V
		7386	47.13	-26.87	74	37.81	35.74	9.86	36.28	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2388.26	58.01	-15.99	74	57.76	31.2	5.47	36.42	346	136	P	H
		2389.95	45.73	-8.27	54	45.48	31.2	5.47	36.42	346	136	A	H
	*	2406	98.95	-	-	98.7	31.21	5.47	36.43	346	136	P	H
	*	2406	90.06	-	-	89.81	31.21	5.47	36.43	346	136	A	H
		2389.3	57.63	-16.37	74	57.38	31.2	5.47	36.42	400	38	P	V
		2389.95	45.17	-8.83	54	44.92	31.2	5.47	36.42	400	38	A	V
	*	2406	97.87	-	-	97.62	31.21	5.47	36.43	400	38	P	V
	*	2406	90.09	-	-	89.84	31.21	5.47	36.43	400	38	A	V
802.11g CH 06 2437MHz		2372.92	54.8	-19.20	74	54.65	31.16	5.45	36.46	387	86	P	H
		2385.4	44.31	-9.69	54	44.16	31.16	5.45	36.46	387	86	A	H
	*	2434	98.86	-	-	98.59	31.23	5.48	36.44	387	86	P	H
	*	2442	90.88	-	-	90.6	31.24	5.49	36.45	387	86	P	H
		2491.9	54.89	-19.11	74	54.56	31.29	5.52	36.48	387	86	P	H
		2484.22	44.32	-9.68	54	44.01	31.27	5.51	36.47	387	86	A	H
		2386.83	54.58	-19.42	74	54.33	31.2	5.47	36.42	380	44	P	V
		2385.01	44.64	-9.36	54	44.49	31.16	5.45	36.46	380	44	A	V
	*	2434	99.04	-	-	98.77	31.23	5.48	36.44	380	44	P	V
	*	2442	90.41	-	-	90.13	31.24	5.49	36.45	380	44	A	V
		2494.6	54.8	-19.20	74	54.47	31.29	5.52	36.48	380	44	P	V
		2486.2	44.36	-9.64	54	44.05	31.27	5.51	36.47	380	44	A	V



802.11g CH 11 2462MHz	*	2458	99.22	-	-	98.92	31.26	5.5	36.46	387	86	P	H
	*	2456	91.12	-	-	90.82	31.26	5.5	36.46	387	86	A	H
		2483.68	56.64	-17.36	74	56.33	31.27	5.51	36.47	387	86	P	H
		2483.56	44.8	-9.20	54	44.49	31.27	5.51	36.47	387	86	A	H
	*	2456	99.8	-	-	99.5	31.26	5.5	36.46	384	48	P	V
	*	2454	91.1	-	-	90.8	31.26	5.5	36.46	384	48	A	V
		2484.58	57.2	-16.8	74	56.89	31.27	5.51	36.47	384	48	P	V
		2483.501	45.07	-8.93	54	44.76	31.27	5.51	36.47	384	48	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g		4824	44.63	-29.37	74	38.07	35.35	7.72	36.51	100	360	P	H
CH 01		4824	44.47	-29.53	74	37.91	35.35	7.72	36.51	100	360	P	V
2412MHz													
802.11g		4872	45.69	-28.31	74	39.15	35.31	7.76	36.53	100	360	P	H
CH 06		7308	47.43	-26.57	74	38.23	35.69	9.76	36.25	100	360	P	H
2437MHz		4872	45	-29.00	74	38.46	35.31	7.76	36.53	100	360	P	V
		7308	48.24	-25.76	74	39.04	35.69	9.76	36.25	100	360	P	V
802.11g		4926	46.29	-27.71	74	39.78	35.27	7.8	36.56	100	360	P	H
CH 11		7386	48.22	-25.78	74	38.9	35.74	9.86	36.28	100	360	P	H
2462MHz		4926	45.71	-28.29	74	39.2	35.27	7.8	36.56	100	360	P	V
		7386	47.21	-26.79	74	37.89	35.74	9.86	36.28	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.56	55.16	-18.84	74	54.91	31.2	5.47	36.42	312	40	P	H
		2389.69	44.78	-9.22	54	44.53	31.2	5.47	36.42	312	40	A	H
	*	2406	95.76	-	-	95.51	31.21	5.47	36.43	312	40	P	H
	*	2404	87.99	-	-	87.74	31.21	5.47	36.43	312	40	A	H
		2376.69	54.46	-19.54	74	54.31	31.16	5.45	36.46	133	112	P	V
		2389.95	44.82	-9.18	54	44.57	31.2	5.47	36.42	133	112	A	V
	*	2406	96.09	-	-	95.84	31.21	5.47	36.43	133	112	P	V
	*	2406	88.18	-	-	87.93	31.21	5.47	36.43	133	112	A	V
802.11n HT20 CH 06 2437MHz		2317.67	54.91	-19.09	74	55.07	31.05	5.39	36.6	384	53	P	H
		2384.75	44.25	-9.75	54	44.1	31.16	5.45	36.46	384	53	A	H
	*	2442	94.61	-	-	94.33	31.24	5.49	36.45	384	53	P	H
	*	2434	86.73	-	-	86.46	31.23	5.48	36.44	384	53	A	H
		2494.6	55.69	-18.31	74	55.36	31.29	5.52	36.48	384	53	P	H
		2487.1	44.41	-9.59	54	44.1	31.27	5.51	36.47	384	53	A	H
		2388.26	54.49	-19.51	74	54.24	31.2	5.47	36.42	100	100	P	V
		2385.79	44.58	-9.42	54	44.33	31.2	5.47	36.42	100	100	A	V
	*	2442	97.32	-	-	97.04	31.24	5.49	36.45	100	100	P	V
	*	2442	89.24	-	-	88.96	31.24	5.49	36.45	100	100	A	V
		2483.56	54.76	-19.24	74	54.45	31.27	5.51	36.47	100	100	P	V
		2486.74	44.33	-9.67	54	44.02	31.27	5.51	36.47	100	100	A	V



802.11n HT20 CH 11 2462MHz	*	2454	95.04	-	-	94.74	31.26	5.5	36.46	336	136	P	H
	*	2468	86.59	-	-	86.29	31.26	5.5	36.46	336	136	A	H
		2493.16	55	-19.00	74	54.67	31.29	5.52	36.48	336	136	P	H
		2483.56	44.66	-9.34	54	44.35	31.27	5.51	36.47	336	136	A	H
	*	2456	96	-	-	95.7	31.26	5.5	36.46	154	88	P	V
	*	2454	87.89	-	-	87.59	31.26	5.5	36.46	154	88	A	V
		2489.62	55.51	-18.49	74	55.18	31.29	5.52	36.48	154	88	P	V
		2485.66	44.82	-9.18	54	44.51	31.27	5.51	36.47	154	88	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4824	44.85	-29.15	74	38.29	35.35	7.72	36.51	100	360	P	H
HT20													
CH 01		4824	44.58	-29.42	74	38.02	35.35	7.72	36.51	100	360	P	V
2412MHz													
802.11n		4872	46.29	-27.71	74	39.75	35.31	7.76	36.53	100	360	P	H
HT20		7308	48.24	-25.76	74	39.04	35.69	9.76	36.25	100	360	P	H
CH 06		4872	44.88	-29.12	74	38.34	35.31	7.76	36.53	100	360	P	V
2437MHz		7308	46.94	-27.06	74	37.74	35.69	9.76	36.25	100	360	P	V
802.11n		4926	46.12	-27.88	74	39.61	35.27	7.8	36.56	100	360	P	H
HT20		7386	48.17	-25.83	74	38.85	35.74	9.86	36.28	100	360	P	H
CH 11		4926	45.22	-28.78	74	38.71	35.27	7.8	36.56	100	360	P	V
2462MHz		7386	47.87	-26.13	74	38.55	35.74	9.86	36.28	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2389.3	58.48	-15.52	74	58.23	31.2	5.47	36.42	337	144	P	H
		2389.56	46.37	-7.63	54	46.12	31.2	5.47	36.42	337	144	A	H
	*	2410	93.09	-	-	92.84	31.21	5.47	36.43	337	144	P	H
	*	2410	85.08	-	-	84.83	31.21	5.47	36.43	337	144	A	H
		2499.52	49.64	-24.36	74	54.56	26.04	5.52	36.48	337	144	P	H
		2489.44	39.09	-14.91	54	44.01	26.04	5.52	36.48	337	114	A	H
		2389.3	59.5	-14.50	74	59.25	31.2	5.47	36.42	157	77	P	V
		2389.95	47.14	-6.86	54	46.89	31.2	5.47	36.42	157	77	A	V
	*	2412	94.94	-	-	94.69	31.21	5.47	36.43	157	77	P	V
	*	2410	86.96	-	-	86.71	31.21	5.47	36.43	157	77	A	V
		2487.82	49.92	-24.08	74	54.84	26.04	5.52	36.48	157	77	P	V
		2488.84	39.15	-14.85	54	44.07	26.04	5.52	36.48	157	77	A	V
802.11n HT40 CH 06 2437MHz		2349.65	54.82	-19.18	74	54.87	31.09	5.41	36.55	331	144	P	H
		2388.78	44.36	-9.64	54	44.11	31.2	5.47	36.42	331	144	A	H
	*	2446	91.89	-	-	91.61	31.24	5.49	36.45	331	144	P	H
	*	2436	82.78	-	-	82.51	31.23	5.48	36.44	331	144	A	H
		2485.72	54.43	-19.57	74	54.12	31.27	5.51	36.47	331	144	P	H
		2489.44	44.25	-9.75	54	43.92	31.29	5.52	36.48	331	144	A	H
		2387.74	55.27	-18.73	74	55.02	31.2	5.47	36.42	184	125	P	V
		2389.95	44.49	-9.51	54	44.24	31.2	5.47	36.42	184	125	A	V
	*	2442	94.32	-	-	94.04	31.24	5.49	36.45	184	125	P	V
	*	2440	85.46	-	-	85.18	31.24	5.49	36.45	184	125	A	V
		2489.2	54.91	-19.09	74	54.58	31.29	5.52	36.48	184	125	P	V
		2484.28	44.32	-9.68	54	44.01	31.27	5.51	36.47	184	125	A	V



802.11n HT40 CH 09 2452MHz		2359.53	49.18	-24.82	74	54.23	26.03	5.43	36.51	363	148	P	H
		2388.65	39.17	-14.83	54	43.82	26.3	5.47	36.42	363	148	A	H
	*	2440	91.37	-	-	91.09	31.24	5.49	36.45	363	148	P	H
	*	2442	83.39	-	-	83.11	31.24	5.49	36.45	363	148	A	H
		2488.54	55.23	-18.77	74	54.9	31.29	5.52	36.48	363	148	P	H
		2483.92	44.83	-9.17	54	44.52	31.27	5.51	36.47	363	148	A	H
		2385.79	50.2	-23.80	74	54.85	26.3	5.47	36.42	105	108	P	V
		2389.82	39.4	-14.60	54	44.05	26.3	5.47	36.42	105	108	A	V
	*	2440	94.9	-	-	94.62	31.24	5.49	36.45	105	108	P	V
	*	2440	86.8	-	-	86.52	31.24	5.49	36.45	105	108	A	V
		2486.8	55.34	-18.66	74	55.03	31.27	5.51	36.47	105	108	P	V
		2483.86	45.19	-8.81	54	44.88	31.27	5.51	36.47	105	108	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4842	45.53	-28.47	74	38.98	35.33	7.74	36.52	100	360	P	H
HT40		7266	47.47	-26.53	74	38.32	35.67	9.72	36.24	100	360	P	H
CH 03		4842	48.01	-25.99	74	41.46	35.33	7.74	36.52	100	360	P	V
2422MHz		7266	47.85	-26.15	74	38.7	35.67	9.72	36.24	100	360	P	V
802.11n		4872	45.43	-28.57	74	38.89	35.31	7.76	36.53	100	360	P	H
HT40		7308	47.72	-26.28	74	38.52	35.69	9.76	36.25	100	360	P	H
CH 06		4872	46.14	-27.86	74	39.6	35.31	7.76	36.53	100	360	P	V
2437MHz		7308	48.68	-25.32	74	39.48	35.69	9.76	36.25	100	360	P	V
802.11n		4902	45.43	-28.57	74	38.92	35.28	7.78	36.55	100	360	P	H
HT40		7356	47.11	-26.89	74	37.84	35.72	9.82	36.27	100	360	P	H
CH 09		4902	46.39	-27.61	74	39.88	35.28	7.78	36.55	100	360	P	V
2452MHz		7356	46.99	-27.01	74	37.72	35.72	9.82	36.27	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		34.85	30.34	-9.66	40	35.48	25.5	0.71	31.35	100	100	P	H
		46.49	23.81	-16.19	40	36.09	18.3	0.84	31.42	-	-	P	H
		95.96	20.85	-22.65	43.5	32.54	18.58	1.18	31.45	-	-	P	H
		192.96	23.91	-19.59	43.5	37.63	16.09	1.69	31.5	-	-	P	H
		454.86	26.47	-19.53	46	29.77	25.28	2.66	31.24	-	-	P	H
		852.56	32.26	-13.74	46	30.47	28.97	3.72	30.9	-	-	P	H
	!	34.85	34.42	-5.58	40	39.56	25.5	0.71	31.35	100	30	P	V
		46.49	30.64	-9.36	40	42.92	18.3	0.84	31.42	-	-	P	V
		57.16	28.62	-11.38	40	44.99	14.14	0.9	31.41	-	-	P	V
		323.91	26.2	-19.80	46	35.16	20.13	2.21	31.3	-	-	P	V
		444.19	26.11	-19.89	46	29.5	25.23	2.62	31.24	-	-	P	V
		955.38	30.3	-15.70	46	27.52	29.5	3.99	30.71	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.52	8.222	0.122	300Hz
802.11g	87.44	1.362	0.734	1kHz
802.11n HT20	85.91	1.272	0.786	1kHz
802.11n HT40	85.92	1.229	0.814	1kHz

802.11b






802.11g



802.11n20





802.11n40

