

# FCC RF Test Report

APPLICANT : ZTE CORPORATION  
EQUIPMENT : WCDMA Wireless Data Terminal  
BRAND NAME : ZTE  
MODEL NAME : ZM5202  
FCC ID : SRQ-ZM5202  
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)  
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jul. 15, 2013 and completely tested on Jul. 25, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL (SHENZHEN) INC.**

**No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.**



## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test .....	6
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	6
1.7 Testing Site .....	7
1.8 Applied Standards.....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System .....	10
2.3 Support Unit used in test configuration and system.....	10
2.4 Measurement Results Explanation Example .....	10
<b>3 TEST RESULT.....</b>	<b>11</b>
3.1 Conducted Output Power Measurement.....	11
3.2 Peak-to-Average Ratio .....	13
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	21
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	27
3.5 Band Edge Measurement.....	47
3.6 Conducted Spurious Emission Measurement.....	60
3.7 Field Strength of Spurious Radiation Measurement .....	76
3.8 Frequency Stability Measurement.....	90
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>97</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>98</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 21.82 dB at 5640.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



# 1 General Description

## 1.1 Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

## 1.2 Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

## 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA Wireless Data Terminal
Brand Name	ZTE
Model Name	ZM5202
FCC ID	SRQ-ZM5202
EUT supports Radios application	GPRS/EGPRS/WCDMA
HW Version	ZM5202-2.0.0
SW Version	BD_ZM5202V1.0.0B04
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 31.06 dBm GSM1900 : 28.39 dBm WCDMA Band V : 21.41 dBm WCDMA Band II : 21.71 dBm
<b>Antenna Type</b>	Fixed External Antenna
<b>Type of Modulation</b>	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink)

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GPRS850 GPRS class 8	GMSK	0.0511	0.04 ppm	244KGXW
Part 22	GPRS850 EDGE class 8	8PSK	0.0148	0.04 ppm	242KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0032	0.02 ppm	4M20F9W
Part 24	GPRS1900 GPRS class 8	GMSK	0.4417	0.03 ppm	246KGXW
Part 24	GPRS1900 EDGE class 8	8PSK	0.2011	0.03 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.0949	0.02 ppm	4M18F9W

## 1.7 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.			
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC/IC Registration No.</b>
	TH01-SZ	03CH01-SZ	OTA01-SZ	831040/4086F-1

## 1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GPRS850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GPRS1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GPRS 850	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
GPRS 1900	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>

**Note:** The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS (GMSK, 1 Tx slot) – CS1	31.06	30.95	30.93	28.18	28.38	28.39
GPRS (GMSK, 2 Tx slots) – CS1	29.49	29.39	29.38	26.66	26.83	26.84
EDGE (GMSK, 1 Tx slot) – MCS1	31.06	30.93	30.91	28.12	28.34	28.37
EDGE (GMSK, 2 Tx slots) – MCS1	29.50	29.38	29.37	26.63	26.79	26.83
EDGE (GMSK, 3 Tx slots) – MCS1	27.61	27.50	27.49	24.77	24.95	24.98
EDGE (GMSK, 4 Tx slots) – MCS1	26.53	26.42	26.40	23.63	23.82	23.83
EDGE (8PSK, 1 Tx slot) – MCS5	25.58	25.49	25.43	24.68	24.89	24.89
EDGE (8PSK, 2 Tx slots) – MCS5	23.57	23.47	23.46	22.68	22.87	22.90
EDGE (8PSK, 3 Tx slots) – MCS5	21.70	21.59	21.61	20.84	20.98	21.02
EDGE (8PSK, 4 Tx slots) – MCS5	25.08	25.00	24.97	24.19	24.35	24.38

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2Kbps	21.35	21.41	21.22	21.67	21.71	21.52

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
2.	Simulator Base Station	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	VOSTRO 1440	FCC DoC	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 7.5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 7.5 + 10 = 17.5 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### 3.1.4 Test Setup



### 3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GPRS850 (GPRS class 8)			GPRS850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	31.06	30.95	30.93	25.58	25.49	25.43	21.35	21.41	21.22
Conducted Power (Watts)	1.28	1.24	1.24	0.36	0.35	0.35	0.14	0.14	0.13

PCS Band									
Modes	GPRS1900 (GPRS class 8)			GPRS1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	28.18	28.38	28.39	24.68	24.89	24.89	21.67	21.71	21.52
Conducted Power (Watts)	0.66	0.69	0.69	0.29	0.31	0.31	0.15	0.15	0.14

**Note:** maximum burst average power for GPRS, and maximum average power for WCDMA.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
  - a. Set EUT in maximum power output.
  - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
  - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
  - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

### 3.2.4 Test Setup





### 3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GPRS1900 (GPRS class 8)			GPRS1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.21	0.21	0.21	2.73	2.79	2.87	2.88	3.32	2.68



### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GPRS 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	-----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 23.JUL.2013 13:46:10


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 23.JUL.2013 13:44:15



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 23.JUL.2013 13:47:16




Band :	GPRS 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	-----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 23.JUL.2013 13:53:58


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 23.JUL.2013 13:50:26



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 23.JUL.2013 13:51:48



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean 20.64 dBm  
 Peak 23.90 dBm  
 Crest 3.26 dB

10 % 1.64 dB  
 1 % 2.44 dB  
 .1 % 2.88 dB  
 .01 % 3.08 dB

Date: 22.JUL.2013 16:45:53

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1


Mean 20.82 dBm  
 Peak 24.75 dBm  
 Crest 3.93 dB

10 % 1.80 dB  
 1 % 2.76 dB  
 .1 % 3.32 dB  
 .01 % 3.64 dB

Date: 22.JUL.2013 16:46:17



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
 Mean 20.65 dBm  
 Peak 23.69 dBm  
 Crest 3.04 dB

10 % 1.60 dB  
 1 % 2.36 dB  
 .1 % 2.68 dB  
 .01 % 2.88 dB

Date: 22.JUL.2013 16:45:27

### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

$P_s$  (dBm) : Input power to substitution antenna.

$G_s$  (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

$R_t$  : The highest received signal in spectrum analyzer for EUT.

$R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup



**3.3.5 Test Result of ERP**

<b>GPRS850 (GPRS class 8) Radiated Power ERP</b>						
Horizontal Polarization						
<b>Frequency (MHz)</b>	<b>Rt (dBm)</b>	<b>Rs (dBm)</b>	<b>Ps (dBm)</b>	<b>Gs (dBd)</b>	<b>ERP (dBm)</b>	<b>ERP (W)</b>
824.20	-33.57	-48.12	0.00	-1.08	13.47	0.0223
836.40	-35.55	-48.28	0.00	-0.93	11.80	0.0151
848.80	-30.51	-48.35	0.00	-0.76	17.08	0.0511
Vertical Polarization						
<b>Frequency (MHz)</b>	<b>Rt (dBm)</b>	<b>Rs (dBm)</b>	<b>Ps (dBm)</b>	<b>Gs (dBd)</b>	<b>ERP (dBm)</b>	<b>ERP (W)</b>
824.20	-40.88	-47.97	0.00	-1.08	6.01	0.0040
836.40	-41.49	-48.01	0.00	-0.93	5.59	0.0036
848.80	-37.93	-48.05	0.00	-0.76	9.36	0.0086

<b>GPRS850 (EDGE class 8) Radiated Power ERP</b>						
Horizontal Polarization						
<b>Frequency (MHz)</b>	<b>Rt (dBm)</b>	<b>Rs (dBm)</b>	<b>Ps (dBm)</b>	<b>Gs (dBd)</b>	<b>ERP (dBm)</b>	<b>ERP (W)</b>
824.20	-38.85	-48.12	0.00	-1.08	8.19	0.0066
836.40	-41.25	-48.28	0.00	-0.93	6.10	0.0041
848.80	-35.90	-48.35	0.00	-0.76	11.69	0.0148
Vertical Polarization						
<b>Frequency (MHz)</b>	<b>Rt (dBm)</b>	<b>Rs (dBm)</b>	<b>Ps (dBm)</b>	<b>Gs (dBd)</b>	<b>ERP (dBm)</b>	<b>ERP (W)</b>
824.20	-45.93	-47.97	0.00	-1.08	0.96	0.0012
836.40	-46.97	-48.01	0.00	-0.93	0.11	0.0010
848.80	-43.53	-48.05	0.00	-0.76	3.76	0.0024



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-42.66	-48.12	0.00	-1.08	4.38	0.0027
836.40	-44.19	-48.28	0.00	-0.93	3.16	0.0021
846.60	-42.56	-48.35	0.00	-0.76	5.03	0.0032
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-49.95	-47.97	0.00	-1.08	-3.06	0.0005
836.40	-50.51	-48.01	0.00	-0.93	-3.43	0.0005
846.60	-49.88	-48.05	0.00	-0.76	-2.59	0.0006

3.3.6 Test Result of EIRP

GPRS1900 (GPRS class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-28.91	-51.88	0.00	1.96	24.93	0.3114
1880.00	-29.33	-52.99	0.00	2.00	25.66	0.3678
1909.80	-29.81	-54.28	0.00	1.98	26.45	0.4417
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-37.40	-52.13	0.00	1.96	16.69	0.0467
1880.00	-37.14	-53.17	0.00	2.00	18.03	0.0635
1909.80	-39.24	-54.13	0.00	1.98	16.87	0.0486

GPRS1900 (EDGE class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-31.49	-51.88	0.00	1.96	22.35	0.1719
1880.00	-33.13	-52.99	0.00	2.00	21.86	0.1535
1909.80	-33.22	-54.28	0.00	1.98	23.04	0.2011
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-41.52	-52.13	0.00	1.96	12.57	0.0181
1880.00	-40.41	-53.17	0.00	2.00	14.76	0.0299
1909.80	-43.47	-54.13	0.00	1.98	12.64	0.0184



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-35.81	-51.88	0.00	1.96	18.03	0.0636
1880.00	-35.81	-52.99	0.00	2.00	19.18	0.0828
1907.60	-36.49	-54.28	0.00	1.98	19.77	0.0949
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-44.76	-52.13	0.00	1.96	9.33	0.0086
1880.00	-44.16	-53.17	0.00	2.00	11.01	0.0126
1907.60	-46.30	-54.13	0.00	1.98	9.81	0.0096

## 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3\*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3\*RBW, peak detector, trace maximum hold.

### 3.4.4 Test Setup



3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GPRS850 (GPRS class 8)			GPRS850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	244.00	244.00	242.00	242.00	242.00	242.00
26dB BW (kHz)	318.00	318.00	318.00	290.00	288.00	296.00

PCS Band						
Modes	GPRS1900 (GPRS class 8)			GPRS1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	244.00	242.00	246.00	246.00	244.00	250.00
26dB BW (kHz)	312.00	314.00	300.00	306.00	304.00	316.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.16	4.18	4.20
26dB BW (MHz)	4.66	4.68	4.68

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.18	4.16
26dB BW (MHz)	4.68	4.68	4.68

### 3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


Band :	GPRS 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.JUL.2013 17:23:54


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.JUL.2013 17:19:02




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.JUL.2013 17:25:19


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.JUL.2013 17:20:27




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 22.JUL.2013 17:26:44

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 22.JUL.2013 17:21:52




Band :	GPRS 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.JUL.2013 23:34:04


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.JUL.2013 23:23:24




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.JUL.2013 23:28:41


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.JUL.2013 23:21:48




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 22.JUL.2013 23:26:55

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 22.JUL.2013 23:24:35




Band :	GPRS 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	-----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.JUL.2013 17:58:40


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.JUL.2013 17:53:49




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 22.JUL.2013 18:00:33


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 22.JUL.2013 17:55:19




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 22.JUL.2013 18:01:59

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 22.JUL.2013 17:56:48




<b>Band :</b>	GPRS 1900	<b>Test Mode :</b>	EDGE class 8 Link (8PSK)
---------------	-----------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.JUL.2013 22:49:43


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.JUL.2013 22:47:41




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date : 23.JUL.2013 21:51:14


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date : 22.JUL.2013 22:45:48




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 22.JUL.2013 22:54:47

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 22.JUL.2013 22:41:37




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 22.JUL.2013 15:33:42


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 22.JUL.2013 15:27:53




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 22.JUL.2013 15:34:11


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 22.JUL.2013 15:27:16




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 22.JUL.2013 15:32:55

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 22.JUL.2013 15:28:23






99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 22.JUL.2013 16:36:44


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 22.JUL.2013 16:32:02




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 22.JUL.2013 16:34:51

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 22.JUL.2013 16:33:22

## 3.5 Band Edge Measurement

### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly  $BW/100$ .
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13\text{dBm}$ .


### 3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GPRS850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-18.44dBm	Measurement Value :	-18.69dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 22.JUL.2013 17:35:53

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
  2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, -18.69dBm + 0.25dB = -18.44dBm

<b>Band :</b>	GPRS850	<b>Test Mode :</b>	GPRS class 8 Link (GMSK)
<b>Correction Factor :</b>	0.25dB	<b>Maximum 26dB Bandwidth :</b>	0.318MHz
<b>Band Edge :</b>	-18.87dBm	<b>Measurement Value :</b>	-19.12dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 22.JUL.2013 17:35:16

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	-0.06dB	Maximum 26dB Bandwidth :	0.296MHz
Band Edge :	-22.68dBm	Measurement Value :	-22.62dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 22.JUL.2013 23:36:15

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	-0.06dB	Maximum 26dB Bandwidth :	0.296MHz
Band Edge :	-23.91dBm	Measurement Value :	-23.85dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 22.JUL.2013 23:37:42

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-21.00dBm	Measurement Value :	-21.20dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 22.JUL.2013 18:11:04

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-21.09dBm	Measurement Value :	-21.29dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 22.JUL.2013 18:10:01

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-22.95dBm	Measurement Value :	-23.18dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 22.JUL.2013 22:58:45

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	GPRS1900	<b>Test Mode :</b>	EDGE class 8 Link (8PSK)
<b>Correction Factor :</b>	0.23dB	<b>Maximum 26dB Bandwidth :</b>	0.316MHz
<b>Band Edge :</b>	-25.42dBm	<b>Measurement Value :</b>	-25.65dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 22.JUL.2013 22:57:17

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	WCDMA Band V	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
<b>Correction Factor :</b>	-3.30dB	<b>Maximum 26dB Bandwidth :</b>	4.680MHz
<b>Band Edge :</b>	-32.87dBm	<b>Measurement Value :</b>	-29.57dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 22.JUL.2013 16:13:09

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-31.86dBm	Measurement Value :	-28.56dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 22.JUL.2013 16:12:43

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	WCDMA Band II	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
<b>Correction Factor :</b>	-3.30dB	<b>Maximum 26dB Bandwidth :</b>	4.680MHz
<b>Band Edge :</b>	-31.68dBm	<b>Measurement Value :</b>	-28.38dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 22.JUL.2013 16:43:51

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-30.55dBm	Measurement Value :	-27.25dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 22.JUL.2013 16:44:16

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

## 3.6 Conducted Spurious Emission Measurement

### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.


### 3.6.4 Test Setup



### 3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GPRS850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.JUL.2013 17:37:41


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.JUL.2013 17:38:45




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.JUL.2013 17:38:53

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 22.JUL.2013 17:39:01




Band :	GPRS850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 23.JUL.2013 00:04:57


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.JUL.2013 23:59:09




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 23.JUL.2013 00:00:50

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 23.JUL.2013 00:02:28




Band :	GPRS1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.JUL.2013 18:19:04


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.JUL.2013 18:13:44




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.JUL.2013 18:19:22


### Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 22.JUL.2013 18:19:30



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 22.JUL.2013 18:19:38




Band :	GPRS1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 23.JUL.2013 00:13:48


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.JUL.2013 22:28:18




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.JUL.2013 22:19:46


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 22.JUL.2013 22:21:16



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 22.JUL.2013 22:22:32




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.JUL.2013 16:18:13


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.JUL.2013 16:21:49




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.JUL.2013 16:23:03

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 22.JUL.2013 16:23:50




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.JUL.2013 16:30:09


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.JUL.2013 16:30:58




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.JUL.2013 16:26:14


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 22.JUL.2013 16:27:33



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 22.JUL.2013 16:28:13

## 3.7 Field Strength of Spurious Radiation Measurement

### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
=  $P(W) - [43 + 10\log(P)]$  (dB)  
=  $[30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
= -13dBm.
12. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
13. ERP (dBm) = EIRP - 2.15

### 3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

<b>Band :</b>	GPRS850	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)371503

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-39.71	-13	-26.71	-56.37	-40.36	0.57	3.37	H	Pass
2510	-41.03	-13	-28.03	-65.13	-43.26	0.78	5.16	H	Pass
3346	-59.16	-13	-46.16	-69.76	-62.80	0.87	6.66	H	Pass
4182	-58.46	-13	-45.46	-73.22	-63.05	0.97	7.71	H	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)371503

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-39.10	-13	-26.10	-52.66	-39.75	0.57	3.37	V	Pass
2510	-40.91	-13	-27.91	-63.00	-43.14	0.78	5.16	V	Pass
3346	-54.18	-13	-41.18	-66.01	-57.82	0.87	6.66	V	Pass
4182	-57.17	-13	-44.17	-72.39	-61.76	0.97	7.71	V	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)371503

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-40.80	-13	-27.80	-57.40	-41.45	0.57	3.37	H	Pass
2510	-40.79	-13	-27.79	-64.95	-43.02	0.78	5.16	H	Pass
3346	-57.22	-13	-44.22	-67.82	-60.86	0.87	6.66	H	Pass
4182	-58.87	-13	-45.87	-73.63	-63.46	0.97	7.71	H	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)371503

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-39.56	-13	-26.56	-53.10	-40.21	0.57	3.37	V	Pass
2510	-41.54	-13	-28.54	-63.55	-43.77	0.78	5.16	V	Pass
3346	-54.04	-13	-41.04	-65.87	-57.68	0.87	6.66	V	Pass
4182	-56.76	-13	-43.76	-71.98	-61.35	0.97	7.71	V	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)371503

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-49.02	-13	-36.02	-62.52	-55.76	1.28	8.02	H	Pass
5640	-42.09	-13	-29.09	-61.32	-50.51	1.58	10.00	H	Pass
7520	-52.26	-13	-39.26	-74.20	-62.58	1.78	12.10	H	Pass
9400	-55.56	-13	-42.56	-77.68	-66.34	2.22	13.00	H	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)371503

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-47.50	-13	-34.50	-62.53	-54.24	1.28	8.02	V	Pass
5640	-34.82	-13	-21.82	-55.18	-43.24	1.58	10	V	Pass
7520	-48.60	-13	-35.60	-70.85	-58.92	1.78	12.1	V	Pass
9400	-53.64	-13	-40.64	-77.26	-64.42	2.22	13	V	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)371503

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-54.15	-13	-41.15	-66.30	-60.89	1.28	8.02	H	Pass
5640	-44.23	-13	-31.23	-63.06	-52.65	1.58	10.00	H	Pass
7520	-53.56	-13	-40.56	-75.50	-63.88	1.78	12.10	H	Pass
9400	-55.70	-13	-42.70	-77.82	-66.48	2.22	13.00	H	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)371503

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-49.15	-13	-36.15	-64.18	-55.89	1.28	8.02	V	Pass
5640	-36.97	-13	-23.97	-56.82	-45.39	1.58	10	V	Pass
7520	-49.17	-13	-36.17	-71.42	-59.49	1.78	12.1	V	Pass
9400	-54.12	-13	-41.12	-77.74	-64.90	2.22	13	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)371503

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-57.20	-13	-44.20	-70.12	-57.85	0.57	3.37	H	Pass
2510	-49.63	-13	-36.63	-71.14	-51.86	0.78	5.16	H	Pass
3346	-61.51	-13	-48.51	-72.11	-65.15	0.87	6.66	H	Pass
4182	-58.92	-13	-45.92	-73.68	-63.51	0.97	7.71	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)371503

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-58.88	-13	-45.88	-69.51	-59.53	0.57	3.37	V	Pass
2510	-52.89	-13	-39.89	-71.74	-55.12	0.78	5.16	V	Pass
3346	-59.80	-13	-46.80	-71.63	-63.44	0.87	6.66	V	Pass
4182	-58.38	-13	-45.38	-73.60	-62.97	0.97	7.71	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)371503

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-53.19	-13	-40.19	-65.34	-59.93	1.28	8.02	H	Pass
5640	-55.86	-13	-42.86	-73.85	-64.28	1.58	10.00	H	Pass
7520	-54.10	-13	-41.10	-76.04	-64.42	1.78	12.10	H	Pass
9400	-55.81	-13	-42.81	-77.93	-66.59	2.22	13.00	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	49~52%
<b>Test Engineer :</b>	Gavin Zhang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)371503

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-52.40	-13	-39.40	-67.43	-59.14	1.28	8.02	V	Pass
5640	-57.00	-13	-44.00	-74.08	-65.42	1.58	10	V	Pass
7520	-53.23	-13	-40.23	-75.48	-63.55	1.78	12.1	V	Pass
9400	-53.19	-13	-40.19	-76.81	-63.97	2.22	13	V	Pass

## 3.8 Frequency Stability Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at  $-30^{\circ}\text{C}$ , the testing lowest temperature will be raised in  $10^{\circ}\text{C}$  step until the EUT can be turned on.

### 3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup





3.8.6 Test Result of Temperature Variation

Band :	GPRS 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	33	+0.04	37	+0.04	PASS
-20	31	+0.04	35	+0.04	
-10	-32	-0.04	-35	-0.04	
0	-33	-0.04	31	+0.04	
10	-34	-0.04	30	+0.04	
20	-35	-0.04	24	+0.03	
30	-32	-0.04	24	+0.03	
40	-34	-0.04	-25	-0.03	
50	-33	-0.04	26	+0.03	
60	-31	-0.04	-26	-0.03	
70	-32	-0.04	24	+0.03	
75	-34	-0.04	27	+0.03	

Note: The manufacturer declared that the EUT could work properly at temperature 75°C.



Band :	GPRS 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	64	+0.03	63	+0.03	PASS
-20	-62	-0.03	62	+0.03	
-10	-61	-0.03	62	+0.03	
0	59	+0.03	58	+0.03	
10	-58	-0.03	-53	-0.03	
20	-56	-0.03	-44	-0.02	
30	-54	-0.03	-47	-0.02	
40	-53	-0.03	-49	-0.03	
50	-55	-0.03	-53	-0.03	
60	-57	-0.03	-51	-0.03	
70	-54	-0.03	-56	-0.03	
75	-56	-0.03	59	+0.03	

Note: The manufacturer declared that the EUT could work properly at temperature 75°C.



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-20	-0.02	PASS
-20	-20	-0.02	
-10	-18	-0.02	
0	-19	-0.02	
10	-18	-0.02	
20	-15	-0.02	
30	17	+0.02	
40	-16	-0.02	
50	-18	-0.02	
60	-20	-0.02	
70	-19	-0.02	
75	-21	-0.02	

**Note:** The manufacturer declared that the EUT could work properly at temperature 75°C.



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-35	-0.02	PASS
-20	-35	-0.02	
-10	-34	-0.02	
0	-32	-0.02	
10	-33	-0.02	
20	-33	-0.02	
30	-35	-0.02	
40	-37	-0.02	
50	-36	-0.02	
60	-38	-0.02	
70	-38	-0.02	
75	-39	-0.02	

**Note:** The manufacturer declared that the EUT could work properly at temperature 75°C.



3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GPRS 850 CH189	GPRS class 8	3.8	-35	-0.04	2.5	PASS
		3.4	-35	-0.04		
		4.2	-36	-0.04		
	EDGE class 8	3.8	24	+0.03		
		3.4	23	+0.03		
		4.2	-26	-0.03		
GPRS 1900 CH661	GPRS class 8	3.8	-56	-0.03		
		3.4	-54	-0.03		
		4.2	-55	-0.03		
	EDGE class 8	3.8	-47	-0.02		
		3.4	-46	-0.02		
		4.2	-49	-0.03		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	-15	-0.02		
		3.4	-16	-0.02		
		4.2	-18	-0.02		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	-33	-0.02		
		3.4	-33	-0.02		
		4.2	-35	-0.02		

Note: Normal Voltage = 3.8V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 28, 2013	Jul. 22, 20.13~ Jul. 23, 20.13	Mar. 27, 2014	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	N/A	Mar. 28, 2013	Jul. 22, 20.13~ Jul. 23, 20.13	Mar. 27, 2014	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	N/A	Mar. 28, 2013	Jul. 22, 20.13~ Jul. 23, 20.13	Mar. 27, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	N/A	Mar. 28, 2013	Jul. 22, 20.13~ Jul. 23, 20.13	Mar. 27, 2014	Conducted (TH01-SZ)
ESCI TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Mar. 28, 2013	Jul. 25, 20.13	Mar. 27, 2014	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP30	101362	9kHz~30GHz	Oct. 11, 2012	Jul. 25, 20.13	Oct. 10, 2013	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 12, 2012	Jul. 25, 20.13	Oct. 11, 2013	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Nov. 03, 2012	Jul. 25, 20.13	Nov. 02, 2013	Radiation (03CH01-SZ)
Turn Table	EM Electronic	EM 1000	N/A	0 ~ 360 degree	N/A	Jul. 25, 20.13	N/A	Radiation (03CH01-SZ)
Antenna Mast	EM Electronic	EM 1000	N/A	1 m - 4 m	N/A	Jul. 25, 20.13	N/A	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3GHz Gain 30dB	Mar. 28, 2013	Jul. 25, 20.13	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	Jul. 25, 20.13	Mar. 27, 2014	Radiation (03CH01-SZ)
SHF-EHF -Horn	Schwarzbeck	BBHA9170	BBHA917024 9	14GHz~40GHz	Nov. 23, 2012	Jul. 25, 20.13	Nov. 22, 2013	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Aug. 22, 2012	Jul. 25, 20.13	Aug. 21, 2013	ERP/EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MH z	N/A	Jul. 25, 20.13	N/A	ERP/EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	Jul. 25, 20.13	N/A	ERP/EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	Jul. 25, 20.13	N/A	ERP/EIRP (OTA01-SZ)

## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.54
---	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.72
---	------