



# FCC RF Test Report

**APPLICANT** : ZTE CORPORATION  
**EQUIPMENT** : WCDMA/CDMA/LTE Multi-Mode Digital Mobile Phone  
**BRAND NAME** : ZTE  
**MODEL NAME** : ZTE A2017U  
**FCC ID** : SRQ-ZTEA2017U  
**STANDARD** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure

The product was received on Mar. 16, 2016 and testing was completed on Apr. 17, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



# TABLE OF CONTENTS

**REVISION HISTORY.....3**

**SUMMARY OF TEST RESULT .....4**

**1 GENERAL DESCRIPTION .....5**

    1.1 Applicant.....5

    1.2 Manufacturer.....5

    1.3 Feature of Equipment Under Test.....5

    1.4 Product Specification of Equipment Under Test.....6

    1.6 Modification of EUT.....7

    1.7 Testing Location.....7

    1.8 Applicable Standards.....7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....8**

    2.1 Carrier Frequency and Channel.....8

    2.2 Pre-Scanned RF Power.....9

    2.3 Test Mode.....10

    2.4 Connection Diagram of Test System.....11

    2.5 Support Unit used in test configuration and system.....12

    2.6 EUT Operation Test Setup.....12

    2.7 Measurement Results Explanation Example.....12

**3 TEST RESULT.....13**

    3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement.....13

    3.2 Maximum Conducted Output Power Measurement.....16

    3.3 Power Spectral Density Measurement.....17

    3.4 Unwanted Emissions Measurement.....19

    3.5 AC Conducted Emission Measurement.....24

    3.6 Frequency Stability Measurement.....28

    3.7 Automatically Discontinue Transmission.....29

    3.8 Antenna Requirements.....30

**4 LIST OF MEASURING EQUIPMENT .....31**

**5 UNCERTAINTY OF EVALUATION .....32**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. RADIATED TEST RESULTS**

**APPENDIX C. DUTY CYCLE PLOTS**

**APPENDIX D. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	≤15.407(b)(4)(i) &15.209(a)	Pass	Under limit 8.64 dB at 45.520 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.07 dB at 0.200 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	WCDMA/CDMA/LTE Multi-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	ZTE A2017U
FCC ID	SRQ-ZTEA2017U
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/DC-HSDPA/LTE/NFC WLAN2.4GHz 802.11b/g/n HT20/HT40 WLAN5GHz 802.11a/n HT20/HT40 WLAN5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0+EDR Bluetooth v4.1 LE Bluetooth v4.2 LE
IMEI Code	Conducted: 990006780003751 Radiation: 990006780003629 Conduction: 990006780003793
HW Version	wwdB
SW Version	A2017UV1.0.0B07
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx/Rx Channel Frequency Range</b>	5745 MHz ~ 5825 MHz
<b>Maximum Output Power</b>	802.11a : 13.22 dBm / 0.0210 W 802.11n HT20 : 10.05 dBm / 0.0101 W 802.11n HT40 : 9.67 dBm / 0.0093 W 802.11ac VHT20: 9.99 dBm / 0.0100 W 802.11ac VHT40: 9.66 dBm / 0.0092 W 802.11ac VHT80: 10.16 dBm / 0.0104 W
<b>99% Occupied Bandwidth</b>	802.11a : 16.78 MHz 802.11n HT20 : 17.73 MHz 802.11n HT40 : 36.06 MHz 802.11ac VHT20: 17.73 MHz 802.11ac VHT40: 35.96 MHz 802.11ac VHT80: 74.93 MHz
<b>Antenna Type / Gain</b>	PIFA Antenna with gain -1.5 dBi
<b>Type of Modulation</b>	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)



### 1.6 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.7 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.			
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC Registration No.</b>
	TH01-KS	CO01-KS	03CH03-KS	306251

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	157	5785
	<b>151</b>	<b>5755</b>	<b>159</b>	<b>5795</b>
	153	5765	161	5805
	155	5775	165	5825

**Note:** The above Frequency and Channel in boldface were 802.11n HT40.



## 2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables.

WLAN 5GHz 802.11a Average Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 149	5745	12.44	CH 165	13.11	13.14	13.21	12.49	12.53	12.48	12.42
CH 157	5785	12.91								
CH 165	5825	13.22								

WLAN 5GHz 802.11n-HT20 Average Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 149	5745	9.28	CH 165	9.90	10.03	9.52	9.59	9.57	9.68	9.52
CH 157	5785	9.70								
CH 165	5825	10.05								

WLAN 5GHz 802.11n-HT40 Average Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 151	5755	8.92	CH 159	9.59	9.57	9.54	9.61	9.55	9.49	9.41
CH 159	5795	9.67								

WLAN 5GHz 802.11ac VHT20 Average Power (dBm)											
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
		MCS0									
CH 149	5745	9.24	CH 165	9.81	9.95	9.52	9.48	9.49	9.44	9.57	9.36
CH 157	5785	9.74									
CH 165	5825	9.99									

WLAN 5GHz 802.11ac VHT40 Average Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
		MCS0										
CH 151	5755	8.82	CH 159	9.60	9.47	9.53	9.62	9.49	9.56	9.46	9.50	9.48
CH 159	5795	9.66										

WLAN 5GHz 802.11n-HT80 Average Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
		MCS0										
CH 155	5775	10.16	CH 155	10.15	10.11	9.46	9.42	9.45	9.78	9.60	9.55	9.53



### 2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0


Test Cases	
<b>AC Conducted Emission</b>	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Earphone + USB Cable (Charging from Adapter)
<b>Remark:</b> For Radiated TCs, the tests were performed with Adapter, Earphone, and USB Cable.	

Ch. #	Band IV : 5745-5825 MHz		
	802.11a	802.11n HT20	802.11n HT40
L Low	149	149	151
M Middle	157	157	-
H High	165	165	159


Ch. #	Band IV : 5745-5825 MHz		
	802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L Low	149	151	-
M Middle	157	-	155
H High	165	159	-

## 2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>





### 2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
6.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2 m	N/A
7.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2 m	N/A

### 2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

### 2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6.2 dB.

Offset (dB) = RF cable loss(dB).

= 6.2 (dB)

### 3 Test Result

#### 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02.  
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.



##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.





**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where  $x$  is the duty cycle.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures


The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02. Section F) Maximum power spectral density.

##### # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


1. The testing follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02.
  - Measure the duty cycle.
  - Set span to encompass the entire emission bandwidth (EBW) of the signal.
  - Set RBW = 300 kHz.
  - Set VBW  $\geq$  1 MHz.
  - Number of points in sweep  $\geq$  2 Span / RBW.
  - Sweep time = auto.
  - Detector = RMS
  - Trace average at least 100 traces in power averaging mode.
  - Add  $10 \log(500\text{kHz}/\text{RBW})$  to the test result.
  - Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.





### 3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

#### 3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:** The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB 789033 D02 General UNII Test Procedures New Rules v01r02 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.



### **3.4.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.4.3 Test Procedures**

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW  $\geq$  3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B.

### 3.4.7 Duty Cycle

Please refer to Appendix C.

### 3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.5.4 Test Setup





3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	43~45%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS  
Condition : FCC PART 15E LISN-L-20151024 LINE

mode : Mode 1  
: 990006780003793 #13

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.20	51.55	-12.07	63.62	41.20	0.22	10.13	QP
2	0.20	38.45	-15.17	53.62	28.10	0.22	10.13	Average
3	0.29	43.67	-16.79	60.46	33.30	0.22	10.15	QP
4	0.29	29.17	-21.29	50.46	18.80	0.22	10.15	Average
5	0.40	43.60	-14.35	57.95	33.20	0.23	10.17	QP
6	0.40	29.60	-18.35	47.95	19.20	0.23	10.17	Average
7	0.49	41.59	-14.60	56.19	31.20	0.23	10.16	QP
8	0.49	26.69	-19.50	46.19	16.30	0.23	10.16	Average
9	0.70	40.69	-15.31	56.00	30.30	0.24	10.15	QP
10	0.70	25.99	-20.01	46.00	15.60	0.24	10.15	Average
11	1.65	35.14	-20.86	56.00	24.80	0.20	10.14	QP
12	1.65	22.94	-23.06	46.00	12.60	0.20	10.14	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	43~45%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS  
Condition : FCC PART 15E LISN-N-20151024 NEUTRAL

mode : Mode 1  
: 990006780003793 #13

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.20	51.04	-12.76	63.80	40.60	0.31	10.13	QP
2	0.20	38.54	-15.26	53.80	28.10	0.31	10.13	Average
3	0.29	43.36	-17.14	60.50	32.90	0.31	10.15	QP
4	0.29	27.96	-22.54	50.50	17.50	0.31	10.15	Average
5	0.40	40.29	-17.52	57.81	29.80	0.32	10.17	QP
6	0.40	24.99	-22.82	47.81	14.50	0.32	10.17	Average
7	0.50	40.08	-15.97	56.05	29.60	0.32	10.16	QP
8	0.50	25.08	-20.97	46.05	14.60	0.32	10.16	Average
9	0.79	37.10	-18.90	56.00	26.60	0.35	10.15	QP
10	0.79	24.00	-22.00	46.00	13.50	0.35	10.15	Average
11	1.06	34.11	-21.89	56.00	23.60	0.37	10.14	QP
12	1.06	21.71	-24.29	46.00	11.20	0.37	10.14	Average

## 3.6 Frequency Stability Measurement

### 3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

### 3.6.4 Test Setup



### 3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



## **3.7 Automatically Discontinue Transmission**

### **3.7.1 Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **3.7.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.7.3 Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



## **3.8 Antenna Requirements**

### **3.8.1 Standard Applicable**

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.8.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.8.3 Antenna Gain**

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	9kHz~30GHz	May 04, 2015	Mar. 24, 2016~ Apr. 17, 2016	May 03, 2016	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 24, 2015	Mar. 24, 2016~ Apr. 17, 2016	Oct. 23, 2016	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 20, 2016	Mar. 24, 2016~ Apr. 17, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Mar. 24, 2016~ Apr. 17, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 24, 2015	Mar. 24, 2016~ Apr. 17, 2016	Oct. 23, 2016	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Sep. 10, 2015	Mar. 24, 2016~ Apr. 15, 2016	Sep. 09, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44GHz	Jun. 05, 2015	Mar. 24, 2016~ Apr. 15, 2016	Jun. 04, 2016	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 07, 2015	Mar. 24, 2016~ Apr. 15, 2016	Nov. 06, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25MHz-2GHz	Mar. 12, 2016	Mar. 24, 2016~ Apr. 15, 2016	Mar. 11, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Mar. 24, 2016~ Apr. 15, 2016	Jun. 24, 2016	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18Ghz-40Ghz	Oct. 10, 2015	Mar. 24, 2016~ Apr. 15, 2016	Oct. 09, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz-3000MHz	Aug. 10, 2015	Mar. 24, 2016~ Apr. 15, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Mar. 24, 2016~ Apr. 15, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Aug. 27, 2015	Mar. 24, 2016~ Apr. 15, 2016	Aug. 26, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 24, 2016~ Apr. 15, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 24, 2016~ Apr. 15, 2016	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 24, 2016~ Apr. 15, 2016	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz	May 04, 2015	Mar. 28, 2016	May 03, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Mar. 28, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Mar. 28, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Mar. 28, 2016	Oct. 23, 2016	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3 dB
-------------------------------------------------------------------------	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5 dB
-------------------------------------------------------------------------	--------



## **Appendix A. Conducted Test Results**

Test Engineer:	Issac Song	Temperature:	24~25	°C
Test Date:	2016/3/24~2016/4/17	Relative Humidity:	49~51	%

**TEST RESULTS DATA**  
**6dB and 26dB EBW and 99% OBW**

Band IV									
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	16.733	20.330	15.305	0.5	Pass
11a	6Mbps	1	157	5785	16.783	20.579	15.325	0.5	Pass
11a	6Mbps	1	165	5825	16.683	20.529	15.305	0.5	Pass
HT20	MCS 0	1	149	5745	17.682	21.528	15.125	0.5	Pass
HT20	MCS 0	1	157	5785	17.732	21.628	15.125	0.5	Pass
HT20	MCS 0	1	165	5825	17.682	21.479	15.125	0.5	Pass
HT40	MCS 0	1	151	5755	36.064	41.718	35.085	0.5	Pass
HT40	MCS 0	1	159	5795	35.964	41.538	35.085	0.5	Pass
VHT20	MCS 0	1	149	5745	17.682	21.578	15.125	0.5	Pass
VHT20	MCS 0	1	157	5785	17.732	21.578	15.125	0.5	Pass
VHT20	MCS 0	1	165	5825	17.682	21.479	15.125	0.5	Pass
VHT40	MCS 0	1	151	5755	35.964	41.628	35.085	0.5	Pass
VHT40	MCS 0	1	159	5795	35.864	41.628	35.085	0.5	Pass
VHT80	MCS 0	1	155	5775	74.925	83.120	75.045	0.5	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Band IV										
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.20	12.44	30.00	-1.50		Pass
11a	6Mbps	1	157	5785	0.20	12.91	30.00	-1.50		Pass
11a	6Mbps	1	165	5825	0.20	13.22	30.00	-1.50		Pass
HT20	MCS 0	1	149	5745	0.25	9.28	30.00	-1.50		Pass
HT20	MCS 0	1	157	5785	0.25	9.70	30.00	-1.50		Pass
HT20	MCS 0	1	165	5825	0.25	10.05	30.00	-1.50		Pass
HT40	MCS 0	1	151	5755	0.44	8.92	30.00	-1.50		Pass
HT40	MCS 0	1	159	5795	0.44	9.67	30.00	-1.50		Pass
VHT20	MCS 0	1	149	5745	0.23	9.24	30.00	-1.50		Pass
VHT20	MCS 0	1	157	5785	0.23	9.74	30.00	-1.50		Pass
VHT20	MCS 0	1	165	5825	0.23	9.99	30.00	-1.50		Pass
VHT40	MCS 0	1	151	5755	0.37	8.82	30.00	-1.50		Pass
VHT40	MCS 0	1	159	5795	0.37	9.66	30.00	-1.50		Pass
VHT80	MCS 0	1	155	5775	0.91	10.16	30.00	-1.50		Pass

**TEST RESULTS DATA**  
**Power Spectral Density**

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.20	2.22	-1.42	30.00	-1.50	Pass
11a	6Mbps	1	157	5785	0.20	2.22	-0.72	30.00	-1.50	Pass
11a	6Mbps	1	165	5825	0.20	2.22	-0.61	30.00	-1.50	Pass
HT20	MCS 0	1	149	5745	0.25	2.22	-4.44	30.00	-1.50	Pass
HT20	MCS 0	1	157	5785	0.25	2.22	-3.90	30.00	-1.50	Pass
HT20	MCS 0	1	165	5825	0.25	2.22	-3.86	30.00	-1.50	Pass
HT40	MCS 0	1	151	5755	0.44	2.22	-8.07	30.00	-1.50	Pass
HT40	MCS 0	1	159	5795	0.44	2.22	-7.20	30.00	-1.50	Pass
VHT20	MCS 0	1	149	5745	0.23	2.22	-4.50	30.00	-1.50	Pass
VHT20	MCS 0	1	157	5785	0.23	2.22	-3.41	30.00	-1.50	Pass
VHT20	MCS 0	1	165	5825	0.23	2.22	-4.08	30.00	-1.50	Pass
VHT40	MCS 0	1	151	5755	0.37	2.22	-8.29	30.00	-1.50	Pass
VHT40	MCS 0	1	159	5795	0.37	2.22	-7.30	30.00	-1.50	Pass
VHT80	MCS 0	1	155	5775	0.91	2.22	-9.86	30.00	-1.50	Pass

**TEST RESULTS DATA**  
**Frequency Stability**

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6M bps	1	149	5745	5745.000	0.000	0.00	20	3.6	
11a	6M bps	1	149	5745	5745.025	0.025	4.35	20	4.4	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	20	3.85	
11a	6M bps	1	149	5745	5745.025	0.025	4.35	-30	3.85	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	50	3.85	



## Appendix B. Radiated Spurious Emission

### Band 4 - 5725~5850MHz WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11a CH 149 5745MHz		5696.28	47.09	-55.47	102.56	42.78	32.02	8.54	36.25	100	121	P	H
		5713.4	47.97	-61.08	109.05	43.66	32.03	8.55	36.27	100	121	P	H
		5723.96	47.37	-72.56	119.93	43.04	32.04	8.57	36.28	100	121	P	H
	*	5748	97.9	-	-	93.56	32.05	8.58	36.29	100	121	P	H
	*	5744	90.5	-	-	86.16	32.05	8.58	36.29	100	121	A	H
		5688.6	47	-49.89	96.89	42.69	32.02	8.54	36.25	303	93	P	V
		5714.04	48	-61.23	109.23	43.69	32.03	8.55	36.27	303	93	P	V
		5720.84	46.54	-66.28	112.82	42.21	32.04	8.57	36.28	303	93	P	V
	*	5746	95.17	-	-	90.83	32.05	8.58	36.29	303	93	P	V
	*	5746	87.58	-	-	83.24	32.05	8.58	36.29	303	93	A	V
802.11a CH 157 5785MHz	*	5782	98.76	-	-	94.41	32.06	8.6	36.31	100	115	P	H
	*	5782	91.29	-	-	86.94	32.06	8.6	36.31	100	115	A	H
	*	5786	95.34	-	-	90.97	32.07	8.62	36.32	300	91	P	V
	*	5788	87.91	-	-	83.54	32.07	8.62	36.32	300	91	A	V
802.11a CH 165 5825MHz	*	5824	97.96	-	-	93.59	32.08	8.64	36.35	100	121	P	H
	*	5824	90.54	-	-	86.17	32.08	8.64	36.35	100	121	A	H
		5853.36	48.25	-66.39	114.64	43.87	32.09	8.65	36.36	100	121	P	H
		5869.36	47.79	-59.09	106.88	43.4	32.1	8.66	36.37	100	121	P	H
		5882.96	46.57	-52.82	99.39	42.18	32.1	8.67	36.38	100	121	P	H
	*	5824	95.54	-	-	91.17	32.08	8.64	36.35	300	87	P	V
	*	5826	88.72	-	-	84.35	32.08	8.64	36.35	300	87	A	V
		5854.72	47.12	-64.42	111.54	42.73	32.1	8.66	36.37	300	87	P	V
		5864.48	48.09	-60.15	108.24	43.7	32.1	8.66	36.37	300	87	P	V
	5878.32	46.29	-56.54	102.83	41.9	32.1	8.67	36.38	300	87	P	V	
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 149 5745MHz		11490	42.45	-31.55	74	50.2	38.59	14.2	60.54	100	0	P	H
802.11a CH 157 5785MHz		11571	42.01	-31.99	74	49.51	38.75	14.25	60.5	100	0	P	H
802.11a CH 165 5825MHz		11649	42.16	-31.84	74	49.44	38.9	14.29	60.47	100	0	P	H
802.11a CH 149 5745MHz		11490	41.46	-32.54	74	49.21	38.59	14.2	60.54	100	0	P	V
802.11a CH 157 5785MHz		11571	41.54	-32.46	74	49.04	38.75	14.25	60.5	100	0	P	V
802.11a CH 165 5825MHz		11649	41.87	-32.13	74	49.15	38.9	14.29	60.47	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 149 5745MHz		5692.2	46.74	-52.81	99.55	42.43	32.02	8.54	36.25	100	120	P	H
		5719	47.32	-63.3	110.62	42.99	32.04	8.57	36.28	100	120	P	H
		5721.24	46.79	-66.94	113.73	42.46	32.04	8.57	36.28	100	120	P	H
	*	5748	94.26	-	-	89.92	32.05	8.58	36.29	100	120	P	H
	*	5746	86.57	-	-	82.23	32.05	8.58	36.29	100	120	A	H
		5686.04	46.27	-48.73	95	41.96	32.02	8.54	36.25	300	72	P	V
		5707.08	47.03	-60.25	107.28	42.72	32.03	8.55	36.27	300	72	P	V
		5723.4	46.47	-72.18	118.65	42.14	32.04	8.57	36.28	300	72	P	V
	*	5742	90.73	-	-	86.39	32.05	8.58	36.29	300	72	P	V
*	5742	82.95	-	-	78.61	32.05	8.58	36.29	300	72	A	V	
802.11n HT20 CH 157 5785MHz	*	5784	92.68	-	-	88.33	32.06	8.6	36.31	100	126	P	H
	*	5782	85.09	-	-	80.74	32.06	8.6	36.31	100	126	A	H
	*	5782	91.19	-	-	86.84	32.06	8.6	36.31	300	94	P	V
	*	5788	83.79	-	-	79.42	32.07	8.62	36.32	300	94	A	V
802.11n HT20 CH 165 5825MHz	*	5824	94.47	-	-	90.1	32.08	8.64	36.35	100	116	P	H
	*	5824	86.73	-	-	82.36	32.08	8.64	36.35	100	116	A	H
		5854.88	46.63	-64.54	111.17	42.24	32.1	8.66	36.37	100	116	P	H
		5866.08	47.47	-60.33	107.8	43.08	32.1	8.66	36.37	100	116	P	H
		5886.72	46.36	-50.24	96.6	41.97	32.1	8.67	36.38	100	116	P	H
	*	5824	93.24	-	-	88.87	32.08	8.64	36.35	300	86	P	V
	*	5828	85.54	-	-	81.17	32.08	8.64	36.35	300	86	A	V
		5852	46.21	-71.53	117.74	41.83	32.09	8.65	36.36	300	86	P	V
		5871.92	47.63	-58.53	106.16	43.24	32.1	8.67	36.38	300	86	P	V
	5885.36	47.03	-50.58	97.61	42.64	32.1	8.67	36.38	300	86	P	V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 149 5745MHz		11490	42.24	-31.76	74	49.99	38.59	14.2	60.54	100	0	P	H
		11490	41.28	-32.72	74	49.03	38.59	14.2	60.54	100	0	P	V
802.11n HT20 CH 157 5785MHz		11571	41.8	-32.2	74	49.3	38.75	14.25	60.5	100	0	P	H
		11571	41.47	-32.53	74	48.97	38.75	14.25	60.5	100	0	P	V
802.11n HT20 CH 165 5825MHz		11649	42.51	-31.49	74	49.79	38.9	14.29	60.47	100	0	P	H
		11649	41.91	-32.09	74	49.19	38.9	14.29	60.47	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 151 5755MHz		5686.2	49.78	-45.34	95.12	45.47	32.02	8.54	36.25	100	114	P	H
		5710.04	50.64	-57.47	108.11	46.33	32.03	8.55	36.27	100	114	P	H
		5721.24	52.99	-60.74	113.73	48.66	32.04	8.57	36.28	100	114	P	H
	*	5748	90.82	-	-	86.48	32.05	8.58	36.29	100	114	P	H
	*	5748	83.47	-	-	79.13	32.05	8.58	36.29	100	114	A	H
		5690.92	47.02	-51.58	98.6	42.71	32.02	8.54	36.25	300	81	P	V
		5713.32	51.08	-57.95	109.03	46.77	32.03	8.55	36.27	300	81	P	V
		5724.04	50.86	-69.25	120.11	46.53	32.04	8.57	36.28	300	81	P	V
	*	5748	88.16	-	-	83.82	32.05	8.58	36.29	300	81	P	V
	*	5750	80.63	-	-	76.29	32.05	8.58	36.29	300	81	A	V
802.11n HT40 CH 159 5795MHz	*	5790	91.53	-	-	87.16	32.07	8.62	36.32	100	117	P	H
	*	5790	84.42	-	-	80.05	32.07	8.62	36.32	100	117	A	H
		5851.92	48.28	-69.64	117.92	43.9	32.09	8.65	36.36	100	117	P	H
		5855.68	49.13	-61.58	110.71	44.74	32.1	8.66	36.37	100	117	P	H
		5876.72	47.45	-56.57	104.02	43.06	32.1	8.67	36.38	100	117	P	H
	*	5804	88.32	-	-	83.94	32.08	8.63	36.33	300	87	P	V
	*	5792	80.78	-	-	76.41	32.07	8.62	36.32	300	87	A	V
		5854.08	48.27	-64.73	113	43.88	32.1	8.66	36.37	300	87	P	V
		5874.08	47.03	-58.53	105.56	42.64	32.1	8.67	36.38	300	87	P	V
	5889.76	46.49	-47.86	94.35	42.1	32.11	8.68	36.4	300	87	P	V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40		11511	41.26	-32.74	74	48.99	38.6	14.21	60.54	100	0	P	H
CH 151 5755MHz		11511	40.77	-33.23	74	48.5	38.6	14.21	60.54	100	0	P	V
802.11n HT40		11589	43.2	-30.8	74	50.64	38.79	14.26	60.49	100	0	P	H
CH 159 5795MHz		11589	42.36	-31.64	74	49.8	38.79	14.26	60.49	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11ac VHT20 CH 149 5745MHz		5689.16	46.84	-50.47	97.31	42.53	32.02	8.54	36.25	100	120	P	H
		5705	47.36	-59.34	106.7	43.05	32.03	8.55	36.27	100	120	P	H
		5724.84	46.42	-75.51	121.93	42.09	32.04	8.57	36.28	100	120	P	H
	*	5742	93.76	-	-	89.42	32.05	8.58	36.29	100	120	P	H
	*	5748	86.19	-	-	81.85	32.05	8.58	36.29	100	120	A	H
		5687.64	46.98	-49.2	96.18	42.67	32.02	8.54	36.25	327	97	P	V
		5704.44	47.81	-58.73	106.54	43.5	32.03	8.55	36.27	327	97	P	V
		5720.36	46.53	-65.19	111.72	42.2	32.04	8.57	36.28	327	97	P	V
	*	5748	92.44	-	-	88.1	32.05	8.58	36.29	327	97	P	V
*	5746	84.88	-	-	80.54	32.05	8.58	36.29	327	97	A	V	
802.11ac VHT20 CH 157 5785MHz	*	5784	93.05	-	-	88.7	32.06	8.6	36.31	119	114	P	H
	*	5782	85.51	-	-	81.16	32.06	8.6	36.31	119	114	A	H
	*	5788	91.58	-	-	87.21	32.07	8.62	36.32	288	81	P	V
	*	5784	84.15	-	-	79.8	32.06	8.6	36.31	288	81	A	V
802.11ac VHT20 CH 165 5825MHz	*	5828	95.16	-	-	90.79	32.08	8.64	36.35	112	118	P	H
	*	5828	87.32	-	-	82.95	32.08	8.64	36.35	112	118	A	H
		5850.64	46.97	-73.87	120.84	42.59	32.09	8.65	36.36	112	118	P	H
		5863.44	47.72	-60.81	108.53	43.33	32.1	8.66	36.37	112	118	P	H
		5883.68	46.56	-52.29	98.85	42.17	32.1	8.67	36.38	112	118	P	H
	*	5828	93.05	-	-	88.68	32.08	8.64	36.35	359	83	P	V
	*	5824	85.5	-	-	81.13	32.08	8.64	36.35	359	83	A	V
		5854.88	46.29	-64.88	111.17	41.9	32.1	8.66	36.37	359	83	P	V
		5867.04	47.93	-59.6	107.53	43.54	32.1	8.66	36.37	359	83	P	V
	5883.04	46.56	-52.77	99.33	42.17	32.1	8.67	36.38	359	83	P	V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11ac VHT20		11490	42.07	-31.93	74	49.82	38.59	14.2	60.54	100	360	P	H
CH 149 5745MHz		11490	44.59	-29.41	74	52.34	38.59	14.2	60.54	100	360	P	V
802.11ac VHT20		11571	42	-32	74	49.5	38.75	14.25	60.5	100	1	P	H
CH 157 5785MHz		11571	42.26	-31.74	74	49.76	38.75	14.25	60.5	100	360	P	V
802.11ac VHT20		11649	43.92	-30.08	74	51.2	38.9	14.29	60.47	100	0	P	H
CH 165 5825MHz		11649	42	-32	74	49.28	38.9	14.29	60.47	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11ac VHT40 CH 151 5755MHz		5697	46.22	-56.87	103.09	41.91	32.02	8.54	36.25	100	114	P	H
		5719.56	49.93	-60.85	110.78	45.6	32.04	8.57	36.28	100	114	P	H
		5721.48	54.69	-59.59	114.28	50.36	32.04	8.57	36.28	100	114	P	H
	*	5764	90.89	-	-	86.55	32.05	8.59	36.3	100	114	P	H
	*	5748	83.38	-	-	79.04	32.05	8.58	36.29	100	114	A	H
		5699.4	48.35	-56.51	104.86	44.04	32.02	8.54	36.25	303	72	P	V
		5713.16	49.48	-59.51	108.99	45.17	32.03	8.55	36.27	303	72	P	V
		5721.4	49.12	-64.97	114.09	44.79	32.04	8.57	36.28	303	72	P	V
	*	5752	87.67	-	-	83.33	32.05	8.59	36.3	303	72	P	V
	*	5750	79.82	-	-	75.48	32.05	8.58	36.29	303	72	A	V
802.11ac VHT40 CH 159 5795MHz	*	5788	91.43	-	-	87.06	32.07	8.62	36.32	100	118	P	H
	*	5792	84.1	-	-	79.73	32.07	8.62	36.32	100	118	A	H
		5853.2	46.27	-68.73	115	41.89	32.09	8.65	36.36	100	118	P	H
		5857.76	48.04	-62.09	110.13	43.65	32.1	8.66	36.37	100	118	P	H
		5885.12	47.72	-50.07	97.79	43.33	32.1	8.67	36.38	100	118	P	H
	*	5798	89.86	-	-	85.49	32.07	8.62	36.32	306	77	P	V
	*	5792	82.05	-	-	77.68	32.07	8.62	36.32	306	77	A	V
		5851.36	48.69	-70.51	119.2	44.31	32.09	8.65	36.36	306	77	P	V
		5859.2	49.36	-60.36	109.72	44.97	32.1	8.66	36.37	306	77	P	V
	5886.16	46.73	-50.28	97.01	42.34	32.1	8.67	36.38	306	77	P	V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include test results for 802.11ac VHT40 CH 151 and CH 159 at 11511 MHz and 11589 MHz.



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT80 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
<b>802.11ac VHT80 CH 155 5775MHz</b>		5694.2	48.14	-52.88	101.02	43.83	32.02	8.54	36.25	105	119	P	H
		5709.24	49.05	-58.84	107.89	44.74	32.03	8.55	36.27	105	119	P	H
		5723.4	51.31	-67.34	118.65	46.98	32.04	8.57	36.28	105	119	P	H
	*	5766	89.48	-	-	85.14	32.05	8.59	36.3	105	119	P	H
	*	5768	81.63	-	-	77.29	32.05	8.59	36.3	105	119	A	H
		5854.48	47.73	-64.36	112.09	43.34	32.1	8.66	36.37	105	119	P	H
		5866.48	48.25	-59.43	107.68	43.86	32.1	8.66	36.37	105	119	P	H
		5884.08	47.48	-51.08	98.56	43.09	32.1	8.67	36.38	105	119	P	H
		5688.6	47.65	-49.24	96.89	43.34	32.02	8.54	36.25	270	88	P	V
		5715	48.28	-61.22	109.5	43.97	32.03	8.55	36.27	270	88	P	V
		5723.8	50.32	-69.24	119.56	45.99	32.04	8.57	36.28	270	88	P	V
	*	5790	87.83	-	-	83.46	32.07	8.62	36.32	270	88	P	V
	*	5780	80.72	-	-	76.37	32.06	8.6	36.31	270	88	A	V
		5853.04	47.35	-68.02	115.37	42.97	32.09	8.65	36.36	270	88	P	V
		5868.56	47.85	-59.25	107.1	43.46	32.1	8.66	36.37	270	88	P	V
	5880.48	47.59	-53.64	101.23	43.2	32.1	8.67	36.38	270	88	P	V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80		11550	43.32	-30.68	74	50.88	38.71	14.24	60.51	100	0	P	H
CH 155 5775MHz		11550	42.68	-31.32	74	50.24	38.71	14.24	60.51	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
5GHz 802.11n HT40 LF		33.88	23.86	-16.14	40	36.06	18.04	0.7	30.94	-	-	P	H
		93.05	23.94	-19.56	43.5	40.9	12.32	1.16	30.44	-	-	P	H
		153.19	32.48	-11.02	43.5	47.76	13.62	1.5	30.4	239	316	P	H
		206.54	29.43	-14.07	43.5	47.07	11.04	1.73	30.41	-	-	P	H
		408.3	25.23	-20.77	46	36.33	17.07	2.5	30.67	-	-	P	H
		760.41	26.77	-19.23	46	32.78	20.99	3.5	30.5	-	-	P	H
		35.82	30.75	-9.25	40	43.77	17.16	0.72	30.9	-	-	P	V
		45.52	31.36	-8.64	40	49.11	12.22	0.83	30.8	122	109	P	V
		90.14	30.43	-13.07	43.5	47.88	11.9	1.15	30.5	-	-	P	V
		154.16	29.68	-13.82	43.5	45.02	13.56	1.5	30.4	-	-	P	V
		426.73	24.35	-21.65	46	35.16	17.22	2.56	30.59	-	-	P	V
	549.92	24.44	-21.56	46	33.21	18.6	2.93	30.3	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



### Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	95.496	2.078	0.481	1kHz
802.11n HT20	94.695	1.928	0.519	1kHz
802.11n HT40	90.440	0.946	1.057	3kHz
802.11ac VHT20	94.814	1.938	0.516	1kHz
802.11ac VHT40	91.794	0.962	1.040	3kHz
802.11ac VHT80	81.185	0.466	2.146	3kHz


802.11a



Date: 24.MAR.2016 10:28:32




802.11n HT20



Date: 24.MAR.2016 10:33:09


802.11n HT40



Date: 24.MAR.2016 10:39:08




802.11ac VHT20



Date: 24.MAR.2016 10:44:14


802.11ac VHT40



Date: 24.MAR.2016 10:50:36



802.11ac VHT80



Date: 24.MAR.2016 10:55:50