



Test Mode:802.11b 2462MHz Chain0


Test Mode: 802.11g



Test Mode:802.11g 2412MHz Chain0





Test Mode:802.11g 2437MHz Chain0





Test Mode:802.11g 2462MHz Chain0

Test Mode: 802.11n HT20





Test Mode:802.11n HT20 2412MHz Chain0

Test Mode:802.11n HT20 2437MHz Chain0




Test Mode:802.11n HT20 2462MHz Chain0

Test Mode: 802.11n HT40



Test Mode:802.11n HT40 2422MHz Chain0


Test Mode:802.11n HT40 2437MHz Chain0




Test Mode:802.11n HT40 2452MHz Chain0

Band edge measurement

Test Mode: 802.11b




Test Mode:802.11b 2412MHz Chain0




Test Mode:802.11b 2462MHz Chain0

Test Mode: 802.11g




Test Mode:802.11g 2412MHz Chain0




Test Mode:802.11g 2462MHz Chain0

Test Mode: 802.11n HT20




Test Mode:802.11n HT20 2412MHz Chain0




Test Mode:802.11n HT20 2462MHz Chain0

Test Mode: 802.11n HT40



Test Mode:802.11n HT40 2422MHz Chain0



Test Mode:802.11n HT40 2452MHz Chain0

APPENDIX B – TEST DATA OF RADIATED EMISSION

Worst case(11b)

Radiated Emission Band Edge

The measurement results are obtained as described below:

Measure Level = Reading Level + Cable loss + Antenna factor Sample calculation: (87.70 dBuV/m) = (53.70 dBμV) + (8.90 dB) + (25.10 dB), the corresponding frequency is 2412MHz.

Note: The scanned graph represents the maximum of both horizontal and vertical polarizations and is not a single horizontal or vertical polarization scan.

Note: There were no emissions above 18GHz found within 20dB of the limit. Thus the test result was not reported according to §15.31 (o)

The measurement results contain the correction factor of the duty cycle.

802.11b

Carrier Frequency (MHz): 2412

Channel No.: 1

Test Mode: 802.11b

Detector: Peak

Frequency (MHz)	Reading Level (dBuV)	Measure Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB)
2412.0	54.30	88.30	N/A	N/A	8.90	25.10
2390.0	6.40	40.40	-33.60	74.00	8.90	25.10

Detector: Average

Frequency (MHz)	Reading Level (dBuV)	Measure Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB)
2412.0	37.50	71.50	N/A	N/A	8.90	25.10
2390.0	-12.10	21.90	-32.10	54.00	8.90	25.10

Carrier Frequency (MHz): 2462

Channel No.: 11

Test Mode: 802.11b

Detector: Peak

Frequency (MHz)	Reading Level (dBuV)	Measure Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB)
2462.0	60.60	94.60	N/A	N/A	8.90	25.10
2483.5	10.60	44.60	-29.40	74.00	8.90	25.10

Detector: Average

Frequency (MHz)	Reading Level (dBuV)	Measure Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB)
2462.0	36.70	70.70	N/A	N/A	8.90	25.10
2483.5	-6.30	27.70	-26.30	54.00	8.90	25.10

Sample Calculations

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Below 1GHz:

$$\text{QuasiPeak} = \text{Reading Value} + A_{Rpl}$$

Above 1GHz:

$$\text{MaxPeak} = \text{Reading MaxPeak} + A_{Rpl}$$

OR

$$\text{Average} = \text{Reading Average} + A_{Rpl}$$

Sample calculation: $(17.45 \text{ dB}\mu\text{V/m}) = (41.25 \text{ dB}\mu\text{V}) + (-23.80 \text{ dB/m})$, the corresponding frequency is 148.437MHz.

The worst case attitude: The mobile lay down.


Spurious Radiated Emissions below 30MHz:

There were no emissions from 9kHz to 30MHz found within 20dB of the limit. Thus, the test result was not reported according to §15.31 (o).

802.11b

Spurious Radiated Emissions from 30MHz to 1GHz:


CH Middle (No.6)




Frequency (MHz)	Reading (dBuV)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	A_{Rpl} (dB)	Polarity
55.705	51.04	31.04	40	8.96	-20	Vertical
80.6825	54.68	28.58	40	11.42	-26.1	Vertical
87.715	51.62	27.52	40	12.48	-24.1	Vertical
148.825	54.70	30.9	43.5	12.6	-23.8	Vertical
200.235	52.21	32.21	43.5	11.29	-20	Vertical
300.145	55.49	38.49	46	7.51	-17	Vertical

Spurious Radiated Emissions from 1GHz to 18GHz:
CH Middle (No.6)

Full Spectrum




Full Spectrum



Frequency (MHz)	Reading MaxPeak (dBuV)	Reading Average (dBuV)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	A _{Rpl} (dB)	Polarity
5710	---	55.04	---	34.34	54	19.66	-20.7	Vertical
8522.5	---	55.38	---	35.28	54	18.72	-20.1	Vertical
10347.5	---	54.64	---	35.64	54	18.36	-19	Vertical
11349.5	---	53.64	---	36.64	54	17.36	-17	Vertical
14398	---	54.40	---	41	54	13	-13.4	Vertical
16805.5	---	57.68	---	45.28	54	8.72	-12.4	Vertical

AC Power line Conducted Emission 100V




L+N Line

MEASUREMENT RESULT:

Range	Frequency MHz	Line	Reading			Factor	Level			Limit	Limit			Margin			Pass/Fail		
			dB(μV)				dB	dB(μV)			dB(μV)	dB(μV)			dB				
			QP	AV	PK			QP	AV			PK	QP	AV	PK	QP		AV	PK
Band1	0.445	L	13.5	5.7		10.1	23.6	15.8		57	47		33.4	31.2		Pass			
Band1	0.473	L	16.2	6.1		10	26.2	16.1		56.5	46.5		30.3	30.4		Pass			
Band1	0.484	L	17.3	5.9		10	27.3	15.9		56.3	46.3		29	30.4		Pass			
Band1	0.487	L	18	9.6		10	28	19.6		56.2	46.2		28.2	26.6		Pass			
Band1	0.489	L	17.9	10.4		10	27.9	20.4		56.2	46.2		28.3	25.8		Pass			
Band1	4.608	L	12.7	4.3		10	22.7	14.3		56	46		33.3	31.7		Pass			
Band1	0.451	N	9.3	0.4		10.1	19.4	10.5		56.9	46.9		37.5	36.4		Pass			
Band1	0.473	N	12.8	3.7		10	22.8	13.7		56.5	46.5		33.7	32.8		Pass			
Band1	0.482	N	13.1	1.8		10	23.1	11.8		56.3	46.3		33.2	34.5		Pass			
Band1	0.489	N	13.8	6.2		10	23.8	16.2		56.2	46.2		32.4	30		Pass			
Band1	0.486	N	14.1	6.2		10	24.1	16.2		56.2	46.2		32.1	30		Pass			
Band1	0.496	N	10.6	2.3		10	20.6	12.3		56.1	46.1		35.5	33.8		Pass			

240V



L+N Line

MEASUREMENT RESULT:

Range	Frequency MHz	Line	Reading			Factor dB	Level			Limit			Margin			Pass/Fail
			dB(μV)				dB(μV)			dB(μV)			dB			
			QP	AV	PK		QP	AV	PK	QP	AV	PK	QP	AV	PK	
Band1	0.449	N	8.7	-0.7		10.1	18.8	9.4		56.9	46.9		38.1	37.5		Pass
Band1	0.468	N	11.5	5.4		10	21.5	15.4		56.6	46.6		35.1	31.2		Pass
Band1	0.474	N	12.3	3.4		10	22.3	13.4		56.5	46.5		34.2	33.1		Pass
Band1	0.48	N	14.3	5.9		10	24.3	15.9		56.3	46.3		32	30.4		Pass
Band1	0.488	N	13.2	5.6		10	23.2	15.6		56.2	46.2		33	30.6		Pass
Band1	0.487	N	12.9	5		10	22.9	15		56.2	46.2		33.3	31.2		Pass
Band1	0.475	L	15.9	5.6		10	25.9	15.6		56.4	46.4		30.5	30.8		Pass
Band1	0.487	L	17.9	9.6		10	27.9	19.6		56.2	46.2		28.3	26.6		Pass
Band1	4.474	L	12.8	4.8		10	22.8	14.8		56	46		33.2	31.2		Pass
Band1	4.523	L	13	4.3		10	23	14.3		56	46		33	31.7		Pass
Band1	8.204	L	16.9	8.7		10	26.9	18.7		60	50		33.1	31.3		Pass
Band1	9.733	L	15.6	8		10	25.6	18		60	50		34.4	32		Pass

---End of the test report---