



FCC PART 15C TEST REPORT No. I14Z47271-SRD02

for

ZTE Corporation

WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone

**Model Name: ZTE Blade Vec, Blade Vec, ZTE Blade Vec 3G, Blade
Vec 3G**

FCC ID: SRQ-ZTEBLADEVEC

with

Hardware Version: wnbq

Software Version: TEL_MX_TB25S_P692S20V1.0.0

Issued Date: 2014-10-10



DAR accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629B

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

Shouxiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633, Fax:+86(0)10-62304633-2504 Email:welcome@emcite.com

CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION.....	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. NORMAL ACCESSORY SETTING	5
3.5. GENERAL DESCRIPTION.....	5
4. REFERENCE DOCUMENTS	6
4.1. DOCUMENTS SUPPLIED BY APPLICANT.....	6
4.2. REFERENCE DOCUMENTS FOR TESTING.....	6
5. LABORATORY ENVIRONMENT	7
6. SUMMARY OF TEST RESULTS.....	8
6.1. SUMMARY OF TEST RESULTS	8
6.2. STATEMENTS.....	8
7. TEST EQUIPMENTS UTILIZED.....	9
ANNEX A: MEASUREMENT RESULTS	10
A.1. MEASUREMENT METHOD.....	10
A.2. PEAK OUTPUT POWER - CONDUCTED.....	11
A.3. FREQUENCY BAND EDGES - CONDUCTED	12
A.4. CONDUCTED EMISSION.....	14
A.5. RADIATED EMISSION.....	23
A.6. 6dB BANDWIDTH.....	31
A.7. MAXIMUM POWER SPECTRAL DENSITY LEVEL.....	34
A.8. AC POWERLINE CONDUCTED EMISSION.....	37

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: Shouxiang Science Building, No 51, Xueyuan Road, Haidian District,
Beijing, P.R.China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304633-2504

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Project Leader: Zi Xiaogang
Testing Start Date: 2014-07-04
Testing End Date: 2014-08-28

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China
City: Shenzhen
Postal Code: 518057
Country: China
Contact Person: Zhang Wen
Contact Email: /
Telephone: +86-21-68897541
Fax: +86-21-50801070

2.2. Manufacturer Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China
City: Shenzhen
Postal Code: 518057
Country: China
Telephone: +86-21-68897541
Fax: +86-21-50801070

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone
Model Name	ZTE Blade Vec, Blade Vec, ZTE Blade Vec 3G, Blade Vec 3G
FCC ID	SRQ-ZTEBLADEVEEC
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation(LE mode)	GFSK
Number of Channels(LE mode)	40
Power Supply	3.8V DC by Battery

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	865047020013483	wnqb	TEL_MX_TB25S_P692S20V1.0.0
EUT2	865047020002098	wnqb	TEL_MX_TB25S_P692S20V1.0.0

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description		
AE1	Battery	/	Inbuilt

AE1

Model	Li3823T43P6hA54236-H
Manufacturer	ZTE
Capacitance	2300mAh
Nominal voltage	3.8V

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery is used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	
FCC Part15	15.209 Radiated emission limits, general requirements;	10-1-13
	15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	
ANSI C63.10	American National Standard for Testing Unlicensed Wireless Devices	2009
FCC Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations	10–1–13

5. LABORATORY ENVIRONMENT

Shielding Room1 (6.0 metersx3.0 metersx2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Semi-anechoic chamber (23 metersx17metersx10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

Abbreviations used in this clause:

- P** Pass, The EUT complies with the essential requirements in the standard.
- F** Fail, The EUT does not comply with the essential requirements in the standard
- NA** Not Applicable, The test was not applicable
- NP** Not Performed, The test was not performed by TMC

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
6dB Bandwidth	15.247 (a)(2)	P
Peak Output Power - Conducted	15.247 (b)(1)	P
Maximum Power Spectral Density Level	15.247(e)	P
Conducted Emission	15.247 (d)	P
Radiated Emission	15.247, 15.205, 15.209	P
Frequency Band Edges	15.247 (d)	P
AC Powerline Conducted Emission	15.107, 15.207	P

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

6.2. Statements

TMC has evaluated the test cases requested by the applicant /manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

7. Test Equipments Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Last Calibration Date	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	2014-1-7	2015-01-06

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Last Calibration Date	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	2013-11-6	2014-11-05
2	EMI Antenna	VULB 9163	9163 175	Schwarzbeck	2012-7-14	2015-07-13
3	EMI Antenna	3117	00119021	ETS-Lindgren	2012-4-20	2015-04-19
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	2012-7-1	2015-06-30
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	2012-7-1	2015-06-30
6	Bluetooth Tester	CBT	100153	Rohde & Schwarz	2014-9-16	2015-09-15
7	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2014-4-15	2015-04-14
8	Pre-amplifier (18GHz)	HFH2-Z2	829324/007	Rohde & Schwarz	/	/
9	Pre-amplifier (26.5GHz)	SCU18	1005277	Rohde & Schwarz	/	/
10	Loop Antenna	SCU26	1006788	Rohde & Schwarz	2011-12-13	2014-12-12

Anechoic chamber

Fully anechoic chamber by Frankonia German.


ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements


The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



A.2. Peak Output Power - Conducted
Measurement Limit:

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

The measurement is made according to ANSI C63.10.

Test Condition

Hopping Mode	RBW	VBW	Span	Sweeptime	Detector	Trace Mode
Hopping OFF	1MHz	5MHz	0	5ms	Peak	Max Hold

Measurement Results:

For GFSK

Frequency	2402 MHz	2440 MHz	2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	-0.56	-0.37	-0.70	P

Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%

Conclusion: PASS

A.3. Frequency Band Edges - Conducted

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

The measurement is made according to ANSI C63.10.

Test Condition

Hopping Mode	RBW	VBW	Span	Sweptime	Detector	Trace Mode
Hopping OFF	100KHz	300KHz	8MHz	5ms	Peak	Max Hold

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.


Measurement Result:

For GFSK

Frequency	Hopping	Band Edge Power (dBc)	Conclusion
2402MHz	Hopping OFF	Fig.1	P
2480MHz	Hopping OFF	Fig.2	P


Conclusion: PASS

Test graphs as below



Date: 28.AUG.2014 11:08:55

Fig.1. Frequency Band Edges: GFSK, 2402 MHz, Hopping Off



Date: 28.AUG.2014 11:16:01

Fig.2. Frequency Band Edges: GFSK, 2480 MHz, Hopping Off

A.4. Conducted Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

The measurement is made according to ANSI C63.10.

Test Condition

Hopping Mode	RBW	VBW	Sweeptime	Detector	Trace Mode
Hopping OFF	100KHz	300KHz	Auto	Peak	Max Hold

Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Set the span to 5-30 % greater than the EBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

**Measurement Results:
For GFSK**

Frequency	Frequency Range	Test Results	Conclusion
2402 MHz	Center Frequency	Fig.3	P
	30 MHz ~ 1 GHz	Fig.4	P
	1 GHz ~ 3 GHz	Fig.5	P
	3 GHz ~ 10 GHz	Fig.6	P
	10GHz ~ 26 GHz	Fig.7	P
2440 MHz	Center Frequency	Fig.8	P
	30 MHz ~ 1 GHz	Fig.9	P
	1 GHz ~ 3 GHz	Fig.10	P
	3 GHz ~ 10 GHz	Fig.11	P
	10GHz ~ 26 GHz	Fig.12	P
2480 MHz	Center Frequency	Fig.13	P
	30 MHz ~ 1 GHz	Fig.14	P
	1 GHz ~ 3GHz	Fig.15	P
	3 GHz ~ 10 GHz	Fig.16	P
	10 GHz ~ 26 GHz	Fig.17	P


Conclusion: PASS

Test graphs as below




Date: 28.AUG.2014 11:07:14

Fig.3. Conducted spurious emission: GFSK,2402MHz




Date: 28.AUG.2014 11:07:31

Fig.4. Conducted spurious emission: GFSK, 2402 MHz, 30MHz - 1GHz




Date: 28.AUG.2014 11:08:02

Fig.5. Conducted spurious emission: GFSK, 2402 MHz, 1GHz - 3GHz




Date: 28.AUG.2014 11:08:19

Fig.6. Conducted spurious emission: GFSK, 2402 MHz,3GHz - 10GHz




Date: 28.AUG.2014 11:08:36

Fig.7. Conducted spurious emission: GFSK, 2402 MHz,10GHz - 26GHz




Date: 28.AUG.2014 11:11:20

Fig.8. Conducted spurious emission: GFSK, 2440MHz




Date: 28.AUG.2014 11:11:36

Fig.9. Conducted spurious emission: GFSK, 2440 MHz, 30MHz - 1GHz




Date: 28.AUG.2014 11:12:08

Fig.10. Conducted spurious emission: GFSK, 2440 MHz, 1GHz – 3GHz




Date: 28.AUG.2014 11:12:24

Fig.11. Conducted spurious emission: GFSK, 2440 MHz, 3GHz – 10GHz




Date: 28.AUG.2014 11:12:41

Fig.12. Conducted spurious emission: GFSK, 2440 MHz, 10GHz – 26GHz




Date: 28.AUG.2014 11:14:21

Fig.13. Conducted spurious emission: GFSK, 2480 MHz




Date: 28.AUG.2014 11:14:38

Fig.14. Conducted spurious emission: GFSK, 2480 MHz, 30MHz - 1GHz




Date: 28.AUG.2014 11:15:09

Fig.15. Conducted spurious emission: GFSK, 2480 MHz, 1GHz - 3GHz



Date: 28.AUG.2014 11:15:26

Fig.16. Conducted spurious emission: GFSK, 2480 MHz, 3GHz - 10GHz



Date: 28.AUG.2014 11:15:42

Fig.17. Conducted spurious emission: GFSK, 2480 MHz, 10GHz - 26GHz

A.5. Radiated Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

Measurement Results:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable los.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}}$$

For GFSK

Frequency	Frequency Range	Test Results	Conclusion
2402 MHz	1 GHz ~ 3 GHz	Fig.18	P
	3 GHz ~ 18 GHz	Fig.19	P
2441 MHz	9 kHz ~ 30 MHz	Fig.20	P
	30 MHz ~ 1 GHz	Fig.21	P
	1 GHz ~ 3 GHz	Fig.22	P
	3 GHz ~ 18 GHz	Fig.23	P

2480 MHz	1 GHz ~ 3 GHz	Fig.24	P
	3 GHz ~ 18 GHz	Fig.25	P
Power	2.38GHz~2.4GHz---L	Fig.26	P
Power	2.45GHz~2.5GHz---H	Fig.27	P
For all channels	18 GHz ~ 26.5 GHz	Fig.28	P

GFSK 2402MHz–Average

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2390.000	33.6	-11.1	44.7	V
17989.500	44.6	27.9	16.7	V
17988.000	44.4	27.9	16.5	V
17994.000	44.3	27.9	16.4	H
17995.500	44.3	27.9	16.4	V
17997.000	44.3	27.9	16.4	V

GFSK 2440MHz–Average

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
17991.000	44.6	27.9	16.700	V
17997.000	44.6	27.9	16.700	V
17989.500	44.4	27.9	16.500	H
17998.500	44.3	27.9	16.400	V
17988.000	44.3	27.9	16.400	V
17992.500	44.2	27.9	16.300	V

GFSK 2480MHz–Average

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2483.500	34.3	-11.2	45.5	H
17998.500	44.4	27.9	16.5	H
18000.000	44.4	26.8	17.6	V
17991.000	44.3	27.9	16.4	V
17994.000	44.3	27.9	16.4	V
17995.500	44.3	27.9	16.4	V

GFSK 2402MHz–Peak

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2389.830	47.1	-11.1	58.2	V
17976.000	56.1	27.9	28.2	V
17986.500	55.4	27.9	27.5	V
17911.500	55.1	27.1	28.0	V
17997.000	55.1	27.9	27.2	V
17991.000	55.1	27.9	27.2	H

GFSK 2440MHz–Peak

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
17868.000	55.7	27.1	28.600	V
17956.500	55.6	27.9	27.700	V
17988.000	55.4	27.9	27.500	V
17991.000	55.4	27.9	27.500	V
17994.000	55.4	27.9	27.500	V
17775.000	55.3	27.1	28.200	V

GFSK 2480MHz–Peak

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2492.350	48.4	-11.2	59.6	V
17998.500	56.5	27.9	28.6	V
17799.000	55.4	27.1	28.3	V
17965.500	55.3	27.9	27.4	V
17982.000	55.2	27.9	27.3	V
17928.000	55.2	27.9	27.3	V

Conclusion: PASS

Test graphs as below:




Fig.18. Radiated emission: GFSK, 2402MHz, 1 GHz - 3GHz




Fig.19. Radiated emission: GFSK, 2402MHz, 3 GHz - 18 GHz




Fig.20. Transmitter Spurious Emission - Radiated: GFSK, 2440MHz, 9 kHz - 30 MHz




Fig.21. Radiated emission: GFSK, 2440MHz, 30 MHz - 1 GHz




Fig.22. Radiated emission: GFSK, 2440MHz, 1 GHz - 3 GHz




Fig.23. Radiated emission: GFSK, 2440MHz, 3 GHz - 18 GHz




Fig.24. Radiated emission: GFSK, 2480MHz, 1 GHz - 3 GHz




Fig.25. Radiated emission: GFSK, 2480MHz, 3 GHz - 18 GHz




Fig.26. Radiated emission (Power): GFSK low channel




Fig.27. Radiated emission (Power): GFSK high channel




Fig.28. Radiated emission: GFSK, 18 GHz - 26 GHz

A.6. 6dB Bandwidth

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(2)	$\geq 500\text{KHz}$

The measurement is made according to ANSI C63.10

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3\text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Condition

Hopping Mode	RBW	VBW	Span	Sweeptime
Hopping OFF	100kHz	300kHz	2MHz	2.5ms


Measurement Results:

For GFSK

Frequency	6dB Bandwidth (kHz)		Conclusion
2402MHz	Fig.29	689.10	P
2440MHz	Fig.30	695.51	P
2480MHz	Fig.31	692.31	P

Conclusion: PASS

Test graphs as below:



Date: 28.AUG.2014 11:13:35

Fig.31. 6dB Bandwidth: GFSK, 2480 MHz

A.7. Maximum Power Spectral Density Level

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(e)	$\leq 8.0\text{dBm}$


1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Set the span to 5-30 % greater than the EBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
9. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $\text{BWCF} = 10\log(3\text{ kHz}/100\text{kHz} = -15.2\text{ dB})$.

Measurement Results:

For GFSK


Frequency	Maximum Power Spectral Density Level(dBm)		Conclusion
2402MHz	Fig.32	-16.96	P
2440MHz	Fig.33	-16.77	P
2480MHz	Fig.34	-17.10	P

Test graphs as below:




Date: 28.AUG.2014 11:06:55

Fig.32. Maximum Power Spectral Density Level Function: GFSK, 2402 MHz



Date: 28.AUG.2014 11:11:01

Fig.33. Maximum Power Spectral Density Level Function: GFSK, 2440 MHz



Date: 28.AUG.2014 11:14:02

Fig.34. Maximum Power Spectral Density Level Function: GFSK, 2480 MHz

A.8. AC Powerline Conducted Emission

Test Condition

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	


NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10

Conclusion: PASS

Test graphs as below:

Traffic:




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.595500	34.8	GND	L1	9.8	21.2	56.0
0.843000	32.6	GND	L1	9.8	23.4	56.0
1.342500	30.0	GND	L1	9.7	26.0	56.0
2.764500	30.2	GND	L1	9.7	25.8	56.0
4.861500	29.6	GND	L1	9.8	26.4	56.0
6.882000	30.9	GND	L1	9.7	29.1	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.604500	15.9	GND	L1	9.8	30.1	46.0
0.852000	15.7	GND	L1	9.8	30.3	46.0
1.356000	12.6	GND	L1	9.7	33.4	46.0
2.850000	13.5	GND	L1	9.7	32.5	46.0
4.807500	11.5	GND	L1	9.8	34.5	46.0
6.882000	13.3	GND	L1	9.7	36.7	50.0

Idle:



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.618000	35.9	GND	L1	9.8	20.1	56.0
0.870000	32.3	GND	L1	9.8	23.7	56.0
1.068000	31.7	GND	L1	9.7	24.3	56.0
1.315500	30.1	GND	L1	9.7	25.9	56.0
2.800500	30.6	GND	L1	9.7	25.4	56.0
4.722000	29.9	GND	L1	9.8	26.1	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.649500	17.7	GND	L1	9.8	28.3	46.0
1.063500	14.8	GND	L1	9.7	31.2	46.0
1.315500	12.9	GND	L1	9.7	33.1	46.0
2.832000	13.2	GND	L1	9.7	32.8	46.0
4.722000	12.4	GND	L1	9.8	33.6	46.0
6.418500	13.2	GND	L1	9.7	36.8	50.0

*** END OF REPORT BODY ***