FCC RF Test Report

APPLICANT	: ZTE CORPORATION
EQUIPMENT	: LTE/CDMA Mutil-Mode Digital Mobile Phone
BRAND NAME	: ZTE
MODEL NAME	: N9132
FCC ID	: SRQ-ZTEN9132
STANDARD	: 47 CFR Part 2, 22(H), 24(E), 27(M)
CLASSIFICATION	: PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Aug. 17, 2015 and completely tested on Sep. 15, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager

Testing Laboratory
2627

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **6**

1.1 Applicant 6
1.2 Manufacturer 6
1.3 Product Feature of Equipment Under Test 6
1.4 Product Specification subjective to this standard 7
1.5 Modification of EUT 8
1.6 Emission Designator 8
1.7 Testing Location 9
1.8 Applicable Standards 9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **10**

2.1 Test Mode 10
2.2 Connection Diagram of Test System 12
2.3 Support Unit used in test configuration and system 12
2.4 Measurement Results Explanation Example 13

3 CONDUCTED TEST ITEMS **14**

3.1 Measuring Instruments 14
3.2 Test Setup 14
3.3 Test Result of Conducted Test 14
3.4 Conducted Output Power and ERP/EIRP 15
3.5 Peak-to-Average Ratio 16
3.6 Occupied Bandwidth 17
3.7 Conducted Band Edge 18
3.8 Conducted Spurious Emission 20
3.9 Frequency Stability 21

4 RADIATED TEST ITEMS **22**

4.1 Measuring Instruments 22
4.2 Test Setup 22
4.3 Test Result of Radiated Test 22
4.4 Effective Radiated Power and Effective Isotropic Radiated Power 23
4.5 Radiated Spurious Emission 25

5 LIST OF MEASURING EQUIPMENT **26**

6 UNCERTAINTY OF EVALUATION **27**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG581705B	Rev. 01	Initial issue of report	Sep. 18, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Conducted Band Edge Measurement (Band 25) (Band 26)	< 43+10log10(P[Watts])	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 41)	Offset 0 ~ 5MHz: < 40+10log10(P[Watts]) Offset 5 ~ 6MHz or EBW: < 43+10log10(P[Watts])		

Report Section	FCC Rule	Description	Limit	Result	Remark
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission (Band 25) (Band 26)	< 43+10log10(P[Watts])	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 41)	< 55+10log$_{10}$(P[Watts])		
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§22.913(a)(2)	Effective Radiated Power (Band 26)	ERP < 7 Watt	PASS	-
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 25) (Band 41)	EIRP < 2Watt		
4.5	§2.1053 §22.917(a) §24.238(a)	Radiated Spurious Emission (Band 25) (Band 26)	< 43+10log$_{10}$(P[Watts])	PASS	Under limit 15.90 dB at 10356.000 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 41)	< 55+10log$_{10}$(P[Watts])		

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE/CDMA Mutil-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	N9132
FCC ID	SRQ-ZTEN9132
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/LTE WLAN2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0+EDR Bluetooth v4.0 LE
IMEI Code	Conducted: 990006080001054 Radiation: 990006080008682 ERP/EIRP: 867232020015658
HW Version	cvzA
SW Version	N9132V1.0.0B01
EUT Stage	Identical Prototype

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	LTE Band 25 : 1850.7MHz ~ 1914.3 MHz LTE Band 26 : 824.7 MHz ~ 848.3 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz
Rx Frequency	LTE Band 25 : 1930.7MHz ~ 1994.3 MHz LTE Band 26: 869.7 MHz ~ 893.3 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz
Bandwidth	LTE Band 25 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 26 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz LTE Band 41 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 25 : 23.25 dBm LTE Band 26 : 23.85 dBm LTE Band 41 : 23.62 dBm
Type of Modulation	QPSK / 16QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Emission Designator

LTE Band 25	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1M10G7D	-	0.4721	1M10W7D	-	0.4046
3	2M74G7D	-	0.4710	2M74W7D	-	0.4046
5	4M53G7D	-	0.4887	4M50W7D	-	0.3990
10	9M09G7D	0.0356	0.4560	9M03W7D	-	0.4207
15	13M4G7D	-	0.4467	13M4W7D	-	0.3784
20	18M2G7D	-	0.4295	18M2W7D	-	0.3581
LTE Band 26	**QPSK**			**16QAM**		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	1M10G7D	-	0.1854	1M09W7D	-	0.1687
3	2M73G7D	-	0.2004	2M74W7D	-	0.1656
5	4M51G7D	-	0.1945	4M52W7D	-	0.1560
10	9M07G7D	0.0209	0.1968	9M03W7D	-	0.1762
15	13M5G7D	-	0.1871	13M5W7D	-	0.1754
15 (ch 26765)	13M5G7D	-	0.1923	13M5W7D	-	0.1589
LTE Band 41	**QPSK**			**16QAM**		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	4M52G7D	-	0.3243	4M51W7D	-	0.2415
10	9M07G7D	0.0077	0.3266	9M05W7D	-	0.2594
15	13M6G7D	-	0.3141	13M5W7D	-	0.2523
20	18M4G7D	-	0.3170	18M5W7D	-	0.2523

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	**Sporton Site No.**		**FCC Registration No.**
	TH01-KS	03CH02-KS	418269

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(M)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	25	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v
	41	-	-	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	25						v	v	v	v		v	v	v	v
	26					v	-	v	v	v		v	v	v	v
	41	-	-				v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	25	v	v	v	v	v	v	v	v			v	v	v	v
	26	v	v	v	v	v	-	v	v			v	v	v	v
	41	-	-	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	25	v	v	v	v	v	v	v	v	v		v	v		v
	26	v	v	v	v	v	-	v	v	v		v	v		v
	41	-	-	v	v	v	v	v	v	v		v	v		v

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Conducted Spurious Emission	25	v	v	v	v	v	v	v	v	v			v	v	v
	26	v	v	v	v	v	-	v	v	v			v	v	v
	41	-	-	v	v	v	v	v	v	v			v	v	v
Frequency Stability	25				v			v				v		v	
	26				v		-	v				v		v	
	41	-	-		v			v				v		v	
E.R.P./ E.I.R.P.	25	v	v	v	v	v	v	v	v	v			v	v	v
	26	v	v	v	v	v	-	v	v	v			v	v	v
	41	-	-	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	25	v	v	v	v	v	v	v		v				v	
	25	v	v	v	v	v	-	v		v				v	
	41	-	-	v	v	v	v	v		v				v	
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	Lenovo	SH100	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6.0 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 6.0 (dB)

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power

3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a) for Band 26

For operations in the 824 – 849 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a) for Band 25

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4) for FCC Band 41:

For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

   = -13dBm.
9. For LTE Band 7, 41, the other 40 dB, and 55 dB have additionally applied same calculation above.

   The limit line is derived from 40+ 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [40 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [40 + 10log(P)] (dB)

   = -10dBm

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

   = -13dBm.

   The limit line is derived from 55+ 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [55 + 10log(P)] (dB)

   = [55 + 10log(P)] (dBm) - [55 + 10log(P)] (dB)

   = -25dBm

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 41:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10^{th} harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.
11. For Band 41
    The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [55+ 10log(P)] (dB)
    = [30+ 10log(P)] (dBm) - [55+ 10log(P)] (dB)
    = -25dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Effective Radiated Power and Effective Isotropic Radiated Power

4.4.1 Description of the ERP/EIRP Measurement

Effective radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-C-2004, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average ERP of 7 watts with LTE band 26.

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-C-2004, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 25 / 41.

4.4.2 Test Procedures

1. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, EIRP = LVL + Correction factor and ERP = EIRP - 2.15. Take the record of the output power at substitution antenna.

	LTE Average					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	100kHz	100kHz	300kHz	300kHz	300kHz
VBW	100kHz	300kHz	300kHz	1MHz	1MHz	1MHz
Detector	RMS	RMS	RMS	RMS	RMS	RMS
Trace	Average	Average	Average	Average	Average	Average
Average Type	Power	Power	Power	Power	Power	Power
Sweep Count	100	100	100	100	100	100

4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.
    For Band 41:
    The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)
12. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
13. ERP (dBm) = EIRP - 2.15

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	9kHz~30GHz	May 04, 2015	Aug. 27, 2015~ Sep. 15, 2015	May 03, 2016	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 25, 2014	Aug. 27, 2015~ Sep. 15, 2015	Oct. 24, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Sep. 10, 2015	Sep. 13, 2015~ Sep. 15, 2015	Sep. 09, 2016	Radiation (03CH02-KS)
Spectrum Analyzer	R&S	FSV40	101040	10kHz~40GHz;Max 30dBm	Sep. 10, 2015	Sep. 13, 2015~ Sep. 15, 2015	Sep. 09, 2016	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz-2GHz	Sep. 12, 2015	Sep. 13, 2015~ Sep. 15, 2015	Sep. 11, 2016	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014	Sep. 13, 2015~ Sep. 15, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Sep. 13, 2015~ Sep. 15, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz ~40GHz	Mar. 03, 2015	Sep. 13, 2015~ Sep. 15, 2015	Mar. 02, 2016	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz ~1000MHz / 32 dB	May 04, 2015	Sep. 13, 2015~ Sep. 15, 2015	May 03, 2016	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1-26.5GHz Gain 30dB	Oct. 28, 2014	Sep. 13, 2015~ Sep. 15, 2015	Oct. 27, 2015	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Sep. 13, 2015~ Sep. 15, 2015	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Sep. 13, 2015~ Sep. 15, 2015	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Sep. 13, 2015~ Sep. 15, 2015	NCR	Radiation (03CH02-KS)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.1 dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.59	22.73	22.77
1.4	1	2		22.82	22.97	23.07
1.4	1	5		22.50	22.93	22.97
1.4	3	0		22.80	22.87	22.81
1.4	3	1		22.79	22.91	22.99
1.4	3	2		22.80	22.90	23.04
1.4	6	0		21.78	21.84	21.95
1.4	1	0	16-QAM	21.85	22.11	21.92
1.4	1	2		21.99	22.24	22.28
1.4	1	5		21.77	22.16	22.25
1.4	3	0		21.76	22.02	22.16
1.4	3	1		21.94	22.02	22.17
1.4	3	2		21.95	22.00	22.15
1.4	6	0		20.57	20.63	20.92
3	1	0	QPSK	22.60	22.62	22.89
3	1	7		22.69	22.91	23.16
3	1	14		22.49	22.84	23.03
3	8	0		21.70	21.87	21.78
3	8	4		21.66	21.85	21.96
3	8	7		21.74	21.88	21.90
3	15	0		21.61	21.77	21.90
3	1	0	16-QAM	22.09	22.00	22.09
3	1	7		22.41	22.13	21.99
3	1	14		22.13	22.11	22.28
3	8	0		21.06	20.91	20.71
3	8	4		21.35	20.90	20.69
3	8	7		20.53	20.81	20.93
3	15	0		20.41	20.89	20.60

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.65	22.66	22.75
5	1	12		22.77	22.94	22.89
5	1	24		22.61	22.83	22.85
5	12	0		21.68	21.80	21.80
5	12	6		21.65	21.86	21.69
5	12	11		21.74	21.80	21.89
5	25	0		21.72	21.86	21.80
5	1	0	16-QAM	22.02	22.21	22.10
5	1	12		22.05	22.32	22.16
5	1	24		22.04	22.15	22.07
5	12	0		20.65	20.85	20.54
5	12	6		20.67	20.75	20.75
5	12	11		20.63	20.85	20.60
5	25	0		20.64	20.92	20.64
10	1	0	QPSK	22.76	22.66	22.82
10	1	24		22.82	23.00	22.91
10	1	49		22.75	22.81	22.90
10	25	0		21.72	21.67	21.93
10	25	12		21.73	21.91	21.75
10	25	24		21.84	21.90	21.73
10	50	0		21.78	21.86	21.76
10	1	0	16-QAM	22.01	21.90	22.24
10	1	24		22.09	22.08	22.28
10	1	49		22.03	22.01	22.11
10	25	0		20.77	20.85	20.80
10	25	12		20.79	20.80	20.76
10	25	24		21.00	20.95	20.66
10	50	0		20.76	20.83	20.75

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.90	22.45	22.84
15	1	37		23.13	22.99	23.03
15	1	74		22.45	22.72	22.89
15	36	0		21.79	21.76	21.98
15	36	18		21.85	21.86	21.90
15	36	37		21.74	21.89	21.75
15	75	0		21.82	21.84	21.93
15	1	0	16-QAM	21.87	21.54	21.96
15	1	37		22.13	22.17	22.25
15	1	74		21.51	21.96	22.20
15	36	0		20.84	20.76	20.91
15	36	18		20.93	20.78	20.80
15	36	37		20.75	20.79	20.68
15	75	0		20.79	20.78	20.72
20	1	0	QPSK	22.86	22.78	22.94
20	1	49		22.97	23.07	23.25
20	1	99		22.35	22.86	23.07
20	50	0		21.80	21.71	21.90
20	50	24		21.83	21.90	21.94
20	50	49		21.63	21.89	21.87
20	100	0		21.75	21.83	21.85
20	1	0	16-QAM	22.03	22.07	22.16
20	1	49		22.11	22.11	22.18
20	1	99		21.64	21.96	21.79
20	50	0		20.89	20.75	21.00
20	50	24		20.75	20.82	20.86
20	50	49		20.50	20.77	20.79
20	100	0		20.73	20.85	20.92

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.40	23.20	23.31
1.4	1	2		23.42	23.19	23.32
1.4	1	5		23.30	23.03	23.12
1.4	3	0		23.38	23.14	23.35
1.4	3	1		23.41	23.16	23.28
1.4	3	2		23.40	23.16	23.33
1.4	6	0		22.48	22.30	22.39
1.4	1	0	16-QAM	22.62	22.58	22.62
1.4	1	2		22.61	22.48	22.38
1.4	1	5		22.63	22.28	22.04
1.4	3	0		22.59	22.55	22.54
1.4	3	1		22.62	22.52	22.60
1.4	3	2		22.62	22.21	22.52
1.4	6	0		21.23	21.10	21.09
3	1	0	QPSK	23.45	23.26	23.37
3	1	7		23.38	23.42	23.33
3	1	14		23.17	23.34	23.24
3	8	0		22.46	22.28	22.44
3	8	4		22.50	22.25	22.22
3	8	7		22.37	22.20	22.25
3	15	0		22.42	22.21	22.25
3	1	0	16-QAM	22.73	22.65	22.69
3	1	7		22.64	22.51	22.50
3	1	14		22.60	22.51	22.53
3	8	0		21.49	21.27	21.21
3	8	4		21.44	21.14	21.07
3	8	7		21.41	21.18	21.19
3	15	0		21.52	21.16	20.94

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.47	23.37	23.38
5	1	12		23.40	23.47	23.39
5	1	24		23.25	23.35	23.23
5	12	0		22.48	22.37	22.32
5	12	6		22.30	22.22	22.25
5	12	11		22.30	22.21	22.18
5	25	0		22.34	22.18	22.18
5	1	0	16-QAM	22.70	22.63	22.50
5	1	12		22.50	22.49	22.47
5	1	24		22.55	22.48	22.46
5	12	0		21.34	21.49	21.24
5	12	6		21.21	21.15	21.09
5	12	11		21.16	21.01	21.05
5	25	0		21.32	21.22	21.29
10	1	0	QPSK	23.33	23.48	23.12
10	1	24		23.44	23.35	23.53
10	1	49		23.29	23.30	23.27
10	25	0		22.47	22.33	22.32
10	25	12		22.43	22.22	22.37
10	25	24		22.37	22.22	22.29
10	50	0		22.45	22.29	22.39
10	1	0	16-QAM	22.71	22.71	22.62
10	1	24		22.66	22.16	22.68
10	1	49		22.54	22.49	22.42
10	25	0		21.50	21.35	21.31
10	25	12		21.42	21.22	21.17
10	25	24		21.28	21.09	21.09
10	50	0		21.36	21.09	21.27

LTE Band 26 Maximum Average Power [dBm]							
BW [MHz]	RB Size	RB Offset	Mod	Ch26765	Lowest	Middle	Highest
15	1	0	QPSK	23.61	23.32	23.39	23.54
15	1	37		23.85	23.06	23.05	23.39
15	1	74		23.45	23.05	23.10	23.16
15	36	0		22.72	22.32	22.26	22.25
15	36	18		22.55	22.21	22.18	22.34
15	36	37		22.54	22.21	22.18	22.23
15	75	0		22.53	22.23	22.13	22.23
15	1	0	16-QAM	22.88	22.69	22.67	22.64
15	1	37		22.91	22.38	22.07	22.57
15	1	74		22.67	22.02	22.39	22.24
15	36	0		21.70	21.04	21.24	21.14
15	36	18		21.50	21.14	21.13	21.21
15	36	37		21.53	21.12	20.98	21.29
15	75	0		21.40	20.98	21.12	21.22

LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.17	22.82	23.06
5	1	12		23.54	23.21	23.19
5	1	24		23.32	22.89	22.97
5	12	0		22.31	22.21	22.17
5	12	6		22.43	22.11	22.21
5	12	11		22.53	22.19	22.26
5	25	0		22.49	22.16	22.21
5	1	0	16-QAM	22.36	22.11	21.94
5	1	12		22.58	21.80	21.99
5	1	24		22.53	22.13	22.32
5	12	0		21.44	21.12	21.28
5	12	6		21.51	20.96	21.10
5	12	11		21.47	21.11	21.11
5	25	0		21.71	21.24	21.23
10	1	0	QPSK	23.40	23.07	23.12
10	1	24		23.62	23.12	23.20
10	1	49		23.55	22.82	23.17
10	25	0		22.71	22.18	22.19
10	25	12		22.78	22.28	22.11
10	25	24		22.54	22.24	22.11
10	50	0		22.54	22.30	22.17
10	1	0	16-QAM	22.30	22.11	22.07
10	1	24		22.62	22.18	22.06
10	1	49		22.61	21.88	22.30
10	25	0		21.81	21.36	21.54
10	25	12		21.72	21.28	21.19
10	25	24		21.62	21.27	21.19
10	50	0		21.42	21.17	21.15

LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.37	22.82	22.83
15	1	37		23.28	22.57	22.97
15	1	74		23.32	22.69	22.89
15	36	0		22.48	22.08	22.19
15	36	18		22.54	21.96	22.25
15	36	37		22.48	21.92	22.12
15	75	0		22.48	22.05	22.10
15	1	0	16-QAM	22.26	22.26	22.17
15	1	37		22.16	21.92	22.00
15	1	74		22.07	22.04	21.71
15	36	0		21.58	21.22	21.26
15	36	18		21.54	21.10	21.29
15	36	37		21.48	21.08	21.25
15	75	0		21.41	21.07	21.17
20	1	0	QPSK	23.52	23.03	23.10
20	1	49		23.49	22.82	23.05
20	1	99		23.41	22.85	22.99
20	50	0		22.64	22.17	22.15
20	50	24		22.47	22.07	22.11
20	50	49		22.46	22.00	22.11
20	100	0		22.46	22.15	22.11
20	1	0	16-QAM	22.40	22.16	22.20
20	1	49		22.27	22.06	22.05
20	1	99		21.88	22.07	22.01
20	50	0		21.57	21.24	21.17
20	50	24		21.44	21.10	21.13
20	50	49		21.23	21.04	21.10
20	100	0		21.42	21.12	21.20

Peak-to-Average Ratio

Mode	LTE Band 25 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.26	4.41	5.30	5.57	PASS
Middle CH	4.58	4.70	5.36	5.71	
Highest CH	4.46	4.58	4.87	5.71	

Mode	LTE Band 26 / 15MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.39	4.96	4.12	5.77	PASS
Middle CH	3.36	5.22	4.23	6.03	
Highest CH	3.30	4.78	4.14	5.86	

Mode	LTE Band 41 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.80	4.75	5.86	6.43	PASS
Middle CH	4.29	5.30	5.36	6.20	
Highest CH	3.57	4.81	5.83	6.00	

LTE Band 25 / 20MHz / QPSK	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
	
Middle Channel / 1RB	**Middle Channel / Full RB**
	
Highest Channel / 1RB	**Highest Channel / Full RB**
	

LTE Band 25 / 20MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
	
Middle Channel / 1RB	**Middle Channel / Full RB**
	
Highest Channel / 1RB	**Highest Channel / Full RB**
	

LTE Band 26 / 15MHz / QPSK	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
	
Middle Channel / 1RB	**Middle Channel / Full RB**
	
Highest Channel / 1RB	**Highest Channel / Full RB**
	

LTE Band 26 / 15MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
	
Middle Channel / 1RB	**Middle Channel / Full RB**
	
Highest Channel / 1RB	**Highest Channel / Full RB**
	

LTE Band 41 / 20MHz / QPSK	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
	
Middle Channel / 1RB	**Middle Channel / Full RB**
Highest Channel / 1RB	**Highest Channel / Full RB**
	

LTE Band 41 / 20MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
	
Middle Channel / 1RB	**Middle Channel / Full RB**
	
Highest Channel / 1RB	**Highest Channel / Full RB**
	

26dB Bandwidth

Mode	LTE Band 25 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.30	1.26	3.01	3.00	4.95	4.86	9.75	9.75	14.21	14.57	20.06	19.94
Middle CH	1.28	1.27	2.99	3.01	4.84	4.89	9.71	9.73	14.51	14.42	20.22	20.06
Highest CH	1.26	1.26	3.02	3.00	4.85	5.00	9.83	9.95	14.27	14.33	19.94	20.30

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		Ch26765	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.30	1.30	3.01	3.02	4.95	4.92	9.77	9.79	14.75	14.36	14.63	14.72
Middle CH	1.27	1.30	3.02	2.97	4.94	4.93	9.81	9.89	14.39	14.51	-	-
Highest CH	1.28	1.29	2.99	3.05	4.98	4.91	9.79	9.81	14.42	14.24	-	-

Mode	LTE Band 41 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.79	4.86	9.63	9.63	14.39	14.15	20.18	20.14
Middle CH	-	-	-	-	4.74	4.81	9.71	9.63	14.30	14.27	20.22	20.10
Highest CH	-	-	-	-	4.74	4.94	9.69	9.69	14.15	14.15	20.14	20.18

LTE Band 25

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 25

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel /3MHz / 16QAM



Highest Channel /3MHz / QPSK



Highest Channel /3MHz / 16QAM



LTE Band 25

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 25

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 25

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK



Highest Channel / 15MHz / 16QAM



LTE Band 25

Lowest Channel / 20MHz / QPSK



Lowest Channel / 20MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK



Highest Channel / 20MHz / 16QAM



LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK

Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel /3MHz / 16QAM



Highest Channel /3MHz / QPSK



Highest Channel /3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 26

Channel 26765 / 15MHz / QPSK



Channel 26765 / 15MHz / 16QAM



Lowest Channel / 15MHz / QPSK

Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



LTE Band 26	
Highest Channel / 15MHz / QPSK	**Highest Channel / 15MHz / 16QAM**





LTE Band 41

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK

Highest Channel / 5MHz / 16QAM



LTE Band 41

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK

Highest Channel / 10MHz / 16QAM



LTE Band 41

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK



Highest Channel / 15MHz / 16QAM



LTE Band 41

Lowest Channel / 20MHz / QPSK



Lowest Channel / 20MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK



Highest Channel / 20MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 25 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.10	2.72	2.72	4.49	4.50	8.99	9.03	13.34	13.40	18.02	18.22
Middle CH	1.09	1.09	2.73	2.73	4.53	4.49	9.01	8.95	13.43	13.40	18.14	18.22
Highest CH	1.10	1.10	2.74	2.74	4.50	4.48	9.09	9.03	13.40	13.43	18.22	18.18

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		Ch26765	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.10	1.09	2.72	2.72	4.49	4.49	8.99	8.97	13.43	13.46	13.49	13.49
Middle CH	1.09	1.09	2.72	2.72	4.51	4.52	9.07	9.03	13.52	13.49	-	-
Highest CH	1.10	1.09	2.73	2.74	4.49	4.50	8.95	8.95	13.40	13.40	-	-

Mode	LTE Band 41 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.51	4.50	8.97	8.93	13.43	13.31	18.22	18.46
Middle CH	-	-	-	-	4.50	4.50	9.01	9.05	13.58	13.52	18.22	18.30
Highest CH	-	-	-	-	4.52	4.51	9.07	9.03	13.40	13.37	18.42	18.38

LTE Band 25

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 25

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 25

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 25

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 25

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM

Highest Channel / 15MHz / QPSK



Highest Channel / 15MHz / 16QAM



LTE Band 25

Lowest Channel / 20MHz / QPSK



Lowest Channel / 20MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK



Highest Channel / 20MHz / 16QAM



LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 26

Channel 26765 / 15MHz / QPSK



Channel 26765 / 15MHz / 16QAM



Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



LTE Band 26	
Highest Channel / 15MHz / QPSK	**Highest Channel / 15MHz / 16QAM**
	

LTE Band 41

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 41

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 41

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK



Highest Channel / 15MHz / 16QAM



LTE Band 41

Lowest Channel / 20MHz / QPSK



Lowest Channel / 20MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK



Highest Channel / 20MHz / 16QAM



Conducted Band Edge

LTE Band 25 / 1.4MHz / QPSK

Lowest Band Edge / 1RB



Date:27.AUG.2015 20:13:31

Highest Band Edge / 1RB



Date:27.AUG.2015 20:07:28

Lowest Band Edge / Full RB



Date:27.AUG.2015 21:45:54

Highest Band Edge / Full RB



Date:27.AUG.2015 20:03:02

LTE Band 25 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB



Date:27.AUG.2015 20:14:44

Highest Band Edge / 1 RB



Date:27.AUG.2015 20:06:06

Lowest Band Edge / Full RB



Date:27.AUG.2015 20:15:33

Highest Band Edge / Full RB



Date:27.AUG.2015 20:04:41