



# FCC RF Test Report

**APPLICANT** : ZTE CORPORATION  
**EQUIPMENT** : LTE/CDMA/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone  
**BRAND NAME** : ZTE  
**MODEL NAME** : N9560  
**FCC ID** : SRQ-ZTEN9560  
**STANDARD** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure

The product was received on Jan. 09, 2017 and testing was completed on Jan. 25, 2017. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China**



# TABLE OF CONTENTS

**REVISION HISTORY ..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test ..... 5

    1.4 Product Specification of Equipment Under Test ..... 6

    1.5 Modification of EUT ..... 7

    1.6 Testing Location ..... 7

    1.7 Applicable Standards ..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1 Carrier Frequency and Channel ..... 8

    2.2 Test Mode ..... 9

    2.3 Connection Diagram of Test System ..... 10

    2.4 Support Unit used in test configuration and system ..... 11

    2.5 EUT Operation Test Setup ..... 11

    2.6 Measurement Results Explanation Example ..... 11

**3 TEST RESULT ..... 12**

    3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement ..... 12

    3.2 Maximum Conducted Output Power Measurement ..... 15

    3.3 Power Spectral Density Measurement ..... 16

    3.4 Unwanted Emissions Measurement ..... 19

    3.5 AC Conducted Emission Measurement ..... 24

    3.6 Frequency Stability Measurement ..... 28

    3.7 Automatically Discontinue Transmission ..... 29

    3.8 Antenna Requirements ..... 30

**4 LIST OF MEASURING EQUIPMENT ..... 31**

**5 UNCERTAINTY OF EVALUATION ..... 32**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. RADIATED SPURIOUS EMISSION**

**APPENDIX C. DUTY CYCLE PLOTS**

**APPENDIX D. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 7.82 dB at 11650.000 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.39 dB at 0.555 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.2 Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	LTE/CDMA/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone
<b>Brand Name</b>	ZTE
<b>Model Name</b>	N9560
<b>FCC ID</b>	SRQ-ZTEN9560
<b>EUT supports Radios application</b>	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/LTE/WLAN 2.4GHz 802.11b/g/n HT20/HT40/WLAN 5GHz 802.11a/n HT20/HT40/WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/Bluetooth v3.0+EDR/Bluetooth v4.0 LE/Bluetooth v4.2 LE
<b>MEID/IMEI Code</b>	Conducted: 99000882000772 Radiation: 990008820007214 Conduction: 990006880007206
<b>HW Version</b>	N9560HW1.0
<b>SW Version</b>	N9560V1.0.0B01
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Channel Frequency Range</b>	5745 MHz ~ 5825 MHz
<b>Maximum Output Power</b>	802.11a : 17.05 dBm / 0.0507 W 802.11n HT20 : 15.86 dBm / 0.0385 W 802.11n HT40 : 15.58 dBm / 0.0361 W 802.11ac VHT20: 15.72 dBm / 0.0373 W 802.11ac VHT40: 10.19 dBm / 0.0104 W 802.11ac VHT80: 10.11 dBm / 0.0103 W
<b>99% Occupied Bandwidth</b>	802.11a : 18.63 MHz 802.11n HT20 : 19.43 MHz 802.11n HT40 : 36.86 MHz 802.11ac VHT80 : 74.69 MHz
<b>Antenna Type / Gain</b>	PIFA Antenna with gain -2 dBi
<b>Type of Modulation</b>	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

**Note:** For 802.11n HT20/ac VHT20 and 802.11n HT40/ac VHT40 mode, the whole testing has assessed only 802.11n HT20/HT40 by referring to their maximum conducted power.



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.			
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC Registration No.</b>
	TH01-KS	03CH02-KS	CO01-KS	418269

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03
- ♦ FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

**Note:**

1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "#n" were 802.11ac VHT80.



## 2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.


Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0

Test Cases	
<b>AC Conducted Emission</b>	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter) + Earphone
<b>Remark:</b> For radiated TCs, the tests were performed with USB cable, adapter and earphone.	


Ch. #		Band IV : 5745-5825 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
<b>L</b>	<b>Low</b>	149	149	151	-
<b>M</b>	<b>Middle</b>	157	157	-	155
<b>H</b>	<b>High</b>	165	165	159	-

## 2.3 Connection Diagram of Test System

### <Radiated Emission Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2m	N/A
5.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A

## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 7.5dB.

$$\begin{aligned}
 \text{Offset (dB)} &= \text{RF cable loss (dB)} \\
 &= 7.5 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.



##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where  $x$  is the duty cycle.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section F) Maximum power spectral density.


##### # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW  $\geq$  1 MHz.
- Number of points in sweep  $\geq$  2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add  $10 \log(500\text{kHz}/\text{RBW})$  to the test result.
- Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.


### 3.3.4 Test Setup





### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.





### 3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

#### 3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:** The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBµV/m)
-17	78.3
- 27	68.3

(3) KDB 789033 D02 General UNII Test Procedures New Rules v01r03 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold


(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





### **3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### **3.4.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix B.

### **3.4.7 Duty Cycle**

Please refer to Appendix C.

### **3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)**

Please refer to Appendix B.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.5.4 Test Setup





### 3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Peter Wei	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter) + Earphone		




Site : CO01-KS  
 Condition : FCC PART 15E LISN-L-20151024 LINE

IMEI : 990006880007206

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.150	48.72	-17.28	66.00	37.80	0.53	10.39	QP
2	0.150	37.72	-18.28	56.00	26.80	0.53	10.39	Average
3	0.208	38.75	-24.52	63.27	28.21	0.22	10.32	QP
4	0.208	27.75	-25.52	53.27	17.21	0.22	10.32	Average
5	0.341	37.46	-21.72	59.18	27.00	0.23	10.23	QP
6	0.341	28.66	-20.52	49.18	18.20	0.23	10.23	Average
7	0.413	35.63	-21.96	57.59	25.20	0.23	10.20	QP
8	0.413	27.53	-20.06	47.59	17.10	0.23	10.20	Average
9	0.459	35.52	-21.19	56.71	25.10	0.23	10.19	QP
10	0.459	26.92	-19.79	46.71	16.50	0.23	10.19	Average
11	4.952	33.93	-22.07	56.00	23.50	0.19	10.24	QP
12	4.952	28.43	-17.57	46.00	18.00	0.19	10.24	Average



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Peter Wei	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter) + Earphone		



Site : CO01-KS  
 Condition : FCC PART 15E LISN-N-20151024 NEUTRAL

IMEI : 990006880007206

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.337	45.55	-13.72	59.27	35.00	0.32	10.23	QP
2	0.337	37.45	-11.82	49.27	26.90	0.32	10.23	Average
3	0.391	40.52	-17.51	58.03	30.00	0.32	10.20	QP
4	0.391	34.02	-14.01	48.03	23.50	0.32	10.20	Average
5	0.433	42.51	-14.69	57.20	31.99	0.32	10.20	QP
6	0.433	33.11	-14.09	47.20	22.59	0.32	10.20	Average
7	0.471	44.11	-12.38	56.49	33.60	0.32	10.19	QP
8	0.471	34.31	-12.18	46.49	23.80	0.32	10.19	Average
9	0.555	43.11	-12.89	56.00	32.60	0.33	10.18	QP
10 *	0.555	35.61	-10.39	46.00	25.10	0.33	10.18	Average
11	2.900	38.19	-17.81	56.00	27.60	0.37	10.22	QP
12	2.900	30.59	-15.41	46.00	20.00	0.37	10.22	Average
13	3.740	39.60	-16.40	56.00	29.00	0.37	10.23	QP
14	3.740	31.90	-14.10	46.00	21.30	0.37	10.23	Average
15	4.224	40.70	-15.30	56.00	30.10	0.36	10.24	QP
16	4.224	32.00	-14.00	46.00	21.40	0.36	10.24	Average
17	4.874	41.20	-14.80	56.00	30.60	0.36	10.24	QP
18	4.874	33.20	-12.80	46.00	22.60	0.36	10.24	Average
19	6.454	41.78	-18.22	60.00	31.20	0.31	10.27	QP
20	6.454	34.18	-15.82	50.00	23.60	0.31	10.27	Average
21	7.810	41.99	-18.01	60.00	31.40	0.29	10.30	QP
22	7.810	33.79	-16.21	50.00	23.20	0.29	10.30	Average

### 3.6 Frequency Stability Measurement

#### 3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

#### 3.6.4 Test Setup



#### 3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



## **3.7 Automatically Discontinue Transmission**

### **3.7.1 Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **3.7.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.7.3 Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



## **3.8 Antenna Requirements**

### **3.8.1 Standard Applicable**

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.8.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.8.3 Antenna Gain**

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Jan. 17, 2017	Aug. 08, 2017	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Jan. 17, 2017	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Jan. 17, 2017	Jan. 19, 2017	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Aug. 09, 2016	Jan. 25, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz, MAX 30dB	Apr. 22, 2016	Jan. 25, 2017	Apr. 21, 2017	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Jan. 25, 2017	Nov. 22, 2017	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Aug. 20, 2016	Jan. 25, 2017	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Jan. 25, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 03, 2016	Jan. 25, 2017	Mar. 02, 2017	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	Apr. 22, 2016	Jan. 25, 2017	Apr. 21, 2017	Radiation (03CH02-KS)
High Gain Amplifier	MITEQ	AMF-7D-00101 800-30-10P	1943529	1GHz~18GHz	Jan. 19, 2017	Jan. 25, 2017	Jan. 18, 2018	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1GHz~26.5GHz	Oct. 13, 2016	Jan. 25, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18GHz~40GHz	Oct. 13, 2016	Jan. 25, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Jan. 25, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 25, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 25, 2017	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz	Apr. 29, 2016	Jan. 22, 2017	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Jan. 22, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Jan. 22, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Jan. 22, 2017	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1 dB
---	--------



## Appendix A. Conducted Test Results

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	Jan. 17, 2017	Relative Humidity:	51~55	%

**TEST RESULTS DATA**  
**6dB and 26dB EBW and 99% OBW**

Band IV									
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	18.63	23.73	16.36	0.5	Pass
11a	6Mbps	1	157	5785	18.63	23.83	16.34	0.5	Pass
11a	6Mbps	1	165	5825	18.53	23.48	16.44	0.5	Pass
HT20	MCS 0	1	149	5745	19.43	23.88	17.58	0.5	Pass
HT20	MCS 0	1	157	5785	19.38	23.83	17.58	0.5	Pass
HT20	MCS 0	1	165	5825	19.33	23.88	17.60	0.5	Pass
HT40	MCS 0	1	151	5755	36.76	45.50	35.37	0.5	Pass
HT40	MCS 0	1	159	5795	36.86	45.23	35.68	0.5	Pass
VHT80	MCS 0	1	155	5775	74.69	84.4	75.13	0.5	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.60	17.01	30.00	-2.00	Pass
11a	6Mbps	1	157	5785	0.60	16.84	30.00	-2.00	Pass
11a	6Mbps	1	165	5825	0.60	17.05	30.00	-2.00	Pass
HT20	MCS 0	1	149	5745	0.64	15.86	30.00	-2.00	Pass
HT20	MCS 0	1	157	5785	0.64	15.57	30.00	-2.00	Pass
HT20	MCS 0	1	165	5825	0.64	15.82	30.00	-2.00	Pass
HT40	MCS 0	1	151	5755	0.64	15.58	30.00	-2.00	Pass
HT40	MCS 0	1	159	5795	0.64	15.34	30.00	-2.00	Pass
VHT20	MCS 0	1	149	5745	0.79	15.72	30.00	-2.00	Pass
VHT20	MCS 0	1	157	5785	0.79	15.21	30.00	-2.00	Pass
VHT20	MCS 0	1	165	5825	0.79	15.61	30.00	-2.00	Pass
VHT40	MCS 0	1	151	5755	1.48	10.19	30.00	-2.00	Pass
VHT40	MCS 0	1	159	5795	1.48	10.00	30.00	-2.00	Pass
VHT80	MCS 0	1	155	5775	2.58	10.11	30.00	-2.00	Pass

***TEST RESULTS DATA***  
***Power Spectral Density***

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.60	2.22	2.63	30.00	-2.00	Pass
11a	6Mbps	1	157	5785	0.60	2.22	2.79	30.00	-2.00	Pass
11a	6Mbps	1	165	5825	0.60	2.22	2.60	30.00	-2.00	Pass
HT20	MCS 0	1	149	5745	0.64	2.22	1.06	30.00	-2.00	Pass
HT20	MCS 0	1	157	5785	0.64	2.22	1.06	30.00	-2.00	Pass
HT20	MCS 0	1	165	5825	0.64	2.22	1.14	30.00	-2.00	Pass
HT40	MCS 0	1	151	5755	0.64	2.22	-1.98	30.00	-2.00	Pass
HT40	MCS 0	1	159	5795	0.64	2.22	-1.78	30.00	-2.00	Pass
VHT80	MCS 0	1	155	5775	2.58	2.22	-9.65	30.00	-2.00	Pass

**TEST RESULTS DATA**  
**Frequency Stability**

Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)
11a	6M bps	1	149	5745	5745.125	0.125	21.76	20	3.5
11a	6M bps	1	149	5745	5745.100	0.100	17.41	20	4.2
11a	6M bps	1	149	5745	5745.075	0.075	13.05	20	3.7
11a	6M bps	1	149	5745	5745.125	0.125	21.76	-30	3.7
11a	6M bps	1	149	5745	5745.050	0.050	8.70	50	3.7



# Appendix B. Radiated Spurious Emission

## Band 4 - 5725~5850MHz

### WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 149 5745MHz		5646.2	53.51	-14.79	68.3	46.47	30.2	7.41	30.57	202	234	P	H
		5692.8	53.52	-46.47	99.99	45.93	30.62	7.47	30.5	202	234	P	H
		5719.4	63.13	-47.6	110.73	55.17	30.89	7.52	30.45	202	234	P	H
		5724.4	74.65	-46.28	120.93	66.69	30.89	7.52	30.45	202	234	P	H
		5752	105.98	-	-	97.66	31.17	7.56	30.41	202	234	P	H
		5752	97.85	-	-	89.53	31.17	7.56	30.41	202	234	A	H
		5643.4	54.64	-13.66	68.3	47.6	30.2	7.41	30.57	194	360	P	V
		5692.4	56.27	-43.43	99.7	48.68	30.62	7.47	30.5	194	360	P	V
		5719.8	63.9	-46.94	110.84	55.94	30.89	7.52	30.45	194	360	P	V
		5724.99	75.83	-46.45	122.28	67.87	30.89	7.52	30.45	194	360	P	V
		5750	107.64	-	-	99.5	31.03	7.54	30.43	194	360	P	V
		5750	100.26	-	-	92.12	31.03	7.54	30.43	194	360	A	V



WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 157 5785MHz		5636	51.99	-16.31	68.3	44.95	30.2	7.41	30.57	191	229	P	H
		5685	54.45	-39.78	94.23	46.86	30.62	7.47	30.5	191	229	P	H
		5717.8	49.65	-60.63	110.28	41.69	30.89	7.52	30.45	191	229	P	H
		5721.2	49.1	-64.54	113.64	41.14	30.89	7.52	30.45	191	229	P	H
		5778	105.67	-	-	97.17	31.31	7.58	30.39	191	229	P	H
		5778	97.68	-	-	89.18	31.31	7.58	30.39	191	229	A	H
		5854.5	50.11	-61.93	112.04	41.02	32	7.62	30.53	191	229	P	H
		5874.25	49.88	-55.63	105.51	40.77	32.05	7.63	30.57	191	229	P	H
		5885.75	49.82	-47.5	97.32	40.71	32.05	7.63	30.57	191	229	P	H
		5930.5	50.8	-17.5	68.3	41.65	32.21	7.64	30.7	191	229	P	H
		5643.6	53	-15.3	68.3	45.96	30.2	7.41	30.57	194	0	P	V
		5693.4	54.29	-46.14	100.43	46.7	30.62	7.47	30.5	194	0	P	V
		5719.6	50.1	-60.69	110.79	42.14	30.89	7.52	30.45	194	0	P	V
		5720.6	50.03	-62.24	112.27	42.07	30.89	7.52	30.45	194	0	P	V
		5790	108.99	-	-	100.3	31.45	7.6	30.36	194	0	P	V
		5790	100.54	-	-	91.85	31.45	7.6	30.36	194	0	A	V
		5850.75	49.7	-70.89	120.59	40.71	31.86	7.62	30.49	194	0	P	V
		5874.25	51.12	-54.39	105.51	42.01	32.05	7.63	30.57	194	0	P	V
		5882.75	53.13	-46.41	99.54	44.02	32.05	7.63	30.57	194	0	P	V
	5951	49.45	-18.85	68.3	40.27	32.27	7.65	30.74	194	0	P	V	



WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 165 5825MHz		5820	105.18	-	-	96.3	31.72	7.61	30.45	189	236	P	H
		5820	97.22	-	-	88.34	31.72	7.61	30.45	189	236	A	H
		5850.75	59.75	-60.84	120.59	50.76	31.86	7.62	30.49	189	236	P	H
		5858.5	54.13	-55.79	109.92	45.04	32	7.62	30.53	189	236	P	H
		5877	52.51	-51.3	103.81	43.4	32.05	7.63	30.57	189	236	P	H
		5925.25	50.09	-18.21	68.3	40.94	32.21	7.64	30.7	189	236	P	H
		5820	107.21	-	-	98.33	31.72	7.61	30.45	100	360	P	V
		5820	98.51	-	-	89.63	31.72	7.61	30.45	100	360	A	V
		5852.25	60.09	-57.08	117.17	51.1	31.86	7.62	30.49	100	360	P	V
		5858.75	54.89	-54.96	109.85	45.8	32	7.62	30.53	100	360	P	V
		5878.75	52.23	-50.28	102.51	43.12	32.05	7.63	30.57	100	360	P	V
		5928.75	50.8	-17.5	68.3	41.65	32.21	7.64	30.7	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 149 5745MHz		11490	48.01	-25.99	74	54.79	39.57	10.63	56.98	100	360	P	H
		11490	45.54	-28.46	74	52.32	39.57	10.63	56.98	100	360	P	V
802.11a CH 157 5785MHz		11570	49.34	-24.66	74	56.42	39.39	10.68	57.15	100	360	P	H
		11570	45.32	-28.68	74	52.4	39.39	10.68	57.15	100	360	P	V
802.11a CH 165 5825MHz		11650	51.8	-22.2	74	59.18	39.19	10.72	57.29	100	360	P	H
		11650	46.18	-7.82	54	53.56	39.19	10.72	57.29	100	360	A	H
		11650	45.32	-28.68	74	52.7	39.19	10.72	57.29	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 149 5745MHz		5643	51.03	-17.27	68.3	43.99	30.2	7.41	30.57	310	277	P	H
		5692.8	51.65	-48.34	99.99	44.06	30.62	7.47	30.5	310	277	P	H
		5718.6	56.75	-53.76	110.51	48.79	30.89	7.52	30.45	310	277	P	H
		5722.6	68.36	-48.47	116.83	60.4	30.89	7.52	30.45	310	277	P	H
		5750	104.91	-	-	96.77	31.03	7.54	30.43	310	277	P	H
		5750	96.18	-	-	88.04	31.03	7.54	30.43	310	277	A	H
		5642.2	49.82	-18.48	68.3	42.78	30.2	7.41	30.57	186	274	P	V
		5692.6	50.41	-49.43	99.84	42.82	30.62	7.47	30.5	186	274	P	V
		5718.4	53.5	-56.95	110.45	45.54	30.89	7.52	30.45	186	274	P	V
		5723.2	63.36	-54.84	118.2	55.4	30.89	7.52	30.45	186	274	P	V
	5752	101.75	-	-	93.43	31.17	7.56	30.41	186	274	P	V	
	5752	93.3	-	-	84.98	31.17	7.56	30.41	186	274	A	V	



WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 157 5785MHz		5642	49.71	-18.59	68.3	42.67	30.2	7.41	30.57	326	278	P	H
		5686.4	51.03	-44.24	95.27	43.44	30.62	7.47	30.5	326	278	P	H
		5717	48.02	-62.04	110.06	40.26	30.75	7.49	30.48	326	278	P	H
		5721.2	47.78	-65.86	113.64	39.82	30.89	7.52	30.45	326	278	P	H
		5790	104.83	-	-	96.14	31.45	7.6	30.36	326	278	P	H
		5790	96.53	-	-	87.84	31.45	7.6	30.36	326	278	A	H
		5852.5	48.95	-67.65	116.6	39.96	31.86	7.62	30.49	326	278	P	H
		5857.25	48.52	-61.75	110.27	39.43	32	7.62	30.53	326	278	P	H
		5911.25	50.12	-28.32	78.44	40.98	32.16	7.64	30.66	326	278	P	H
		5981.25	49.41	-18.89	68.3	40.2	32.37	7.66	30.82	326	278	P	H
		5643	50.73	-17.57	68.3	43.69	30.2	7.41	30.57	100	354	P	V
		5695.4	52.6	-49.31	101.91	45.01	30.62	7.47	30.5	100	354	P	V
		5701.6	49.01	-56.74	105.75	41.25	30.75	7.49	30.48	100	354	P	V
		5724	48.48	-71.54	120.02	40.52	30.89	7.52	30.45	100	354	P	V
		5782	105.86	-	-	97.36	31.31	7.58	30.39	100	354	P	V
		5782	97.29	-	-	88.79	31.31	7.58	30.39	100	354	A	V
		5850.01	49.08	-73.2	122.28	40.09	31.86	7.62	30.49	100	354	P	V
		5868.25	48.98	-58.21	107.19	39.89	32	7.62	30.53	100	354	P	V
	5879.75	50.33	-51.44	101.77	41.22	32.05	7.63	30.57	100	354	P	V	
	5934.25	49.65	-18.65	68.3	40.5	32.21	7.64	30.7	100	354	P	V	



WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 165 5825MHz		5830	103.89	-	-	95.01	31.72	7.61	30.45	322	279	P	H
		5830	95.74	-	-	86.86	31.72	7.61	30.45	322	279	A	H
		5850.25	58.37	-63.36	121.73	49.38	31.86	7.62	30.49	322	279	P	H
		5856.75	51.54	-58.87	110.41	42.45	32	7.62	30.53	322	279	P	H
		5878	51.57	-51.5	103.07	42.46	32.05	7.63	30.57	322	279	P	H
		5998.5	49.51	-18.79	68.3	40.29	32.42	7.66	30.86	322	279	P	H
		5828	106.64	-	-	97.76	31.72	7.61	30.45	141	13	P	V
		5828	98.43	-	-	89.55	31.72	7.61	30.45	141	13	A	V
		5850.01	58.39	-63.89	122.28	49.4	31.86	7.62	30.49	141	13	P	V
		5856.25	54.32	-56.23	110.55	45.23	32	7.62	30.53	141	13	P	V
		5877.25	52.69	-50.94	103.63	43.58	32.05	7.63	30.57	141	13	P	V
	5929.25	50.64	-17.66	68.3	41.49	32.21	7.64	30.7	141	13	P	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 149 5745MHz		11490	43.59	-30.41	74	50.37	39.57	10.63	56.98	100	360	P	H
802.11n HT20 CH 157 5785MHz		11570	43.65	-30.35	74	50.73	39.39	10.68	57.15	100	360	P	H
802.11n HT20 CH 165 5825MHz		11650	42.98	-31.02	74	50.36	39.19	10.72	57.29	100	360	P	H
802.11n HT20 CH 157 5785MHz		11570	44.42	-29.58	74	51.5	39.39	10.68	57.15	100	360	P	V
802.11n HT20 CH 149 5745MHz		11490	45.12	-28.88	74	51.9	39.57	10.63	56.98	100	360	P	V
802.11n HT20 CH 165 5825MHz		11650	43.61	-30.39	74	50.99	39.19	10.72	57.29	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 151 5755MHz		5645.4	49.97	-18.33	68.3	42.93	30.2	7.41	30.57	100	68	P	H
		5651.8	49.94	-19.7	69.64	42.71	30.34	7.43	30.54	100	68	P	H
		5718.6	64.27	-46.24	110.51	56.31	30.89	7.52	30.45	100	68	P	H
		5724.2	68.69	-51.79	120.48	60.73	30.89	7.52	30.45	100	68	P	H
		5752	100.44	-	-	92.12	31.17	7.56	30.41	100	68	P	H
		5752	92.33	-	-	84.01	31.17	7.56	30.41	100	68	A	H
		5853.75	49.52	-64.23	113.75	40.43	32	7.62	30.53	100	68	P	H
		5858.5	50.57	-59.35	109.92	41.48	32	7.62	30.53	100	68	P	H
		5912	49.14	-28.75	77.89	40	32.16	7.64	30.66	100	68	P	H
		5953.25	49.71	-18.59	68.3	40.53	32.27	7.65	30.74	100	68	P	H
		5646.8	49.55	-18.75	68.3	42.51	30.2	7.41	30.57	100	71	P	V
		5671.8	49.53	-34.94	84.47	42.12	30.48	7.45	30.52	100	71	P	V
		5719.6	57.75	-53.04	110.79	49.79	30.89	7.52	30.45	100	71	P	V
		5723.6	61.48	-57.63	119.11	53.52	30.89	7.52	30.45	100	71	P	V
		5752	95.09	-	-	86.77	31.17	7.56	30.41	100	71	P	V
		5752	86.69	-	-	78.37	31.17	7.56	30.41	100	71	A	V
		5852	48.4	-69.34	117.74	39.41	31.86	7.62	30.49	100	71	P	V
		5869.75	48.38	-58.39	106.77	39.29	32	7.62	30.53	100	71	P	V
	5881.5	49.53	-50.94	100.47	40.42	32.05	7.63	30.57	100	71	P	V	
	5940.5	49.22	-19.08	68.3	40.04	32.27	7.65	30.74	100	71	P	V	



WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 159 5795MHz		5615.4	51.47	-16.83	68.3	44.46	30.26	7.36	30.61	105	67	P	H
		5692.2	51.5	-48.05	99.55	43.91	30.62	7.47	30.5	105	67	P	H
		5710.2	49.97	-58.19	108.16	42.21	30.75	7.49	30.48	105	67	P	H
		5722.2	47.99	-67.93	115.92	40.03	30.89	7.52	30.45	105	67	P	H
		5784	101.35	-	-	92.85	31.31	7.58	30.39	105	67	P	H
		5784	92.41	-	-	83.91	31.31	7.58	30.39	105	67	A	H
		5852.75	50.08	-65.95	116.03	41.09	31.86	7.62	30.49	105	67	P	H
		5859.5	50.08	-59.56	109.64	40.99	32	7.62	30.53	105	67	P	H
		5891	50.43	-43	93.43	41.3	32.11	7.63	30.61	105	67	P	H
		5964.75	50.14	-18.16	68.3	40.95	32.32	7.65	30.78	105	67	P	H
		5612	51.54	-16.76	68.3	44.53	30.26	7.36	30.61	133	360	P	V
		5689.8	53.03	-44.75	97.78	45.44	30.62	7.47	30.5	133	360	P	V
		5713.8	52.64	-56.53	109.17	44.88	30.75	7.49	30.48	133	360	P	V
		5724	49.46	-70.56	120.02	41.5	30.89	7.52	30.45	133	360	P	V
		5784	104.36	-	-	95.86	31.31	7.58	30.39	133	360	P	V
		5784	95.58	-	-	87.08	31.31	7.58	30.39	133	360	A	V
		5854.5	51.22	-60.82	112.04	42.13	32	7.62	30.53	133	360	P	V
		5856.75	51.67	-58.74	110.41	42.58	32	7.62	30.53	133	360	P	V
		5899.5	51.77	-35.36	87.13	42.64	32.11	7.63	30.61	133	360	P	V
	5928	50.6	-17.7	68.3	41.45	32.21	7.64	30.7	133	360	P	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 151 5755MHz		11510	43.33	-30.67	74	50.11	39.6	10.64	57.02	100	360	P	H
802.11n HT40 CH 159 5795MHz		11590	50.97	-23.03	74	58.13	39.34	10.69	57.19	100	360	P	H
802.11n HT40 CH 151 5755MHz		11510	43.84	-30.16	74	50.62	39.6	10.64	57.02	100	360	P	V
802.11n HT40 CH 159 5795MHz		11590	46.61	-27.39	74	53.77	39.34	10.69	57.19	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11ac VHT80 CH 155 5775MHz		5634.4	48.36	-19.94	68.3	41.32	30.2	7.41	30.57	140	323	P	H
		5695	50.93	-50.68	101.61	43.34	30.62	7.47	30.5	140	323	P	H
		5719.8	53.37	-57.47	110.84	45.41	30.89	7.52	30.45	140	323	P	H
		5725	54.89	-67.41	122.3	46.93	30.89	7.52	30.45	140	323	P	H
		5778	92.81	-	-	84.31	31.31	7.58	30.39	140	323	P	H
		5778	85.07	-	-	76.57	31.31	7.58	30.39	140	323	A	H
		5854.5	51.42	-60.62	112.04	42.33	32	7.62	30.53	140	323	P	H
		5856.25	50.15	-60.4	110.55	41.06	32	7.62	30.53	140	323	P	H
		5877.5	49.4	-54.04	103.44	40.29	32.05	7.63	30.57	140	323	P	H
		5996.75	49.11	-19.19	68.3	39.89	32.42	7.66	30.86	140	323	P	H
		5605.6	48.84	-19.46	68.3	41.83	30.26	7.36	30.61	165	360	P	V
		5692	51.64	-47.76	99.4	44.05	30.62	7.47	30.5	165	360	P	V
		5719.8	54.2	-56.64	110.84	46.24	30.89	7.52	30.45	165	360	P	V
		5724.4	58.2	-62.73	120.93	50.24	30.89	7.52	30.45	165	360	P	V
		5788	96.23	-	-	87.54	31.45	7.6	30.36	165	360	P	V
		5788	88.91	-	-	80.22	31.45	7.6	30.36	165	360	A	V
		5850	51.51	-70.79	122.3	42.52	31.86	7.62	30.49	165	360	P	V
		5855.75	51.27	-59.42	110.69	42.18	32	7.62	30.53	165	360	P	V
	5888.75	50.76	-44.33	95.09	41.63	32.11	7.63	30.61	165	360	P	V	
	5928.25	49.32	-18.98	68.3	40.17	32.21	7.64	30.7	165	360	P	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11ac VHT80		11550	46.25	-27.75	74	53.26	39.44	10.67	57.12	100	360	P	H
CH 155 5775MHz		11550	45.23	-28.77	74	52.24	39.44	10.67	57.12	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz
5GHz WIFI 802.11a (LF @ 3m)

Table with 14 columns: WIFI, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include 5GHz 802.11a LF data and a Remark section.



Note symbol

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



## Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	87.13	1.36	0.73	1kHz
802.11n HT20	86.20	1.28	0.78	1kHz
802.11n HT40	86.33	1.23	0.82	1kHz
802.11ac VHT80	55.16	0.25	4.04	10kHz

### 802.11a






802.11n HT20



802.11n HT40





802.11ac VHT80

