


FCC Test Report


APPLICANT : ZTE CORPORATION
EQUIPMENT : 4G Wireless Router
BRAND NAME : ZTE
MODEL NAME : MF253
FCC ID : SRQMF253
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product testing was completed on Jan. 14, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Louis Wu / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Feature of Equipment Under Test..... 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Site 7

 1.7. Applied Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system..... 11

 2.4. EUT Operation Test Setup 11

3. TEST RESULT 12

 3.1. Test of AC Conducted Emission Measurement 12

 3.2. Test of Radiated Emission Measurement 16

4. LIST OF MEASURING EQUIPMENT 21

5. UNCERTAINTY OF EVALUATION 22

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.44 dB at 10.790 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 5.26 dB at 43.580 MHz

1. General Description

1.1. Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2. Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3. Feature of Equipment Under Test

Product Feature	
Equipment	4G Wireless Router
Brand Name	ZTE
Model Name	MF253
FCC ID	SRQMF253
EUT supports Radios application	GPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE WLAN2.4GHz 802.11bgn (HT20/HT40)
HW Version	d68A
SW Version	EN_ZTE_MF253V1.0.0B05
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900 : 1850.2 MHz ~ 1909.8MHz WCDMA Band V : 826.4 MHz ~ 846.6 MHz WCDMA Band II : 1852.4 MHz ~ 1907.6 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz
Rx Frequency	GSM850 : 869.2 MHz ~ 893.8 MHz GSM1900 : 1930.2 MHz ~ 1989.8 MHz WCDMA Band V : 871.4 MHz ~ 891.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz
Antenna Type	WWAN : Monopole Antenna WLAN : PCB Antenna
Type of Modulation	GPRS: GMSK WCDMA: QPSK (Uplink) HSDPA/DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Uplink) DC-HSDPA: 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	CO01-KS	03CH01-KS	149928

1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.


Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Operating Mode	☒	☒	☒

Abbreviations:

- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1	Mode 1: GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone Mode 2: WCDMA Band II Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone Mode 3: LTE Band 4 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone
Radiated Emissions < 1GHz	1	Mode 1: GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone Mode 2: WCDMA Band II Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone Mode 3: LTE Band 4 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone
Radiated Emissions ≥ 1GHz	1	Mode 1: GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone
Remark: <ol style="list-style-type: none"> 1. The worst case of AC is mode 1; only the test data of this mode is reported. 2. The worst case of RE < 1G is mode 1; only the test data of this mode is reported. 3. TC stands for Test Configuration. 		

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Telephone	Bubugao	HCD007(6082)TSD	N/A	N/A	N/A
4.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m
5.	iPod	Apple	A1199	FCC DoC	Unshielded, 1.2 m	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization. The EUT link with telephone via RJ-11 and the EUT is connected with notebook via RJ-45 cable, execute "PING IP" function under the "cmd" of Window system to transfer packet bi-directionally.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Harvey Tang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone		




Site : C001-KS
 Condition: FCC CLASS-B LISN-L20130306 LINE
 Project : (FC) 3D3106
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	56.14	-9.77	65.91	43.50	1.93	10.71	QP
2	0.15	42.64	-13.27	55.91	30.00	1.93	10.71	Average
3	0.16	54.76	-10.71	65.47	42.30	1.79	10.67	QP
4	0.16	42.16	-13.31	55.47	29.70	1.79	10.67	Average
5	0.44	42.13	-14.89	57.02	31.60	0.26	10.27	QP
6	0.44	29.23	-17.79	47.02	18.70	0.26	10.27	Average
7	7.37	42.63	-17.37	60.00	32.10	0.20	10.33	QP
8	7.37	38.23	-11.77	50.00	27.70	0.20	10.33	Average
9	7.94	40.74	-19.26	60.00	30.20	0.20	10.34	QP
10	7.94	33.84	-16.16	50.00	23.30	0.20	10.34	Average
11	9.40	41.46	-18.54	60.00	30.90	0.20	10.36	QP
12	9.40	34.66	-15.34	50.00	24.10	0.20	10.36	Average
13	10.29	39.06	-20.94	60.00	28.50	0.20	10.36	QP
14	10.29	30.96	-19.04	50.00	20.40	0.20	10.36	Average
15	10.79	46.86	-13.14	60.00	36.30	0.20	10.36	QP
16	10.79	45.56	-4.44	50.00	35.00	0.20	10.36	Average



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Harvey Tang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone		



Site : C001-KS
 Condition: FCC CLASS-B LISN-N20130306 NEUTRAL
 Project : (FC) 3D3106
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	56.92	-8.82	65.74	44.40	1.83	10.69	QP
2	0.15	43.52	-12.22	55.74	31.00	1.83	10.69	Average
3	0.16	55.26	-10.08	65.34	42.90	1.70	10.66	QP
4	0.16	41.26	-14.08	55.34	28.90	1.70	10.66	Average
5	0.42	43.55	-13.82	57.37	32.90	0.37	10.28	QP
6	0.42	31.65	-15.72	47.37	21.00	0.37	10.28	Average
7	0.44	43.92	-13.06	56.98	33.30	0.35	10.27	QP
8	0.44	30.52	-16.46	46.98	19.90	0.35	10.27	Average
9	7.37	41.03	-18.97	60.00	30.50	0.20	10.33	QP
10	7.37	38.03	-11.97	50.00	27.50	0.20	10.33	Average
11	7.94	42.74	-17.26	60.00	32.20	0.20	10.34	QP
12	7.94	31.34	-18.66	50.00	20.80	0.20	10.34	Average
13	9.40	34.96	-25.04	60.00	24.40	0.20	10.36	QP
14	9.40	30.56	-19.44	50.00	20.00	0.20	10.36	Average
15	10.07	31.66	-28.34	60.00	21.10	0.20	10.36	QP
16	10.07	27.26	-22.74	50.00	16.70	0.20	10.36	Average
17	10.29	31.26	-28.74	60.00	20.70	0.20	10.36	QP
18	10.29	27.16	-22.84	50.00	16.60	0.20	10.36	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Stone Gu	Relative Humidity :	43~44%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone		
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH01-KS
 Condition : FCC CLASS-B 3m LF_ANT_100803 HORIZONTAL

Mode : mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	20.73	-19.27	40.00	35.82	18.00	0.48	33.57	---	---	Peak
2	93.05	23.67	-19.83	43.50	46.89	9.51	0.89	33.62	---	---	Peak
3	195.87	29.31	-14.19	43.50	52.79	8.80	1.28	33.56	200	0	Peak
4	251.16	31.80	-14.20	46.00	51.77	12.01	1.46	33.44	---	---	Peak
5	402.48	21.61	-24.39	46.00	37.06	16.01	1.85	33.31	---	---	Peak
6 *	881.66	53.11			62.48	20.47	2.68	32.52	---	---	Peak
7	945.68	31.69	-14.31	46.00	40.61	20.71	2.81	32.44	---	---	Peak



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Stone Gu	Relative Humidity :	43~44%
Test Distance :	3m	Polarization :	Vertical
Function Type :	GSM850 Idle + LAN Link + WLAN Idle + USB Link + TC + Adapter + Phone		
Remark :	#6 is system simulator signal which can be ignored.		



Site : 03CH01-KS
 Condition : FCC CLASS-B 3m LF_ANT_100803 VERTICAL

Mode : mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 !	43.58	34.74	-5.26	40.00	57.71	10.03	0.62	33.62	100	0 Peak
2	100.81	28.63	-14.87	43.50	50.69	10.62	0.93	33.61	---	---
3	195.87	28.97	-14.53	43.50	52.45	8.80	1.28	33.56	---	---
4	250.19	19.52	-26.48	46.00	39.51	12.00	1.45	33.44	---	---
5	375.32	20.53	-25.47	46.00	36.85	15.25	1.76	33.33	---	---
6 *	881.66	48.88			58.25	20.47	2.68	32.52	---	---
7	945.68	30.57	-15.43	46.00	39.49	20.71	2.81	32.44	---	---

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	May 23, 2013	Jan. 14, 2014	May 22, 2014	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 10, 2013	Jan. 14, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	60105	9kHz~30MHz	Dec. 10, 2013	Jan. 14, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	N/A	May 25, 2013	Jan. 14, 2014	May 24, 2014	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Jan. 02, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 23, 2013	Jan. 02, 2014	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2013	Jan. 02, 2014	Dec. 06, 2014	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	75959	1GHz~18GHz	Dec. 07, 2013	Jan. 02, 2014	Dec. 06, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Jan. 02, 2014	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2013	Jan. 02, 2014	Dec. 28, 2014	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 07, 2013	Jan. 02, 2014	Nov. 06, 2014	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0 ~ 360 degree	N/A	Jan. 02, 2014	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m - 4 m	N/A	Jan. 02, 2014	N/A	Radiation (03CH01-KS)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------