

FCC RF Test Report


APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE UFI MODEM
BRAND NAME : ZTE
MODEL NAME : MF90
FCC ID : SRQMF90
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 09, 2014 and testing was completed on May 21, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 7

 1.6 Testing Site 7

 1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Carrier Frequency and Channel 8

 2.2 Pre-Scanned RF Power 9

 2.3 Test Mode 11

 2.4 Connection Diagram of Test System 15

 2.5 Support Unit used in test configuration and system 16

 2.6 EUT Operation Test Setup 16

 2.7 Measurement Results Explanation Example 17

3 TEST RESULT 18

 3.1 6dB Bandwidth Measurement 18

 3.2 Peak Output Power Measurement 22

 3.3 Power Spectral Density Measurement 27

 3.4 Conducted Band Edges and Spurious Emission Measurement 31

 3.5 Radiated Band Edges and Spurious Emission Measurement 74

 3.6 AC Conducted Emission Measurement 119

 3.7 Antenna Requirements 123

4 LIST OF MEASURING EQUIPMENT 124

5 UNCERTAINTY OF EVALUATION 125

APPENDIX A. SETUP PHOTOGRAPHS

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.76 dB at 2389.830 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.27 dB at 0.640 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	LTE UFI MODEM
Brand Name	ZTE
Model Name	MF90
FCC ID	SRQMF90
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE/ WLAN 2.4GHz 802. 11b/g/n HT20/HT40/ WLAN 5GHz 802. 11a/n HT20/HT40
HW Version	xq5B
SW Version	EN_ZTE_MF90LATINV1.0.0B05
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard																				
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz 802.11a/n: 5745~5825MHz.																			
Maximum Output Power to antenna	<2412 MHz ~ 2462 MHz > 802.11b : 18.91 dBm (0.0778 W) 802.11g : 21.11 dBm (0.1291 W) 802.11n HT20 : 21.77 dBm (0.1503 W) 802.11n HT40 : 19.97 dBm (0.0993 W) <5745 MHz ~ 5825 MHz > 802.11a : 19.64 dBm (0.0920 W) 802.11n HT20 : 22.68 dBm (0.1854 W) 802.11n HT40 : 21.99 dBm (0.1581 W)																			
Antenna Type	Chain Port 0: PIFA Antenna Chain Port 1: PIFA Antenna																			
Antenna Gain	<2.4GHz> Chain Port 0 : 1.00 dBi Chain Port 1 : 1.00 dBi Chain Port 0 + 1 : 1.00 dBi <5GHz> Chain Port 0 : 1.00 dBi Chain Port 1 : 1.00 dBi Chain Port 0 + 1 : 1.00 dBi																			
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)																			
Antenna Function for Transmitter	<table border="1"> <thead> <tr> <th></th> <th>Chain Port 0</th> <th>Chain Port 1</th> </tr> </thead> <tbody> <tr> <td>802.11 b</td> <td>V</td> <td>V</td> </tr> <tr> <td>802.11 g</td> <td>V</td> <td>V</td> </tr> <tr> <td>802.11 a</td> <td>V</td> <td>V</td> </tr> <tr> <td>802.11 n SISO</td> <td>V</td> <td>V</td> </tr> <tr> <td>802.11 n MIMO</td> <td>V</td> <td>V</td> </tr> </tbody> </table>			Chain Port 0	Chain Port 1	802.11 b	V	V	802.11 g	V	V	802.11 a	V	V	802.11 n SISO	V	V	802.11 n MIMO	V	V
	Chain Port 0	Chain Port 1																		
802.11 b	V	V																		
802.11 g	V	V																		
802.11 a	V	V																		
802.11 n SISO	V	V																		
802.11 n MIMO	V	V																		

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-KS	03CH01-KS	CO01-KS
			149928

Note: The test site complies with ANSI C63.4 2003 requirement.

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4	149	5745	159	5795
	151	5755	161	5805
	153	5765	165	5825
	157	5785	-	-



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b Peak Power (dBm)				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Chain Port 0	17.72	17.66	17.67	17.31
Chain Port 1	18.91	18.89	18.79	18.67

2.4GHz 802.11g Peak Power (dBm)								
Data Rate (MHz)	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Chain Port 0	19.51	19.38	18.78	18.97	18.86	18.67	18.72	18.86
Chain Port 1	21.11	20.81	20.75	20.53	20.47	20.53	20.43	20.64

2.4GHz 802.11n HT20 Peak Power (dBm)								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Chain Port 0	18.47	18.27	18.30	17.94	17.59	17.69	18.06	17.84
Chain Port 1	19.31	18.98	19.10	18.68	19.13	19.06	19.26	18.94
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Chain Port 0+1(0)	17.79	17.46	17.61	17.27	16.98	17.19	17.39	17.36
Chain Port 0+1(1)	19.56	19.36	19.31	19.21	19.19	18.95	18.89	19.08
Chain Port 0+1	21.77	21.52	21.55	21.36	21.23	21.17	21.21	21.31

2.4GHz 802.11n HT40 Peak Power (dBm)								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Chain Port 0	15.77	15.67	15.58	15.49	15.54	15.71	15.59	15.48
Chain Port 1	17.83	17.76	17.53	17.53	16.84	17.42	17.53	17.28
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Chain Port 0+1(0)	15.54	15.41	15.37	15.33	15.14	15.51	15.32	15.51
Chain Port 0+1(1)	18.03	17.56	17.66	18.01	17.92	17.92	17.86	17.93
Chain Port 0+1	19.97	19.63	19.67	19.88	19.76	19.89	19.78	19.90



5GHz 802.11a Peak Power (dBm)								
Data Rate (MHz)	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Chain Port 0	19.07	18.97	18.42	18.75	18.52	18.32	18.46	18.59
Chain Port 1	19.64	19.41	19.16	19.17	19.03	19.16	19.20	19.08

5GHz 802.11n HT20 Peak Power (dBm)								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Chain Port 0	19.46	19.05	19.04	19.25	19.26	19.43	19.32	19.40
Chain Port 1	20.04	19.62	19.67	19.84	19.55	19.64	19.76	19.95
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Chain Port 0+1(0)	19.53	19.41	19.31	19.33	19.43	19.32	19.45	19.28
Chain Port 0+1(1)	19.80	19.65	19.74	19.76	19.75	19.79	19.66	19.65
Chain Port 0+1	22.68	22.54	22.54	22.56	22.60	22.57	22.57	22.48

5GHz 802.11n HT40 Peak Power (dBm)								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Chain Port 0	19.09	18.93	18.89	18.90	18.78	18.74	18.60	18.85
Chain Port 1	19.10	18.96	19.08	19.00	19.01	18.98	18.95	18.96
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Chain Port 0+1(0)	19.18	18.86	18.93	18.88	19.00	19.10	19.12	18.96
Chain Port 0+1(1)	18.76	18.68	18.58	18.55	18.49	18.56	18.60	18.70
Chain Port 0+1	21.99	21.78	21.77	21.73	21.76	21.85	21.88	21.84

Note:

- Chain Port 0+1 is a calculated result from sum of the power Chain Port 0+1(0) and Chain Port 0+1(1).
- The data rates of WLAN 802.11 b/g/a/n were set in 1Mbps for 2.4GHz 802.11b (Chain Port 1), 6Mbps for 2.4GHz 802.11g (Chain Port 1), MCS0 for 2.4GHz 802.11n HT20 (Chain Port 1), MCS8 for 2.4GHz 802.11n HT20 (Chain Port 0+1), MCS0 for 2.4GHz 802.11n HT40 (Chain Port 1), MCS8 for 2.4GHz 802.11n HT40 (Chain Port 0+1), 6Mbps for 5GHz 802.11a (Chain Port 1), MCS0 for 5GHz 802.11n HT20 (Chain Port 1), MCS8 for 5GHz 802.11n HT20 (Chain Port 0+1), MCS0 for 5GHz 802.11n HT40 (Chain Port 1) and MCS8 for 5GHz 802.11n HT40 (Chain Port 0+1) due to the highest RF output power.

2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.

<2.4GHz>

Test Cases					
	Test Items	Mode	Data Rate	Test Channel	Remark
	Conducted TCs	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
802.11g			6 Mbps	1/6/11	Chain Port 1
802.11n HT20			MCS0	1/6/11	Chain Port 1
802.11n HT20			MCS8	1/6/11	Chain Port 0+1 (0)
802.11n HT20			MCS8	1/6/11	Chain Port 0+1 (1)
802.11n HT40			MCS0	3/6/9	Chain Port 1
802.11n HT40			MCS8	3/6/9	Chain Port 0+1 (0)
802.11n HT40			MCS8	3/6/9	Chain Port 0+1 (1)
Output Power		802.11b	1 Mbps	1/6/11	Chain Port 0
		802.11b	1 Mbps	1/6/11	Chain Port 1
		802.11g	6 Mbps	1/6/11	Chain Port 0
		802.11g	6 Mbps	1/6/11	Chain Port 1
		802.11n HT20	MCS0	1/6/11	Chain Port 0
		802.11n HT20	MCS0	1/6/11	Chain Port 1
		802.11n HT20	MCS8	1/6/11	Chain Port 0+1 (0)
		802.11n HT20	MCS8	1/6/11	Chain Port 0+1 (1)
		802.11n HT20	MCS8	1/6/11	Chain Port 0+1
		802.11n HT40	MCS0	3/6/9	Chain Port 0
		802.11n HT40	MCS0	3/6/9	Chain Port 1
		802.11n HT40	MCS8	3/6/9	Chain Port 0+1 (0)
Conducted Band Edge		802.11b	1 Mbps	1/11	Chain Port 1
		802.11g	6 Mbps	1/11	Chain Port 1
		802.11n HT20	MCS0	1/11	Chain Port 1
		802.11n HT20	MCS8	1/11	Chain Port 0+1 (0)
		802.11n HT20	MCS8	1/11	Chain Port 0+1 (1)
		802.11n HT40	MCS0	3/9	Chain Port 1
		802.11n HT40	MCS8	3/9	Chain Port 0+1 (0)
Conducted Spurious Emission		802.11b	1 Mbps	1/6/11	Chain Port 1
		802.11g	6 Mbps	1/6/11	Chain Port 1
		802.11n HT20	MCS0	1/6/11	Chain Port 1
		802.11n HT20	MCS8	1/6/11	Chain Port 0+1 (0)
		802.11n HT20	MCS8	1/6/11	Chain Port 0+1 (1)
		802.11n HT40	MCS0	3/6/9	Chain Port 1
		802.11n HT40	MCS8	3/6/9	Chain Port 0+1 (0)
		802.11n HT40	MCS8	3/6/9	Chain Port 0+1 (1)



	Test Items	Mode	Data Rate	Test Channel	Remark
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11	Chain Port 1
		802.11g	6 Mbps	1/11	Chain Port 1
		802.11n HT20	MCS0	1/11	Chain Port 1
		802.11n HT20	MCS8	1/11	Chain Port 0+1
		802.11n HT40	MCS0	3/9	Chain Port 1
		802.11n HT40	MCS8	3/9	Chain Port 0+1
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11	Chain Port 1
		802.11g	6 Mbps	1/6/11	Chain Port 1
		802.11n HT20	MCS0	1/6/11	Chain Port 1
		802.11n HT20	MCS8	1/6/11	Chain Port 0+1
		802.11n HT40	MCS0	3/6/9	Chain Port 1
		802.11n HT40	MCS8	3/6/9	Chain Port 0+1



<5GHz>


Test Cases						
	Test Items	Mode	Data Rate	Test Channel	Remark	
Conducted TCs	6dB BW Power Spectral Density	802.11a	6 Mbps	149/157/165	Chain Port 1	
		802.11n HT20	MCS0	149/157/165	Chain Port 1	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1 (0)	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1 (1)	
		802.11n HT40	MCS0	151/159	Chain Port 1	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (0)	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (1)	
	Output Power	802.11a	6 Mbps	149/157/165	Chain Port 0	
		802.11a	6 Mbps	149/157/165	Chain Port 1	
		802.11n HT20	MCS0	149/157/165	Chain Port 0	
		802.11n HT20	MCS0	149/157/165	Chain Port 1	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1 (0)	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1 (1)	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1	
		802.11n HT40	MCS0	151/159	Chain Port 0	
		802.11n HT40	MCS0	151/159	Chain Port 1	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (0)	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (1)	
	Conducted Band Edge	802.11a	6 Mbps	149/165	Chain Port 1	
		802.11n HT20	MCS0	149/165	Chain Port 1	
		802.11n HT20	MCS8	149/165	Chain Port 0+1 (0)	
		802.11n HT20	MCS8	149/165	Chain Port 0+1 (1)	
		802.11n HT40	MCS0	151/159	Chain Port 1	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (0)	
	Conducted Spurious Emission	802.11a	6 Mbps	149/157/165	Chain Port 1	
		802.11n HT20	MCS0	149/157/165	Chain Port 1	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1 (0)	
		802.11n HT20	MCS8	149/157/165	Chain Port 0+1 (1)	
		802.11n HT40	MCS0	151/159	Chain Port 1	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (0)	
		802.11n HT40	MCS8	151/159	Chain Port 0+1 (1)	
	Radiated TCs	Radiated Spurious Emission	802.11a	6 Mbps	149/157/165	Chain Port 1
			802.11n HT20	MCS0	149/157/165	Chain Port 1
802.11n HT20			MCS8	149/157/165	Chain Port 0+1	
802.11n HT40			MCS0	151/159	Chain Port 1	
802.11n HT40			MCS8	151/159	Chain Port 0+1	




AC Conducted Emission	Mode 1 : GPRS850 Idle + WLAN 2.4GHz Link + USB Cable (Charging from Adapter) Mode 2 : GPRS850 Idle + WLAN 5GHz Link + USB Cable (Charging from Adapter)
Remark: <ol style="list-style-type: none">1. The worst case of AC conducted emission is mode 2; only the test data of it is reported.2. For radiated TCs, the tests were performed with adapter and USB Cable.	

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Acer	MS2204	QDS-BRCM1018	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 6.3 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset (dB)} &= \text{RF cable loss (dB)} + \text{attenuator factor (dB)} \\ &= 6.3 + 10 = 16.3 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup





3.1.5 Test Result of 6dB Occupied Bandwidth


Test Band :	2.4GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	6dB Bandwidth (MHz)		6dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Chain Port 0	Chain Port 1		
11b	1Mbps	1	1	2412	-	8.02	0.5	Pass
11b	1Mbps	1	6	2437	-	8.04	0.5	Pass
11b	1Mbps	1	11	2462	-	7.54	0.5	Pass
11g	6Mbps	1	1	2412	-	15.44	0.5	Pass
11g	6Mbps	1	6	2437	-	15.38	0.5	Pass
11g	6Mbps	1	11	2462	-	15.26	0.5	Pass
HT20	MCS0	1	1	2412	-	15.70	0.5	Pass
HT20	MCS0	1	6	2437	-	15.88	0.5	Pass
HT20	MCS0	1	11	2462	-	15.06	0.5	Pass
HT40	MCS0	1	3	2422	-	35.40	0.5	Pass
HT40	MCS0	1	6	2437	-	35.48	0.5	Pass
HT40	MCS0	1	9	2452	-	35.68	0.5	Pass
HT20	MCS8	2	1	2412	16.80	16.32	0.5	Pass
HT20	MCS8	2	6	2437	15.68	15.88	0.5	Pass
HT20	MCS8	2	11	2462	15.08	15.64	0.5	Pass
HT40	MCS8	2	3	2422	35.24	35.68	0.5	Pass
HT40	MCS8	2	6	2437	36.04	35.72	0.5	Pass
HT40	MCS8	2	9	2452	35.88	35.68	0.5	Pass



Test Band :	5GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	6dB Bandwidth (MHz)		6dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Chain Port 0	Chain Port 1		
11a	6Mbps	1	149	5745	-	15.60	0.5	Pass
11a	6Mbps	1	157	5785	-	15.64	0.5	Pass
11a	6Mbps	1	165	5825	-	15.36	0.5	Pass
HT20	MCS0	1	149	5745	-	15.12	0.5	Pass
HT20	MCS0	1	157	5785	-	15.08	0.5	Pass
HT20	MCS0	1	165	5825	-	15.12	0.5	Pass
HT40	MCS0	1	151	5755	-	36.08	0.5	Pass
HT40	MCS0	1	159	5795	-	36.08	0.5	Pass
HT20	MCS8	2	149	5745	15.30	16.28	0.5	Pass
HT20	MCS8	2	157	5785	15.12	16.24	0.5	Pass
HT20	MCS8	2	165	5825	15.04	16.28	0.5	Pass
HT40	MCS8	2	151	5755	36.40	36.32	0.5	Pass
HT40	MCS8	2	159	5795	36.32	36.32	0.5	Pass



3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz and 5725-5850MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test Band :	2.4GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Max. Limit (dBm)		DG (dBi)		Pass/Fail
					Chain Port 0	Chain Port 1	SUM	Chain Port 0	Chain Port 1	Chain Port 0	Chain Port 1	
11b	1Mbps	1	1	2412	16.98	18.22	-	30.00	30.00	1.00	1.00	Pass
11b	1Mbps	1	6	2437	17.72	18.91	-	30.00	30.00	1.00	1.00	Pass
11b	1Mbps	1	11	2462	16.78	18.53	-	30.00	30.00	1.00	1.00	Pass
11g	6Mbps	1	1	2412	18.65	20.56	-	30.00	30.00	1.00	1.00	Pass
11g	6Mbps	1	6	2437	19.51	21.11	-	30.00	30.00	1.00	1.00	Pass
11g	6Mbps	1	11	2462	19.14	20.55	-	30.00	30.00	1.00	1.00	Pass
HT20	MCS0	1	1	2412	17.83	19.16	-	30.00	30.00	1.00	1.00	Pass
HT20	MCS0	1	6	2437	18.47	19.31	-	30.00	30.00	1.00	1.00	Pass
HT20	MCS0	1	11	2462	17.59	19.09	-	30.00	30.00	1.00	1.00	Pass
HT40	MCS0	1	3	2422	15.61	17.43	-	30.00	30.00	1.00	1.00	Pass
HT40	MCS0	1	6	2437	15.77	17.83	-	30.00	30.00	1.00	1.00	Pass
HT40	MCS0	1	9	2452	15.44	17.64	-	30.00	30.00	1.00	1.00	Pass
HT20	MCS8	2	1	2412	17.09	19.27	21.33	30.00	30.00	1.00	1.00	Pass
HT20	MCS8	2	6	2437	17.79	19.56	21.77	30.00	30.00	1.00	1.00	Pass
HT20	MCS8	2	11	2462	17.11	19.35	21.38	30.00	30.00	1.00	1.00	Pass
HT40	MCS8	2	3	2422	15.32	17.42	19.51	30.00	30.00	1.00	1.00	Pass
HT40	MCS8	2	6	2437	15.54	18.03	19.97	30.00	30.00	1.00	1.00	Pass
HT40	MCS8	2	9	2452	15.51	17.61	19.70	30.00	30.00	1.00	1.00	Pass

Note: Measured power (dBm) has offset with cable loss.



Test Band :	5GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Max. Limit (dBm)		DG (dBi)		Pass/Fail
					Chain Port 0	Chain Port 1	SUM	Chain Port 0	Chain Port 1	Chain Port 0	Chain Port 1	
11a	6Mbps	1	149	5745	18.65	18.51	-	30.00	30.00	1.00	1.00	Pass
11a	6Mbps	1	157	5785	18.67	19.62		30.00	30.00	1.00	1.00	Pass
11a	6Mbps	1	165	5825	19.07	19.64		30.00	30.00	1.00	1.00	Pass
HT20	MCS0	1	149	5745	18.99	19.57		30.00	30.00	1.00	1.00	Pass
HT20	MCS0	1	157	5785	19.36	19.64		30.00	30.00	1.00	1.00	Pass
HT20	MCS0	1	165	5825	19.46	20.04		30.00	30.00	1.00	1.00	Pass
HT40	MCS0	1	151	5755	18.39	18.48		30.00	30.00	1.00	1.00	Pass
HT40	MCS0	1	159	5795	19.09	19.10		30.00	30.00	1.00	1.00	Pass
HT20	MCS8	2	149	5745	18.49	19.38	21.97	30.00		1.00		Pass
HT20	MCS8	2	157	5785	19.22	19.46	22.35	30.00		1.00		Pass
HT20	MCS8	2	165	5825	19.53	19.80	22.68	30.00		1.00		Pass
HT40	MCS8	2	151	5755	18.56	18.66	21.62	30.00		1.00		Pass
HT40	MCS8	2	159	5795	19.18	18.76	21.99	30.00		1.00		Pass

Note: Measured power (dBm) has offset with cable loss.



3.2.6 Test Result of Average output Power (Reporting Only)

Test Band :	2.4GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			
					Chain Port 0	Chain Port 1	Chain Port 0	Chain Port 1	Sum Power	
11b	1Mbps	1	1	2412	0.00	0.00	13.48	14.77		
11b	1Mbps	1	6	2437	0.00	0.00	14.25	15.62		
11b	1Mbps	1	11	2462	0.00	0.00	13.27	14.99		
11g	6Mbps	1	1	2412	0.20	0.19	8.58	10.02		
11g	6Mbps	1	6	2437	0.20	0.19	9.47	10.62		
11g	6Mbps	1	11	2462	0.20	0.19	8.72	10.28		
HT20	MCS0	1	1	2412	0.22	0.22	7.24	9.27		
HT20	MCS0	1	6	2437	0.22	0.22	7.90	9.48		
HT20	MCS0	1	11	2462	0.22	0.22	7.15	9.06		
HT40	MCS0	1	3	2422	0.53	0.44	6.18	7.71		
HT40	MCS0	1	6	2437	0.53	0.44	6.57	8.26		
HT40	MCS0	1	9	2452	0.53	0.44	6.37	7.86		
HT20	MCS8	2	1	2412	0.43	0.42	7.21	9.14		11.29
HT20	MCS8	2	6	2437	0.43	0.42	7.60	9.70		11.78
HT20	MCS8	2	11	2462	0.43	0.42	7.35	9.43		11.52
HT40	MCS8	2	3	2422	0.81	0.81	6.02	8.29	10.31	
HT40	MCS8	2	6	2437	0.81	0.81	6.43	8.74	10.75	
HT40	MCS8	2	9	2452	0.81	0.81	6.18	8.43	10.46	

Note: Measured power (dBm) has offset with cable loss and duty factor.



Test Band :	5GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			
					Chain Port 0	Chain Port 1	Chain Port 0	Chain Port 1	Sum Power	
11a	6Mbps	1	149	5745	0.20	0.20	7.65	8.49	-	
11a	6Mbps	1	157	5785	0.20	0.20	8.25	9.14		
11a	6Mbps	1	165	5825	0.20	0.20	8.52	9.40		
HT20	MCS0	1	149	5745	0.22	0.22	8.32	9.13		
HT20	MCS0	1	157	5785	0.22	0.22	8.26	9.26		
HT20	MCS0	1	165	5825	0.22	0.22	8.46	9.29		
HT40	MCS0	1	151	5755	0.39	0.40	8.47	8.68		
HT40	MCS0	1	159	5795	0.39	0.40	8.53	9.61		
HT20	MCS8	2	149	5745	0.42	0.41	7.80	9.58		11.79
HT20	MCS8	2	157	5785	0.42	0.41	9.49	10.10		12.81
HT20	MCS8	2	165	5825	0.42	0.41	9.67	10.33	13.06	
HT40	MCS8	2	151	5755	0.78	0.78	8.79	8.98	11.89	
HT40	MCS8	2	159	5795	0.78	0.78	9.13	9.44	12.30	

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

If measurements performed using method (2) plus $10 \log(N)$ exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.


Method (2): Measure and add $10 \log(N)$ dB, where N is the number of outputs. (N=2)



Test Band :	5GHz	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Power Density (dBm/3kHz)			Max. Limit (dBm/3kHz)		DG (dBi)		Pass/Fail
					Chain Port 0	Chain Port 1	Worst +10log(2)	Chain Port 0	Chain Port 1	Chain Port 0	Chain Port 1	
11a	6Mbps	1	149	5745	-	-15.18	-	8.00	8.00	1.00	1.00	Pass
11a	6Mbps	1	157	5785	-	-15.63		8.00	8.00	1.00	1.00	Pass
11a	6Mbps	1	165	5825	-	-14.89		8.00	8.00	1.00	1.00	Pass
HT20	MCS0	1	149	5745	-	-14.97		8.00	8.00	1.00	1.00	Pass
HT20	MCS0	1	157	5785	-	-14.28		8.00	8.00	1.00	1.00	Pass
HT20	MCS0	1	165	5825	-	-14.53		8.00	8.00	1.00	1.00	Pass
HT40	MCS0	1	151	5755	-	-18.21		8.00	8.00	1.00	1.00	Pass
HT40	MCS0	1	159	5795	-	-18.55		8.00	8.00	1.00	1.00	Pass
HT20	MCS8	2	149	5745	-14.89	-15.60	-11.88	8.00	8.00	4.01	4.01	Pass
HT20	MCS8	2	157	5785	-15.16	-15.01	-12.00	8.00	8.00	4.01	4.01	Pass
HT20	MCS8	2	165	5825	-15.22	-14.66	-11.65	8.00	8.00	4.01	4.01	Pass
HT40	MCS8	2	151	5755	-17.94	-18.60	-14.93	8.00	8.00	4.01	4.01	Pass
HT40	MCS8	2	159	5795	-18.37	-17.82	-14.81	8.00	8.00	4.01	4.01	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Number of TX = 1, Chain Port 1

Number of TX	1	Chain Port	1
Test Mode :	802.11b	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Adonis Li







Number of TX :	1	Chain Port	1
Test Mode :	802.11b	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11b	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Adonis Li

WLAN 802.11b Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11g	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Adonis Li

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11g	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11g	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Adonis Li

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Adonis Li







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Adonis Li







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	03	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 03


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	09	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11a	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	149	Test Engineer :	Adonis Li

WLAN 802.11a Channel 149


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11a	Temperature :	23~24°C
Test Band :	5GHz Mid	Relative Humidity :	47~48%
Test Channel :	157	Test Engineer :	Adonis Li

WLAN 802.11a Channel 157


100kHz PSD reference Level



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11a	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	165	Test Engineer :	Adonis Li

WLAN 802.11a Channel 165


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	149	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 149


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz Mid	Relative Humidity :	47~48%
Test Channel :	157	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 157


100kHz PSD reference Level



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	165	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 165


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	151	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 151


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	1	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	159	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 159


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz






Number of TX = 2, Chain Port 0


Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Adonis Li





Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	03	Test Engineer :	Adonis Li







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	09	Test Engineer :	Adonis Li







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	149	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 149


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz Mid	Relative Humidity :	47~48%
Test Channel :	157	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 157


100kHz PSD reference Level



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	165	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 165


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	151	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 151


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	0
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	159	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 159


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz






Number of TX = 2, Chain Port 1


Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li






Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Adonis Li






Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	03	Test Engineer :	Adonis Li






Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Adonis Li





Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	09	Test Engineer :	Adonis Li







Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	149	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 149


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz Mid	Relative Humidity :	47~48%
Test Channel :	157	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 157


100kHz PSD reference Level



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	165	Test Engineer :	Adonis Li

WLAN 802.11n HT20 Channel 165


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	5GHz Low	Relative Humidity :	47~48%
Test Channel :	151	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 151


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz







Number of TX :	2	Chain Port	1
Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Band :	5GHz High	Relative Humidity :	47~48%
Test Channel :	159	Test Engineer :	Adonis Li

WLAN 802.11n HT40 Channel 159


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~6GHz



Spurious Emission 5GHz~40GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting.
1	802.11b	100.00	-	-	10Hz
1	802.11g	95.65	2.069	0.483	1kHz
1	2.4G 802.11n HT20	95.14	1.920	0.521	1kHz
0+1	2.4G 802.11n HT20	90.88	0.996	1.004	3kHz
1	2.4G 802.11n HT40	90.37	0.938	1.066	3kHz
0+1	2.4G 802.11n HT40	83.00	0.498	2.008	3kHz
1	802.11a	95.39	2.070	0.483	1kHz
1	5G 802.11n HT20	95.07	1.928	0.519	1kHz
0+1	5G 802.11n HT20	91.01	0.992	1.008	3kHz
1	5G 802.11n HT40	91.23	0.936	1.068	3kHz
0+1	5G 802.11n HT40	83.61	0.500	2.000	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b - Chain Port 1	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.83	51.35	-22.65	74	48.16	32.86	3.59	33.26	101	272	Peak
2387.31	40.61	-13.39	54	37.42	32.86	3.59	33.26	101	272	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.21	53.8	-20.2	74	50.61	32.86	3.59	33.26	100	164	Peak
2387.22	44.2	-9.8	54	41.01	32.86	3.59	33.26	100	164	Average

Test Mode :	802.11b - Chain Port 1	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.56	50.34	-23.66	74	46.97	33.01	3.65	33.29	195	145	Peak
2483.5	39.71	-14.29	54	36.34	33.01	3.65	33.29	195	145	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.71	49.54	-24.46	74	46.17	33.01	3.65	33.29	100	220	Peak
2483.5	38.18	-15.82	54	34.81	33.01	3.65	33.29	100	220	Average



Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.92	59.25	-14.75	74	56.06	32.86	3.59	33.26	110	352	Peak
2389.74	38.92	-15.08	54	35.73	32.86	3.59	33.26	110	352	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.11	66.93	-7.07	74	63.74	32.86	3.59	33.26	121	165	Peak
2389.92	44.3	-9.7	54	41.11	32.86	3.59	33.26	121	165	Average

Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.98	57.87	-16.13	74	54.5	33.01	3.65	33.29	189	141	Peak
2483.62	39.8	-14.2	54	36.43	33.01	3.65	33.29	189	141	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.46	56.61	-17.39	74	53.24	33.01	3.65	33.29	117	208	Peak
2483.56	39.41	-14.59	54	36.04	33.01	3.65	33.29	117	208	Average



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.74	57.28	-16.72	74	54.09	32.86	3.59	33.26	165	275	Peak
2389.74	41.75	-12.25	54	38.56	32.86	3.59	33.26	165	275	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.83	65.08	-8.92	74	61.89	32.86	3.59	33.26	123	165	Peak
2389.92	46.95	-7.05	54	43.76	32.86	3.59	33.26	123	165	Average

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.59	63.71	-10.29	74	60.34	33.01	3.65	33.29	102	165	Peak
2483.5	41.6	-12.4	54	38.23	33.01	3.65	33.29	102	165	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.16	60.32	-13.68	74	56.95	33.01	3.65	33.29	100	212	Peak
2483.62	39.4	-14.6	54	36.03	33.01	3.65	33.29	100	212	Average



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2390	66.43	-7.57	74	63.24	32.86	3.59	33.26	162	155	Peak
2389.83	48.24	-5.76	54	45.05	32.86	3.59	33.26	164	155	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.47	64.05	-9.95	74	60.86	32.86	3.59	33.26	100	177	Peak
2389.83	48.23	-5.77	54	45.04	32.86	3.59	33.26	100	177	Average

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	66.28	-7.72	74	62.91	33.01	3.65	33.29	106	157	Peak
2483.5	45.66	-8.34	54	42.29	33.01	3.65	33.29	106	157	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.8	62.29	-11.71	74	58.92	33.01	3.65	33.29	100	173	Peak
2483.53	41.89	-12.11	54	38.52	33.01	3.65	33.29	100	173	Average



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	03	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.47	58.96	-15.04	74	55.77	32.86	3.59	33.26	100	19	Peak
2389.2	39.33	-14.67	54	36.14	32.86	3.59	33.26	100	19	Average
2483.74	52.26	-21.74	74	48.89	33.01	3.65	33.29	198	164	Peak
2483.8	36.88	-17.12	54	33.51	33.01	3.65	33.29	198	164	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.83	66.29	-7.71	74	63.1	32.86	3.59	33.26	100	114	Peak
2389.74	42.46	-11.54	54	39.27	32.86	3.59	33.26	100	114	Average
2484.52	48.3	-25.7	74	44.93	33.01	3.65	33.29	100	213	Peak
2483.62	35.38	-18.62	54	32.01	33.01	3.65	33.29	100	213	Average



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	09	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.13	48.82	-25.18	74	45.63	32.86	3.59	33.26	100	125	Peak
2387.4	35.2	-18.8	54	32.01	32.86	3.59	33.26	100	125	Average
2483.62	66.42	-7.58	74	63.05	33.01	3.65	33.29	200	164	Peak
2483.53	40.54	-13.46	54	37.17	33.01	3.65	33.29	200	164	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.93	56.28	-17.72	74	53.09	32.86	3.59	33.26	100	151	Peak
2389.92	36.49	-17.51	54	33.3	32.86	3.59	33.26	100	157	Average
2483.59	64.9	-9.1	74	61.53	33.01	3.65	33.29	200	100	Peak
2483.65	40.59	-13.41	54	37.22	33.01	3.65	33.29	125	100	Average



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	03	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.84	61.44	-12.56	74	58.25	32.86	3.59	33.26	100	322	Peak
2389.65	38.91	-15.09	54	35.72	32.86	3.59	33.26	100	322	Average
2484.16	51.29	-22.71	74	47.92	33.01	3.65	33.29	100	144	Peak
2483.65	35.52	-18.48	54	32.15	33.01	3.65	33.29	100	144	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.65	66.48	-7.52	74	63.29	32.86	3.59	33.26	100	345	Peak
2389.74	41.47	-12.53	54	38.28	32.86	3.59	33.26	100	345	Average
2483.62	48.75	-25.25	74	45.38	33.01	3.65	33.29	100	45	Peak
2484.13	34.77	-19.23	54	31.4	33.01	3.65	33.29	100	45	Average



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	09	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.04	49.73	-24.27	74	46.54	32.86	3.59	33.26	100	291	Peak
2388.21	35.18	-18.82	54	31.99	32.86	3.59	33.26	100	291	Average
2483.68	61.31	-12.69	74	57.94	33.01	3.65	33.29	100	169	Peak
2483.62	38.43	-15.57	54	35.06	33.01	3.65	33.29	100	169	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.57	54.36	-19.64	74	51.17	32.86	3.59	33.26	100	327	Peak
2389.92	36.49	-17.51	54	33.3	32.86	3.59	33.26	100	327	Average
2484.07	63	-11	74	59.63	33.01	3.65	33.29	127	239	Peak
2483.53	39.14	-14.86	54	35.77	33.01	3.65	33.29	215	234	Average

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	802.11b-Chain Port 1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	103.34	-	-	100.11	32.89	3.61	33.27	100	271	Peak
2412	97.15	-	-	93.92	32.89	3.61	33.27	100	271	Average
4824	53.03	-20.97	74	46.41	35.17	5.25	33.8	100	359	Peak
4824	45.01	-8.99	54	38.39	35.17	5.25	33.8	100	359	Average

Test Mode :	802.11b-Chain Port 1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is Fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	105.71	-	-	102.48	32.89	3.61	33.27	100	12	Peak
2412	99.76	-	-	96.53	32.89	3.61	33.27	100	12	Average
4824	49.82	-24.18	74	43.2	35.17	5.25	33.8	100	145	Peak



Test Mode :	802.11b - Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	103.03	-	-	99.73	32.95	3.63	33.28	100	273	Peak
2437	97.74	-	-	94.44	32.95	3.63	33.28	100	273	Average
4874	51.56	-22.44	74	44.9	35.18	5.28	33.8	100	359	Peak
4874	43.57	-10.43	54	36.91	35.18	5.28	33.8	100	359	Average
7312	48.71	-25.29	74	40.03	36.2	6.61	34.13	100	147	Peak

Test Mode :	802.11b - Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	105.4	-	-	102.1	32.95	3.63	33.28	155	211	Peak
2437	100.47	-	-	97.17	32.95	3.63	33.28	155	211	Average
4874	53.78	-20.22	74	47.12	35.18	5.28	33.8	100	346	Peak
4874	47.16	-6.84	54	40.5	35.18	5.28	33.8	100	346	Average
7312	49.23	-24.77	74	40.55	36.2	6.61	34.13	100	120	Peak



Test Mode :	802.11b - Chain Port 1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	103.7	-	-	100.37	32.98	3.64	33.29	100	280	Peak
2462	98.84	-	-	95.51	32.98	3.64	33.29	100	280	Average
4924	52.33	-21.67	74	45.63	35.19	5.31	33.8	100	0	Peak
4924	43.48	-10.52	54	36.78	35.19	5.31	33.8	100	0	Average
7386	49.26	-24.74	74	40.48	36.24	6.7	34.16	100	129	Peak

Test Mode :	802.11b - Chain Port 1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	103.43	-	-	100.1	32.98	3.64	33.29	100	215	Peak
2462	97.4	-	-	94.07	32.98	3.64	33.29	100	215	Average
4924	51.15	-22.85	74	44.45	35.19	5.31	33.8	100	178	Peak
4924	40.58	-13.42	54	33.88	35.19	5.31	33.8	100	178	Average
7386	49.35	-24.65	74	40.57	36.24	6.7	34.16	101	45	Peak



Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	100.16	-	-	96.93	32.89	3.61	33.27	103	273	Peak
2412	89.11	-	-	85.88	32.89	3.61	33.27	103	273	Average
4824	48.4	-25.6	74	41.78	35.17	5.25	33.8	101	223	Peak

Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	103.17	-	-	99.94	32.89	3.61	33.27	123	182	Peak
2412	91.83	-	-	88.6	32.89	3.61	33.27	123	182	Average
4824	47.24	-26.76	74	40.62	35.17	5.25	33.8	100	162	Peak



Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	100.6	-	-	97.3	32.95	3.63	33.28	161	281	Peak
2437	89.32	-	-	86.02	32.95	3.63	33.28	161	281	Average
4874	47.33	-26.67	74	40.67	35.18	5.28	33.8	115	216	Peak
7312	50.45	-23.55	74	41.77	36.2	6.61	34.13	174	100	Peak

Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	104.01	-	-	100.71	32.95	3.63	33.28	159	13	Peak
2437	91.97	-	-	88.67	32.95	3.63	33.28	159	13	Average
4874	48.19	-25.81	74	41.53	35.18	5.28	33.8	100	162	Peak
7312	50.01	-23.99	74	41.33	36.2	6.61	34.13	100	120	Peak



Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	104.75	-	-	101.42	32.98	3.64	33.29	197	167	Peak
2462	93.57	-	-	90.24	32.98	3.64	33.29	197	167	Average
4924	50.17	-23.83	74	43.47	35.19	5.31	33.8	100	162	Peak
7386	49.96	-24.04	74	41.18	36.24	6.7	34.16	100	145	Peak

Test Mode :	802.11g - Chain Port 1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	101.05	-	-	97.72	32.98	3.64	33.29	100	270	Peak
2462	88.9	-	-	85.57	32.98	3.64	33.29	100	270	Average
4924	47.28	-26.72	74	40.58	35.19	5.31	33.8	132	225	Peak
7386	48.64	-25.36	74	39.86	36.24	6.7	34.16	100	178	Peak



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	99.28	-	-	96.05	32.89	3.61	33.27	102	277	Peak
2412	88.12	-	-	84.89	32.89	3.61	33.27	102	277	Average
4824	47.27	-26.73	74	40.65	35.17	5.25	33.8	100	184	Peak

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	100.28	-	-	97.05	32.89	3.61	33.27	100	177	Peak
2412	89.19	-	-	85.96	32.89	3.61	33.27	100	177	Average
4824	46.7	-27.3	74	40.08	35.17	5.25	33.8	103	227	Peak



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	101.85	-	-	98.55	32.95	3.63	33.28	107	135	Peak
2437	90.77	-	-	87.47	32.95	3.63	33.28	107	135	Average
4874	47.1	-26.9	74	40.44	35.18	5.28	33.8	145	112	Peak
7312	48.55	-25.45	74	39.87	36.2	6.61	34.13	174	112	Peak

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	99.83	-	-	96.53	32.95	3.63	33.28	101	264	Peak
2437	85.86	-	-	82.56	32.95	3.63	33.28	101	264	Average
4874	46.16	-27.84	74	39.5	35.18	5.28	33.8	112	208	Peak
7312	48.59	-25.41	74	39.91	36.2	6.61	34.13	146	55	Peak

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	101.26	-	-	97.93	32.98	3.64	33.29	100	280	Peak
2462	89.23	-	-	85.9	32.98	3.64	33.29	100	280	Average
4924	47.25	-26.75	74	40.55	35.19	5.31	33.8	132	226	Peak
7386	49.21	-24.79	74	40.43	36.24	6.7	34.16	162	221	Peak

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	102.39	-	-	99.06	32.98	3.64	33.29	145	163	Peak
2462	90.38	-	-	87.05	32.98	3.64	33.29	145	163	Average
4924	47.46	-26.54	74	40.76	35.19	5.31	33.8	132	122	Peak
7386	49.43	-24.57	74	40.65	36.24	6.7	34.16	147	321	Peak



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
43.58	25.03	-14.97	40	48	10.03	0.62	33.62	-	-	Peak
110.51	24.19	-19.31	43.5	45.02	11.8	0.98	33.61	-	-	Peak
128.94	28.9	-14.6	43.5	49.74	11.71	1.04	33.59	100	200	Peak
234.67	17.27	-28.73	46	38.09	11.23	1.42	33.47	-	-	Peak
343.31	21.05	-24.95	46	38.36	14.35	1.7	33.36	-	-	Peak
564.47	19.07	-26.93	46	31.38	18.52	2.17	33	-	-	Peak
2412	105.12	-	-	101.89	32.89	3.61	33.27	110	157	Peak
2412	93.48	-	-	90.25	32.89	3.61	33.27	110	157	Average
4824	48.67	-25.33	74	42.05	35.17	5.25	33.8	100	328	Peak



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
53.28	32.47	-7.53	40	58.57	6.8	0.68	33.58	133	252	Peak
100.81	27.63	-15.87	43.5	49.69	10.62	0.93	33.61	-	-	Peak
128.94	26.25	-17.25	43.5	47.09	11.71	1.04	33.59	-	-	Peak
225.94	22	-24	46	43.53	10.59	1.38	33.5	-	-	Peak
521.79	18.71	-27.29	46	32	17.74	2.05	33.08	-	-	Peak
659.53	19.92	-26.08	46	31.58	18.96	2.32	32.94	-	-	Peak
2412	103.54	-	-	100.31	32.89	3.61	33.27	100	177	Peak
2412	91.25	-	-	88.02	32.89	3.61	33.27	100	177	Average
4824	47.82	-26.18	74	41.2	35.17	5.25	33.8	100	184	Peak



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	103.49	-	-	100.19	32.95	3.63	33.28	100	60	Peak
2437	90.98	-	-	87.68	32.95	3.63	33.28	100	60	Average
4874	47.87	-26.13	74	41.21	35.18	5.28	33.8	179	85	Peak
7312	48.85	-25.15	74	40.17	36.2	6.61	34.13	116	262	Peak

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	104.83	-	-	101.53	32.95	3.63	33.28	200	80	Peak
2437	93.71	-	-	90.41	32.95	3.63	33.28	199	81	Average
4874	47.1	-26.9	74	40.44	35.18	5.28	33.8	121	184	Peak
7312	49.07	-24.93	74	40.39	36.2	6.61	34.13	103	151	Peak



Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	105.42	-	-	102.09	32.98	3.64	33.29	106	157	Peak
2462	93.12	-	-	89.79	32.98	3.64	33.29	106	157	Average
4924	47.26	-26.74	74	40.56	35.19	5.31	33.8	162	211	Peak
7386	49.21	-24.79	74	40.43	36.24	6.7	34.16	132	89	Peak

Test Mode :	2.4GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	103.52	-	-	100.19	32.98	3.64	33.29	100	173	Peak
2462	91.11	-	-	87.78	32.98	3.64	33.29	100	173	Average
4924	47.48	-26.52	74	40.78	35.19	5.31	33.8	155	120	Peak
7386	49.38	-24.62	74	40.6	36.24	6.7	34.16	200	0	Peak



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	03	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2422	94.85	-	-	91.59	32.92	3.62	33.28	100	24	Peak
2422	83.6	-	-	80.34	32.92	3.62	33.28	100	24	Average
4844	46.94	-27.06	74	40.3	35.18	5.26	33.8	132	284	Peak
7266	48.14	-25.86	74	39.5	36.19	6.56	34.11	174	103	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	03	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2422	100.46	-	-	97.2	32.92	3.62	33.28	146	94	Peak
2422	90.14	-	-	86.88	32.92	3.62	33.28	146	94	Average
4844	45.79	-28.21	74	39.15	35.18	5.26	33.8	132	200	Peak
7266	48.78	-25.22	74	40.14	36.19	6.56	34.11	100	0	Peak



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	100.47	-	-	97.17	32.95	3.63	33.28	137	167	Peak
2437	89.59	-	-	86.29	32.95	3.63	33.28	137	167	Average
4874	46.62	-27.38	74	39.96	35.18	5.28	33.8	136	295	Peak
7312	47.83	-26.17	74	39.15	36.2	6.61	34.13	199	210	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	99.13	-	-	95.83	32.95	3.63	33.28	144	116	Peak
2437	88.1	-	-	84.8	32.95	3.63	33.28	144	116	Average
4874	46.82	-27.18	74	40.16	35.18	5.28	33.8	100	321	Peak
7312	48.26	-25.74	74	39.58	36.2	6.61	34.13	163	185	Peak



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	09	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2452	98.4	-	-	95.1	32.95	3.63	33.28	200	171	Peak
2452	87.83	-	-	84.53	32.95	3.63	33.28	200	171	Average
4904	46.8	-27.2	74	40.11	35.19	5.3	33.8	100	23	Peak
7356	48.78	-25.22	74	40.05	36.22	6.66	34.15	192	120	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	09	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2452	100.2	-	-	96.9	32.95	3.63	33.28	117	108	Peak
2452	90.17	-	-	86.87	32.95	3.63	33.28	117	108	Average
4904	47.04	-26.96	74	40.35	35.19	5.3	33.8	132	166	Peak
7356	48.58	-25.42	74	39.85	36.22	6.66	34.15	110	213	Peak



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	03	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2422	100.77	-	-	97.51	32.92	3.62	33.28	100	35	Peak
2422	86.83	-	-	83.57	32.92	3.62	33.28	100	35	Average
4844	47.23	-26.77	74	40.59	35.18	5.26	33.8	100	329	Peak
7266	49.34	-24.66	74	40.7	36.19	6.56	34.11	100	237	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	03	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2422	100.78	-	-	97.52	32.92	3.62	33.28	100	138	Peak
2422	88.84	-	-	85.58	32.92	3.62	33.28	100	138	Average
4844	45.83	-28.17	74	39.19	35.18	5.26	33.8	100	152	Peak
7266	49.47	-24.53	74	40.83	36.19	6.56	34.11	100	262	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	99.56	-	-	96.26	32.95	3.63	33.28	100	292	Peak
2437	88.18	-	-	84.88	32.95	3.63	33.28	100	292	Average
4874	47.16	-26.84	74	40.5	35.18	5.28	33.8	133	252	Peak
7311	48.24	-25.76	74	39.56	36.2	6.61	34.13	192	100	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	100.56	-	-	97.26	32.95	3.63	33.28	100	173	Peak
2437	89.85	-	-	86.55	32.95	3.63	33.28	100	173	Average
4874	47.04	-26.96	74	40.38	35.18	5.28	33.8	133	260	Peak
7312	48.84	-25.16	74	40.16	36.2	6.61	34.13	200	15	Peak



Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	09	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2452	97.16	-	-	93.86	32.95	3.63	33.28	100	299	Peak
2452	86.28	-	-	82.98	32.95	3.63	33.28	100	299	Average
4904	47.07	-26.93	74	40.38	35.19	5.3	33.8	200	166	Peak
7356	48.82	-25.18	74	40.09	36.22	6.66	34.15	100	75	Peak

Test Mode :	2.4GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	09	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2452	100.77	-	-	97.47	32.95	3.63	33.28	129	330	Peak
2452	89.05	-	-	85.75	32.95	3.63	33.28	129	330	Average
4904	47.65	-26.35	74	40.96	35.19	5.3	33.8	100	102	Peak
7356	49.46	-24.54	74	40.73	36.22	6.66	34.15	174	45	Peak



Test Mode :	802.11a - Chain Port 1	Temperature :	22~23°C
Test Channel :	149	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5745 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5745	101.8	-	-	94.31	35.52	5.67	33.7	100	178	Peak
5745	90.09	-	-	82.6	35.52	5.67	33.7	100	178	Average
11490	35.34	-38.66	74	56.03	4.47	8.84	34	100	0	Peak

Test Mode :	802.11a - Chain Port 1	Temperature :	22~23°C
Test Channel :	149	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5745 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5745	96.8	-	-	89.31	35.52	5.67	33.7	195	306	Peak
5745	84.57	-	-	77.08	35.52	5.67	33.7	195	306	Average
11490	35.54	-38.46	74	56.23	4.47	8.84	34	120	300	Peak



Test Mode :	802.11a - Chain Port 1	Temperature :	22~23°C
Test Channel :	157	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5785 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5785	100.52	-	-	92.99	35.53	5.7	33.7	100	178	Peak
5785	90.03	-	-	82.5	35.53	5.7	33.7	100	178	Average
11571	35.51	-38.49	74	56.35	4.38	8.8	34.02	145	120	Peak

Test Mode :	802.11a - Chain Port 1	Temperature :	22~23°C
Test Channel :	157	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5785 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5785	97.31	-	-	89.78	35.53	5.7	33.7	178	297	Peak
5785	85.47	-	-	77.94	35.53	5.7	33.7	178	297	Average
11571	35.65	-38.35	74	56.49	4.38	8.8	34.02	100	20	Peak



Test Mode :	802.11a - Chain Port 1	Temperature :	22~23°C
Test Channel :	165	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5825 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	20.35	-19.65	40	35.44	18	0.48	33.57	-	-	Peak
108.57	25.21	-18.29	43.5	46.17	11.68	0.97	33.61	-	-	Peak
128.94	25.95	-17.55	43.5	46.79	11.71	1.04	33.59	122	152	Peak
235.64	18.58	-27.42	46	39.34	11.29	1.42	33.47	-	-	Peak
396.66	17.78	-28.22	46	33.31	15.94	1.84	33.31	-	-	Peak
705.12	20.87	-25.13	46	32.01	19.34	2.39	32.87	-	-	Peak
5825	100.85	-	-	93.24	35.55	5.76	33.7	100	177	Peak
5825	89.49	-	-	81.88	35.55	5.76	33.7	100	177	Average
11649	36.78	-37.22	74	57.9	4.2	8.73	34.05	152	132	Peak



Test Mode :	802.11a - Chain Port 1	Temperature :	22~23°C
Test Channel :	165	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5825 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
54.25	32.27	-7.73	40	58.68	6.49	0.68	33.58	116	220	Peak
100.81	25.55	-17.95	43.5	47.61	10.62	0.93	33.61	-	-	Peak
128.94	25.69	-17.81	43.5	46.53	11.71	1.04	33.59	-	-	Peak
232.73	14.92	-31.08	46	35.88	11.11	1.41	33.48	-	-	Peak
386.96	16.36	-29.64	46	32.21	15.68	1.79	33.32	-	-	Peak
576.11	19.7	-26.3	46	31.94	18.55	2.19	32.98	-	-	Peak
5825	96.11	-	-	88.5	35.55	5.76	33.7	190	298	Peak
5825	85.78	-	-	78.17	35.55	5.76	33.7	190	298	Average
11649	37.78	-36.22	74	58.9	4.2	8.73	34.05	154	120	Peak



Test Mode :	5GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	149	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5745 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5745	101.95	-	-	94.46	35.52	5.67	33.7	100	180	Peak
5745	90.07	-	-	82.58	35.52	5.67	33.7	100	180	Average
11490	35.57	-38.43	74	56.26	4.47	8.84	34	162	184	Peak

Test Mode :	5GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	149	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5745 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5745	97.85	-	-	90.36	35.52	5.67	33.7	196	299	Peak
5745	85.83	-	-	78.34	35.52	5.67	33.7	196	299	Average
11490	33.96	-40.04	74	54.65	4.47	8.84	34	120	10	Peak



Test Mode :	5GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	157	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5785 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5785	101.94	-	-	94.41	35.53	5.7	33.7	100	178	Peak
5785	90.33	-	-	82.8	35.53	5.7	33.7	100	178	Average
11571	34.84	-39.16	74	55.68	4.38	8.8	34.02	174	120	Peak

Test Mode :	5GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	157	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5785 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5785	93.53	-	-	86	35.53	5.7	33.7	178	297	Peak
5785	82	-	-	74.47	35.53	5.7	33.7	178	297	Average
11571	34.14	-39.86	74	54.98	4.38	8.8	34.02	132	296	Peak



Test Mode :	5GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	165	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5825 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5825	101.88	-	-	94.27	35.55	5.76	33.7	100	185	Peak
5825	90.46	-	-	82.85	35.55	5.76	33.7	100	185	Average
11649	36.94	-37.06	74	58.06	4.2	8.73	34.05	162	285	Peak

Test Mode :	5GHz 802.11n HT20 – Chain Port 1	Temperature :	22~23°C
Test Channel :	165	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5825 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5825	98.41	-	-	90.8	35.55	5.76	33.7	175	298	Peak
5825	86.53	-	-	78.92	35.55	5.76	33.7	175	298	Average
11649	35.74	-38.26	74	56.86	4.2	8.73	34.05	174	45	Peak



Test Mode :	5GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	149	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5745 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5745	101.87	-	-	94.38	35.52	5.67	33.7	100	182	Peak
5745	90.33	-	-	82.84	35.52	5.67	33.7	100	182	Average
11490	35.5	-38.5	74	56.19	4.47	8.84	34	115	147	Peak

Test Mode :	5GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	149	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5745 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5745	95.68	-	-	88.19	35.52	5.67	33.7	133	24	Peak
5745	84.24	-	-	76.75	35.52	5.67	33.7	133	24	Average
11490	34.51	-39.49	74	55.2	4.47	8.84	34	174	300	Peak



Test Mode :	5GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	157	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5785 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5785	103.99	-	-	96.46	35.53	5.7	33.7	100	0	Peak
5785	92.35	-	-	84.82	35.53	5.7	33.7	100	0	Average
11571	35.11	-38.89	74	55.95	4.38	8.8	34.02	195	245	Peak

Test Mode :	5GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	157	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5785 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5785	96.88	-	-	89.35	35.53	5.7	33.7	100	326	Peak
5785	83.79	-	-	76.26	35.53	5.7	33.7	100	326	Average
11571	34.45	-39.55	74	55.29	4.38	8.8	34.02	188	221	Peak



Test Mode :	5GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	165	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5825 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5825	104.26	-	-	96.65	35.55	5.76	33.7	100	0	Peak
5825	94.13	-	-	86.52	35.55	5.76	33.7	100	0	Average
11649	37.64	-36.36	74	58.76	4.2	8.73	34.05	162	144	Peak

Test Mode :	5GHz 802.11n HT20 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	165	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5825 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5825	98.94	-	-	91.33	35.55	5.76	33.7	178	233	Peak
5825	87.35	-	-	79.74	35.55	5.76	33.7	178	233	Average
11649	36.38	-37.62	74	57.5	4.2	8.73	34.05	159	226	Peak



Test Mode :	5GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	151	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5755 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5755	98.06	-	-	90.55	35.53	5.68	33.7	100	182	Peak
5755	85.45	-	-	77.94	35.53	5.68	33.7	100	182	Average
11511	34.28	-39.72	74	54.89	4.53	8.86	34	132	100	Peak

Test Mode :	5GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	151	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5755 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5755	93.46	-	-	85.95	35.53	5.68	33.7	195	290	Peak
5755	82.67	-	-	75.16	35.53	5.68	33.7	195	290	Average
11511	34.62	-39.38	74	55.23	4.53	8.86	34	132	62	Peak



Test Mode :	5GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	159	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5795 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5795	103.55	-	-	95.99	35.54	5.72	33.7	100	169	Peak
5795	91.31	-	-	83.75	35.54	5.72	33.7	100	169	Average
11589	35.09	-38.91	74	56	4.34	8.78	34.03	122	78	Peak

Test Mode :	5GHz 802.11n HT40 – Chain Port 1	Temperature :	22~23°C
Test Channel :	159	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5795 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5795	99.46	-	-	91.9	35.54	5.72	33.7	195	287	Peak
5795	87.73	-	-	80.17	35.54	5.72	33.7	195	287	Average
11589	35.87	-38.13	74	56.78	4.34	8.78	34.03	169	48	Peak



Test Mode :	5GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	151	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5755 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5755	105.22	-	-	97.71	35.53	5.68	33.7	100	12	Peak
5755	93.69	-	-	86.18	35.53	5.68	33.7	100	12	Average
11511	35.06	-38.94	74	55.67	4.53	8.86	34	145	48	Peak

Test Mode :	5GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	151	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5755 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5755	100.27	-	-	92.76	35.53	5.68	33.7	100	331	Peak
5755	88.25	-	-	80.74	35.53	5.68	33.7	100	331	Average
11511	35.27	-38.73	74	55.88	4.53	8.86	34	100	189	Peak



Test Mode :	5GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	159	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 5795 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5795	107.57	-	-	100.01	35.54	5.72	33.7	100	2	Peak
5795	94.87	-	-	87.31	35.54	5.72	33.7	100	2	Average
11589	35.05	-38.95	74	55.96	4.34	8.78	34.03	111	184	Peak

Test Mode :	5GHz 802.11n HT40 – Chain Port 0+1	Temperature :	22~23°C
Test Channel :	159	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 5795 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5795	105.4	-	-	97.84	35.54	5.72	33.7	194	231	Peak
5795	94.34	-	-	86.78	35.54	5.72	33.7	194	231	Average
11589	35.41	-38.59	74	56.32	4.34	8.78	34.03	200	0	Peak

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	21~23°C
Test Engineer :	Eligah Wang	Relative Humidity :	35~37%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GPRS850 Idle + WLAN 5GHz Link + USB Cable (Charging from Adapter)		




Site : C001-KS
 Condition: FCC PART15C LISN-L20130306 LINE
 Project : (FR) 440903
 mode : Mode 2

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.45	39.12	-17.73	56.85	28.60	0.25	10.27	QP
2	0.45	30.42	-16.43	46.85	19.90	0.25	10.27	Average
3	0.60	42.34	-13.66	56.00	31.90	0.20	10.24	QP
4	0.60	35.34	-10.66	46.00	24.90	0.20	10.24	Average
5	0.64	37.73	-8.27	46.00	27.30	0.20	10.23	Average
6	0.64	45.83	-10.17	56.00	35.40	0.20	10.23	QP
7	0.66	34.32	-11.68	46.00	23.90	0.20	10.22	Average
8	0.66	43.22	-12.78	56.00	32.80	0.20	10.22	QP
9	0.70	37.21	-18.79	56.00	26.80	0.20	10.21	QP
10	0.70	31.81	-14.19	46.00	21.40	0.20	10.21	Average
11	0.86	36.93	-19.07	56.00	26.60	0.14	10.19	QP
12	0.86	30.23	-15.77	46.00	19.90	0.14	10.19	Average



Test Mode :	Mode 2	Temperature :	21~23°C
Test Engineer :	Eligah Wang	Relative Humidity :	35~37%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GPRS850 Idle + WLAN 5GHz Link + USB Cable (Charging from Adapter)		



Site : C001-KS
 Condition: FCC PART15C LISN-M20130306 NEUTRAL
 Project : (FR) 440903
 mode : Mode 2

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.39	33.12	-15.05	48.17	22.40	0.43	10.29	Average
2	0.39	38.82	-19.35	58.17	28.10	0.43	10.29	QP
3	0.46	36.21	-20.55	56.76	25.60	0.34	10.27	QP
4	0.46	29.21	-17.55	46.76	18.60	0.34	10.27	Average
5	0.60	34.08	-11.92	46.00	23.60	0.24	10.24	Average
6	0.60	40.08	-15.92	56.00	29.60	0.24	10.24	QP
7	0.63	42.75	-13.25	56.00	32.30	0.22	10.23	QP
8	0.63	37.35	-8.65	46.00	26.90	0.22	10.23	Average
9	0.67	37.93	-18.07	56.00	27.50	0.21	10.22	QP
10	0.67	32.53	-13.47	46.00	22.10	0.21	10.22	Average
11	0.90	36.21	-19.79	56.00	25.90	0.12	10.19	QP
12	0.90	29.91	-16.09	46.00	19.60	0.12	10.19	Average

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

Non-standard antenna connector is used.

3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

For CDD transmissions, directional gain is calculated as

Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

The EUT supports CDD mode.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
	Ant. 0	Ant. 1	for	for	Limit	Limit
	(dBi)	(dBi)	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	1.00	1.00	1.00	4.01	0.00	0.00
5 GHz	1.00	1.00	1.00	4.01	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 28, 2013	May 08, 2014~ May 21, 2014	Dec. 27, 2014	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Feb. 27, 2014	May 08, 2014~ May 21, 2014	Feb. 26, 2015	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Feb. 27, 2014	May 08, 2014~ May 21, 2014	Feb. 26, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	May 07, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 23, 2013	May 07, 2014	May 22, 2014	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 09, 2013	May 07, 2014	Oct. 08, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	May 07, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 08, 2014	May 07, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Mar. 10, 2014	May 07, 2014	Mar. 09, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 18, 2013	May 07, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	May 07, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A023 71	1GHz~26.5GHz	Dec.10, 2013	May 07, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	May 07, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	May 07, 2014	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	May 23, 2013	Apr. 26, 2014	May 22, 2014	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Dec. 10, 2013	Apr. 26, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Dec. 10, 2013	Apr. 26, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Dec. 10, 2013	Apr. 26, 2014	Dec. 09, 2014	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------