



TESTING LABORATORY  
CERTIFICATE #4820.01



FCC PART 15.407  
RSS-GEN, ISSUE 5, APRIL 2018  
RSS-247, ISSUE 2, FEBRUARY 2017  
TEST REPORT

For

**SZ DJI TECHNOLOGY CO., LTD**

14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave,  
Nanshan, Shenzhen, Guangdong, China

**FCC ID: SS3-P1GS1902**  
**IC: 11805A-P1GS1902**

|                                                                                                                                                                                                                                                                               |                                         |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                        | <b>Product Name:</b><br>DJI FPV Goggles |
| <b>Report Number:</b> RDG190315002-00B                                                                                                                                                                                                                                        |                                         |
| <b>Report Date:</b> 2019-05-14                                                                                                                                                                                                                                                |                                         |
| <b>Reviewed By:</b>                                                                                                                                                                                                                                                           | Jerry Zhang<br>EMC Manager              |
| <b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Dongguan)<br>No.69 Pulongcun, Puxinhu Industry Area,<br>Tangxia, Dongguan, Guangdong, China<br>Tel: +86-769-86858888<br>Fax: +86-769-86858891<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                         |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*\*".

## **TABLE OF CONTENTS**

|                                                                                                         |           |
|---------------------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                                         | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                                | 4         |
| OBJECTIVE .....                                                                                         | 4         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                                                      | 4         |
| TEST METHODOLOGY .....                                                                                  | 4         |
| MEASUREMENT UNCERTAINTY .....                                                                           | 5         |
| TEST FACILITY .....                                                                                     | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                                   | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                                 | 6         |
| EUT EXERCISE SOFTWARE .....                                                                             | 6         |
| EQUIPMENT MODIFICATIONS .....                                                                           | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                                | 7         |
| SUPPORT CABLE LIST AND DETAILS .....                                                                    | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                                       | 7         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                                    | <b>9</b>  |
| <b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1093, RSS-102 §4- RF EXPOSURE.....</b>                        | <b>10</b> |
| APPLICABLE STANDARD .....                                                                               | 10        |
| TEST RESULT .....                                                                                       | 10        |
| <b>FCC §15.203&amp; RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT .....</b>                                  | <b>11</b> |
| APPLICABLE STANDARD .....                                                                               | 11        |
| ANTENNA INFORMATION AND CONNECTOR CONSTRUCTION.....                                                     | 12        |
| <b>FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS .....</b>                                      | <b>13</b> |
| APPLICABLE STANDARD .....                                                                               | 13        |
| EUT SETUP.....                                                                                          | 13        |
| EMI TEST RECEIVER SETUP.....                                                                            | 13        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                                          | 13        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                                    | 14        |
| TEST PROCEDURE .....                                                                                    | 14        |
| TEST DATA .....                                                                                         | 14        |
| <b>FCC §15.209, §15.205 , §15.407(b) &amp; RSS-247 §6.2, RSS-GEN§8.10 –UNWANTED EMISSION .....</b>      | <b>17</b> |
| APPLICABLE STANDARD .....                                                                               | 17        |
| EUT SETUP .....                                                                                         | 19        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                                       | 20        |
| TEST PROCEDURE .....                                                                                    | 21        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                                          | 21        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                                    | 22        |
| TEST DATA .....                                                                                         | 23        |
| <b>FCC §15.407(a)(e) &amp; RSS-247 §6.2,RSS-Gen §6.7–EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH.....</b> | <b>30</b> |
| APPLICABLE STANDARD .....                                                                               | 30        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                                    | 30        |
| TEST PROCEDURE .....                                                                                    | 30        |
| TEST DATA .....                                                                                         | 30        |
| <b>FCC §15.407(a) &amp; RSS-247 §6.2 –MAXIMUM CONDUCTED OUTPUT POWER.....</b>                           | <b>34</b> |
| APPLICABLE STANDARD .....                                                                               | 34        |

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 36        |
| TEST PROCEDURE .....                                                  | 36        |
| TEST DATA .....                                                       | 37        |
| <b>FCC §15.407(a)&amp; RSS-247 §6.2- POWER SPECTRAL DENSITY .....</b> | <b>38</b> |
| APPLICABLE STANDARD .....                                             | 38        |
| TEST PROCEDURE .....                                                  | 40        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 40        |
| TEST DATA .....                                                       | 41        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                              |                                           |
|----------------------------------------------|-------------------------------------------|
| <b>EUT Name:</b>                             | DJI FPV Goggles                           |
| <b>Model:</b>                                | P1GS                                      |
| <b>Operation Frequency:</b>                  | 5731.5-5844.5 MHz                         |
| <b>Maximum Output Power<br/>(Conducted):</b> | 19.85 dBm                                 |
| <b>Modulation Type:</b>                      | OFDM                                      |
| <b>Rated Input Voltage:</b>                  | 7.4Vdc-17.6Vdc from external power supply |
| <b>External Dimension:</b>                   | 202(L)*110mm(W)*126mm(H)                  |
| <b>Serial Number:</b>                        | 190315002                                 |
| <b>EUT Received Date:</b>                    | 2019-04-18                                |

### Objective

This type approval report is prepared on behalf of **SZ DJI TECHNOLOGY CO., LTD** in accordance with Part 2-Subpart J, Part 15-Subparts A, and E of the Federal Communications Commission's rules. And RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, April 2018 of the Innovation, Science and Economic Development Canada.

The tests were performed in order to determine compliance with FCC Rules Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules and RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, April 2018 of the Innovation, Science and Economic Development Canada.

### Related Submittal(s)/Grant(s)

FCC submissions with Part 15B JBP, FCC ID: SS3-P1GS1902

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, and RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, April 2018 of the Innovation, Science and Economic Development Canada.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

**Measurement Uncertainty**

| Parameter                         | Measurement Uncertainty                                                                                                                                    |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Occupied Channel Bandwidth        | ±5 %                                                                                                                                                       |
| RF output power, conducted        | ±0.61dB                                                                                                                                                    |
| Power Spectral Density, conducted | ±0.61 dB                                                                                                                                                   |
| Unwanted Emissions, radiated      | 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical<br>200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical<br>1G~6GHz: 4.45 dB, 6G~40GHz: 5.23 dB |
| Unwanted Emissions,conducted      | ±1.5 dB                                                                                                                                                    |
| Temperature                       | ±1 °C                                                                                                                                                      |
| Humidity                          | ±5%                                                                                                                                                        |
| DC and low frequency voltages     | ±0.4%                                                                                                                                                      |
| Duty Cycle                        | 1%                                                                                                                                                         |
| AC Power Lines Conducted Emission | 3.12 dB (150 kHz to 30 MHz)                                                                                                                                |

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxihu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

The EUT has 4 antennas, the system configure 2T3R:(Chain 0+2 Tx/Rx, Chain 3 Rx), or (Chain 1+2 Tx/Rx, Chain 3 Rx), that is depend on better performance by the system automatically recognizes.

The device employs total 123 channels, please refer to the operational description. 3 channels were tested: 5731.5MHz, 5784.12 MHz and 5844.5MHz


### EUT Exercise Software

Test software: 'DjiSdrConsole\_V1.3.5.59.exe ' was used in test, the maximum power with maximum duty cycle was configured as below setting:

| Channel | Frequency (MHz) | Power level |
|---------|-----------------|-------------|
| Low     | 5731.5          | 1           |
| Middle  | 5784.12         | 1           |
| High    | 5844.5          | 1           |

The duty cycle as below:

| T <sub>on</sub> (ms) | T <sub>on+off</sub> (ms) | Duty Cycle(x) (%) | Duty cycle Factor (10*log(1/x)) |
|----------------------|--------------------------|-------------------|---------------------------------|
| 100                  | 100                      | 100               | 0                               |



## Equipment Modifications

No modification was made to the EUT.

## Support Equipment List and Details


| Manufacturer | Description  | Model        | Serial Number |
|--------------|--------------|--------------|---------------|
| Redzone      | LiPo Battery | /            | /             |
| Huawei       | Earphone     | /            | /             |
| SanDisk      | SD Card      | 4G           | /             |
| HUAWEI       | AC Adapter   | HW-120200E5W | /             |

## Support Cable List and Details


| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port       | To             |
|-------------------|----------------|--------------|------------|-----------------|----------------|
| Power Cable       | Yes            | No           | 1.2        | Battery/Adapter | DC Port of EUT |
| Earphone Cable    | Yes            | No           | 1.2        | EUT             | Earphone       |

## Block Diagram of Test Setup

Adapter Power Supply(Conducted Emissions):



Battery Power supply(Radiation Test):





**SUMMARY OF TEST RESULTS**

| Rules                                              | Description of Test                    | Result     |
|----------------------------------------------------|----------------------------------------|------------|
| FCC §15.247 (i) & §1.1310 & §2.1093<br>RSS-102 §4  | RF Exposure                            | Compliance |
| FCC§15.203,<br>RSS-GEN§6.8                         | Antenna Requirement                    | Compliance |
| FCC§15.407(b)(6)&<br>§15.207(a),<br>RSS-Gen §8.8   | Conducted Emissions                    | Compliance |
| FCC§15.205& §15.209<br>&§15.407(b),<br>RSS-247§6.2 | Undesirable Emission& Restricted Bands | Compliance |
| FCC§15.407(b)<br>RSS-247§6.2                       | Out Of Band Emissions                  | Compliance |
| FCC§15.407(a) (e),<br>RSS-247 §6.2<br>RSS-Gen§6.7  | Emission Bandwidth                     | Compliance |
| FCC§15.407(g)                                      | Frequency Stability                    | Compliance |
| FCC§15.407(a)<br>RSS-247 §6.2                      | Conducted Transmitter Output Power     | Compliance |
| FCC§15.407 (a),<br>RSS-247 §6.2                    | Power Spectral Density                 | Compliance |

**FCC §15.247 (i) & §1.1310 & §2.1093, RSS-102 §4- RF EXPOSURE****Applicable Standard**

According to §15.247(i), §1.1310 and §2.1093.

According to RSS-102 §4 Table 3, SAR limits for device used by the general public

| Body Region                    | Average SAR<br>(W/Kg) | Averaging Time<br>(minutes) | Mass Average<br>(g) |
|--------------------------------|-----------------------|-----------------------------|---------------------|
| Whole Body                     | 0.08                  | 6                           | Whole Body          |
| Localized Head, Neck and Trunk | 1.6                   | 6                           | 1                   |
| Localized Limbs                | 4                     | 6                           | 10                  |

**Test Result**

Compliant, please refer to the SAR report: RDG190315002-20.

---

**FCC §15.203& RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT**

---

**Applicable Standard**

According to FCC§ 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

According to RSS-Gen §6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

**Antenna Information And Connector Construction**

The EUT has 4 external antenna arrangement, use unique connector coupling to the radio board, fulfill the requirement of this section. Please refer to the EUT photos and below information:

| Antenna       | Antenna Type | Connector Type | input impedance (Ohm) | Antenna Gain /Frequency |
|---------------|--------------|----------------|-----------------------|-------------------------|
| Chain 0/1/2/3 | Dipole       | RP-SMA         | 50                    | 2.84 dBi/5.8GHz         |


**Result:** Compliance.

## FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a), §15.407(b) (6)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisen with a 120 V/60 Hz AC power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_c$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

| Manufacturer | Description        | Model     | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|-----------|---------------|------------------|----------------------|
| Unknown      | Coaxial Cable      | C-NJNJ-50 | C-0200-01     | 2018-09-05       | 2019-09-05           |
| R&S          | Test Software      | EMC32     | Version8.53.0 | N/A              | N/A                  |
| R&S          | Two-line V-network | ENV 216   | 101614        | 2018-12-10       | 2019-12-10           |
| R&S          | EMI Test Receiver  | ESCI      | 101121        | 2019-03-23       | 2020-03-23           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Test Data

#### Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25.3 °C   |
| Relative Humidity: | 52 %      |
| ATM Pressure:      | 100.5 kPa |

The testing was performed by Lily Xie from 2019-04-24.

Test Mode: Transmitting (Tx Chain 0+2 Low channel was the worst)


Adapter Power supply mode:

**AC120 V, 60 Hz, Line:**



| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.159228        | 54.8             | 9.000           | L1   | 11.1       | 10.7        | 65.5         | Compliance |
| 0.190460        | 53.0             | 9.000           | L1   | 10.7       | 11.0        | 64.0         | Compliance |
| 0.223330        | 50.3             | 9.000           | L1   | 10.5       | 12.4        | 62.7         | Compliance |
| 0.292162        | 44.4             | 9.000           | L1   | 10.2       | 16.1        | 60.5         | Compliance |
| 0.329215        | 44.9             | 9.000           | L1   | 10.1       | 14.6        | 59.5         | Compliance |
| 0.349469        | 43.7             | 9.000           | L1   | 10.0       | 15.3        | 59.0         | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.234722        | 31.6           | 9.000           | L1   | 10.4       | 20.7        | 52.3         | Compliance |
| 0.319533        | 41.5           | 9.000           | L1   | 10.1       | 8.2         | 49.7         | Compliance |
| 0.342583        | 38.1           | 9.000           | L1   | 10.0       | 11.0        | 49.1         | Compliance |
| 0.370968        | 30.9           | 9.000           | L1   | 10.0       | 17.6        | 48.5         | Compliance |
| 10.296163       | 32.7           | 9.000           | L1   | 9.8        | 17.3        | 50.0         | Compliance |
| 11.260762       | 35.8           | 9.000           | L1   | 9.8        | 14.2        | 50.0         | Compliance |

**AC120 V, 60 Hz, Neutral:**

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.153015        | 56.3             | 9.000           | N    | 11.1       | 9.5         | 65.8         | Compliance |
| 0.277982        | 45.9             | 9.000           | N    | 10.2       | 15.0        | 60.9         | Compliance |
| 0.295084        | 45.4             | 9.000           | N    | 10.2       | 15.0        | 60.4         | Compliance |
| 0.329215        | 43.2             | 9.000           | N    | 10.1       | 16.3        | 59.5         | Compliance |
| 0.409780        | 38.6             | 9.000           | N    | 10.0       | 19.1        | 57.7         | Compliance |
| 0.461750        | 37.2             | 9.000           | N    | 9.9        | 19.5        | 56.7         | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.289269        | 31.5           | 9.000           | N    | 10.2       | 19.0        | 50.5         | Compliance |
| 0.319533        | 38.0           | 9.000           | N    | 10.1       | 11.7        | 49.7         | Compliance |
| 0.346009        | 37.3           | 9.000           | N    | 10.0       | 11.8        | 49.1         | Compliance |
| 0.370968        | 30.8           | 9.000           | N    | 10.0       | 17.7        | 48.5         | Compliance |
| 10.296163       | 33.1           | 9.000           | N    | 9.8        | 16.9        | 50.0         | Compliance |
| 11.487103       | 36.2           | 9.000           | N    | 9.8        | 13.8        | 50.0         | Compliance |



---

**FCC §15.209, §15.205 , §15.407(b) &RSS-247 §6.2, RSS-GEN§8.10 –  
UNWANTED EMISSION**

---

**Applicable Standard**

FCC §15.407; §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

(7) The provisions of §15.205 apply to intentional radiators operating under this section.

According to RSS-247§6.2

## **Frequency band 5150-5250 MHz**

### **6.2.1.2 Unwanted emission limits**

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

## **Frequency band 5250-5350 MHz**

### **6.2.2.2 Unwanted emission limits**

Devices shall comply with the following:

- a) All emissions outside the band 5250-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p.; or
- b) All emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. and its power shall comply with the spectral power density for operation within the band 5150-5250 MHz. The device, except devices installed in vehicles, shall be labelled or include in the user manual the following text “for indoor use only.”

## **Frequency bands 5470-5600 MHz and 5650-5725 MHz:**

### **6.2.3.2 Unwanted emission limits**

Emissions outside the band 5470-5600 MHz and 5650-5725 MHz shall not exceed -27 dBm/MHz e.i.r.p. However, devices with bandwidth overlapping the band edge of 5725 MHz can meet the emission limit of -27 dBm/MHz e.i.r.p. at 5850 MHz instead of 5725 MHz.

## Frequency band 5725-5850 MHz

### 6.2.4.2 Unwanted emission limits

Devices operating in the band 5725-5850 MHz with antenna gain greater than 10 dBi can have unwanted emissions that comply with either the limits in this section or in section 5.5 until six (6) months after the publication date of this standard for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2018.


Devices operating in the band 5725-5850 MHz with antenna gain of 10 dBi or less can have unwanted emissions that comply with either the limits in this section or in section 5.5 until April 1, 2018 for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2020.



Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

- 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- 27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

## EUT Setup

### Below 1 GHz:



**1-26.5 GHz:****26.5-40 GHz:**

The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.407 and RSS-247, RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

| Measurement | RBW     | Video B/W | IF B/W |
|-------------|---------|-----------|--------|
| QP          | 120 kHz | 300 kHz   | 120kHz |

1GHz- 40GHz:

| Measurement | Duty cycle | RBW  | Video B/W |
|-------------|------------|------|-----------|
| PK          | Any        | 1MHz | 3 MHz     |
| Ave.        | >98%       | 1MHz | 10 Hz     |
|             | <98%       | 1MHz | 1/T       |

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as:  $E [dB\mu V/m] = EIRP[dBm] + 95.2$ , for  $d = 3$  meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 1.5m or 1m

Distance extrapolation factor =  $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$  dB = 6.02 dB  
or

Distance extrapolation factor =  $20 \log (\text{specific distance } [3m] / \text{test distance } [1m])$  dB = 9.54 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

## Corrected Amplitude & Margin Calculation

For the range 30MHz-1GHz, the Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

For the range 1GHz-40GHz, Test performed at 1.5m or 1m, the Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading and the Distance extrapolation factor. The basic equation is as follows:

Corrected Amplitude

= Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain-Distance extrapolation factor

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

| Manufacturer          | Description       | Model                       | Serial Number      | Calibration Date | Calibration Due Date |
|-----------------------|-------------------|-----------------------------|--------------------|------------------|----------------------|
| R&S                   | EMI Test Receiver | ESPI                        | 100120             | 2018-12-10       | 2019-12-10           |
| Farad                 | Test Software     | EZ-EMC                      | V1.1.4.2           | N/A              | N/A                  |
| Sunol Sciences        | Antenna           | JB3                         | A060611-1          | 2017-11-10       | 2020-11-10           |
| Unknown               | Coaxial Cable     | C-NJNJ-50                   | C-0400-01          | 2018-09-05       | 2019-09-05           |
| Unknown               | Coaxial Cable     | C-NJNJ-50                   | C-0075-01          | 2018-09-05       | 2019-09-05           |
| Unknown               | Coaxial Cable     | C-NJNJ-50                   | C-1400-01          | 2018-05-06       | 2019-05-06           |
| HP                    | Amplifier         | 8447D                       | 2727A05902         | 2018-09-05       | 2019-09-05           |
| Agilent               | Spectrum Analyzer | E4440A                      | SG43360054         | 2019-01-04       | 2020-01-04           |
| R&S                   | Spectrum Analyzer | FSV40                       | 101474             | 2019-1-9         | 2020-1-9             |
| ETS-Lindgren          | Horn Antenna      | 3115                        | 000 527 35         | 2017-01-05       | 2020-01-04           |
| Ducommun Technologies | Horn Antenna      | ARH-4223-02                 | 1007726-01<br>1304 | 2016-11-18       | 2019-11-18           |
| Ducommun Technologies | Horn Antenna      | ARH-2823-02                 | 1007726-01<br>1302 | 2016-11-18       | 2019-11-18           |
| Unknown               | Coaxial Cable     | C-SJSJ-50                   | C-0800-01          | 2018-09-05       | 2019-09-05           |
| Unknown               | Coaxial Cable     | C-2.4J2.4J-50               | C-0700-02          | 2018-06-27       | 2019-06-27           |
| MITEQ                 | Amplifier         | AFS42-00101800-<br>25-S-42  | 2001271            | 2018-09-05       | 2019-09-05           |
| Quinstar              | Amplifier         | QLW-18405536-JO             | 15964001001        | 2018-06-27       | 2019-06-27           |
| Sinoscite             | Bandstop Filters  | BSF5150-5850MN-<br>0899-003 | 0899003            | 2018-05-06       | 2019-05-06           |
| Mini Circuits         | High Pass Filter  | VHF-6010+                   | 31118              | 2018-06-16       | 2019-06-16           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data

### Environmental Conditions


|                    |              |
|--------------------|--------------|
| Temperature:       | 25.8~27.8 °C |
| Relative Humidity: | 53~66 %      |
| ATM Pressure:      | 100.3 kPa    |

\* The testing was performed by Neil Liao&Lucy Lu on 2019-04-23 to 2019-04-24

Test Mode: Transmitting(Adapter power supply mode was the worst)


1) 30MHz-1GHz(Tx Chain 0+2 Low channel was the worst)

### Horizontal



| Frequency (MHz) | Receiver Reading (dBμV) | Detector | Correction Factor (dB/m) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|-------------------------|----------|--------------------------|---------------------|----------------|-------------|
| 30.0000         | 25.65                   | peak     | 1.72                     | 27.37               | 40.00          | 12.63       |
| 140.5800        | 31.42                   | peak     | -5.78                    | 25.64               | 43.50          | 17.86       |
| 298.6900        | 29.49                   | peak     | -3.88                    | 25.61               | 46.00          | 20.39       |
| 594.5400        | 32.34                   | peak     | 0.86                     | 33.20               | 46.00          | 12.80       |
| 828.3100        | 26.69                   | peak     | 5.06                     | 31.75               | 46.00          | 14.25       |
| 968.9600        | 10.80                   | peak     | 22.98                    | 33.78               | 54.00          | 20.22       |

## Vertical



| Frequency (MHz) | Receiver Reading (dB $\mu$ V) | Detector | Correction Factor (dB/m) | Cord. Amp. (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
|-----------------|-------------------------------|----------|--------------------------|---------------------------|----------------------|-------------|
| 30.0000         | 27.13                         | peak     | 1.72                     | 28.85                     | 40.00                | 11.15       |
| 90.1400         | 36.78                         | peak     | -11.19                   | 25.59                     | 43.50                | 17.91       |
| 360.7700        | 34.27                         | peak     | -2.80                    | 31.47                     | 46.00                | 14.53       |
| 594.5400        | 30.20                         | peak     | 0.86                     | 31.06                     | 46.00                | 14.94       |
| 899.1200        | 36.31                         | peak     | -3.86                    | 32.45                     | 46.00                | 13.55       |
| 967.9900        | 10.89                         | peak     | 22.96                    | 33.85                     | 54.00                | 20.15       |



**2) 1GHz-40GHz:****Tx Chain 0+2:**




| Frequency<br>(MHz)          | Receiver          |          | Rx Antenna     |                  | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Extrapolation<br>result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----------------------------|-------------------|----------|----------------|------------------|-----------------------|---------------------------|------------------------------------|-------------------------------------|-------------------|----------------|
|                             | Reading<br>(dBμV) | Detector | Polar<br>(H/V) | Factor<br>(dB/m) |                       |                           |                                    |                                     |                   |                |
| Low Channel: 5731.5 MHz     |                   |          |                |                  |                       |                           |                                    |                                     |                   |                |
| 5731.50                     | 90.23             | PK       | H              | 34.19            | 3.69                  | 0.00                      | 128.11                             | 122.09                              | N/A               | N/A            |
| 5731.50                     | 80.70             | AV       | H              | 34.19            | 3.69                  | 0.00                      | 118.58                             | 112.56                              | N/A               | N/A            |
| 5731.50                     | 93.90             | PK       | V              | 34.19            | 3.69                  | 0.00                      | 131.78                             | 125.76                              | N/A               | N/A            |
| 5731.50                     | 84.73             | AV       | V              | 34.19            | 3.69                  | 0.00                      | 122.61                             | 116.59                              | N/A               | N/A            |
| 5725.00                     | 38.30             | PK       | V              | 34.19            | 3.69                  | 0.00                      | 76.18                              | 70.16                               | 122.20            | 52.04          |
| 5720.00                     | 36.68             | PK       | V              | 34.19            | 3.69                  | 0.00                      | 74.56                              | 68.54                               | 110.80            | 42.26          |
| 5700.00                     | 30.47             | PK       | V              | 34.18            | 3.68                  | 0.00                      | 68.33                              | 62.31                               | 105.20            | 42.89          |
| 5650.00                     | 29.12             | PK       | V              | 34.16            | 3.63                  | 0.00                      | 66.91                              | 60.89                               | 68.20             | 7.31           |
| 11463.00                    | 55.96             | PK       | V              | 38.96            | 6.59                  | 37.34                     | 64.17                              | 58.15                               | 74.00             | 15.85          |
| 11463.00                    | 43.35             | AV       | V              | 38.96            | 6.59                  | 37.34                     | 51.56                              | 45.54                               | 54.00             | 8.46           |
| 17194.50                    | 56.19             | PK       | V              | 41.33            | 8.77                  | 38.63                     | 67.66                              | 61.64                               | 68.20             | 6.56           |
| Middle Channel: 5784.12 MHz |                   |          |                |                  |                       |                           |                                    |                                     |                   |                |
| 5784.12                     | 89.65             | PK       | H              | 34.21            | 3.71                  | 0.00                      | 127.57                             | 121.55                              | N/A               | N/A            |
| 5784.12                     | 81.47             | AV       | H              | 34.21            | 3.71                  | 0.00                      | 119.39                             | 113.37                              | N/A               | N/A            |
| 5784.12                     | 92.84             | PK       | V              | 34.21            | 3.71                  | 0.00                      | 130.76                             | 124.74                              | N/A               | N/A            |
| 5784.12                     | 83.63             | AV       | V              | 34.21            | 3.71                  | 0.00                      | 121.55                             | 115.53                              | N/A               | N/A            |
| 11568.24                    | 54.45             | PK       | V              | 39.00            | 6.61                  | 37.44                     | 62.62                              | 56.6                                | 74.00             | 17.40          |
| 11568.24                    | 42.65             | AV       | V              | 39.00            | 6.61                  | 37.44                     | 50.82                              | 44.8                                | 54.00             | 9.20           |
| 17352.36                    | 52.66             | PK       | V              | 42.24            | 8.81                  | 38.52                     | 65.19                              | 59.17                               | 68.20             | 9.03           |
| High Channel: 5844.5 MHz    |                   |          |                |                  |                       |                           |                                    |                                     |                   |                |
| 5844.50                     | 87.97             | PK       | H              | 34.24            | 3.75                  | 0.00                      | 125.96                             | 119.94                              | N/A               | N/A            |
| 5844.50                     | 78.62             | AV       | H              | 34.24            | 3.75                  | 0.00                      | 116.61                             | 110.59                              | N/A               | N/A            |
| 5844.50                     | 90.70             | PK       | V              | 34.24            | 3.75                  | 0.00                      | 128.69                             | 122.67                              | N/A               | N/A            |
| 5844.50                     | 81.57             | AV       | V              | 34.24            | 3.75                  | 0.00                      | 119.56                             | 113.54                              | N/A               | N/A            |
| 5850.00                     | 36.95             | PK       | V              | 34.24            | 3.75                  | 0.00                      | 74.94                              | 68.92                               | 122.20            | 53.28          |
| 5855.00                     | 34.03             | PK       | V              | 34.24            | 3.75                  | 0.00                      | 72.02                              | 66                                  | 110.80            | 44.80          |
| 5875.00                     | 28.76             | PK       | V              | 34.25            | 3.77                  | 0.00                      | 66.78                              | 60.76                               | 105.20            | 44.44          |
| 5925.00                     | 27.97             | PK       | V              | 34.27            | 3.80                  | 0.00                      | 66.04                              | 60.02                               | 68.20             | 8.18           |
| 11689.00                    | 53.20             | PK       | V              | 39.00            | 6.65                  | 37.58                     | 61.27                              | 55.25                               | 74.00             | 18.75          |
| 11689.00                    | 42.10             | AV       | V              | 39.00            | 6.65                  | 37.58                     | 50.17                              | 44.15                               | 54.00             | 9.85           |
| 17533.50                    | 48.94             | PK       | V              | 43.31            | 8.85                  | 38.39                     | 62.71                              | 56.69                               | 68.20             | 11.51          |


## Tx Chain 1+2:

| Frequency<br>(MHz)          | Receiver          |          | Rx Antenna     |                  | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Extrapolation<br>result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----------------------------|-------------------|----------|----------------|------------------|-----------------------|---------------------------|------------------------------------|-------------------------------------|-------------------|----------------|
|                             | Reading<br>(dBμV) | Detector | Polar<br>(H/V) | Factor<br>(dB/m) |                       |                           |                                    |                                     |                   |                |
| Low Channel: 5731.5 MHz     |                   |          |                |                  |                       |                           |                                    |                                     |                   |                |
| 5731.50                     | 89.56             | PK       | H              | 34.19            | 3.69                  | 0.00                      | 127.44                             | 121.42                              | N/A               | N/A            |
| 5731.50                     | 80.26             | AV       | H              | 34.19            | 3.69                  | 0.00                      | 118.14                             | 112.12                              | N/A               | N/A            |
| 5731.50                     | 92.59             | PK       | V              | 34.19            | 3.69                  | 0.00                      | 130.47                             | 124.45                              | N/A               | N/A            |
| 5731.50                     | 83.62             | AV       | V              | 34.19            | 3.69                  | 0.00                      | 121.50                             | 115.48                              | N/A               | N/A            |
| 5725.00                     | 38.12             | PK       | V              | 34.19            | 3.69                  | 0.00                      | 76.00                              | 69.98                               | 122.20            | 52.22          |
| 5720.00                     | 35.05             | PK       | V              | 34.19            | 3.69                  | 0.00                      | 72.93                              | 66.91                               | 110.80            | 43.89          |
| 5700.00                     | 30.39             | PK       | V              | 34.18            | 3.68                  | 0.00                      | 68.25                              | 62.23                               | 105.20            | 42.97          |
| 5650.00                     | 29.02             | PK       | V              | 34.16            | 3.63                  | 0.00                      | 66.81                              | 60.79                               | 68.20             | 7.41           |
| 11463.00                    | 56.45             | PK       | V              | 38.96            | 6.59                  | 37.34                     | 64.66                              | 58.64                               | 74.00             | 15.36          |
| 11463.00                    | 44.31             | AV       | V              | 38.96            | 6.59                  | 37.34                     | 52.52                              | 46.5                                | 54.00             | 7.50           |
| 17194.50                    | 56.12             | PK       | V              | 41.33            | 8.77                  | 38.63                     | 67.59                              | 61.57                               | 68.20             | 6.63           |
| Middle Channel: 5784.12 MHz |                   |          |                |                  |                       |                           |                                    |                                     |                   |                |
| 5784.12                     | 91.81             | PK       | H              | 34.21            | 3.71                  | 0.00                      | 129.73                             | 123.71                              | N/A               | N/A            |
| 5784.12                     | 82.88             | AV       | H              | 34.21            | 3.71                  | 0.00                      | 120.80                             | 114.78                              | N/A               | N/A            |
| 5784.12                     | 92.80             | PK       | V              | 34.21            | 3.71                  | 0.00                      | 130.72                             | 124.7                               | N/A               | N/A            |
| 5784.12                     | 84.19             | AV       | V              | 34.21            | 3.71                  | 0.00                      | 122.11                             | 116.09                              | N/A               | N/A            |
| 11568.24                    | 53.75             | PK       | V              | 39.00            | 6.61                  | 37.44                     | 61.92                              | 55.9                                | 74.00             | 18.10          |
| 11568.24                    | 42.19             | AV       | V              | 39.00            | 6.61                  | 37.44                     | 50.36                              | 44.34                               | 54.00             | 9.66           |
| 17352.36                    | 52.48             | PK       | V              | 42.24            | 8.81                  | 38.52                     | 65.01                              | 58.99                               | 68.20             | 9.21           |
| High Channel: 5844.5 MHz    |                   |          |                |                  |                       |                           |                                    |                                     |                   |                |
| 5844.50                     | 89.08             | PK       | H              | 34.24            | 3.75                  | 0.00                      | 127.07                             | 121.05                              | N/A               | N/A            |
| 5844.50                     | 80.16             | AV       | H              | 34.24            | 3.75                  | 0.00                      | 118.15                             | 112.13                              | N/A               | N/A            |
| 5844.50                     | 90.10             | PK       | V              | 34.24            | 3.75                  | 0.00                      | 128.09                             | 122.07                              | N/A               | N/A            |
| 5844.50                     | 80.94             | AV       | V              | 34.24            | 3.75                  | 0.00                      | 118.93                             | 112.91                              | N/A               | N/A            |
| 5850.00                     | 36.88             | PK       | V              | 34.24            | 3.75                  | 0.00                      | 74.87                              | 68.85                               | 122.20            | 53.35          |
| 5855.00                     | 33.75             | PK       | V              | 34.24            | 3.75                  | 0.00                      | 71.74                              | 65.72                               | 110.80            | 45.08          |
| 5875.00                     | 28.87             | PK       | V              | 34.25            | 3.77                  | 0.00                      | 66.89                              | 60.87                               | 105.20            | 44.33          |
| 5925.00                     | 27.45             | PK       | V              | 34.27            | 3.80                  | 0.00                      | 65.52                              | 59.5                                | 68.20             | 8.70           |
| 11689.00                    | 54.31             | PK       | V              | 39.00            | 6.65                  | 37.58                     | 62.38                              | 56.36                               | 74.00             | 17.64          |
| 11689.00                    | 42.70             | AV       | V              | 39.00            | 6.65                  | 37.58                     | 50.77                              | 44.75                               | 54.00             | 9.25           |
| 17533.50                    | 48.72             | PK       | V              | 43.31            | 8.85                  | 38.39                     | 62.49                              | 56.47                               | 68.20             | 11.73          |

**Worst Test Plots(Tx Chain 0+2 Low channel was the worst)  
Horizontal**



Fundamental  
Test with Band  
Rejection Filter







### Vertical

Fundamental  
Test with Band  
Rejection Filter





## FCC §15.407(a)(e) & RSS-247 §6.2, RSS-Gen §6.7—EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH

### Applicable Standard

15.407(a) (e), RSS-247 §6.2 and RSS-Gen §6.7

### Test Equipment List and Details

| Manufacturer | Description       | Model       | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|-------------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSV40       | 101474        | 2019-01-09       | 2020-01-09           |
| Unknown      | Coaxial Cable     | C-SJ00-0010 | C0010/01      | Each time        | N/A                  |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

### Test Data

#### Environmental Conditions

|                    |          |
|--------------------|----------|
| Temperature:       | 27.8°C   |
| Relative Humidity: | 66 %     |
| ATM Pressure:      | 100.3kPa |


The testing was performed by on Carrie He 2019-04-24

**Test Result:** Pass. Please refer to the following tables and plots.


Test mode: Transmitting (Test only performed at Chain 0)

| Frequency (MHz) | 6 dB Emission Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | 6dB Emission Bandwidth Limit (MHz) |
|-----------------|-------------------------------|------------------------------|------------------------------------|
| 5731.5          | 1.120                         | 1.385                        | ≥0.5                               |
| 5784.12         | 1.120                         | 1.385                        | ≥0.5                               |
| 5844.5          | 1.125                         | 1.372                        | ≥0.5                               |

Note: the 99% Occupied Bandwidth have not fall into the band 5250-5350MHz or 5470-5725MHz.


**6dB Emission Bandwidth:****Low Channel**

Date: 24.APR.2019 09:52:56

**Middle Channel**

Date: 24.APR.2019 09:56:41


## High Channel



Date: 24.APR.2019 10:10:00

## 99% Occupied Bandwidth:

## Low Channel



Date: 24.APR.2019 14:23:41



## Middle Channel



Date: 24.APR.2019 14:31:10

## High Channel



Date: 24.APR.2019 14:35:03

## **FCC §15.407(a) & RSS-247 §6.2 –MAXIMUM CONDUCTED OUTPUT POWER**

---

### **Applicable Standard**

According to FCC §15.407(a)

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

According to RSS-247 §6.2:

### **Frequency band 5150-5250 MHz**

#### **6.2.1.1 Power limits**

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10} B$ , dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or  $10 + 10 \log_{10} B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

### **Frequency band 5250-5350 MHz**

#### **6.2.2.1 Power limits**

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10} B$ , dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or  $11 + 10 \log_{10} B$ , dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or  $17 + 10 \log_{10} B$ , dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

**Frequency bands 5470-5600 MHz and 5650-5725 MHz****6.2.3.1 Power limits**

The maximum conducted output power shall not exceed 250 mW or  $11 + 10 \log_{10} B$ , dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or  $17 + 10 \log_{10} B$ , dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

**Frequency band 5725-5850 MHz****6.2.4.1 Power limits**

For equipment operating in the band 5725-5850 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint<sup>3</sup> systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

**Test Equipment List and Details**

| Manufacturer | Description               | Model       | Serial Number | Calibration Date | Calibration Due Date |
|--------------|---------------------------|-------------|---------------|------------------|----------------------|
| Agilent      | USB Wideband Power Sensor | U2022XA     | MY5417006     | 2018-12-10       | 2019-12-10           |
| Unknown      | Coaxial Cable             | C-SJ00-0010 | C0010/01      | Each time        | N/A                  |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Procedure**

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

**Test Data****Environmental Conditions**

|                           |          |
|---------------------------|----------|
| <b>Temperature:</b>       | 27.8°C   |
| <b>Relative Humidity:</b> | 66 %     |
| <b>ATM Pressure:</b>      | 100.3kPa |

The testing was performed by on Carrie He 2019-04-24

Test Mode: Transmitting

Tx Chain 0+2:

| Frequency<br>(MHz) | Maximum Conducted Average Output Power<br>(dBm) |         |       | Limit<br>(dBm) |
|--------------------|-------------------------------------------------|---------|-------|----------------|
|                    | Chain 0                                         | Chain 2 | Total |                |
| 5731.50            | 21.69                                           | 22.42   | 25.08 | 30             |
| 5784.12            | 21.78                                           | 22.46   | 25.14 | 30             |
| 5844.50            | 21.92                                           | 22.71   | 25.34 | 30             |

Tx Chain 1+2:

| Frequency<br>(MHz) | Maximum Conducted Average Output Power<br>(dBm) |         |       | Limit<br>(dBm) |
|--------------------|-------------------------------------------------|---------|-------|----------------|
|                    | Chain 0                                         | Chain 2 | Total |                |
| 5731.50            | 22.56                                           | 23.14   | 25.87 | 30             |
| 5784.12            | 21.87                                           | 22.66   | 25.29 | 30             |
| 5844.50            | 22.46                                           | 22.76   | 25.62 | 30             |

Note:

The antennas maximum antenna gains are 2.84dBi @ 5.8GHz band, and employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

So:

Directional gain = G<sub>ANT</sub> + Array Gain = 2.84dBi

---

**FCC §15.407(a)& RSS-247 §6.2- POWER SPECTRAL DENSITY**

---

**Applicable Standard**

According to FCC §15.407(a)

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output



power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

According to RSS-247 §6.2:

### **Frequency band 5150-5250 MHz**

#### **6.2.1.1 Power limits**

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10}B$ , dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or  $10 + 10 \log_{10}B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

### **Frequency band 5250-5350 MHz**

#### **6.2.2.1 Power limits**

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10}B$ , dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or  $11 + 10 \log_{10}B$ , dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or  $17 + 10 \log_{10}B$ , dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

**Frequency bands 5470-5600 MHz and 5650-5725 MHz****6.2.3.1 Power limits**

The maximum conducted output power shall not exceed 250 mW or  $11 + 10 \log_{10} B$ , dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or  $17 + 10 \log_{10} B$ , dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

**Frequency band 5725-5850 MHz****6.2.4.1 Power limits**

For equipment operating in the band 5725-5850 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint<sup>3</sup> systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

**Test Procedure**

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

**Test Equipment List and Details**

| Manufacturer | Description       | Model       | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|-------------|---------------|------------------|----------------------|
| Unknown      | Coaxial Cable     | C-SJ00-0010 | C0010/01      | Each time        | N/A                  |
| R&S          | Spectrum Analyzer | FSU 26      | 200256        | 2019-01-04       | 2020-01-04           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



**Test Data****Environmental Conditions**

|                           |          |
|---------------------------|----------|
| <b>Temperature:</b>       | 27.3°C   |
| <b>Relative Humidity:</b> | 62 %     |
| <b>ATM Pressure:</b>      | 100.7kPa |

The testing was performed by on Carrie He 2019-05-14

**Test Result: Compliance.**

Test Mode: Transmitting

Tx Chain 0+2:

| Frequency<br>(MHz) | Maximum Power Spectral Density<br>(dBm/500kHz) |         |       | Limit<br>(dBm/500kHz) |
|--------------------|------------------------------------------------|---------|-------|-----------------------|
|                    | Chain 0                                        | Chain 2 | Total |                       |
| 5731.50            | 19.51                                          | 20.43   | 23.00 | 30                    |
| 5784.12            | 19.77                                          | 20.03   | 22.91 | 30                    |
| 5844.50            | 19.21                                          | 20.87   | 23.13 | 30                    |

Tx Chain 1+2:

| Frequency<br>(MHz) | Maximum Power Spectral Density<br>(dBm/500kHz) |         |       | Limit<br>(dBm/500kHz) |
|--------------------|------------------------------------------------|---------|-------|-----------------------|
|                    | Chain 1                                        | Chain 2 | Total |                       |
| 5731.50            | 20.51                                          | 21.31   | 23.94 | 30                    |
| 5784.12            | 19.87                                          | 20.32   | 23.11 | 30                    |
| 5844.50            | 19.55                                          | 20.50   | 23.06 | 30                    |

Note:

The device employs Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:


Array Gain =  $10 \log(N_{\text{ANT}}/N_{\text{SS}})$  dB.

So:

Directional gain = G<sub>ANT</sub> + Array Gain = 2.84 +  $10 \log(2/1)$  = 5.84 dBi


**Tx Chain 0+2: Chain 0**

**Low Channel**




Date: 14.MAY.2019 19:29:06

**Middle Channel**



Date: 14.MAY.2019 19:31:26


### High Channel



Date: 14.MAY.2019 19:32:37


### Tx Chain 0+2: Chain 2

### Low Channel




Date: 14.MAY.2019 19:36:56

### Middle Channel



Date: 14.MAY.2019 19:37:17


### 1.4MHz, High Channel



Date: 14.MAY.2019 19:34:13


## Tx Chain 1+2: Chain 1

### Low Channel




Date: 14.MAY.2019 19:44:00

### Middle Channel



Date: 14.MAY.2019 19:43:17


### High Channel



Date: 14.MAY.2019 19:42:36


### Tx Chain 1+2: Chain 2

### Low Channel




Date: 14.MAY.2019 19:39:19

### Middle Channel



Date: 14.MAY.2019 19:39:59

### High Channel



Date: 14.MAY.2019 19:41:10

\*\*\*\*\* END OF REPORT \*\*\*\*\*