



No.:
FCCSZ2025-0036-RF2

TEST REPORT

FCC ID : SS4S20W1


NAME OF SAMPLE : Enterprise Full Touch Handheld Computer

APPLICANT : BLUEBIRD INC.

CLASSIFICATION OF TEST : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Applicant	Name: BLUEBIRD INC. Address: 3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea		
Manufacturer	Name: BLUEBIRD INC. Address: 3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea		
Equipment Under Test	Product Name: Enterprise Full Touch Handheld Computer Model Name: S20 Additional Model Name: N/A Brand Name: BLUEBIRD Serial NO.: N/A Sample NO.: FCCSZ2025-0036_4-1		
Date of Receipt.	Apr. 21, 2025	Date of Testing	Apr. 21, 2025 ~ Jun. 04, 2025
Test Specification		Test Result	
FCC Part 15, Subpart C, Section 15.247		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: Jun. 04, 2025		
Compiled by:  Zhu Yulin Name Signature	Reviewed by:  Mo Xianbiao Name Signature	Approved by:  Dong Sanbi Name Signature	
Other Aspects: NONE.			
Abbreviations: OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 TEST LOCATION	5
1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
1.3 MEASUREMENT UNCERTAINTY	7
2 GENERAL INFORMATION	8
2.1 GENERAL PRODUCT INFORMATION	8
2.2 DESCRIPTION OF ACCESSORIES	9
2.3 OPERATING FREQUENCY OF EACH CHANNEL	10
2.4 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
2.6 DESCRIPTION OF SUPPORT UNITS	14
3 TEST TYPES AND RESULTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION AND RESTRICTED BANDS MEASUREMENTS	20
3.3 6dB BANDWIDTH MEASUREMENT	33
3.4 CONDUCTED OUTPUT POWER	34
3.5 POWER SPECTRAL DENSITY MEASUREMENT	35
3.6 OUT OF BAND EMISSION AND BAND EDGE MEASUREMENTS	36
3.7 OCCUPIED BANDWIDTH MEASUREMENT	37
3.8 ANTENNA REQUIREMENT	38
4 PHOTOGRAPHS OF TEST SETUP	40
5 PHOTOGRAPHS OF THE EUT	41



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2025-0036-RF2	Original release	Jun. 04, 2025



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15 Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
FCC Part 15.207	AC Power Conducted Emission	PASS	See section 3.1
FCC Part 15.247(d) FCC Part 15.209 FCC Part 15.205	Radiated Emission and Restricted bands Measurements	PASS	See section 3.2
	Conducted Spurious Emission	PASS	Appendix E of FCCSZ2025-0036-RF2-A1&A2
	Band Edge Measurements	PASS	Appendix F of FCCSZ2025-0036-RF2-A1&A2
FCC Part 15.247(a)(2)	6dB Bandwidth Measurement	PASS	Appendix A of FCCSZ2025-0036-RF2-A1&A2
---	Occupied Channel Bandwidth	N/A	Appendix B of FCCSZ2025-0036-RF2-A1&A2 (For reference)
FCC Part 15.247(b)	Conducted Output power	PASS	Appendix C of FCCSZ2025-0036-RF2-A1&A2
FCC Part 15.247(e)	Power Spectral Density	PASS	Appendix D of FCCSZ2025-0036-RF2-A1&A2
FCC Part 15.203 FCC Part 15.247(b)	Antenna Requirement	PASS	See section 3.8

1.1 TEST LOCATION

The tests and measurements refer to this report were performed by EMC testing Lab of CVC Testing Technology (Shenzhen) Co., Ltd.

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110 Tel: 0755-23763060-8805
Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn
FCC(Test firm designation number: CN1363)
IC(Test firm CAB identifier number: CN0137)
CNAS(Test firm designation number: L16091)



1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial Number	Cal. interval	Cal. Due
Antenna Port Conducted Test					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 30	104408	1 year	2026/4/22
#3Shielding room	MORI	443	N/A	3 year	2026/5/16
Wideband radio communication tester	Rohde&Schwarz	CMW 500	168587	1 year	2025/7/2
Analog signal Generator (100kHz ~ 40GHz)	Rohde&Schwarz	SMB 100A	181934	1 year	2026/4/22
Vector signal Generator (9kHz ~ 6GHz)	Rohde&Schwarz	SGT 100A	111724	1 year	2026/4/22
RF control unit(BT/WiFi)	Tonscend	JS0806-2-8CH	CS0300023	1 year	2026/4/22
10db attenuator	JUNKE	SMA-10-18-N	250312743	1 year	2026/6/6
Power splitter	Anritsu	K240CPOWERDIVIDER	012334	1 year	2026/6/6
Temperature and humidity meter	/	C193561457	C193561457	1 year	2026/4/28
Radiation Spurious Test - 3M Chamber #2					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 40	101898	1 year	2026/4/22
EMI Test Receiver	Rohde&Schwarz	ESR3	102694	1 year	2026/5/21
Antenna(30MHz~1001MHz)	SCHWARZBECK	VULB 9168	01133	1 year	2026/1/22
Horn antenna(1GHz-18GHz)	ETS	3117	227611	1 year	2026/3/28
Horn antenna(18GHz-40GHz)	QMS	QMS-00880	22051	1 year	2026/3/21
3m anechoic chamber	MORI	966	CS0300011	3 year	2026/5/18
Filter group(RSE-BT/WiFi)	Rohde&Schwarz	WiFi /BT Variant 1	100820	1 year	2026/4/22
Filter group(RSE-Cellular)	Rohde&Schwarz	Cellular Variant 1	100768	1 year	2026/4/22
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100299	1 year	2026/4/22
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100799	1 year	2026/4/22
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100801	1 year	2026/4/22
Preamplifier(18GHz-40GHz)	Rohde&Schwarz	SCU-40A	101209	1 year	2026/4/22
Temperature and humidity meter	/	C193561517	C193561517	1 year	2026/4/28
Radiation Spurious Test - 3M Chamber #1					
EMI Test Receiver	Rohde&Schwarz	ESR 26	101718	1 year	2026/5/21
Loop antenna(8.3k~30MHz)	Rohde&Schwarz	HFH2-Z2E	100951	1 year	2026/6/5
Antenna(30MHz~1000MHz)	SCHWARZBECK	VULB 9168	01132	1 year	2026/2/27
Horn antenna(1GHz-18GHz)	SCHWARZBECK	BBHA9120D	02793	1 year	2026/1/20
3m anechoic chamber	MORI	966	N/A	1 year	2026/5/18
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100298	1 year	2026/4/22
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100799	1 year	2026/4/22
Attenuator	/	SJ-5dB	607684	1 year	2026/2/27
#1 control room	MORI	433	/	1 year	2026/5/16
Temperature and humidity meter	/	C193561473	C193561473	1 year	2026/4/28
Conducted emission					
EMI Test Receiver	Rohde&Schwarz	ESR3	102693	1 year	2026/5/21
limiter(10 dB)	Rohde&Schwarz	VTSD 9561	01216	1 year	2026/4/22
Voltage probe	Rohde&Schwarz	CVP9222C	00028	1 year	2026/4/28
Current probe	Rohde&Schwarz	EZ-17	101442	1 year	2026/4/22
ISN network	Rohde&Schwarz	ENV 81	100401	1 year	2026/4/22
ISN network	Rohde&Schwarz	ENV 81 Cat6	101896	1 year	2026/4/22
#1Shielding room	MORI	854	N/A	3 year	2026/5/16
LISN	SCHWARZBECK	NSLK 8129	5021	1 year	2026/4/22
Temperature and humidity meter	/	C193561430	C193561430	1 year	2026/4/28



1.3 MEASUREMENT UNCERTAINTY


Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

No.	Item	Measurement Uncertainty
1	Occupied Channel Bandwidth	$\pm 1.86\%$
2	RF output power, conducted	$\pm 0.9\text{ dB}$
3	Power Spectral Density, conducted	$\pm 0.8\text{ dB}$
4	Conducted emission test	$\pm 2.7\text{ dB}$
5	Radiated emission 9kHz-30MHz	$\pm 5.6\text{ dB}$
	Radiated emission 30MHz-1GHz	$\pm 4.6\text{ dB}$
	Radiated emission 1GHz-18GHz	$\pm 4.4\text{ dB}$
	Radiated emission 18GHz-40GHz	$\pm 5.1\text{ dB}$
6	Temperature	$\pm 0.73\text{ }^{\circ}\text{C}$
7	Humidity	$\pm 3.90\%$
8	Supply voltages	$\pm 0.37\%$
9	Time	$\pm 0.27\%$
Remark: 95% Confidence Levels, k=2.		

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed.

The measurement uncertainty is mentioned in this test report, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.





2 GENERAL INFORMATION

2.1 GENERAL PRODUCT INFORMATION

PRODUCT NAME	Enterprise Full Touch Handheld Computer
BRAND NAME	BLUEBIRD
MODEL NAME	S20
ADDITIONAL MODEL NAME	N/A
POWER SUPPLY	1. DC 3.85V (1*3.85V Rechargeable Li-ion Polymer battery) 2. DC 5V From Adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA GFSK for DTS
OPERATING FREQUENCY	2412MHz ~ 2462MHz for 802.11b/g/n(HT20)/ax(HE20) 2422MHz ~ 2452MHz 802.11n(HT40)/ax(HE40) 2402MHz ~ 2480MHz for BT-LE(1M/2M)
NUMBER OF CHANNEL	802.11b/g/n(HT20)/ax(HE20): 11 802.11n(HT40)/ax(HE40): 7 BT-LE (1M/2M): 40
PEAK OUTPUT POWER	WLAN: 16.59dBm (Maximum) BT-LE: 6.07dBm (Maximum)
ANTENNA TYPE AND GAIN (Remark 4/5)	WiFi 2.4G: ANT1: PIFA Antenna, with -1.58dBi gain ANT2: PIFA Antenna, with -0.05dBi gain BT-LE: PIFA Antenna, with -1.58dBi gain
HARDWARE VERSION:	V1.01
SOFTWARE VERSION:	R1.00
FIX FREQUENCY SOFTWARE	Qualcomm Radio Control Tool
I/O PORTS	Refer to user' s manual
CABLE SUPPLIED	USB Cabel, 100cm, unshielded

Remark:

1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document for detailed product photo. (Report NO.: FCCSZ2025-0036-EUT)
4. Please refer to the antenna report.
5. Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
6. The EUT have MIMO function, provides 2 completed transmitter and 2 receiver.



2.2 DESCRIPTION OF ACCESSORIES

	Adapter
Brand	ULLPOWER
Model No.:	ICP20-050-3000B
Input:	100-240V~50/60Hz 0.6A
Output:	5.0V $\overline{\overline{=}}$ 3.0A, 15.0W
SN	82-2-2686-3235
AC Cable:	Unshielded without ferrite
DC Cable:	Unshielded without ferrite



2.3 OPERATING FREQUENCY OF EACH CHANNEL

2.4G WIFI							
802.11b/g/n(HT20)/ax(HE20)							
CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
1	2412	5	2432	9	2452		
2	2417	6	2437	10	2457		
3	2422	7	2442	11	2462		
4	2427	8	2447				
802.11n(HT40)/ax(HE40)							
CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
3	2422	6	2437	9	2452		
4	2427	7	2442				
5	2432	8	2447				
BT-LE (1M/2M)							
CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

- The channels which were indicated in bold type of the above channel list were selected as representative test channel. Therefore only the data of the test channels were recorded in this report.
- By means of test software which provided by manufacture, the power levels during the tests were set

802.11b		802.11g		802.11n(HT20)		802.11n(HT40)		BT-LE 1M&2M	
FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING
2412	default	2412	default	2412	default	2412	default	2402	default
2437	default	2437	default	2437	default	2437	default	2440	default
2462	default	2462	default	2462	default	2462	default	2480	default



2.4 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, xyz axis and antenna ports

EUT CONFIGURE MODE	APPLICABLE TEST ITEMS				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	2.4G WIFI Function
B	√	√	√	√	BT Function

Where **RE < 1G**: Radiated Emission below 1GHz

RE ≥ 1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

TEST CASES	ANTENNA 1	ANTENNA 2	MIMO/CDD	PARTIAL RU
AC Power Conducted Emission	/	/	O	/
Radiated Emissions	/	/	O	O
Out of band Emission Measurement	O	O	O	O
6dB bandwidth	O	O	/	/
Occupied Bandwidth Measurement	O	O	/	/
Conducted Output power	O	O	O	/
Power Spectral Density	O	O	O	O
RU Configure (OFDMA)	802.11 ax(HE20)		802.11ax(HE40)	
26 Tone RU Index 0	O		/	
26 Tone RU Index 8	O		/	
52 Tone RU Index 37	O		/	
52 Tone RU Index 40	O		/	
106 Tone RU Index 53	O		/	
106 Tone RU Index 54	O		/	
242 Tone RU Index 61	/		O	
242 Tone RU Index 62	/		O	
Full RU	O		O	
Note1:“O” mean test				
Note2: As for Partial RU PSD < Full RU PSD,perform additional testing on Partial RU modes for band edge and spurious emissions				
Note3: All the RU mode have been tested, only worst case are recorded				



RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The worst case was found when positioned on x axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1	DSSS	DBPSK	1.0
B	BT-LE	0 to 39	0	DTS	GFSK	1.0

For the test results, only the worst case was shown in test report.

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
--	WiFi (2.4G) + BT-LE Link

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The worst case was found when positioned on x axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE PARAMETER
A	802.11b	1 to 13	1, 7, 13	DSSS	DBPSK	1.0 Mbps
A	802.11g	1 to 13	1, 7, 13	OFDM	BPSK	6.0 Mbps
A	802.11n (HT20)	1 to 13	1, 7, 13	OFDM	BPSK	MCS0
A	802.11n (HT40)	3 to 11	3, 7, 11	OFDM	BPSK	MCS0
A	802.11ax (HE20)	1 to 13	1, 7, 13	OFDMA	BPSK	MCS0
A	802.11ax (HE40)	3 to 11	3, 7, 11	OFDMA	BPSK	MCS0
B	BT-LE	0 to 39	0,19, 39	DTS	GFSK	1.0 Mbps
B	BT-LE	0 to 39	0,19, 39	DTS	GFSK	2.0 Mbps



ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE PARAMETER
A	802.11b	1 to 13	1, 7, 13	DSSS	DBPSK	1.0 Mbps
A	802.11g	1 to 13	1, 7, 13	OFDM	BPSK	6.0 Mbps
A	802.11n (HT20)	1 to 13	1, 7, 13	OFDM	BPSK	MCS0
A	802.11n (HT40)	3 to 11	3, 7, 11	OFDM	BPSK	MCS0
A	802.11ax (HE20)	1 to 13	1, 7, 13	OFDMA	BPSK	MCS0
A	802.11ax (HE40)	3 to 11	3, 7, 11	OFDMA	BPSK	MCS0
B	BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1.0 Mbps
B	BT-LE	0 to 39	0, 19, 39	DTS	GFSK	2.0 Mbps

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	24.5deg. C, 55%RH	DC 5V from USB host unit	Liu Yuan
RE≥1G	24.5deg. C, 55%RH	DC 5V from USB host unit	Liu Yuan
PLC	25.2deg. C, 53%RH	DC 5V from USB host unit	Zhou Ye
APCM	24.2deg. C, 57%RH	DC 5V from USB host unit	Zhu Yulin



2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC PART 15, Subpart C. Section 15.247

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards

2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support Equipment							
NO	Description	Brand	Model No.	Serial Number	Supplied by		
1	N/A	N/A	N/A	N/A	N/A		
Support Cable							
NO	Description	Quantity (Number)	Length (cm)	Detachable (Yes/ No)	Shielded (Yes/ No)	Cores (Number)	Supplied by
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 Limit


Frequency (MHz)	Conducted Limits(dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
NOTE: 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.2 Measurement procedure


- The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the Test photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source. The equipment under test shall be placed on a support of non-metallic material, the height of which shall be 1.5m above the ground,
- The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
- Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.


3.1.3 Test setup







3.1.4 Test results











3.2 RADIATED EMISSION AND RESTRICTED BANDS MEASUREMENTS

3.2.1 Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (Microvolts/Meter)	MEASUREMENT DISTANCE (Meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE: 1. The lower limit shall apply at the transition frequencies.
NOTE: 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
NOTE: 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 Measurement procedure


- The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

3.2.3 Test setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:




Above 1GHz Test Setup:






3.2.4 Test results

BELOW 1GHz WORST-CASE DATA








Worst Test Mode	802.11b CDD	Channel	CH 1
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Horizontal




NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]
1	33.201	3.23	19.76	22.99	40.00	17.01	200	104
2	41.059	2.34	20.59	22.93	40.00	17.07	100	1
3	102.272	4.41	17.28	21.69	43.50	21.81	300	99
4	119.443	7.28	19.16	26.44	43.50	17.06	300	261
5	153.105	9.09	21.27	30.36	43.50	13.14	200	31
6	188.320	9.53	18.01	27.54	43.50	15.96	200	66

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.
2. The emission levels of other frequencies were greater than 20dB margin.
3. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
4. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
5. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



Worst Test Mode	802.11b CDD	Channel	CH 1
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Vertical



NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]
1	33.880	13.68	19.82	33.50	40.00	6.50	100	206
2	55.708	6.73	19.75	26.48	40.00	13.52	100	164
3	84.810	10.76	16.14	26.90	40.00	13.10	100	32
4	125.167	8.80	19.31	28.11	43.50	15.39	100	326
5	152.620	11.47	21.28	32.75	43.50	10.75	100	287
6	217.132	7.62	17.88	25.50	46.00	20.50	100	358

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.
2. The emission levels of other frequencies were greater than 20dB margin.
3. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
4. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
5. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



ABOVE 1GHz DATA

All modes have been tested, and the worst-case was recorded in this report.

Channel		802.11b CDD CH 1		Frequency		2412MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	2379.40	51.13	-1.53	49.60	74.00	24.40	PK
2	2384.38	40.96	-1.45	39.51	54.00	14.49	AV
3	2390.00	49.88	-1.37	48.51	74.00	25.49	PK
4	2390.00	39.76	-1.37	38.39	54.00	15.61	AV
5	2412.60	94.30	-1.19	93.11			AV
6	2412.85	96.28	-1.19	95.09			PK
7	4824.00	42.88	9.58	52.46	74.00	21.54	PK
8	4824.00	34.18	9.58	43.76	54.00	10.24	AV
9	7236.00	29.53	13.96	43.49	74.00	30.51	PK
10	7236.00	20.74	13.96	34.70	54.00	19.30	AV
11	9648.00	28.51	14.33	42.84	74.00	31.16	PK
12	9648.00	20.21	14.33	34.54	54.00	19.46	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	2362.94	51.11	-1.30	49.81	74.00	24.19	PK
2	2387.97	41.28	-1.40	39.88	54.00	14.12	AV
3	2390.00	39.48	-1.37	38.11	54.00	15.89	AV
4	2390.00	50.40	-1.37	49.03	74.00	24.97	PK
5	2411.07	91.83	-1.19	90.64			AV
6	2411.11	94.15	-1.19	92.96			PK
7	4824.00	42.38	9.58	51.96	74.00	22.04	PK
8	4824.00	35.09	9.58	44.67	54.00	9.33	AV
9	7236.00	29.98	13.96	43.94	74.00	30.06	PK
10	7236.00	20.58	13.96	34.54	54.00	19.46	AV
11	9648.00	27.77	14.33	42.10	74.00	31.90	PK
12	9648.00	20.36	14.33	34.69	54.00	19.31	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBμV/m] - Level [dBuV/m].							



Channel		802.11b CDD CH 6		Frequency		2437MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	4874.00	43.65	9.66	53.31	74.00	20.69	PK
2	4874.00	34.42	9.66	44.08	54.00	9.92	AV
3	7311.00	21.67	12.65	34.32	54.00	19.68	AV
4	7311.00	29.65	12.65	42.30	74.00	31.70	PK
5	9748.00	27.26	14.73	41.99	74.00	32.01	PK
6	9748.00	19.61	14.73	34.34	54.00	19.66	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	4874.00	43.40	9.66	53.06	74.00	20.94	PK
2	4874.00	34.87	9.66	44.53	54.00	9.47	AV
3	7311.00	22.57	12.65	35.22	54.00	18.78	AV
4	7311.00	29.06	12.65	41.71	74.00	32.29	PK
5	9748.00	26.97	14.73	41.70	74.00	32.30	PK
6	9748.00	20.20	14.73	34.93	54.00	19.07	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel		802.11b CDD CH 11		Frequency		2462MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	2461.00	96.70	-1.14	95.56			AV
2	2461.06	98.28	-1.14	97.14			PK
3	2483.50	45.83	-1.15	44.68	74.00	29.32	PK
4	2483.50	37.21	-1.15	36.06	54.00	17.94	AV
5	2486.24	47.65	-1.02	46.63	74.00	27.37	PK
6	2490.10	38.39	-0.84	37.55	54.00	16.45	AV
7	4824.00	42.09	10.19	52.28	74.00	21.72	PK
8	4824.00	33.99	10.19	44.18	54.00	9.82	AV
9	7236.00	20.92	11.57	32.49	54.00	21.51	AV
10	7236.00	28.34	11.57	39.91	74.00	34.09	PK
11	9648.00	28.00	14.74	42.74	74.00	31.26	PK
12	9648.00	20.17	14.74	34.91	54.00	19.09	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	2460.94	92.81	-1.14	91.67			AV
2	2461.08	94.41	-1.14	93.27			PK
3	2483.50	44.56	-1.15	43.41	74.00	30.59	PK
4	2483.50	36.63	-1.15	35.48	54.00	18.52	AV
5	2488.41	38.22	-0.91	37.31	54.00	16.69	AV
6	2493.40	47.64	-0.90	46.74	74.00	27.26	PK
7	4924.00	42.94	10.19	53.13	74.00	20.87	PK
8	4924.00	34.47	10.19	44.66	54.00	9.34	AV
9	7386.00	29.89	11.57	41.46	74.00	32.54	PK
10	7386.00	20.95	11.57	32.52	54.00	21.48	AV
11	9848.00	27.28	14.74	42.02	74.00	31.98	PK
12	9848.00	19.83	14.74	34.57	54.00	19.43	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



All modes have been tested, and the worst-case was recorded in this report.

in mode have been tested, and the worst case was recorded in this report.

Channel		BT-LE(1Mbps) CH0		Frequency		2402MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector
1	2384.36	55.05	-1.45	53.60	74.00	20.40	PK
2	2384.68	50.08	-1.45	48.63	54.00	5.37	AV
3	2390.00	39.19	-1.37	37.82	54.00	16.18	AV
4	2390.00	49.76	-1.37	48.39	74.00	25.61	PK
5	2401.78	95.36	-1.26	94.10			PK
6	2401.85	94.70	-1.26	93.44			AV
7	4804.00	42.46	9.19	51.65	74.00	22.35	PK
8	4804.00	34.86	9.19	44.05	54.00	9.95	AV
9	7206.00	20.70	14.32	35.02	54.00	18.98	AV
10	7206.00	29.78	14.32	44.10	74.00	29.90	PK
11	9608.00	28.23	14.44	42.67	74.00	31.33	PK
12	9608.00	20.08	14.44	34.52	54.00	19.48	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector
1	2373.25	51.06	-1.52	49.54	74.00	24.46	PK
2	2381.88	42.99	-1.51	41.48	54.00	12.52	AV
3	2390.00	39.79	-1.37	38.42	54.00	15.58	AV
4	2390.00	48.09	-1.37	46.72	74.00	27.28	PK
5	2401.76	91.32	-1.26	90.06			PK
6	2401.87	90.70	-1.26	89.44			AV
7	4804.00	42.55	9.19	51.74	74.00	22.26	PK
8	4804.00	34.15	9.19	43.34	54.00	10.66	AV
9	7206.00	21.14	14.32	35.46	54.00	18.54	AV
10	7206.00	29.23	14.32	43.55	74.00	30.45	PK
11	9608.00	28.06	14.44	42.50	74.00	31.50	PK
12	9608.00	20.08	14.44	34.52	54.00	19.48	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel		BT-LE(1Mbps) CH19		Frequency		2440MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	4880.00	41.95	9.75	51.70	74.00	22.30	PK
2	4880.00	34.13	9.75	43.88	54.00	10.12	AV
3	7320.00	21.81	12.66	34.47	54.00	19.53	AV
4	7320.00	30.26	12.66	42.92	74.00	31.08	PK
5	9760.00	27.49	14.77	42.26	74.00	31.74	PK
6	9760.00	20.18	14.77	34.95	54.00	19.05	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	4880.00	43.16	9.75	52.91	74.00	21.09	PK
2	4880.00	35.11	9.75	44.86	54.00	9.14	AV
3	7320.00	21.59	12.66	34.25	54.00	19.75	AV
4	7320.00	30.00	12.66	42.66	74.00	31.34	PK
5	9760.00	27.17	14.77	41.94	74.00	32.06	PK
6	9760.00	19.46	14.77	34.23	54.00	19.77	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel		BT-LE(1Mbps) CH39		Frequency		2480MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	2479.79	97.75	-1.30	96.45			PK
2	2479.85	97.09	-1.30	95.79			AV
3	2483.50	36.90	-1.15	35.75	54.00	18.25	AV
4	2483.50	45.43	-1.15	44.28	74.00	29.72	PK
5	2487.72	45.31	-0.95	44.36	54.00	9.64	AV
6	2487.73	52.50	-0.95	51.55	74.00	22.45	PK
7	4960.00	42.88	10.78	53.66	74.00	20.34	PK
8	4960.00	34.37	10.78	45.15	54.00	8.85	AV
9	7440.00	21.96	11.55	33.51	54.00	20.49	AV
10	7440.00	30.95	11.55	42.50	74.00	31.50	PK
11	9920.00	27.20	15.37	42.57	74.00	31.43	PK
12	9920.00	20.35	15.37	35.72	54.00	18.28	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	2479.93	90.38	-1.31	89.07			AV
2	2480.25	91.23	-1.30	89.93			PK
3	2483.50	46.62	-1.15	45.47	74.00	28.53	PK
4	2483.50	41.29	-1.15	40.14	54.00	13.86	AV
5	2491.27	49.52	-0.87	48.65	74.00	25.35	PK
6	2491.28	42.93	-0.87	42.06	54.00	11.94	AV
7	4960.00	42.59	10.78	53.37	74.00	20.63	PK
8	4960.00	34.39	10.78	45.17	54.00	8.83	AV
9	7440.00	22.75	11.55	34.30	54.00	19.70	AV
10	7440.00	30.47	11.55	42.02	74.00	31.98	PK
11	9920.00	27.41	15.37	42.78	74.00	31.22	PK
12	9920.00	19.95	15.37	35.32	54.00	18.68	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



3.3 6dB BANDWIDTH MEASUREMENT


3.3.1 Limits

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 Measurement procedure

- Set resolution bandwidth (RBW) = 100KHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3.3 Test setup





3.4 CONDUCTED OUTPUT POWER


3.4.1 Limits

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

3.4.2 Measurement procedure

- A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.
- An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

3.4.3 Test setup





3.5 POWER SPECTRAL DENSITY MEASUREMENT


3.5.1 Limits

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 Measurement procedure

- Set instrument center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set RBW to: 3KHz
- Set VBW $\geq 3 \times$ RBW.
- Detector = peak
- Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- Sweep time = auto couple.
- Use the peak marker function to determine the maximum amplitude level.

3.5.3 Test setup





3.6 OUT OF BAND EMISSION AND BAND EDGE MEASUREMENTS

3.6.1 Limits

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 Measurement procedure

Measurement Procedure -Reference Level

- Set the RBW = 100 kHz.
- Set the VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHzband segment within the fundamental EBW.

Measurement Procedure –Unwanted Emission Level

- Set RBW = 100 kHz.
- Set VBW $\geq$ 300 kHz.
- Set span to encompass the spectrum to be examined
- Detector = peak.
- Trace Mode = max hold.
- Sweep = auto couple.

3.6.3 Test setup



3.7 OCCUPIED BANDWIDTH MEASUREMENT

3.7.1 Measurement procedure

The transmitter antenna output was connected to the spectrum analyzer through an attenuator. The resolution bandwidth shall be set to the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.7.2 Test setup





3.8 ANTENNA REQUIREMENT

3.8.1 LIMITS OF ANTENNA REQUIREMENT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b) , if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 ANTENNA ANTI-REPLACEMENT CONSTRUCTION

The antenna used for this product is PIFA Antenna, that no antenna other than that furnished by the responsible party shall be used with the device.



3.8.3 ANTENNA GAIN

Refer to KDB662911 D01 Multiple Transmitter Output v02r01.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements on all devices,

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

Operation Band	Chain 1 Antenna Gain(dBi)	Chain 2 Antenna Gain(dBi)	DG For PSD (dBi)	DG For Power (dBi)	PSD Limit Reduction	Power Limit Reduction
WiFi 2.4G	-1.58	-0.05	2.23	-0.05	0	0
BLE	-1.58	/	-1.58	-1.58	0	0

Calculation example:

$G_{ANT1} = -1.58\text{dBi}$; $G_{ANT2} = -0.05\text{dBi}$

Directional gain of power measurement = $\max(-1.58, -0.05) = -0.05\text{dBi}$

Directional gain of PSD derived from formula which is:

$10 \log \{ [10^{(-1.58 \text{ dBi}/20)} + 10^{(-0.05 \text{ dBi}/20)}]^2 / 2 \} = 2.23\text{dBi}$

Power and PSD limit reduction = Composite gain -6dBi



4 PHOTOGRAPHS OF TEST SETUP

Please refer to the attached file (Test Setup Photo).



5 PHOTOGRAPHS OF THE EUT

Please refer to the attached file (External Photos report and Internal Photos).

----- End of the Report -----



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>