



FCC&IC TEST REPORT

FCC ID: SY4-A02033

On Behalf of

Shanghai Huace Navigation Technology Ltd.

Geodetic GNSS Receiver

Model No.: i83

Prepared for : Shanghai Huace Navigation Technology Ltd.
Address : Building D, 599 Gaojing Road, Qingpu District, Shanghai, China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2112293-C02-R01
Date of Receipt : January 6, 2022
Date of Test : January 6, 2022-February 28, 2022
Date of Report : March 2, 2022
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT).....	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description.....	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. Maximum Peak Output power	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Setup.....	11
3.4. Test Result	11
4. Bandwidth.....	12
4.1. Limit	12
4.2. Test Procedure	12
4.3. Test Result	12
5. Carrier Frequency Separation.....	23
5.1. Limit	23
5.2. Test Procedure	23
5.3. Test Result	23
6. Number Of Hopping Channel.....	25
6.1. Limit	25
6.2. Test Procedure	25
6.3. Test Result	25
7. Dwell Time.....	27
7.1. Test limit	27
7.2. Test Procedure	27
7.3. Test Result	27
8. Radiated emissions.....	30
8.1. Limit	30
8.2. Block Diagram of Test setup	31
8.3. Test Procedure	32
8.4. Test Result	32
9. Band Edge Compliance	47

9.1. Block Diagram of Test Setup.....	47
9.2. Limit	47
9.3. Test Procedure	47
9.4. Test Result	47
10. Power Line Conducted Emissions	54
10.1. Block Diagram of Test Setup.....	54
10.2. Limit	54
10.3. Test Procedure	54
10.4. Test Result	55
11. Antenna Requirements	58
11.1. Limit	58
11.2. Result	58
12. Test setup photo	59
12.1. Photos of Radiated Emission test	59
12.2. Photos of Conducted Emission test	60
13. Photos of EUT	61

TEST REPORT DECLARATION

Applicant : Shanghai Huace Navigation Technology Ltd.
Address : Building D, 599 Gaojing Road, Qingpu District, Shanghai, China
Manufacturer : Shanghai Huace Navigation Technology Ltd.
Address : Building D, 599 Gaojing Road, Qingpu District, Shanghai, China
EUT Description : Geodetic GNSS Receiver
(A) Model No. : i83
(B) Trademark : 

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247,
ANSI C63.10:2013**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Lucas Pang
Project Engineer



Approved by (name + signature).....: Simple Guan
Project Manager



Date of issue.....: March 2, 2022

Revision History

Revision	Issue Date	Revisions	Revised By
V0	March 2, 2022	Initial released Issue	Reak Yang

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description/PMN : Geodetic GNSS Receiver

Model : i83

Number/FVIN(s)

Diff. : N/A

Trademark : 

Test Voltage : DC 5V from adapter, DC 7.2V from battery

Radio Technology : Bluetooth V5.0 EDR

Operation frequency : 2402-2480MHz

Channel No. : 79 Channels

Modulation type : GFSK, $\pi/4$ DQPSK, 8- DPSK

Antenna Type : Internal antenna, Maximum Gain is 2.5dBi.

Software version : V1.0.0

Hardware : V1.0.1
Version/FVIN

Remark: The worst-case simultaneous transmission configuration was evaluated with no non-compliance found.
Results in this report are only for Bluetooth (BR+ EDR) function, and there is no other transmitter involved.


2.2.Accessories of Device (EUT)

Accessories1	:	AC Adapter
Manufacturer	:	EDAC POWER Electronics Co., Ltd
Model	:	EA1012AVRU-050
Ratings	:	Input: 100-240Vac~50/60Hz 1.0A Output: 5.0V=2.4A

2.3.Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	Notebook PC	Lenovo	ThinkPad E14	N/A	SDOC

2.4.Block Diagram of connection between EUT and simulators



2.5.Test Mode Description

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
$\pi/4$ DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8- DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	25°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

Designation Number: CN1236

July 15, 2019 Certificated by IC

Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.16dB(Polarize: H)
	4.13dB(Polarize: V)
Uncertainty for radio frequency	5.4×10^{-8}
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2020.09.02	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2021.08.25	1Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2021.08.25	1Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-10208 2-Wa	2021.08.25	1Year
Receiver	R&S	ESCI	101165	2021.08.25	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2020.04.12	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2020.04.12	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2021.08.30	2Year
RF Cable	Resenberger	Cable 1	RE1	2021.08.25	1Year
RF Cable	Resenberger	Cable 2	RE2	2021.08.25	1Year
RF Cable	Resenberger	Cable 3	CE1	2021.08.25	1Year
Pre-amplifier	HP	HP8347A	2834A00455	2021.08.25	1Year
Pre-amplifier	Agilent	8449B	3008A02664	2021.08.25	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126-466	2021.08.25	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2021.08.25	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2021.08.30	2 Year
Preamplifier	SKET	LNPA_1840 -50	SK2018101801	2021.08.25	1 Year
Power Meter	Agilent	E9300A	MY41496628	2021.08.25	1 Year
Power Sensor	DARE	RPR3006W	15100041SNO91	2021.08.25	1 Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000 -40-880	100631	2021.04.21	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2021.08.25	1 Year
Adjustable attenuator	MWRFtest	N/A	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	N/A	N/A	N/A

3. MAXIMUM PEAK OUTPUT POWER

3.1.Limit


Please refer FCC part 15.247

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2.Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3.Test Setup



3.4.Test Result

Mode	Freq (MHz)	PK Output Power (dBm)	Limit (dBm)	Result
GFSK	2402	3.670	30	Pass
	2441	4.131	30	Pass
	2480	5.076	30	Pass
$\pi/4$ DQPSK	2402	1.400	21	Pass
	2441	1.097	21	Pass
	2480	1.736	21	Pass
8- DPSK	2402	1.131	21	Pass
	2441	0.828	21	Pass
	2480	1.502	21	Pass
Conclusion: PASS				

4. BANDWIDTH

4.1.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3.Test Result

-20dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.896	/	Pass
NVNT	1-DH1	2441	Ant1	0.998	/	Pass
NVNT	1-DH1	2480	Ant1	0.916	/	Pass
NVNT	2-DH1	2402	Ant1	1.334	/	Pass
NVNT	2-DH1	2441	Ant1	1.314	/	Pass
NVNT	2-DH1	2480	Ant1	1.272	/	Pass
NVNT	3-DH1	2402	Ant1	1.308	/	Pass
NVNT	3-DH1	2441	Ant1	1.262	/	Pass
NVNT	3-DH1	2480	Ant1	1.264	/	Pass

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1



Date: 12.JAN.2022 11:07:02

-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1




Date: 12.JAN.2022 11:09:28

-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1




Date: 12.JAN.2022 11:11:16

-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1




Date: 12.JAN.2022 11:35:46

-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1




Date: 12.JAN.2022 11:38:17

-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1




Date: 12.JAN.2022 11:39:45


-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1




Date: 12.JAN.2022 13:23:52

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.851
NVNT	1-DH1	2441	Ant1	0.927
NVNT	1-DH1	2480	Ant1	0.915
NVNT	2-DH1	2402	Ant1	1.189
NVNT	2-DH1	2441	Ant1	1.195
NVNT	2-DH1	2480	Ant1	1.191
NVNT	3-DH1	2402	Ant1	1.183
NVNT	3-DH1	2441	Ant1	1.183
NVNT	3-DH1	2480	Ant1	1.185

OBW NVNT 1-DH1 2402MHz Ant1




Date: 12.JAN.2022 11:06:54


OBW NVNT 1-DH1 2441MHz Ant1




OBW NVNT 1-DH1 2480MHz Ant1




OBW NVNT 2-DH1 2402MHz Ant1




OBW NVNT 2-DH1 2441MHz Ant1




OBW NVNT 2-DH1 2480MHz Ant1




OBW NVNT 3-DH1 2402MHz Ant1



OBW NVNT 3-DH1 2441MHz Ant1



OBW NVNT 3-DH1 2480MHz Ant1



5. CARRIER FREQUENCY SEPARATION

5.1.Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


5.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3.Test Result


Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	2441.039	2442.041	1.002	0.998	Pass
NVNT	2-DH1	2441.026	2442.028	1.002	0.876	Pass
NVNT	3-DH1	2441.024	2442.026	1.002	0.841	Pass

CFS NVNT 1-DH1 2441MHz Ant1




Date: 12.JAN.2022 11:21:09

CFS NVNT 2-DH1 2441MHz Ant1



Date: 12.JAN.2022 11:43:42

CFS NVNT 3-DH1 2441MHz Ant1



Date: 12.JAN.2022 13:32:31

6. NUMBER OF HOPPING CHANNEL

6.1.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3.Test Result


Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1




Date: 12.JAN.2022 11:24:35

Hopping No. NVNT 2-DH1 2441MHz Ant1



Hopping No. NVNT 3-DH1 2441MHz Ant1



7. DWELL TIME

7.1. Test limit

Please refer FCC part 15.247.

Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

Mode	Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Conclusion
GFSK	DH1	2441	0.384	0.1229	<0.4	PASS
	DH3	2441	1.64	0.2624		PASS
	DH5	2441	2.887	0.3079		PASS
$\pi/4$ DQPSK	DH1	2441	0.39	0.1248	<0.4	PASS
	DH3	2441	1.641	0.2626		PASS
	DH5	2441	2.883	0.3075		PASS
8DPSK	DH1	2441	0.39	0.1248	<0.4	PASS
	DH3	2441	1.64	0.2624		PASS
	DH5	2441	2.891	0.3084		PASS

Note: 1 A period time = 0.4 (s) * 79 = 31.6(s)



2 DH1 time slot = Pulse Duration * (1600/(2*79)) * A period time/1000

DH3 time slot = Pulse Duration * (1600/(4*79)) * A period time/1000


DH5 time slot = Pulse Duration * (1600/(6*79)) * A period time/1000

Dwell time


GFSK

 $\pi/4$ -DQPSK


Channel 39 / 2441 MHz - DH1




Channel 39 / 2441 MHz - 2DH1



Channel 39 / 2441 MHz - DH3




Channel 39 / 2441 MHz - 2DH3




Channel 39 / 2441 MHz - DH5

Channel 39 / 2441 MHz - 2DH5


Dwell time 8DPSK



Channel 39 / 2441 MHz - 3DH1



Channel 39 / 2441 MHz - 3DH3



Channel 39 / 2441 MHz - 3DH5

8. RADIATED EMISSIONS

8.1.Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	


Note: The peak limit is 20 dB higher than the average limit

8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 0.8 m high above ground for below 1GHz testing and 1.5m high for above 1GHz testing inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
- (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result


We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency. Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


From 30MHz to 1000MHz: Conclusion: PASS

Vertical:



Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		45.4949	10.96	14.10	25.06	40.00	-14.94	peak		
2		80.1860	11.22	9.90	21.12	40.00	-18.88	peak		
3		143.2633	14.46	14.55	29.01	43.50	-14.49	peak		
4		214.8907	17.38	11.40	28.78	43.50	-14.72	peak		
5		286.4796	13.63	13.77	27.40	46.00	-18.60	peak		
6	*	731.5996	11.73	22.16	33.89	46.00	-12.11	peak		

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Remark: All modes have been tested, and only worst data of 8-DPSK mode, Channel 2480MHz (AC 120V/60Hz) was listed in this report.

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.07	V	33.95	10.18	34.26	53.94	74	-20.06	PK
4804	35.17	V	33.95	10.18	34.26	45.04	54	-8.96	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	48.01	H	33.95	10.18	34.26	57.88	74	-16.12	PK
4804	36.65	H	33.95	10.18	34.26	46.52	54	-7.48	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	44.75	V	33.93	10.20	34.29	54.59	74	-19.41	PK
4882	35.71	V	33.93	10.20	34.29	45.55	54	-8.45	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	43.54	H	33.93	10.20	34.29	53.38	74	-20.62	PK
4882	35.63	H	33.93	10.20	34.29	45.47	54	-8.53	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	46.34	V	33.98	10.22	34.25	56.29	74	-17.71	PK
4960	36.44	V	33.98	10.22	34.25	46.39	54	-7.61	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	44.80	H	33.98	10.22	34.25	54.75	74	-19.25	PK
4960	33.97	H	33.98	10.22	34.25	43.92	54	-10.08	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Test Mode: $\pi/4$ DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.82	V	33.95	10.18	34.26	54.69	74	-19.31	PK
4804	35.35	V	33.95	10.18	34.26	45.22	54	-8.78	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	47.87	H	33.95	10.18	34.26	57.74	74	-16.26	PK
4804	36.24	H	33.95	10.18	34.26	46.11	54	-7.89	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX Mid									
4882	44.48	V	33.93	10.20	34.29	54.32	74	-19.68	PK
4882	36.38	V	33.93	10.20	34.29	46.22	54	-7.78	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	43.80	H	33.93	10.20	34.29	53.64	74	-20.36	PK
4882	35.98	H	33.93	10.20	34.29	45.82	54	-8.18	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX High									
4960	46.07	V	33.98	10.22	34.25	56.02	74	-17.98	PK
4960	36.21	V	33.98	10.22	34.25	46.16	54	-7.84	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	44.99	H	33.98	10.22	34.25	54.94	74	-19.06	PK
4960	34.03	H	33.98	10.22	34.25	43.98	54	-10.02	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

From 1G-25GHz

Test Mode: 8- DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.13	V	33.95	10.18	34.26	54.00	74	-20.00	PK
4804	34.99	V	33.95	10.18	34.26	44.86	54	-9.14	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	47.99	H	33.95	10.18	34.26	57.86	74	-16.14	PK
4804	36.79	H	33.95	10.18	34.26	46.66	54	-7.34	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: 8- DQPSK TX Mid									
4882	44.17	V	33.93	10.20	34.29	54.01	74	-19.99	PK
4882	36.68	V	33.93	10.20	34.29	46.52	54	-7.48	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	43.68	H	33.93	10.20	34.29	53.52	74	-20.48	PK
4882	35.46	H	33.93	10.20	34.29	45.30	54	-8.70	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: 8- DQPSK TX High									
4960	46.43	V	33.98	10.22	34.25	56.38	74	-17.62	PK
4960	36.40	V	33.98	10.22	34.25	46.35	54	-7.65	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	45.26	H	33.98	10.22	34.25	55.21	74	-18.79	PK
4960	33.78	H	33.98	10.22	34.25	43.73	54	-10.27	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Conducted RF Spurious Emission

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref



Date: 12.JAN.2022 11:07:23

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission




Date: 12.JAN.2022 11:07:37


Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission



9. BAND EDGE COMPLIANCE

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in FCC part 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with FCC part 15.209 limits.

9.3. Test Procedure


Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.


9.4. Test Result

PASS. (See below detailed test data)

Test Mode: GFSK-Low Hopping-off




Test Mode: GFSK-High Hopping-off




Test Mode: GFSK-Low Hopping-on

Polarization: Vertical







Test Mode: GFSK-High Hopping-on

Polarization: Horizontal



Note: 1. *:Maximum data; x:Over limit; !:over margin.


2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Test Mode: $\pi/4$ DQPSK-Low Hopping-offTest Mode: $\pi/4$ DQPSK-High Hopping-offTest Mode: $\pi/4$ DQPSK-Low Hopping-onTest Mode: $\pi/4$ DQPSK-High Hopping-on


Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Test Mode: 8DPSK-Low Hopping-off




Test Mode: 8DPSK-High Hopping-off



Test Mode: 8DPSK-Low Hopping-on



Test Mode: 8DPSK-High Hopping-on



Note: 1. *:Maximum data; x:Over limit; !:over margin.


2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Conducted Method


GFSK Mode:

Test channel:

Lowest channel




No-hopping mode




Hopping mode

Test channel:

Highest channel




No-hopping mode



Hopping mode


$\pi/4$ DQPSK Mode:

Test channel:




No-hopping mode

Lowest channel




Hopping mode

Test channel:



No-hopping mode

Highest channel




Hopping mode


8DPSK Mode:

Test channel:

Lowest channel




No-hopping mode




Hopping mode

Test channel:

Highest channel




No-hopping mode



Hopping mode

10. POWER LINE CONDUCTED EMISSIONS

10.1. Block Diagram of Test Setup



10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.


(5) The frequency range from 150 KHz to 30MHz is checked.

10.4. Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit

Line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1920	45.30	9.92	55.22	63.95	-8.73	QP	
2		0.1920	27.05	9.92	36.97	53.95	-16.98	AVG	
3		0.2880	40.23	9.93	50.16	60.58	-10.42	peak	
4		0.3450	37.78	9.95	47.73	59.08	-11.35	peak	
5		0.4620	33.40	9.95	43.35	56.66	-13.31	QP	
6		0.4620	23.44	9.95	33.39	46.66	-13.27	AVG	
7		0.8760	31.80	9.96	41.76	56.00	-14.24	QP	
8		0.8760	22.30	9.96	32.26	46.00	-13.74	AVG	
9		5.2110	29.28	10.05	39.33	60.00	-20.67	peak	

*:Maximum data x:Over limit !:over margin

〈Reference Only

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:

*:Maximum data x:Over limit !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data of 8-DPSK mode, Channel 2480MHz (AC 120V/60Hz) was listed in this report.

11.ANTENNA REQUIREMENTS

11.1.Limit


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2.Result


The EUT antenna is internal antenna. It complies with the standard requirement.

12. TEST SETUP PHOTO

12.1. Photos of Radiated Emission test



12.2.Photos of Conducted Emission test



13. PHOTOS OF EUT



