



FCC TEST REPORT

FCC ID: SY4-A02057

On Behalf of

Shanghai Huace Navigation Technology Ltd.

Tablet

Model No.: CB-H12

Prepared for : Shanghai Huace Navigation Technology Ltd.
Address : 577 Songying Road, Qingpu District, 201706 Shanghai, China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2410134-C07-R01
Date of Receipt : October 31, 2024
Date of Test : October 31, 2024 – November 6, 2024
Date of Report : November 6, 2024
Version Number : V0
Test Result : Pass

ALPHA's reports is using a digital certificate that is trusted on Adobe's official server. If there is no digital certificate or the digital certificate shows damaged in your report. Please do not accept the report.

E-mail: service@a-lab.cn Tel: 4008300895 Website: <http://www.a-lab.cn/certificate>

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. Summary of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. Maximum Peak Output power	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Setup	11
3.4. Test Result	11
4. Bandwidth	12
4.1. Limit	12
4.2. Test Procedure	12
4.3. Test Result	12
5. Carrier Frequency Separation	23
5.1. Limit	23
5.2. Test Procedure	23
5.3. Test Result	23
6. Number Of Hopping Channel	25
6.1. Limit	25
6.2. Test Procedure	25
6.3. Test Result	25
7. Dwell Time	27
7.1. Test limit	27
7.2. Test Procedure	27
7.3. Test Result	27
8. Radiated emissions	37
8.1. Limit	37
8.2. Block Diagram of Test setup	38
8.3. Test Procedure	39
8.4. Test Result	39
9. Band Edge Compliance	54
9.1. Block Diagram of Test Setup	54

9.2. Limit	54
9.3. Test Procedure	54
9.4. Test Result.....	54
10. Power Line Conducted Emissions.....	70
10.1. Block Diagram of Test Setup	70
10.2. Limit	70
10.3. Test Procedure	70
10.4. Test Result.....	70
11. Antenna Requirements.....	71
11.1. Limit.....	71
11.2. Result	71
12. Test setup photo	72
12.1. Photo of Radiated Emission test	72
13. EUT Photo.....	73

TEST REPORT DECLARATION

Applicant : Shanghai Huace Navigation Technology Ltd.
Address : 577 Songying Road, Qingpu District, 201706 Shanghai, China
Manufacturer : Shanghai Huace Navigation Technology Ltd.
Address : 577 Songying Road, Qingpu District, 201706 Shanghai, China
EUT Description : Tablet
(A) Model No. : CB-H12
(B) Trademark : 

Measurement Standard Used:
FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:	Yannis Wen Project Engineer	
Approved by (name + signature).....:	Jack Xu Project Manager	
Date of issue.....:	November 6, 2024	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	November 6, 2024	Initial released Issue	Yannis Wen

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209, FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	N/A
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

1. Pass: The EUT complies with the essential requirements in the standard.
2. Frequency Stability: The manufacturer stated in the user's manual.
3. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	: Tablet
Model No.	: CB-H12
DIFF.	: N/A
Power supply	: Input: 9-36Vdc 3.0A
Radio Technology	: Bluetooth EDR
Operation frequency	: 2402-2480MHz
Channel No.	: 79 Channels
Channel spacing	: 1MHz
Modulation type	: GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	: Internal antenna, Maximum Gain is 3.52dB : Antenna information is provided by applicant.
Software version	: HCD1_SPRING-12_A_V1.0.9_LCD12_B0_4G_EU_MDM_20240926
Hardware version	: CP029-MAIN-PCB-V1.3
Connector cable loss	: N/A
Intend use environment	: Residential, commercial and light industrial environment


2.2. Accessories of Device (EUT)

Accessories : /
 Manufacturer : /
 Model : /
 INPUT : /
 OUTPUT : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1.	--	--	--	--	--

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
$\pi/4$ DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
 Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
 Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
 Registration Number: 293961

July 15, 2019 Certificated by IC
 Registration Number: 12135A
 CAB identifier: CN0085

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.18	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2024.08.08	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2024.08.08	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-102082-Wa	2024.08.08	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2024.08.08	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2023.08.19	2Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	2Year
RF Cable	Resenberger	Cable 1	/	RE1	2024.08.08	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2024.08.08	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2024.08.08	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2024.08.08	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2024.08.08	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2024.08.08	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2024.08.08	1Year
Horn Antenna	SCHWARZBECK	BBHA 9170	/	00946	2023.08.19	2Year
Preamplifier	SKET	LNPA_1840-50	/	SK2018101801	2024.08.08	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2024.08.08	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2024.08.08	1 Year
Electronic Thermo-Hygrometer	S.H.Qixiang	HTC-1	/	N/A	2024.08.11	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2024.08.08	1 Year
Adjustable attenuator	MWRFTest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information

Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit


Please refer section 15.247

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	5.863	21	Pass
NVNT	1-DH1	2441	Ant1	6.104	21	Pass
NVNT	1-DH1	2480	Ant1	5.588	21	Pass
NVNT	1-DH3	2441	Ant1	6.207	21	Pass
NVNT	1-DH5	2441	Ant1	7.986	21	Pass
NVNT	2-DH1	2402	Ant1	7.3	21	Pass
NVNT	2-DH1	2441	Ant1	7.643	21	Pass
NVNT	2-DH1	2480	Ant1	7.169	21	Pass
NVNT	2-DH3	2441	Ant1	7.633	21	Pass
NVNT	2-DH5	2441	Ant1	7.66	21	Pass
NVNT	3-DH1	2402	Ant1	7.493	21	Pass
NVNT	3-DH1	2441	Ant1	7.879	21	Pass
NVNT	3-DH1	2480	Ant1	7.348	21	Pass
NVNT	3-DH3	2441	Ant1	7.973	21	Pass
NVNT	3-DH5	2441	Ant1	7.721	21	Pass

4. BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated..


4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


4.3. Test Result

-20dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.966	Pass
NVNT	1-DH1	2441	Ant1	1.02	Pass
NVNT	1-DH1	2480	Ant1	0.87	Pass
NVNT	2-DH1	2402	Ant1	1.228	Pass
NVNT	2-DH1	2441	Ant1	1.224	Pass
NVNT	2-DH1	2480	Ant1	1.256	Pass
NVNT	3-DH1	2402	Ant1	1.238	Pass
NVNT	3-DH1	2441	Ant1	1.244	Pass
NVNT	3-DH1	2480	Ant1	1.24	Pass

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1


Date: 24.OCT.2024 10:24:36

-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1


Date: 24.OCT.2024 10:28:57

-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1


Date: 24.OCT.2024 10:31:22

-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1


Date: 24.OCT.2024 10:51:04

-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1


Date: 24.OCT.2024 10:59:47

-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1

Date: 24.OCT.2024 11:01:28


-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1

Date: 24.OCT.2024 11:21:29

-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1

Date: 24.OCT.2024 11:23:00

-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1




Date: 24.OCT.2024 11:24:39

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.912
NVNT	1-DH1	2441	Ant1	0.907
NVNT	1-DH1	2480	Ant1	0.909
NVNT	2-DH1	2402	Ant1	1.125
NVNT	2-DH1	2441	Ant1	1.135
NVNT	2-DH1	2480	Ant1	1.127
NVNT	3-DH1	2402	Ant1	1.099
NVNT	3-DH1	2441	Ant1	1.093
NVNT	3-DH1	2480	Ant1	1.105

OBW NVNT 1-DH1 2402MHz Ant1




Date: 24.OCT.2024 10:24:27

OBW NVNT 1-DH1 2441MHz Ant1




Date: 24.OCT.2024 10:28:49

OBW NVNT 1-DH1 2480MHz Ant1




Date: 24.OCT.2024 10:31:14

OBW NVNT 2-DH1 2402MHz Ant1




Date: 24.OCT.2024 10:50:55

OBW NVNT 2-DH1 2441MHz Ant1




Date: 24.OCT.2024 10:59:38

OBW NVNT 2-DH1 2480MHz Ant1




Date: 24.OCT.2024 11:01:20

OBW NVNT 3-DH1 2402MHz Ant1




Date: 24.OCT.2024 11:21:21

OBW NVNT 3-DH1 2441MHz Ant1



Date: 24.OCT.2024 11:22:51

OBW NVNT 3-DH1 2480MHz Ant1



Date: 24.OCT.2024 11:24:30

5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2440.826	2441.83	1.004	0.680	Pass
NVNT	2-DH1	Ant1	2440.822	2441.822	1	0.816	Pass
NVNT	3-DH1	Ant1	2440.838	2441.946	1.108	0.829	Pass

CFS NVNT 1-DH1 2441MHz Ant1




Date: 24.OCT.2024 15:12:15

CFS NVNT 2-DH1 2441MHz Ant1



Date: 24.OCT.2024 11:08:34

CFS NVNT 3-DH1 2441MHz Ant1



Date: 24.OCT.2024 15:10:32

6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result


Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1




Date: 24.OCT.2024 10:37:59

Hopping No. NVNT 2-DH1 2441MHz Ant1



Hopping No. NVNT 3-DH1 2441MHz Ant1



7. DWELL TIME

7.1. Test limit

Please refer section 15.247.

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.


7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.383	122.560	318	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.639	262.240	158	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.887	307.947	115	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.392	125.440	320	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.643	262.880	167	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.891	308.373	120	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.392	125.440	318	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.641	262.560	167	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.892	308.480	98	31600	400	Pass


Note: Total Dwell Time= Pulse Time* Burst Count

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Date: 24.OCT.2024 10:38:17

Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 10:38:52

Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Date: 24.OCT.2024 10:42:48

Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 10:43:23

Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Date: 24.OCT.2024 10:48:01

Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 10:48:35

Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Date: 24.OCT.2024 11:10:27

Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 11:11:02

Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Date: 24.OCT.2024 11:15:58

Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 11:16:32

Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Date: 24.OCT.2024 11:18:50

Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 11:19:25

Dwell NVNT 3-DH1 2441MHz Ant1 One Burst




Date: 24.OCT.2024 11:31:00

Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 11:31:34

Dwell NVNT 3-DH3 2441MHz Ant1 One Burst




Date: 24.OCT.2024 11:34:35

Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated




Date: 24.OCT.2024 11:35:10

Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Date: 24.OCT.2024 11:37:28

Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



Date: 24.OCT.2024 11:38:03

8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	


Note: The peak limit is 20 dB higher than the average limit

8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result


We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS


Vertical:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	35.4536	17.56	13.74	31.30	40.00	-8.70	peak		
2		42.5202	14.33	14.29	28.62	40.00	-11.38	peak		
3		63.0105	13.45	12.51	25.96	40.00	-14.04	peak		
4		103.8297	22.95	11.23	34.18	43.50	-9.32	peak		
5		162.6673	13.05	14.78	27.83	43.50	-15.67	peak		
6		229.7759	20.45	12.30	32.75	46.00	-13.25	peak		

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	102.5032	22.53	11.10	33.63	43.50	-9.87	peak		
2		144.0144	11.03	14.61	25.64	43.50	-17.86	peak		
3		194.9995	17.36	11.19	28.55	43.50	-14.95	peak		
4		231.7719	19.86	12.35	32.21	46.00	-13.79	peak		
5		248.4646	18.90	12.73	31.63	46.00	-14.37	peak		
6		454.3629	10.57	17.61	28.18	46.00	-17.82	peak		

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Remark: All modes have been tested, and only worst data of GFSK 2402MHz was listed in this report.

From 1G-25GHz


Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	46.11	V	33.95	10.18	34.26	55.98	74	-18.02	PK
4804	31.95	V	33.95	10.18	34.26	41.82	54	-12.18	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	47.40	H	33.95	10.18	34.26	57.27	74	-16.73	PK
4804	33.58	H	33.95	10.18	34.26	43.45	54	-10.55	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	43.87	V	33.93	10.2	34.29	53.71	74	-20.29	PK
4882	36.79	V	33.93	10.2	34.29	46.63	54	-7.37	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	45.45	H	33.93	10.2	34.29	55.29	74	-18.71	PK
4882	33.11	H	33.93	10.2	34.29	42.95	54	-11.05	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	44.81	V	33.93	10.2	34.29	54.65	74	-19.35	PK
4960	33.85	V	33.93	10.2	34.29	43.69	54	-10.31	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	46.00	H	33.93	10.2	34.29	55.84	74	-18.16	PK
4960	34.21	H	33.93	10.2	34.29	44.05	54	-9.95	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:

- 1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Conducted RF Spurious Emission

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref




Date: 24.OCT.2024 10:25:09

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission




Date: 24.OCT.2024 10:25:23


Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission

