



## FCC TEST REPORT

FCC ID: SY4-A02058

On Behalf of

Shanghai Huace Navigation Technology Ltd.

Tablet

Model No.: CB-H10 Pro

Prepared for : Shanghai Huace Navigation Technology Ltd.  
Address : 577 Songying Road, Qingpu District, 201706 Shanghai, China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
Shenzhen, Guangdong, China

Report Number : A2410134-C08-R01  
Date of Receipt : October 23, 2024  
Date of Test : October 23, 2024 – November 22, 2024  
Date of Report : November 22, 2024  
Version Number : V0  
**Test Result : Pass**

ALPHA's reports is using a digital certificate that is trusted on Adobe's official server. If there is no digital certificate or the digital certificate shows damaged in your report. Please do not accept the report.

E-mail: [service@a-lab.cn](mailto:service@a-lab.cn) Tel: 4008300895 Website: <http://www.a-lab.cn/certificate>

## TABLE OF CONTENTS

| <u>Description</u>                                                | <u>Page</u> |
|-------------------------------------------------------------------|-------------|
| <b>1. Summary of Standards And Results .....</b>                  | <b>6</b>    |
| 1.1. Description of Standards and Results .....                   | 6           |
| <b>2. General Information .....</b>                               | <b>7</b>    |
| 2.1. Description of Device (EUT) .....                            | 7           |
| 2.2. Accessories of Device (EUT) .....                            | 8           |
| 2.3. Tested Supporting System Details .....                       | 8           |
| 2.4. Block Diagram of connection between EUT and simulators ..... | 8           |
| 2.5. Test Mode Description .....                                  | 8           |
| 2.6. Test Conditions .....                                        | 9           |
| 2.7. Test Facility .....                                          | 9           |
| 2.8. Measurement Uncertainty .....                                | 9           |
| 2.9. Test Equipment List .....                                    | 10          |
| <b>3. Maximum Peak Output power .....</b>                         | <b>11</b>   |
| 3.1. Limit .....                                                  | 11          |
| 3.2. Test Procedure .....                                         | 11          |
| 3.3. Test Setup .....                                             | 11          |
| 3.4. Test Result .....                                            | 11          |
| <b>4. Bandwidth .....</b>                                         | <b>12</b>   |
| 4.1. Limit .....                                                  | 12          |
| 4.2. Test Procedure .....                                         | 12          |
| 4.3. Test Result .....                                            | 12          |
| <b>5. Carrier Frequency Separation .....</b>                      | <b>23</b>   |
| 5.1. Limit .....                                                  | 23          |
| 5.2. Test Procedure .....                                         | 23          |
| 5.3. Test Result .....                                            | 23          |
| <b>6. Number Of Hopping Channel .....</b>                         | <b>25</b>   |
| 6.1. Limit .....                                                  | 25          |
| 6.2. Test Procedure .....                                         | 25          |
| 6.3. Test Result .....                                            | 25          |
| <b>7. Dwell Time .....</b>                                        | <b>27</b>   |
| 7.1. Test limit .....                                             | 27          |
| 7.2. Test Procedure .....                                         | 27          |
| 7.3. Test Result .....                                            | 27          |
| <b>8. Radiated emissions .....</b>                                | <b>37</b>   |
| 8.1. Limit .....                                                  | 37          |
| 8.2. Block Diagram of Test setup .....                            | 38          |
| 8.3. Test Procedure .....                                         | 39          |
| 8.4. Test Result .....                                            | 39          |
| <b>9. Band Edge Compliance .....</b>                              | <b>54</b>   |
| 9.1. Block Diagram of Test Setup .....                            | 54          |

|                                                |           |
|------------------------------------------------|-----------|
| 9.2. Limit .....                               | 54        |
| 9.3. Test Procedure .....                      | 54        |
| 9.4. Test Result.....                          | 54        |
| <b>10. Power Line Conducted Emissions.....</b> | <b>70</b> |
| 10.1. Block Diagram of Test Setup .....        | 70        |
| 10.2. Limit .....                              | 70        |
| 10.3. Test Procedure .....                     | 70        |
| 10.4. Test Result.....                         | 70        |
| <b>11. Antenna Requirements.....</b>           | <b>71</b> |
| 11.1. Limit.....                               | 71        |
| 11.2. Result .....                             | 71        |
| <b>12. Test setup photo .....</b>              | <b>72</b> |
| 12.1. Photo of Radiated Emission test .....    | 72        |
| <b>13. EUT Photo.....</b>                      | <b>73</b> |

## TEST REPORT DECLARATION

Applicant : Shanghai Huace Navigation Technology Ltd.  
Address : 577 Songying Road, Qingpu District, 201706 Shanghai, China  
Manufacturer : Shanghai Huace Navigation Technology Ltd.  
Address : 577 Songying Road, Qingpu District, 201706 Shanghai, China  
EUT Description : Tablet  
(A) Model No. : CB-H10 Pro  
(B) Trademark : 

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247**

**ANSI C63.10:2013**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen  
Project Engineer



Approved by (name + signature).....: Jack Xu  
Project Manager



Date of issue.....: November 22, 2024

**Revision History**

| Revision | Issue Date        | Revisions              | Revised By |
|----------|-------------------|------------------------|------------|
| V0       | November 22, 2024 | Initial released Issue | Yannis Wen |

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

| Test Item                                                                                                                                                                                   | Standards Paragraph                                              | Result |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|--------|
| Maximum Peak Output Power                                                                                                                                                                   | FCC Part 15: 15.247(b)(1)<br>ANSI C63.10 :2013                   | P      |
| Bandwidth                                                                                                                                                                                   | FCC Part 15: 15.215<br>ANSI C63.10 :2013                         | P      |
| Carrier Frequency Separation                                                                                                                                                                | FCC Part 15: 15.247(a)(1)<br>ANSI C63.10 :2013                   | P      |
| Number Of Hopping Channel                                                                                                                                                                   | FCC Part 15: 15.247(a)(1)<br>ANSI C63.10 :2013                   | P      |
| Dwell Time                                                                                                                                                                                  | FCC Part 15: 15.247(a)(1)<br>ANSI C63.10 :2013                   | P      |
| Radiated Emission                                                                                                                                                                           | FCC Part 15: 15.209, FCC Part 15: 15.247(d)<br>ANSI C63.10 :2013 | P      |
| Band Edge Compliance                                                                                                                                                                        | FCC Part 15: 15.247(d)<br>ANSI C63.10 :2013                      | P      |
| Power Line Conducted Emissions                                                                                                                                                              | FCC Part 15: 15.207<br>ANSI C63.10 :2013                         | N/A    |
| Antenna requirement                                                                                                                                                                         | FCC Part 15: 15.203                                              | P      |
| Note: <ol style="list-style-type: none"> <li>1. P is an abbreviation for Pass.</li> <li>2. F is an abbreviation for Fail.</li> <li>3. N/A is an abbreviation for Not Applicable.</li> </ol> |                                                                  |        |

1. Pass: The EUT complies with the essential requirements in the standard.
2. Frequency Stability: The manufacturer stated in the user's manual.
3. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

|                        |                                                                                               |
|------------------------|-----------------------------------------------------------------------------------------------|
| Description            | : Tablet                                                                                      |
| Model No.              | : CB-H10 Pro                                                                                  |
| DIFF.                  | : N/A                                                                                         |
| Power supply           | : Input: 9-36Vdc 3.0A                                                                         |
| Radio Technology       | : Bluetooth EDR                                                                               |
| Operation frequency    | : 2402-2480MHz                                                                                |
| Channel No.            | : 79 Channels                                                                                 |
| Channel spacing        | : 1MHz                                                                                        |
| Modulation type        | : GFSK, $\pi/4$ DQPSK, 8DPSK                                                                  |
| Antenna Type           | : Internal antenna, Maximum Gain is 1.75dB<br>: Antenna information is provided by applicant. |
| Software version       | : HCD1_SPRING-12_A_V1.0.9_LCD12_B0_4G_EU_MDM_20240926                                         |
| Hardware version       | : CP029-MAIN-PCB-V1.3                                                                         |
| Connector cable loss   | : N/A                                                                                         |
| Intend use environment | : Residential, commercial and light industrial environment                                    |


## 2.2. Accessories of Device (EUT)

Accessories : /  
 Manufacturer : /  
 Model : /  
 INPUT : /  
 OUTPUT : /

## 2.3. Tested Supporting System Details

| No. | Description | Manufacturer | Model | Serial Number | Certification or SDoC |
|-----|-------------|--------------|-------|---------------|-----------------------|
| 1.  | --          | --           | --    | --            | --                    |

## 2.4. Block Diagram of connection between EUT and simulators



## 2.5. Test Mode Description

| Tested mode, channel information |              |                 |
|----------------------------------|--------------|-----------------|
| Mode                             | Channel      | Frequency (MHz) |
| GFSK                             | Low :CH1     | 2402            |
|                                  | Middle: CH40 | 2441            |
|                                  | High: CH79   | 2480            |
| $\pi/4$ DQPSK                    | Low :CH1     | 2402            |
|                                  | Middle: CH40 | 2441            |
|                                  | High: CH79   | 2480            |
| 8DPSK                            | Low :CH1     | 2402            |
|                                  | Middle: CH40 | 2441            |
|                                  | High: CH79   | 2480            |

## 2.6. Test Conditions

| Items              | Required  | Actual |
|--------------------|-----------|--------|
| Temperature range: | 15-35°C   | 24°C   |
| Humidity range:    | 25-75%    | 56%    |
| Pressure range:    | 86-106kPa | 980kPa |

## 2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

July 15, 2019 Certificated by IC

Registration Number: 12135A

CAB identifier: CN0085

## 2.8. Measurement Uncertainty

(95% confidence levels, k=2)

| Item                                                                      | Uncertainty               |
|---------------------------------------------------------------------------|---------------------------|
| Uncertainty for Power point Conducted Emissions Test                      | 1.63dB                    |
| Uncertainty for Radiation Emission test in 3m chamber<br>(below 30MHz)    | 3.5dB                     |
| Uncertainty for Radiation Emission test in 3m chamber<br>(30MHz to 1GHz)  | 3.74dB(Polarize: V)       |
|                                                                           | 3.76dB(Polarize: H)       |
| Uncertainty for Radiation Emission test in 3m chamber<br>(1GHz to 25GHz)  | 3.77dB(Polarize: V)       |
|                                                                           | 3.80dB(Polarize: H)       |
| Uncertainty for Radiation Emission test in 3m chamber<br>(18GHz to 40GHz) | 4.31 dB(Polarize: V)      |
|                                                                           | 4.30 dB(Polarize: H)      |
| Uncertainty for radio frequency                                           | $5.06 \times 10^{-8}$ GHz |
| Uncertainty for conducted RF Power                                        | 0.40dB                    |
| Uncertainty for temperature                                               | 0.2°C                     |
| Uncertainty for humidity                                                  | 1%                        |
| Uncertainty for DC and low frequency voltages                             | 0.06%                     |

## 2.9. Test Equipment List

| Equipment                    | Manufacture   | Model No.    | Firmware version | Serial No.             | Last cal.  | Cal Interval |
|------------------------------|---------------|--------------|------------------|------------------------|------------|--------------|
| 9*6*6 anechoic chamber       | CHENYU        | 9*6*6        | /                | N/A                    | 2022.05.18 | 3Year        |
| Spectrum analyzer            | ROHDE&SCHWARZ | FSV40-N      | 2.3              | 102137                 | 2024.08.08 | 1Year        |
| Spectrum analyzer            | Agilent       | N9020A       | A.14.16          | MY499100060            | 2024.08.08 | 1Year        |
| Receiver                     | ROHDE&SCHWARZ | ESR          | 2.28 SP1         | 1316.3003K03-102082-Wa | 2024.08.08 | 1Year        |
| Receiver                     | R&S           | ESCI         | 4.42 SP1         | 101165                 | 2024.08.08 | 1Year        |
| Bilog Antenna                | Schwarzbeck   | VULB 9168    | /                | VULB 9168#627          | 2023.08.28 | 2Year        |
| Horn Antenna                 | SCHWARZBECK   | BBHA 9120 D  | /                | 2106                   | 2023.08.19 | 2Year        |
| Loop Antenna                 | SCHWARZBECK   | FMZB 1519B   | /                | 00128                  | 2023.08.19 | 2Year        |
| RF Cable                     | Resenberger   | Cable 1      | /                | RE1                    | 2024.08.08 | 1Year        |
| RF Cable                     | Resenberger   | Cable 2      | /                | RE2                    | 2024.08.08 | 1Year        |
| RF Cable                     | Resenberger   | Cable 3      | /                | CE1                    | 2024.08.08 | 1Year        |
| Pre-amplifier                | HP            | HP8347A      | /                | 2834A00455             | 2024.08.08 | 1Year        |
| Pre-amplifier                | Agilent       | 8449B        | /                | 3008A02664             | 2024.08.08 | 1Year        |
| L.I.S.N.#1                   | Schwarzbeck   | NSLK8126     | /                | 8126-466               | 2024.08.08 | 1Year        |
| L.I.S.N.#2                   | ROHDE&SCHWARZ | ENV216       | /                | 101043                 | 2024.08.08 | 1Year        |
| Horn Antenna                 | SCHWARZBECK   | BBHA 9170    | /                | 00946                  | 2023.08.19 | 2Year        |
| Preamplifier                 | SKET          | LNPA_1840-50 | /                | SK2018101801           | 2024.08.08 | 1 Year       |
| Power Meter                  | Agilent       | E9300A       | /                | MY41496628             | 2024.08.08 | 1 Year       |
| Power Sensor                 | DARE          | RPR3006W     | /                | 15100041SNO91          | 2024.08.08 | 1 Year       |
| Electronic Thermo-Hygrometer | S.H.Qixiang   | HTC-1        | /                | N/A                    | 2024.08.11 | 1 Year       |
| Switching Mode Power Supply  | JUNKE         | JK12010S     | /                | 20140927-6             | 2024.08.08 | 1 Year       |
| Adjustable attenuator        | MWRFTest      | N/A          | /                | N/A                    | N/A        | N/A          |
| 10dB Attenuator              | Mini-Circuits | DC-6G        | /                | N/A                    | N/A        | N/A          |

## Software Information

| Test Item | Software Name | Manufacturer | Version   |
|-----------|---------------|--------------|-----------|
| RE        | EZ-EMC        | EZ           | Alpha-3A1 |
| CE        | EZ-EMC        | EZ           | Alpha-3A1 |
| RF-CE     | MTS 8310      | MW           | V2.0.0.0  |

### 3. MAXIMUM PEAK OUTPUT POWER

#### 3.1. Limit


Please refer section 15.247

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

#### 3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

#### 3.3. Test Setup



#### 3.4. Test Result

| Condition | Mode  | Frequency (MHz) | Antenna | Conducted Power (dBm) | Limit (dBm) | Verdict |
|-----------|-------|-----------------|---------|-----------------------|-------------|---------|
| NVNT      | 1-DH1 | 2402            | Ant1    | <b>7.281</b>          | 21          | Pass    |
| NVNT      | 1-DH1 | 2441            | Ant1    | 7.174                 | 21          | Pass    |
| NVNT      | 1-DH1 | 2480            | Ant1    | 7.089                 | 21          | Pass    |
| NVNT      | 1-DH3 | 2441            | Ant1    | 7.046                 | 21          | Pass    |
| NVNT      | 1-DH5 | 2441            | Ant1    | 6.878                 | 21          | Pass    |
| NVNT      | 2-DH1 | 2402            | Ant1    | 7.216                 | 21          | Pass    |
| NVNT      | 2-DH1 | 2441            | Ant1    | 6.405                 | 21          | Pass    |
| NVNT      | 2-DH1 | 2480            | Ant1    | 6.733                 | 21          | Pass    |
| NVNT      | 2-DH3 | 2441            | Ant1    | 6.699                 | 21          | Pass    |
| NVNT      | 2-DH5 | 2441            | Ant1    | 5.753                 | 21          | Pass    |
| NVNT      | 3-DH1 | 2402            | Ant1    | 6.204                 | 21          | Pass    |
| NVNT      | 3-DH1 | 2441            | Ant1    | 6.026                 | 21          | Pass    |
| NVNT      | 3-DH1 | 2480            | Ant1    | 6.085                 | 21          | Pass    |
| NVNT      | 3-DH3 | 2441            | Ant1    | 6.73                  | 21          | Pass    |
| NVNT      | 3-DH5 | 2441            | Ant1    | 6.917                 | 21          | Pass    |

## 4. BANDWIDTH

### 4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated..

### 4.2. Test Procedure


The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 4.3. Test Result

#### -20dB Bandwidth


| Condition | Mode  | Frequency (MHz) | Antenna | -20 dB Bandwidth (MHz) | Verdict |
|-----------|-------|-----------------|---------|------------------------|---------|
| NVNT      | 1-DH1 | 2402            | Ant1    | 1.028                  | Pass    |
| NVNT      | 1-DH1 | 2441            | Ant1    | 0.992                  | Pass    |
| NVNT      | 1-DH1 | 2480            | Ant1    | 0.958                  | Pass    |
| NVNT      | 2-DH1 | 2402            | Ant1    | 1.242                  | Pass    |
| NVNT      | 2-DH1 | 2441            | Ant1    | 1.216                  | Pass    |
| NVNT      | 2-DH1 | 2480            | Ant1    | 1.236                  | Pass    |
| NVNT      | 3-DH1 | 2402            | Ant1    | 1.23                   | Pass    |
| NVNT      | 3-DH1 | 2441            | Ant1    | 1.232                  | Pass    |
| NVNT      | 3-DH1 | 2480            | Ant1    | 1.242                  | Pass    |

## -20dB Bandwidth NVNT 1-DH1 2402MHz Ant1




Date: 31.OCT.2024 13:57:27

## -20dB Bandwidth NVNT 1-DH1 2441MHz Ant1




Date: 31.OCT.2024 14:00:23

## -20dB Bandwidth NVNT 1-DH1 2480MHz Ant1




Date: 31.OCT.2024 14:02:03

## -20dB Bandwidth NVNT 2-DH1 2402MHz Ant1




Date: 31.OCT.2024 19:37:54

## -20dB Bandwidth NVNT 2-DH1 2441MHz Ant1




Date: 31.OCT.2024 19:41:47


## -20dB Bandwidth NVNT 2-DH1 2480MHz Ant1



Date: 31.OCT.2024 19:47:16


**-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1**

Date: 31.OCT.2024 20:22:07

**-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1**

Date: 31.OCT.2024 20:27:53

## -20dB Bandwidth NVNT 3-DH1 2480MHz Ant1




Date: 31.OCT.2024 20:29:41

## Occupied Channel Bandwidth


| Condition | Mode  | Frequency (MHz) | Antenna | 99% OBW (MHz) |
|-----------|-------|-----------------|---------|---------------|
| NVNT      | 1-DH1 | 2402            | Ant1    | 0.909         |
| NVNT      | 1-DH1 | 2441            | Ant1    | 0.891         |
| NVNT      | 1-DH1 | 2480            | Ant1    | 0.885         |
| NVNT      | 2-DH1 | 2402            | Ant1    | 1.137         |
| NVNT      | 2-DH1 | 2441            | Ant1    | 1.119         |
| NVNT      | 2-DH1 | 2480            | Ant1    | 1.139         |
| NVNT      | 3-DH1 | 2402            | Ant1    | 1.101         |
| NVNT      | 3-DH1 | 2441            | Ant1    | 1.105         |
| NVNT      | 3-DH1 | 2480            | Ant1    | 1.095         |

## OBW NVNT 1-DH1 2402MHz Ant1




Date: 31.OCT.2024 13:57:19

## OBW NVNT 1-DH1 2441MHz Ant1




Date: 31.OCT.2024 14:00:15

## OBW NVNT 1-DH1 2480MHz Ant1




Date: 31.OCT.2024 14:01:56

## OBW NVNT 2-DH1 2402MHz Ant1




Date: 31.OCT.2024 19:37:46

## OBW NVNT 2-DH1 2441MHz Ant1




Date: 31.OCT.2024 19:41:40

## OBW NVNT 2-DH1 2480MHz Ant1




Date: 31.OCT.2024 19:47:08

## OBW NVNT 3-DH1 2402MHz Ant1




Date: 31.OCT.2024 20:21:59

## OBW NVNT 3-DH1 2441MHz Ant1



Date: 31.OCT.2024 20:27:44

OBW NVNT 3-DH1 2480MHz Ant1



Date: 31.OCT.2024 20:29:32

## 5. CARRIER FREQUENCY SEPARATION

### 5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


### 5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

### 5.3. Test Result


| Condition | Mode  | Antenna | Hopping Freq1 (MHz) | Hopping Freq2 (MHz) | HFS (MHz) | Limit (MHz) | Verdict |
|-----------|-------|---------|---------------------|---------------------|-----------|-------------|---------|
| NVNT      | 1-DH1 | Ant1    | 2440.822            | 2441.822            | 1         | 0.685       | Pass    |
| NVNT      | 2-DH1 | Ant1    | 2440.824            | 2441.832            | 1.008     | 0.811       | Pass    |
| NVNT      | 3-DH1 | Ant1    | 2440.828            | 2441.828            | 1         | 0.821       | Pass    |

CFS NVNT 1-DH1 2441MHz Ant1




Date: 31.OCT.2024 14:05:32

## CFS NVNT 2-DH1 2441MHz Ant1



Date: 31.OCT.2024 19:53:20

## CFS NVNT 3-DH1 2441MHz Ant1



Date: 31.OCT.2024 20:53:24

## 6. NUMBER OF HOPPING CHANNEL

### 6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


### 6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

### 6.3. Test Result


| Condition | Mode  | Antenna | Hopping Number | Limit | Verdict |
|-----------|-------|---------|----------------|-------|---------|
| NVNT      | 1-DH1 | Ant1    | 79             | 15    | Pass    |
| NVNT      | 2-DH1 | Ant1    | 79             | 15    | Pass    |
| NVNT      | 3-DH1 | Ant1    | 79             | 15    | Pass    |

Hopping No. NVNT 1-DH1 2441MHz Ant1




Date: 31.OCT.2024 14:05:58

## Hopping No. NVNT 2-DH1 2441MHz Ant1



Date: 31.OCT.2024 19:53:51

## Hopping No. NVNT 3-DH1 2441MHz Ant1



Date: 31.OCT.2024 20:54:34

## 7. DWELL TIME

### 7.1. Test limit

Please refer section 15.247.

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

### 7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.


7.2.5. Repeat above procedures until all frequency measured were complete.

### 7.3. Test Result

| Condition | Mode  | Frequency (MHz) | Antenna | Pulse Time (ms) | Total Dwell Time (ms) | Burst Count | Period Time (ms) | Limit (ms) | Verdict |
|-----------|-------|-----------------|---------|-----------------|-----------------------|-------------|------------------|------------|---------|
| NVNT      | 1-DH1 | 2441            | Ant1    | 0.383           | 121.028               | 316         | 31600            | 400        | Pass    |
| NVNT      | 1-DH3 | 2441            | Ant1    | 1.639           | 244.211               | 149         | 31600            | 400        | Pass    |
| NVNT      | 1-DH5 | 2441            | Ant1    | 2.887           | 300.248               | 104         | 31600            | 400        | Pass    |
| NVNT      | 2-DH1 | 2441            | Ant1    | 0.391           | 123.556               | 316         | 31600            | 400        | Pass    |
| NVNT      | 2-DH3 | 2441            | Ant1    | 1.643           | 253.022               | 154         | 31600            | 400        | Pass    |
| NVNT      | 2-DH5 | 2441            | Ant1    | 2.435           | 153.405               | 63          | 31600            | 400        | Pass    |
| NVNT      | 3-DH1 | 2441            | Ant1    | 0.391           | 123.556               | 316         | 31600            | 400        | Pass    |
| NVNT      | 3-DH3 | 2441            | Ant1    | 1.642           | 251.226               | 153         | 31600            | 400        | Pass    |
| NVNT      | 3-DH5 | 2441            | Ant1    | 2.892           | 294.984               | 102         | 31600            | 400        | Pass    |


Note: Total Dwell Time= Pulse Time\* Burst Count

## Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Date: 31.OCT.2024 14:06:05

## Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 14:06:39

## Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Date: 31.OCT.2024 19:23:08

## Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 19:23:42

## Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Date: 31.OCT.2024 19:33:15

## Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 19:33:50

## Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Date: 31.OCT.2024 19:53:58

## Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 19:54:32

## Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Date: 31.OCT.2024 19:56:28

## Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 19:57:03

## Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Date: 31.OCT.2024 20:11:23

## Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 20:11:57

## Dwell NVNT 3-DH1 2441MHz Ant1 One Burst




Date: 31.OCT.2024 20:54:41

## Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 20:55:15

## Dwell NVNT 3-DH3 2441MHz Ant1 One Burst




Date: 31.OCT.2024 21:18:15

## Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated




Date: 31.OCT.2024 21:18:49

## Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Date: 31.OCT.2024 21:22:18

## Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



Date: 31.OCT.2024 21:22:53

## 8. RADIATED EMISSIONS

### 8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

| MHz                        | MHz                   | MHz             | GHz              |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.7 - 156.9         | 2690 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 240 - 285             | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |


15.209 Limit

| FREQUENCY<br>MHz | DISTANCE<br>Meters | FIELD STRENGTHS LIMIT                           |          |
|------------------|--------------------|-------------------------------------------------|----------|
|                  |                    | μV/m                                            | dB(μV)/m |
| 0.009-0.490      | 300                | 2400/F(KHz)                                     | /        |
| 0.490-1.705      | 30                 | 24000/F(KHz)                                    | /        |
| 1.705-30         | 30                 | 30                                              | 29.5     |
| 30 ~ 88          | 3                  | 100                                             | 40.0     |
| 88 ~ 216         | 3                  | 150                                             | 43.5     |
| 216 ~ 960        | 3                  | 200                                             | 46.0     |
| 960 ~ 1000       | 3                  | 500                                             | 54.0     |
| Above 1000       | 3                  | 74.0 dB(μV)/m (Peak)<br>54.0 dB(μV)/m (Average) |          |


Note: The peak limit is 20 dB higher than the average limit

## 8.2. Block Diagram of Test setup


### 8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



### 8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



### 8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

### 8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
  - (a) Change work frequency or channel of device if practicable.
  - (b) Change modulation type of device if practicable.
  - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

### 8.4. Test Result

We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency.  
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS


**Vertical:**



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Antenna<br>Height<br>cm | Table<br>Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|-------------------------|-----------------|---------|
| 1   |     | 35.4536      | 17.06                    | 13.74                   | 30.80                      | 40.00           | -9.20        | peak                    |                 |         |
| 2   |     | 42.5202      | 13.83                    | 14.29                   | 28.12                      | 40.00           | -11.88       | peak                    |                 |         |
| 3   |     | 63.0105      | 14.45                    | 12.51                   | 26.96                      | 40.00           | -13.04       | peak                    |                 |         |
| 4   | *   | 103.8297     | 23.95                    | 11.23                   | 35.18                      | 43.50           | -8.32        | peak                    |                 |         |
| 5   |     | 162.6673     | 13.55                    | 14.78                   | 28.33                      | 43.50           | -15.17       | peak                    |                 |         |
| 6   |     | 215.9987     | 20.60                    | 11.47                   | 32.07                      | 43.50           | -11.43       | peak                    |                 |         |

Note: 1. \*: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

**Horizontal:**

| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Margin | Antenna Height | Table Degree |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | cm             | degree       | Comment |
| 1   |     | 47.7813  | 11.36         | 14.08          | 25.44       | 40.00  | -14.56 | peak           |              |         |
| 2   |     | 73.0939  | 13.93         | 10.81          | 24.74       | 40.00  | -15.26 | peak           |              |         |
| 3   | *   | 102.5032 | 23.53         | 11.10          | 34.63       | 43.50  | -8.87  | peak           |              |         |
| 4   |     | 231.7718 | 19.36         | 12.35          | 31.71       | 46.00  | -14.29 | peak           |              |         |
| 5   |     | 248.4645 | 18.90         | 12.73          | 31.63       | 46.00  | -14.37 | peak           |              |         |
| 6   |     | 632.2793 | 10.86         | 20.88          | 31.74       | 46.00  | -14.26 | peak           |              |         |

Note:1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Remark: All modes have been tested, and only worst data of GFSK 2402MHz was listed in this report.

From 1G-25GHz

| Test Mode: GFSK TX Low  |                     |             |                       |                |                 |                 |                |             |        |
|-------------------------|---------------------|-------------|-----------------------|----------------|-----------------|-----------------|----------------|-------------|--------|
| Freq (MHz)              | Read Level (dBuV/m) | Polar (H/V) | Antenna Factor (dB/m) | Cable loss(dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 4804                    | 44.36               | V           | 33.95                 | 10.18          | 34.26           | 54.23           | 74             | -19.77      | PK     |
| 4804                    | 38.03               | V           | 33.95                 | 10.18          | 34.26           | 47.90           | 54             | -6.10       | AV     |
| 7206                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 9608                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 4804                    | 44.50               | H           | 33.95                 | 10.18          | 34.26           | 54.37           | 74             | -19.63      | PK     |
| 4804                    | 33.99               | H           | 33.95                 | 10.18          | 34.26           | 43.86           | 54             | -10.14      | AV     |
| 7206                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 9608                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| Test Mode: GFSK TX Mid  |                     |             |                       |                |                 |                 |                |             |        |
| 4882                    | 42.05               | V           | 33.93                 | 10.2           | 34.29           | 51.89           | 74             | -22.11      | PK     |
| 4882                    | 33.82               | V           | 33.93                 | 10.2           | 34.29           | 43.66           | 54             | -10.34      | AV     |
| 7323                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 9764                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 4882                    | 44.28               | H           | 33.93                 | 10.2           | 34.29           | 54.12           | 74             | -19.88      | PK     |
| 4882                    | 34.71               | H           | 33.93                 | 10.2           | 34.29           | 44.55           | 54             | -9.45       | AV     |
| 7323                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 9764                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| Test Mode: GFSK TX High |                     |             |                       |                |                 |                 |                |             |        |
| 4960                    | 45.00               | V           | 33.98                 | 10.22          | 34.25           | 54.95           | 74             | -19.05      | PK     |
| 4960                    | 35.70               | V           | 33.98                 | 10.22          | 34.25           | 45.65           | 54             | -8.35       | AV     |
| 7440                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 9920                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 4960                    | 43.38               | H           | 33.98                 | 10.22          | 34.25           | 53.33           | 74             | -20.67      | PK     |
| 4960                    | 34.46               | H           | 33.98                 | 10.22          | 34.25           | 44.41           | 54             | -9.59       | AV     |
| 7440                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |
| 9920                    | /                   | /           | /                     | /              | /               | /               | /              | /           | /      |

Note:


- 1, Result = Read level + Antenna factor + cable loss-Amp factor
- 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.






## Conducted RF Spurious Emission

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref




Date: 31.OCT.2024 13:58:03

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission




Date: 31.OCT.2024 13:58:16


## Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref




## Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission




## Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref



## Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission




## Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref




Date: 31.OCT.2024 19:38:28

## Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Date: 31.OCT.2024 19:38:52

## Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref



Date: 31.OCT.2024 19:42:11

## Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission



Date: 31.OCT.2024 19:42:35

