



Test report issued by an Accredited Testing Laboratory

 Accred. no. 1761
 Testing
 ISO/IEC 17025

EMF Test Report: Ericsson Dot 4442 B25 B66A (FCC)

Document number:	GFTL-21:000220 Uen, Rev A		
Testing laboratory:	Ericsson EMF Research Laboratory Ericsson AB SE-164 80 Stockholm Sweden	Company/Client:	Denis Lalonde Ericsson Canada 349 Terry Fox Drive Ottawa ON K2K 2V6 Canada
Tests performed by:	Davide Colombi	Dates of tests:	2021-02-22 (Rev A)
Manufacturer and market name(s) of device:	Ericsson Dot 4442 B25 B66A		
Testing has been performed in accordance with:	FCC OET Bulletin 65		
Test results:	Minimum separation distance for which the RF EMF exposure complies with the limits in FCC 47 CFR 1.1310 to be included in the Customer Product Information (CPI) for Ericsson Dot 4442.		
Additional information:	Testing was conducted for mobile exposure conditions according to KDB447498 DO1		
Signature:	Test Engineer  Davide Colombi Master Researcher davide.colombi@ericsson.com Tel: +46767602089	Laboratory and Quality Manager  Christer Törnevik Senior Expert – EMF and Health christer.tornevik@ericsson.com Tel: +46705863148	

1 Summary of EMF Test Report¹

Equipment under test (EUT)

Product name	Ericsson Dot 4442 B25 B66A		
Product number	KRY 901 386/1		
Supported bands, Tx frequency range (MHz), and standards	B25 B66A	1930–1995 2110–2200	LTE, NR
Exposure environment	General public/uncontrolled		

Results

The minimum (test) separation distance required for the equipment under test (EUT) to comply with the mobile device exposure conditions and relevant limits applicable in the USA [1]-[3] is provided in the table below for the general public (uncontrolled exposure).

RF exposure assessment results for general public (uncontrolled) exposure as obtained for Dot 4442 B25 B66A together with an assumed output power tolerance of 2 dB using procedures applicable for the US market [3].

Band	Standard	Nominal output power from the radio	Test position	Separation distance
B25 + B66A	LTE, NR	4 x 0.05 W	Direction of maximum gain	20 cm

¹ This page contains a summary of the test results. The full report provides a complete description of all test details and results.

2 General information

The test results reported in this document have been obtained by simple calculations according to plane-wave equivalent conditions [3]. The purpose of the tests was to verify that the EUT is in compliance with the appropriate RF exposure standards, recommendations and limits [1]–[3].

It should be noted that the test results presented in this test report are valid for the frequency range and for the antenna properties specified in Table 1, in addition to the power level and the power tolerance specified in Table 2. These data were supplied by the client and may affect the validity of the results.

Proposed EMF health and safety information for inclusion in the Customer Product Information (CPI) is provided in Appendices A and B.

3 Equipment under test

Table 1 summarizes the technical data for the EUT. Photographs of the EUT are presented in Appendix C.

Table 1 Technical data for the EUT.

Product name	Ericsson Dot 4442 B25 B66A		
Product tested	KRY 901 386/1		
Supported bands, Tx frequency range (MHz), and standards	B25 B66A	1930–1995 2110–2200	LTE, NR
Dimensions of Radio head, H x D (mm)	52 x 140		
Configuration(s) covered by this report	B25 + B66A		
Antenna(s)	Four internal antenna branches		Maximum antenna gain: 2.9 dBi
Exposure environment	General public/uncontrolled		

In Table 2 nominal output power levels are given.

Table 2 Nominal output power levels.

Band	Standard	Nominal output power ² [dBm]	Power tolerance [dB]	Transmission loss [dB]	Maximum time-averaged output power [dBm] ³
B25 + B66A	LTE, NR	17	2	0	25

The EUT related data in Table 1 and Table 2 were supplied by the client.

4 EMF exposure assessments

FCC procedures [3] specify exposure assessment methods to verify compliance with EMF exposure limits [1] of mobile devices. A minimum test separation distance of at least 20 cm is required between the device and nearby persons to apply mobile device exposure limits. The minimum test separation distance for which the equipment is shown to comply with the exposure limits must be clearly provided in the operating and installation instructions.

The assessments were conducted for maximum power configurations, i.e., by assuming 100% utilization. Effects of real RBS utilization (time-averaged) is reasonably foreseeable and will significantly reduce the time-averaged power and the RF exposure. This factor was not considered in this assessment, which adds to the

² Nominal output power per port.

³ Conservative measure of the total maximum possible output power level delivered to the antennas including losses and tolerances.

conservativeness of the obtained compliance boundaries.

4.1 Field strength calculations

The total effective radiated power based on the maximum antenna gain of Table 1 and the output power level of Table 2 is 0.4 W. As a consequence, the categorical exclusion provision of FCC CFR title 47, § 2.1091(c) applies [5] and the minimum test separation distance may be estimated by simple calculations according to plane-wave equivalent conditions [3].

The minimum test separation distance is determined assuming correlated transmit signals. Based on the maximum gain of the single antenna ($G_{\text{ant}} = 2.9 \text{ dBi}$, see Table 1), the directional gain, G , may be taken as 8.9 dBi according to [4] ($G = G_{\text{ant}} + 10 \log_{10} N$, where N is the number of simultaneously transmitting antennas). This is most likely a very conservative assumption since the antennas are spatially separated and their maximum gain occurs at different locations which add extra conservativeness of the results.

Power density may be conservatively estimated as

$$S_{\text{est}} = \frac{P_{\text{tot}}G}{4\pi r^2},$$

where

P_{tot} : Total conducted power for the cellular bands⁴,

G : Directional gain⁵,

r : Separation distance from antenna

S_{est} : Estimated power density.

For a minimum test separation distance of 20 cm (Table 3), the estimated power density is below 10 W/m² and the EUT complies with the mobile device exposure conditions and relevant limits applicable in the USA [1]-[3] (see Table 4) for the general public (uncontrolled exposure).

Table 3 RF exposure assessment results for general public (uncontrolled) exposure as obtained for Dot 4442 B25 B66A together with an assumed output power tolerance of 2 dB using procedures applicable for the US market [3].

Band	Standard	Nominal output power from the radio	Test position	Separation distance
B25 + B66A	LTE, NR	4 x 0.05 W	Direction of maximum gain	20 cm

Table 4 General public (uncontrolled) RF EMF exposure limits applicable in the US market.

Band	S_{lim} (W/m ²)
B25	10
B66A	10

5 Conclusion

The results in Section 4 show that the plane-wave equivalent power density for the Ericsson Dot 4442 B25 B66A, estimated according to the requirements of FCC [3] is below the relevant MPE limits [1] at a separation distance of at least 20 cm between the equipment and any nearby person.

⁴ This is equal to the maximum output power (in W) in Table 2.

⁵ This is equal to linear value of G .

6 References

- [1] FCC, Code of Federal Regulations CFR title 47, part 1.1310 "Radiofrequency radiation exposure limits", Federal Communications Commission (FCC), 2017.
- [2] FCC, OET Bulletin 65, "Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", 1997.
- [3] FCC KDB 447498 D01, "Mobile and Portable Devices RF exposure procedures and Equipment Authorization Policies", 2015.
- [4] FCC KDB 662911 D01, "Emissions Testing of Transmitters with Multiple Outputs in the Same Band", 2013.
- [5] FCC, Code of Federal Regulations CFR title 47, part 2.1091, " Radiofrequency radiation exposure evaluation: mobile devices", Federal Communications Commission (FCC), 2017.

7 Revision History

Rev.	Date	Description
A	2021-02-22	First revision

Appendix A. Information to be included in the CPI

Table A.1 lists the minimum separation distance for which the RF EMF exposure from Dot 4442 B25 B66A is below the limits specified by the FCC as applicable in:

- USA (47 CFR 1.1310)

Table A.1: Minimum separation distance for general public/uncontrolled exposure applicable in USA and markets employing the FCC RF exposure limits

Band	Standard	Nominal output power from the radio	Test position	Separation distance
B25 + B66A	LTE, NR	4 x 0.05 W	Direction of maximum gain	20 cm

Appendix B. Guidelines on how to install the product

The Ericsson Dot 4442 B25 B66A shall be installed to make sure that the general public does not have access to the applicable RF EMF compliance boundary. The compliance boundary dimensions were determined for the product transmitting in free space.

Appendix C. Photographs of the EUT



Figure D.1: Top view on the EUT front side.



Figure D.2: Top view on the EUT back side.