



Product Service

**Choose certainty.
Add value.**



Report On

FCC and IC Testing of the
Ericsson Remote Radio Unit LTE KRC 161 254/1 and KRC 161 254/2,
RRUS 11 B4 (2100 MHz), with compatible Main Unit in a Base Station
configuration in accordance with FCC CFR 47 Part 2, FCC CFR 47
Part 27, Industry Canada RSS-GEN and Industry Canada RSS-139

COMMERCIAL-IN-CONFIDENCE

FCC ID: TA8AKRC161254-1, TA8AKRC161254/2, TA8BKRC161254/2
IC ID: 278AB-AS1612541, 278AB-AS1612542, 278AB-BS1612542

PREPARED BY

Maggie Whiting
Key Account Manager

APPROVED BY

Steve Scarfe
Authorised Signatory

DATED

05 April 2018

Document 75941045 Report 10 Issue 2

April 2018



Product Service

CONTENTS

Section	Page No
1	REPORT INFORMATION 2
1.1	Report Details 3
1.2	Brief Summary of Results 4
1.3	Configuration Description 5
1.4	Declaration of Build Status 6
1.5	Product Information 7
1.6	Test Setup 8
1.7	Test Conditions 9
1.8	Deviation From The Standard 9
1.9	Modification Record 9
1.10	Additional Information 9
2	TEST DETAILS 10
2.1	Maximum Peak Output Power and Peak to Average Ratio - Conducted 11
2.2	Occupied Bandwidth 15
2.3	Band Edge 21
2.4	Transmitter Spurious Emissions 27
2.5	Radiated Spurious Emissions 42
3	TEST EQUIPMENT USED 62
3.1	Test Equipment Used 63
3.2	Measurement Uncertainty 65
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 66
4.1	Accreditation, Disclaimers and Copyright 67
ANNEX A	Module Lists A.2



Product Service

SECTION 1

REPORT INFORMATION



Product Service

1.1 REPORT DETAILS

Manufacturer	Ericsson
Address	Torshamnsgatan 23 Kista SE-16480 Stockholm Sweden
Product Name	RRUS 11 B4
Product Number	KRC 161 254/2
IC Model Name	AS1612542 BS1612542
Serial Number(s)	CF82590507
Software Version	xrus_NBIoT_GB_SA_for_FCC_test (based on CXP9013268/6 R66BM)
Hardware Version	R3A
Test Specification/Issue/Date	FCC CFR 47 Part 2: 2016 FCC CFR 47 Part 27: 2016 Industry Canada RSS-GEN: Issue 4: 2014 Industry Canada RSS-139: Issue 3: 2015
Non- Tested Variant	KRC 1612541
Non-Tested Variant IC Model Name	AS1612541
Start of Test	06 February 2018
Finish of Test	14 February 2018
Name of Engineer(s)	Raj Kumar Kallem Graeme Lawler
Related Document(s)	KDB 971168 D01 v02r02 KDB 662911 D01 v02r01

This report has been up issued to Issue 2 and should be read in place of Issue 1. This report has been up issued to Issue 2 to amend a typographical error from B14 to B4.



Product Service

1.2 BRIEF SUMMARY OF RESULTS

A brief summary of results for each configuration, in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 27 and Industry Canada RSS-139 is shown below.

Section	Specification Clause				Test Description	Result
	FCC CFR 47 Part 2	FCC CFR 47 Part 27	RSS-GEN	RSS-139		
2.1	2.1046	27.50	-	6.4	Maximum Peak Output Power and Peak to Average Ratio - Conducted	Pass
2.2	2.1049	27.53	6.6	-	Occupied Bandwidth	Pass
2.3	2.1051	27.53 (h)	-	6.5	Band Edge	Pass
2.4	2.1051	27.53 (h)	-	6.5	Transmitter Spurious Emissions	Pass
2.5	2.1053	27.53 (c)	-	6.5	Radiated Spurious Emissions	Pass



Product Service

1.3 CONFIGURATION DESCRIPTION

Configuration	RAT	No. Of carriers	Carrier Bandwidth	Carrier Frequency Configuration (MHz)		
				Bottom	Middle	Top
A	LTE+NB IoT GB	1	10 MHz	2115.0	-	2150.0
			15 MHz	2117.5	-	2147.5
			20 MHz	2120.0	-	2145.0
B	NB IoT SA	1	0.18 MHz	2110.2	2132.5	2154.8

1.4 DECLARATION OF BUILD STATUS

MAIN EUT		
MANUFACTURING DESCRIPTION	Radio Unit	
MANUFACTURER	Ericsson AB	
PRODUCT NAME	RRUS11 B4	
PART NUMBER	KRC 161 254/1	KRC 161 254/2
IC Model Name	AS1612541	AS1612542 BS1612542
SERIAL NUMBER	-	CF82590507
HARDWARE VERSION	-	R3A
SOFTWARE VERSION	-	xrus_NB-IoT_GB_SA_for_FCC_test (based on CXP9013268/6 R668M)
TRANSMITTER OPERATING RANGE	2110 to 2155 MHz	
MODULATIONS	LTE, WCDMA: QPSK, 16QAM, 64QAM, 256QAM ²	LTE, WCDMA: QPSK, 16QAM, 64QAM, 256QAM ² CDMA: QPSK, 8-PSK, 16QAM
INTERMEDIATE FREQUENCIES	-	
ITU DESIGNATION OF EMISSION	WCDMA: 3M90F9W, 4M20F9W	CDMA: 1M30F9W
	1,4 MHz BW channel: 1M10F9W	WCDMA: 3M90F9W, 4M20F9W
	3 MHz BW channel: 2M70F9W	1,4 MHz BW channel: 1M10F9W
	5 MHz BW channel: 4M50F9W	3 MHz BW channel: 2M70F9W
	10 MHz BW channel ¹ : 9M50F9W	5 MHz BW channel: 4M50F9W
	15 MHz BW channel ¹ : 14M0F9W	10 MHz BW channel ¹ : 9M50F9W
	20 MHz BW channel ¹ : 18M5F9W	15 MHz BW channel ¹ : 14M0F9W
	NB-IoT SA: 210KW7D	20 MHz BW channel ¹ : 18M5F9W
		NB-IoT SA channel: 210KW7D
OUTPUT POWER (RMS) (W or dBm)	1x30W ¹ (per port)	1x40W ¹ (per port)
	NB-IoT SA 1x20W	NB-IoT SA 1x20W
FCC ID	TA8AKRC161254-1	TA8AKRC161254-2 TA8BKRC161254-2
IC ID	287AB-AS1612541	287AB-AS1612542 287AB-BS1612542
TECHNICAL DESCRIPTION (a brief description of the intended use and operation)	Base station radio	

¹ Including 2 NB-IoT GB carriers.

² Used in LTE only.

Signature


Linda Grell

Date

2018-03-27


No responsibility will be accepted by TÜV SÜD Product Service UK Limited as to the accuracy of the information declared in this document by the manufacturer.

1.5 PRODUCT INFORMATION

1.5.1 Technical Description


The Equipment Under Test (EUT) KRC 161 254/1 and KRC 161 254/2 is an Ericsson AB Radio Unit working in the public mobile service 2100 MHz band which provides communication connections to 2100 MHz network. The KRC 161 254/1 and KRC 161 254/2 operates from a - 48V DC supply.

The Equipment Under Test (EUT) is shown in the photograph below. A full technical description can be found in the Manufacturer's documentation.



Equipment Under Test

1.6 TEST SETUP





Product Service

1.7 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure, test laboratories or a chamber as appropriate.

The EUT was powered from a -48V DC supply.

FCC Measurement Facility Registration Number
90987 Octagon House, Fareham Test Laboratory

1.8 DEVIATION FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

1.9 MODIFICATION RECORD

No modifications were made to the EUT during testing.

1.10 ADDITIONAL INFORMATION

The test results relate only to the item(s) tested RRUS 11 B4 KRC 161 254/2

The KRC 161 254/1 is a low power version of the KRC 161 254/2, it has the same Hardware but the output power is 30W and so can also be considered as compliant too.



Product Service

SECTION 2

TEST DETAILS



Product Service

2.1 MAXIMUM PEAK OUTPUT POWER AND PEAK TO AVERAGE RATIO - CONDUCTED

2.1.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1046
FCC CFR 47 Part 27, Clause 27.50
Industry Canada RSS-139, Clause 6.4

2.1.2 Date of Test and Modification State

12 February 2018 - Modification State 0

2.1.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.4 Environmental Conditions

Ambient Temperature 20.7°C
Relative Humidity 26%

2.1.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01, clause 5.2.1 and summed in accordance with FCC KDB 662911 D01.

2.1.6 Test Results

Configuration A

Maximum Output Power 45/46 dBm

Antenna	LTE Modulation	LTE Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power	
			Channel Position B	
			PAR (dB)	Average Power
A	64QAM	10.0 MHz	6.73	dBm
Total			-	45.47
A	64QAM	15.0 MHz	6.67	45.57
Total			-	45.57
A	64QAM	20.0 MHz	6.70	45.62
Total			-	45.62



Product Service

Configuration A

Maximum Output Power 45/46 dBm


Antenna	LTE Modulation	LTE Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power	
			Channel Position T	
			PAR (dB)	Average Power dBm
A	QPSK	10.0 MHz	6.71	45.70
Total			-	45.70
A	64QAM	15.0 MHz	6.67	45.81
Total			-	45.81
A	QPSK	20.0 MHz	6.71	45.81
Total			-	45.81

Configuration B

Maximum Output Power 43 dBm

Antenna	NB IoT Modulation	NB IoT Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power	
			Channel Position B	
			PAR (dB)	Average Power dBm
A	QPSK	0.2 MHz	4.07	42.27
Total			-	42.27

Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position B






Product Service

Configuration B

Maximum Output Power 43 dBm

Antenna	NB IoT Modulation	NB IoT Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power	
			Channel Position M	
			PAR (dB)	Average Power
A	QPSK	0.2 MHz	4.07	42.23
Total			-	42.23

Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position M



Configuration B


Maximum Output Power 43 dBm

Antenna	NB IoT Modulation	NB IoT Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power	
			Channel Position T	
			PAR (dB)	Average Power
A	QPSK	0.2 MHz	4.11	42.25
Total			-	42.25



Product Service

Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position T



Limit	
Peak Power	≤ 500 W or $\leq +57$ dBm
Peak to Average Ratio	13 dB



Product Service

2.2 OCCUPIED BANDWIDTH

2.2.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1049
FCC CFR 47 Part 27, Clause 27.53
Industry Canada RSS-GEN, Clause 6.6

2.2.2 Date of Test and Modification State

12 February 2018 - Modification State 0

2.2.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.4 Environmental Conditions

Ambient Temperature 20.7°C
Relative Humidity 26%

2.2.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01.

2.2.6 Test Results

Configuration A


Maximum Output Power 45/46 dBm

Antenna	LTE Modulation	LTE Carrier Bandwidth	Result (KHz)					
			Channel Position B		Channel Position M		Channel Position T	
			Occupied Bandwidth	-26 dB Bandwidth	Occupied Bandwidth	-26 dB Bandwidth	Occupied Bandwidth	-26 dB Bandwidth
A	64QAM	10.0 MHz	9,428.11	9,767.42	-	-	9,423.51	9,800.03
A	64QAM	15.0 MHz	14,043.00	14,730.00	-	-	14,044.00	14,660.00
A	64QAM	20.0 MHz	18,455.98	19,466.37	-	-	18,489.44	19,560.46




Product Service


Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position B




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position T




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position B




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position T



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position B



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position T






Product Service

Configuration B


Maximum Output Power 43 dBm

Antenna	NB IoT Modulation	NB IoT Carrier Bandwidth	Result (KHz)					
			Channel Position B		Channel Position M		Channel Position T	
			Occupied Bandwidth	-26 dB Bandwidth	Occupied Bandwidth	-26 dB Bandwidth	Occupied Bandwidth	-26 dB Bandwidth
A	QPSK	0.2 MHz	209.59	318.30	209.44	318.30	209.44	318.30


Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position B



Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position M



Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position T





Product Service

2.3 BAND EDGE

2.3.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
FCC CFR 47 Part 27, Clause 27.53 (h)
Industry Canada RSS-139, Clause 6.5

2.3.2 Date of Test and Modification State

12 and 14 February 2018 - Modification State 0

2.3.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.3.4 Environmental Conditions

Ambient Temperature 20.7 - 21.2°C
Relative Humidity 26 - 27.6%

2.3.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01.

Each antenna port has been declared as being equivalent, therefore measurements were made on one antenna port only. To account for this, the limit was tightened by $10 * \log(N)$, where N is equal to the number of MIMO antenna ports.

For four ports, the limit was calculated as being $-13 \text{ dBm} - 10 * \log(4) = -19 \text{ dBm}$.

For dual dual port, the limit was calculated as being $-13 \text{ dBm} - 10 * \log(2) = -16 \text{ dBm}$.


2.3.6 Test Results

Configuration A


Maximum Output Power 45/46 dBm

Antenna	LTE Modulation	LTE Carrier Bandwidth	Band Edge (MHz)	
			Channel Position B	Channel Position T
A	64QAM	10.0 MHz	2,115.0	2,150.0
A	64QAM	15.0 MHz	2,117.5	2,147.5
A	64QAM	20.0 MHz	2,120.0	2,145.0


Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position B




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position T



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position B




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position T



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position B



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position T






Product Service

Configuration B

Maximum Output Power 43 dBm

Antenna	NB IoT Modulation	NB IoT Carrier Bandwidth	Band Edge (MHz)	
			Channel Position B	Channel Position T
A	QPSK	0.2 MHz	2,110.2	2,154.8


Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position B





Product Service

Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position T



Limit MIMO

-19 dBm



Product Service

2.4 TRANSMITTER SPURIOUS EMISSIONS

2.4.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
FCC CFR 47 Part 27, Clause 27.53 (h)
Industry Canada RSS-139, Clause 6.5

2.4.2 Date of Test and Modification State

12 February 2018 - Modification State 0

2.4.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.4 Environmental Conditions

Ambient Temperature	20.7°C
Relative Humidity	26%

2.4.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01.

Each antenna port has been declared as being equivalent, therefore measurements were made on one antenna port only. To account for this, the limit was tightened by $10 * \log(N)$, where N is equal to the number of MIMO antenna ports.

For four ports carrier, the limit was calculated as being $-13 \text{ dBm} - 10 * \log(4) = -19 \text{ dBm}$.


For dual ports, the limit was calculated as being $-13 \text{ dBm} - 10 * \log(2) = -16 \text{ dBm}$.

2.4.6 Test Results


Configuration A

Maximum Output Power 45/46 dBm


Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position B - Band 1 - Range 0.9000 to 1000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position T - Band 1 - Range 0.9000 to 1000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position B - Band 1 - Range 0.9000 to 1000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position T - Band 1 - Range 0.9000 to 1000 MHz



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position B - Band 1 - Range 0.9000 to 1000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position T - Band 1 - Range 0.9000 to 1000 MHz






Product Service

Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position B - Band 1 - Range 3000 to 10000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position T - Band 1 - Range 3000 to 10000 MHz






Product Service

Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position B - Band 2 - Range 3000 to 10000 MHz



Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position T - Band 2 - Range 3000 to 10000 MHz






Product Service

Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position B - Band 1 - Range 3000 to 10000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position T - Band 1 - Range 3000 to 10000 MHz






Product Service

Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position B - Band 1 - Range 10000 to 22000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 10.0 MHz - Channel Position T - Band 1 - Range 10000 to 22000 MHz






Product Service

Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position B - Band 3 - Range 10000 to 22000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 15.0 MHz - Channel Position T - Band 3 - Range 10000 to 22000 MHz






Product Service

Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position B - Band 1 - Range 10000 to 22000 MHz




Antenna A - LTE Modulation 64QAM - LTE Carrier Bandwidth 20.0 MHz - Channel Position T - Band 1 - Range 10000 to 22000 MHz



Configuration B

Maximum Output Power 43 dBm


Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position
B - Band 1 - Range 0.9000 to 1000 MHz




Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position
B - Band 1 - Range 3000 to 10000 MHz




Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position B - Band 1 - Range 10000 to 22000 MHz




Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position M - Band 1 - Range 0.9000 to 1000 MHz



Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position M - Band 1 - Range 3000 to 10000 MHz




Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position M - Band 1 - Range 10000 to 22000 MHz






Product Service

Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position T
- Band 1 - Range 0.9000 to 1000 MHz




Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position T
- Band 1 - Range 3000 to 10000 MHz





Product Service

Antenna A - NB IoT Modulation QPSK - NB IoT Carrier Bandwidth 0.2 MHz - Channel Position T
- Band 1 - Range 10000 to 22000 MHz



Limit	-19dBm
-------	--------



Product Service

2.5 RADIATED SPURIOUS EMISSIONS

2.5.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1053
FCC CFR 47 Part 27, Clause 27.53(m)
Industry Canada RSS-139, Clause 6.5

2.5.2 Date of Test and Modification State

04 February 2018 - Modification State 0

2.5.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.4 Environmental Conditions

Ambient Temperature	18.9°C
Relative Humidity	33.0 %

2.5.5 Test Method

The test was applied in accordance with test method requirements of ANSI/TIA-603-C-2004.

A preliminary profile of the Spurious Radiated Emissions was obtained by operating the EUT on a remotely controlled turntable within the chamber. Measurements of emissions from the EUT were obtained with the Measurement Antenna in both Horizontal and Vertical Polarisations.

The Applicant declared that the highest internally generated frequency would be up to 2500MHz and so the upper limit for measurement was calculated at 10 times this, which is 25GHz.

Emissions identified within the range 30MHz – 25GHz were then formally measured using a Peak detector as the worst case.

In the frequency Range 30MHz – 1GHz, the measurement was performed with a resolution bandwidth of 100kHz.

In the frequency Range 1GHz – 25GHz, the measurement was performed with a resolution bandwidth of 1MHz.

The measurements were performed at a 3m distance unless otherwise stated.

The limits for Spurious Emissions have been calculated, as shown below using the following formula:

Field Strength of Carrier - $(43 + 10\log(P))$ dB

Where:

Field Strength is measured in dBμV/m

P is measured Transmitter Power in Watts



Product Service

Determination of Spurious Emission Limit

As the EUT does not have an integral antenna, the field strength of the carrier has been calculated assuming that the power is to be fed to a half-wave tuned dipole as per 2.1053 (a).

$$E_{(v/m)} = (30 \times G_i \times P_o)^{0.5} / d$$

Where G_i is the antenna gain of an ideal half-wave dipole,
 P_o is the power out of the transceiver in W,
 d is the measurement distance in meter.

Therefore at 3m measurement distance the field strength using the lowest transceiver output power would be:

$$E_{(v/m)} = (30 \times 1.64 \times 46)^{0.5} / 3 = 27.47V/m = 148.78dB\mu V/m$$

As per 27.53 (c)(1)) the spurious emission must be attenuated by $43 + 10\log(P_o)$ dB this gives:

$$43 + 10\log(46) = 59.63dB$$

Therefore the limit at 3m measurement distance is:

$$148.78 - 59.63 = 89.15 \text{ dB}\mu V/m$$

This limit has been used to determine Pass or Fail for the harmonics measured and detailed in the following results.

2.5.6 Test Results


Configuration A

Maximum Output Power 46 dBm per port, LTE Bandwidth 10.0MHz




Product Service

Channel Position B –Bandwidth 10.0MHz – 30MHz – 1GHz



Date: 4.FEB.2018 21:32:17

Channel Position T –Bandwidth 10.0MHz – 30MHz – 1GHz




Date: 4.FEB.2018 21:29:15




Product Service

Channel Position B –Bandwidth 10.0MHz – 1GHz – 8GHz



Date: 4.FEB.2018 17:16:02

Channel Position T–Bandwidth 10.0MHz – 1GHz – 8GHz




Date: 4.FEB.2018 17:22:03




Product Service

Channel Position B –Bandwidth 10.0MHz – 8GHz – 18GHz



Date: 4.FEB.2018 19:21:16

Channel Position T –Bandwidth 10.0MHz – 8GHz – 18GHz




Date: 4.FEB.2018 19:17:58




Product Service

Channel Position B –Bandwidth 10.0MHz – 18GHz – 25GHz



Date: 4.FEB.2018 19:53:44

Channel Position T –Bandwidth 10.0MHz – 18GHz – 25GHz




Date: 4.FEB.2018 19:57:54



Product Service


Maximum Output Power 46 dBm per port, LTE Bandwidth 15.0MHz

Channel Position B –Bandwidth 15.0MHz – 30MHz – 1GHz



Date: 4.FEB.2018 21:24:41

Channel Position T –Bandwidth 15.0MHz – 30MHz – 1GHz




Date: 4.FEB.2018 21:21:05




Product Service

Channel Position B –Bandwidth 15.0MHz – 1GHz – 8GHz



Date: 4.FEB.2018 17:03:00

Channel Position T–Bandwidth 15.0MHz – 1GHz – 8GHz




Date: 4.FEB.2018 17:09:45




Product Service

Channel Position B –Bandwidth 15.0MHz – 8GHz – 18GHz



Date: 4.FEB.2018 19:13:17

Channel Position T –Bandwidth 15.0MHz – 8GHz – 18GHz




Date: 4.FEB.2018 19:05:39




Product Service

Channel Position B –Bandwidth 15.0MHz – 18GHz – 25GHz



Date: 4.FEB.2018 20:04:15

Channel Position T –Bandwidth 15.0MHz – 18GHz – 25GHz




Date: 4.FEB.2018 20:11:28



Product Service


Maximum Output Power 46 dBm per port, LTE Bandwidth 20.0MHz

Channel Position B –Bandwidth 20.0MHz – 30MHz – 1GHz



Date: 4.FEB.2018 21:15:22

Channel Position T –Bandwidth 20.0MHz – 30MHz – 1GHz




Date: 4.FEB.2018 21:08:43




Product Service

Channel Position B –Bandwidth 20.0MHz – 1GHz – 8GHz



Date: 4.FEB.2018 17:30:28

Channel Position T–Bandwidth 20.0MHz – 1GHz – 8GHz




Date: 4.FEB.2018 17:36:29




Product Service

Channel Position B –Bandwidth 20.0MHz – 8GHz – 18GHz



Date: 4.FEB.2018 18:57:29

Channel Position T –Bandwidth 20.0MHz – 8GHz – 18GHz




Date: 4.FEB.2018 18:44:24




Product Service

Channel Position B –Bandwidth 20.0MHz – 18GHz – 25GHz



Date: 4.FEB.2018 20:18:21

Channel Position T –Bandwidth 20.0MHz – 18GHz – 25GHz




Date: 4.FEB.2018 20:25:24



Product Service


Maximum Output Power 46 dBm per port, NB IoT Bandwidth 0.18MHz

Channel Position B –Bandwidth 0.18MHz – 30MHz – 1GHz



Date: 4.FEB.2018 21:06:13

Channel Position M –Bandwidth 0.18MHz – 30MHz – 1GHz




Date: 4.FEB.2018 21:03:18




Product Service

Channel Position T –Bandwidth 0.18MHz – 30MHz – 1GHz



Date: 4.FEB.2018 20:58:21

Channel Position B –Bandwidth 0.18MHz – 1GHz – 8GHz




Date: 4.FEB.2018 17:45:14




Product Service

Channel Position M –Bandwidth 0.18MHz – 1GHz – 8GHz



Date: 4.FEB.2018 17:50:06

Channel Position T–Bandwidth 0.18MHz – 1GHz – 8GHz




Date: 4.FEB.2018 17:54:37




Product Service

Channel Position B –Bandwidth 0.18MHz – 8GHz – 18GHz



Date: 4.FEB.2018 18:31:45

Channel Position M –Bandwidth 0.18MHz – 8GHz – 18GHz




Date: 4.FEB.2018 18:22:22




Product Service

Channel Position T –Bandwidth 0.18MHz – 8GHz – 18GHz



Date: 4.FEB.2018 18:13:02

Channel Position B –Bandwidth 0.18MHz – 18GHz – 25GHz




Date: 4.FEB.2018 20:39:49




Product Service

Channel Position M –Bandwidth 0.18MHz – 18GHz – 25GHz



Date: 4.FEB.2018 20:36:05

Channel Position T –Bandwidth 0.18MHz – 18GHz – 25GHz



Date: 4.FEB.2018 20:44:14



Product Service

SECTION 3

TEST EQUIPMENT USED



Product Service

3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Maximum Peak Output Power and Peak to Average Ratio - Conducted					
Spectrum Analyser	Keysight	PXA	MY54410231	12	30-Nov-2018
Network Analyser	Rohde&Schwarz	ZVA40	TE3548	12	02-Oct-2018
Calibration unit	Rohde&Schwarz	ZV-Z54	TE4368	12	19-Sep-2018
RF Load	weinschel	WA49-40-33	A1563	N/A	O/P Mon
Attenuator	Ericsson china	TSG150R	1504020007	N/A	O/P Mon
Power Supply	Agilent	N8738A	BAMS1001518021	N/A	O/P Mon
Hygromer	RS	TE3220	0427452	12	30-Aug-2018
Digital Volt Meter	White gold	79 III	TE00190	12	24-Nov-2018
Band Edge					
Spectrum Analyser	Keysight	PXA	MY54410231	12	30-Nov-2018
Network Analyser	Rohde&Schwarz	ZVA40	TE3548	12	02-Oct-2018
Calibration unit	Rohde&Schwarz	ZV-Z54	TE4368	12	19-Sep-2018
RF Load	weinschel	WA49-40-33	A1563	N/A	O/P Mon
Attenuator	Ericsson china	TSG150R	1504020007	N/A	O/P Mon
Power Supply	Agilent	N8738A	BAMS1001518021	N/A	O/P Mon
Hygromer	RS	TE3220	0427452	12	30-Aug-2018
Digital Volt Meter	White gold	79 III	TE00190	12	24-Nov-2018
Transmitter Spurious Emissions					
Spectrum Analyser	Keysight	PXA	MY49430624	12	30-Jun-2018
Spectrum Analyser	Keysight	PXA	MY49430624	12	30-Jun-2018
Spectrum Analyser	Keysight	PXA	MY54410231	12	30-Nov-2018
Network Analyser	Rohde&Schwarz	ZVA40	TE3548	12	02-Oct-2018
Calibration unit	Rohde&Schwarz	ZV-Z54	TE4368	12	19-Sep-2018
Attenuator	Narda	769-20	TE3367	12	31-May-2018
High Pass filter	K&L	11SH10-3000/X18000-0/0	4412	N/A	O/P Mon
Attenuator	Ericsson china	SHX	DTS100G-40dB-18G	N/A	O/P Mon
Attenuator	Narda	769-30	TE3369	12	31-May-2018
RF Load	weinschel	WA49-40-33	A1563	N/A	O/P Mon
Attenuator	Ericsson china	TSG150R	1504020007	N/A	O/P Mon
Power Supply	Agilent	N8738A	BAMS1001518021	N/A	O/P Mon
Hygromer	RS	TE3220	0427452	12	30-Aug-2018
Digital Volt Meter	White gold	79 III	TE00190	12	24-Nov-2018
Spurious Radiated Emissions					
Antenna (Bilog)	Schaffner	CBL6143	287	24	18-Apr-2018
Filter (High Pass)	Lorch	SHP7-7000-SR	566	12	05-Apr-2018
Signal Generator (10MHz to 40GHz)	Rohde & Schwarz	SMR40	1002	12	20-Oct-2018
Power Supply Unit	Farnell	H 60/50	1095	-	TU
Antenna 18-40GHz (Double Ridge Guide)	Q-Par Angus Ltd	QSH 180K	1511	24	07-Dec-2018
Pre-Amplifier	Phase One	PS04-0086	1533	12	12-Jan-2019



Product Service

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
18GHz - 40GHz Pre-Amplifier	Phase One	PSO4-0087	1534	12	27-Feb-2018
Screened Room (5)	Rainford	Rainford	1545	36	08-Jul-2019
Turntable Controller	Inn-Co GmbH	CO 1000	1606	-	TU
Multimeter	Iso-tech	IDM 101	2118	12	07-Feb-2018
Digital Multimeter	Iso-tech	IDM-101	2895	12	20-Jul-2018
Comb Generator	Schaffner	RSG1000	3034	-	TU
Cable (N-N, 8m)	Rhophase	NPS-2302-8000-NPS	3248	12	02-May-2018
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	22-Nov-2018
Tilt Antenna Mast	maturo GmbH	TAM 4.0-P	3916	-	TU
Mast Controller	maturo GmbH	NCD	3917	-	TU
1 Metre SMA Cable	Rhophase	3PS-1801A-1000-3PS	4099	12	19-Sep-2018
Cable 1503 2M 2.92(P)m 2.92(P)m	Rhophase	KPS-1503A-2000-KPS	4293	12	27-Feb-2018
Digital thermo Hygrometer	Radio Spares	1260	4300	12	30-Aug-2018
Cable (Rx, Km-Km 2m)	Scott Cables	KPS-1501-2000-KPS	4526	6	22-May-2018
Cable (Rx, SMAm-SMAm 0.5m)	Scott Cables	SLSLL18-SMSM-00.50M	4528	-	O/P Mon
Double Ridged Waveguide Horn Antenna	ETS-Lindgren	3117	4722	12	17-Feb-2018
Double Ridge Broadband Horn Antenna	Schwarzbeck	BBHA 9120 B	4848	12	17-Feb-2018

TU – Traceability Unscheduled

N/A – Not Applicable

O/P Mon – Output Monitored with Calibrated Equipment



Product Service

3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	Frequency / Parameter	MU
Conducted Maximum Peak Output Power	30 MHz to 20 GHz Amplitude	± 0.1 dB
Conducted Emissions	30 MHz to 20 GHz Amplitude	± 2.3 dB
Frequency Stability	30 MHz to 2 GHz	± 5.0 Hz
Occupied Bandwidth	Up to 20 MHz Bandwidth	± 1.1 Hz
Band Edge	30 MHz to 20 GHz Amplitude	± 2.3 dB
Radiated Emissions, Bilog Antenna, AOATS	30MHz to 1GHz Amplitude	5.1dB*
Radiated Emissions, Horn Antenna, AOATS	1GHz to 40GHz Amplitude	6.3dB*
Worst case error for both Time and Frequency measurement 12 parts in 10^6		



Product Service

SECTION 5

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA
(Not UKAS Accredited).

© 2018 TÜV SÜD Product Service



Product Service

ANNEX A

MODULE LIST



Product Service

Configuration A			
Product	Product No	R-State	Serial No
CT10	LPC 102 487/1	R1C	T01F307249
RRUS 11 B4	KRC 161 254/2	R3A	CF82590507
Software Version:		xrus_NBIoT_GB_SA_for_FCC_test (based on CXP9013268/6 R66BM)	