



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Sensys Networks, Inc.

Model: APCC-SPP

Description: Traffic Sensor System

Serial Number: 20151

FCC ID: TDB-FLEXSPP

To

FCC Part 1.1310

Date of Issue: June 13, 2017

On the behalf of the applicant:

**Sensys Networks, Inc.
2560 Ninth St.
Berkeley, CA 94710**

Attention of:

**Sebastian Lodahl, Compliance Manager
Ph: (510)847-6189
Email: slodahl@sensysnetworks.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1750012**

**Alex Macon
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	June 1, 2017	Alex Macon	Original Document
2.0	June 12, 2017	Alex Macon	Updated 1.1310 report to show EIRP instead of conducted. This was a template error.



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: APCC-SPP

Description: Traffic Sensor

Firmware: N/A

Software: N/A

S/N: 20151

Additional Information: None



Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Radiated Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
2480	4.25	100	4.25 mW



MPE Evaluation

This is a fixed device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	2480
Power, EIRP, mW (P)	4.25
Antenna Type	patch
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) =0.0008
Limit =(from above table) = 1.0

END OF TEST REPORT