



FCC PART 15.247

TEST REPORT

For

TP-Link Technologies Co., Ltd.

Building 24 (floors 1,3,4,5) and 28 (floors1-4),Central Science and Technology
Park,Nanshan,Shenzhen,China

FCC ID: TE7C7SV1

Report Type: Original Report	Product Type: C7s FDD-LTE Smartphone
Report Number: RSZ190327003-00C	
Report Date: 2019-05-06	
Reviewed By: RF Engineer	Candy Li <i>Candy . Li</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS.....	11
TEST EQUIPMENT LIST	12
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	14
APPLICABLE STANDARD	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	16
CORRECTED FACTOR & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST RESULTS SUMMARY	22
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	40
APPLICABLE STANDARD	40

TEST PROCEDURE40

TEST DATA40

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....42

APPLICABLE STANDARD42

TEST PROCEDURE42

TEST DATA42

FCC §15.247(e) - POWER SPECTRAL DENSITY47

APPLICABLE STANDARD47

TEST PROCEDURE47

TEST DATA47

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	C7s FDD-LTE Smartphone
Tested Model	TP7051C
Multiple Model [#]	TP7051CXYZZ
Frequency Range	Bluetooth LE: 2402~2480MHz Wi-Fi: 2412~2462MHz
Transmit Power	Bluetooth LE: 5.96dBm Wi-Fi: 802.11b: 18.89dBm 802.11g: 22.48dBm 802.11n-HT20: 22.01dBm
Modulation Technique	Bluetooth LE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification	Internal Antenna Bluetooth/ Wi-Fi: -0.1dBi
Voltage Range	DC 3.8V from battery or DC 5.0V from adapter
Date of Test	2019-04-02~2019-04-30
Sample serial number	DE7051C930100001
Received date	2019-03-27
Sample/EUT Status	Good condition
Adapter information	Model: A8-501000 Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5V, 1A

Notes: This series products model: TP7051C and TP7051CXYZZ are electrically identical, the differences between them are the model number. Model TP7051C was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

Objective

This report is prepared on behalf of *TP-Link Technologies Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS and Part 22H/24E/27 PCE submissions with FCC ID: TE7C7SV1.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2437
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2437
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2462
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

BLE & Wi-Fi test in the engineer mode.


The device was tested with the worst case was performed as below:

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	15	16	16
802.11g	6 Mbps	13	13	13
802.11n-HT20	MCS0	12	13	13
BLE	/	Default	Default	Default

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.


Duty cycle

802.11b mode




Date: 30.APR.2019 11:27:10

802.11g mode




Date: 30.APR.2019 11:28:57

802.11n-HT20 Mode



Date: 30.APR.2019 11:29:27

BLE Mode



Date: 5.APR.2019 17:25:30

Mode	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	100	-	-	10Hz	-
802.11g	100	-	-	10Hz	-
802.11n-HT20	100	-	-	10Hz	-
BLE	19.2	120	8.33	9kHz	7.17

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
unknown	Earphone	unknow	unknow

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding detachable USB Cable	0.8	EUT	Adapter

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2018-12-21	2019-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-11-12	2019-05-12
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Un-known	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-05-12
Radiated Emission Test					
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma instrument	Amplifier	310 N	186238	2018-11-12	2019-05-12
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2018-07-11	2019-07-11
Ducommun technologies	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-07-11	2021-07-10
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2018-11-19	2019-05-21
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Heatsink Required	Amplifier	QLW-18405536-J0	15964001002	2018-11-12	2019-11-12
Sinoscite	Band Reject Filter	BSF2402-2480MN-0898-001	99632	2018-11-12	2019-11-12
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	USB windebond power meter	U2021XA	MY54250003	2018-06-23	2019-06-23
WEINSCHL	10dB Attenuator	5324	AU 3842	Each Time	
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2017-12-24	2018-12-24
WEINSCHL	3dB Attenuator	6231	666	Each Time	
Ducommun technologies	RF Cable	RG-214	3	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case about BLE:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	6.0	3.98	5	1.3	3.0	Yes

Result: No SAR test is required

For Wi-Fi:

Please refer to the report number: RSZ190327003-SA.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is -0.1 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-04-02.

EUT operation mode: Transmitting

Worst case at 802.11g mode, Middle channel**AC 120V/60 Hz, Line**

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.161500	48.8	19.9	65.4	16.6	QP
0.173500	49.9	19.9	64.8	14.9	QP
0.181500	49.1	19.9	64.4	15.3	QP
0.205500	42.9	19.8	63.4	20.5	QP
0.233500	40.0	19.8	62.3	22.3	QP
0.278501	38.4	19.8	60.9	22.5	QP
0.161500	32.2	19.9	55.4	23.2	Ave.
0.173500	33.3	19.9	54.8	21.5	Ave.
0.181500	33.1	19.9	54.4	21.3	Ave.
0.205500	31.8	19.8	53.4	21.6	Ave.
0.233500	31.0	19.8	52.3	21.3	Ave.
0.278501	30.7	19.8	50.9	20.2	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.306530	43.5	19.7	60.1	16.6	QP
0.322770	43.2	19.8	59.6	16.4	QP
0.364450	39.9	19.9	58.6	18.7	QP
0.428330	37.6	19.8	57.3	19.7	QP
0.505470	37.2	19.8	56.0	18.8	QP
1.266890	35.6	19.8	56.0	20.4	QP
0.306530	37.7	19.7	50.1	12.4	Ave.
0.322770	37.3	19.8	49.6	12.3	Ave.
0.364450	33.3	19.9	48.6	15.3	Ave.
0.428330	30.1	19.8	47.3	17.2	Ave.
0.505470	29.3	19.8	46.0	16.7	Ave.
1.266890	27.2	19.8	46.0	18.8	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	52~56 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Curry and Yooube on 2019-04-03 and 2019-04-29.

EUT operation mode: Transmitting

30 MHz~1 GHz: Worst case at 802.11g mode, Middle channel

Frequency (MHz)	Corrected Amplitude (dB μ V/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
30.384438	14.83	113.0	V	232.0	-7.9	40.00	25.17
37.047875	13.93	195.0	V	327.0	-11.9	40.00	26.07
586.082250	20.04	179.0	H	234.0	-2.6	46.00	25.96
684.675500	21.13	312.0	V	35.0	-1.9	46.00	24.87
838.492500	29.61	261.0	V	156.0	5.8	46.00	16.39
941.801750	29.83	386.0	H	192.0	9.0	46.00	16.17

1 GHz-25 GHz (Wi-Fi):**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2333.56	28.33	PK	237	1.9	H	31.64	59.97	74	14.03
2333.56	14.16	Ave.	237	1.9	H	31.64	45.80	54	8.20
2496.94	27.35	PK	163	1.6	H	32.13	59.48	74	14.52
2496.94	13.45	Ave.	163	1.6	H	32.13	45.58	54	8.42
4824.00	44.33	PK	30	1.2	H	6.28	50.61	74	23.39
4824.00	31.27	Ave.	30	1.2	H	6.28	37.55	54	16.45
Middle Channel (2437MHz)									
4874.00	42.84	PK	225	1.6	H	6.76	49.60	74	24.40
4874.00	30.45	Ave.	225	1.6	H	6.76	37.21	54	16.79
High Channel (2462 MHz)									
2344.94	28.38	PK	258	1.3	H	31.64	60.02	74	13.98
2344.94	14.02	Ave.	258	1.3	H	31.64	45.66	54	8.34
2489.41	27.07	PK	113	2.0	H	32.13	59.20	74	14.80
2489.41	13.67	Ave.	113	2.0	H	32.13	45.80	54	8.20
4924.00	44.68	PK	208	1.4	H	6.76	51.44	74	22.56
4924.00	30.99	Ave.	208	1.4	H	6.76	37.75	54	16.25

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2390.00	29.87	PK	204	2.1	H	31.87	61.74	74	12.26
2390.00	14.48	Ave.	204	2.1	H	31.87	46.35	54	7.65
2486.97	27.44	PK	212	1.6	H	32.13	59.57	74	14.43
2486.97	13.46	Ave.	212	1.6	H	32.13	45.59	54	8.41
4824.00	43.23	PK	34	2.3	H	6.28	49.51	74	24.49
4824.00	29.23	Ave.	34	2.3	H	6.28	35.51	54	18.49
Middle Channel (2437MHz)									
4874.00	42.31	PK	311	1.3	H	6.76	49.07	74	24.93
4874.00	28.34	Ave.	311	1.3	H	6.76	35.10	54	18.90
High Channel (2462 MHz)									
2336.77	28.20	PK	332	2.5	H	31.64	59.84	74	14.16
2336.77	14.03	Ave.	332	2.5	H	31.64	45.67	54	8.33
2484.17	31.33	PK	259	2.3	H	32.13	63.46	74	10.54
2484.17	14.54	Ave.	259	2.3	H	32.13	46.67	54	7.33
4924.00	43.48	PK	279	2.1	H	6.76	50.24	74	23.76
4924.00	29.09	Ave.	279	2.1	H	6.76	35.85	54	18.15

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.98	31.99	PK	201	2.0	H	31.87	63.86	74	10.14
2389.98	14.64	Ave.	201	2.0	H	31.87	46.51	54	7.49
2497.74	26.90	PK	177	1.7	H	32.13	59.03	74	14.97
2497.74	13.45	Ave.	177	1.7	H	32.13	45.58	54	8.42
4824.00	43.60	PK	52	1.3	H	6.28	49.88	74	24.12
4824.00	29.34	Ave.	52	1.3	H	6.28	35.62	54	18.38
Middle Channel (2437MHz)									
4874.00	43.07	PK	277	1.1	H	6.76	49.83	74	24.17
4874.00	28.88	Ave.	277	1.1	H	6.76	35.64	54	18.36
High Channel (2462 MHz)									
2355.37	27.86	PK	146	2.2	H	31.77	59.63	74	14.37
2355.37	14.02	Ave.	146	2.2	H	31.77	45.79	54	8.21
2484.95	33.46	PK	242	1.4	H	32.13	65.59	74	8.41
2484.95	15.54	Ave.	242	1.4	H	32.13	47.67	54	6.33
4924.00	43.38	PK	208	1.9	H	6.76	50.14	74	23.86
4924.00	29.26	Ave.	208	1.9	H	6.76	36.02	54	17.98

1 GHz-25 GHz (BLE):

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2331.36	29.45	PK	163	1.4	V	32.97	62.42	74	11.58
2331.36	17.85	Ave.	163	1.4	V	32.97	50.82	54	3.18
2488.16	29.12	PK	319	1.5	V	33.20	62.32	74	11.68
2488.16	17.56	Ave.	319	1.5	V	33.20	50.76	54	3.24
4804.00	42.55	PK	178	2.3	V	7.88	50.43	74	23.57
4804.00	30.25	Ave.	178	2.3	V	7.88	38.13	54	15.87
Middle Channel (2440 MHz)									
4880.00	41.82	PK	224	2.1	V	9.21	51.03	74	22.97
4880.00	30.54	Ave.	224	2.1	V	9.21	39.75	54	14.25
High Channel (2480 MHz)									
2371.53	28.57	PK	51	2.5	V	33.00	61.57	74	12.43
2371.53	17.88	Ave.	51	2.5	V	33.00	50.88	54	3.12
2489.35	28.66	PK	181	1.8	V	33.20	61.86	74	12.14
2489.35	17.67	Ave.	181	1.8	V	33.20	50.87	54	3.13
4960.00	43.61	PK	244	1.4	V	9.07	52.68	74	21.32
4960.00	31.73	Ave.	244	1.4	V	9.07	40.80	54	13.20

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor



Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude



The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.



**Pre-scan with 802.11g Mode, High channel
Horizontal - Peak**





Vertical - Peak



Pre-scan for Average Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Data****Environmental Conditions**

Temperature:	24~25 °C
Relative Humidity:	52~55 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Kieroy Luo from 2019-04-05 to 2019-04-30.

Test Result: Pass.


Please refer to the following table and plots.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	9.462	≥ 500
Middle	2437	9.173	≥ 500
High	2462	9.548	≥ 500
802.11g			
Low	2412	16.221	≥ 500
Middle	2437	16.413	≥ 500
High	2462	16.462	≥ 500
802.11n-HT20 mode			
Low	2412	17.375	≥ 500
Middle	2437	17.663	≥ 500
High	2462	17.663	≥ 500


Channel	Frequency (MHz)	6 dB Emission Bandwidth(MHz)	Limit (kHz)
BLE mode			
Low	2402	0.516	≥ 500
Middle	2440	0.513	≥ 500
High	2480	0.510	≥ 500

802.11b Low Channel




Date: 30.APR.2019 10:24:38

802.11b Middle Channel




Date: 30.APR.2019 10:28:17

802.11b High Channel




Date: 30.APR.2019 10:30:09

802.11g Low Channel




Date: 30.APR.2019 10:38:49

802.11g Middle Channel




Date: 30.APR.2019 10:34:31

802.11g High Channel




Date: 30.APR.2019 10:32:12

802.11n-HT20 Low Channel




Date: 30.APR.2019 10:54:35

802.11n-HT20 Middle Channel




Date: 30.APR.2019 10:56:31

802.11n-HT20 High Channel



Date: 30.APR.2019 10:58:23

BLE Low Channel



Date: 5.APR.2019 17:19:41

Ref 15 dBm

* Att 20 dB

* RBW 100 kHz

* VBW 300 kHz

SWT 2.5 ms

Delta 1 [T1]

0.13 dB

512.820512820 kHz

Offset 3.5 dB

Marker 1 [T1]

0.95 dBm

D1 5.7 dBm

D2 -9.3 dBm

1

1

2.439673077 GHz

1 PK


MAXH

Center 2.44 GHz

200 kHz/

Span 2 MHz

BLE High Channel




FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	50~53 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Kieroy Luo from 2019-04-02 to 2019-04-28.

EUT operation mode: Transmitting

Wi-Fi mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	18.59	15.93	30
Middle	2437	18.89	16.32	30
High	2462	18.64	15.93	30
802.11g				
Low	2412	22.48	16.41	30
Middle	2437	22.10	16.01	30
High	2462	22.07	16.16	30
802.11n HT20				
Low	2412	22.01	15.93	30
Middle	2437	21.57	15.72	30
High	2462	21.57	15.64	30

BLE mode

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	4.47	30	Pass
Middle	2440	5.96	30	Pass
High	2480	4.46	30	Pass


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	52~55 %
ATM Pressure:	100.9~101.0 kPa


The testing was performed by Kieroy Luo from 2019-04-05 to 2019-04-30.

EUT operation mode: Transmitting

Test Result: Compliance


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 30.APR.2019 11:11:23

802.11b: Band Edge, Right Side




Date: 30.APR.2019 11:15:05

802.11g: Band Edge, Left Side




Date: 30.APR.2019 11:09:17

802.11g: Band Edge, Right Side




Date: 30.APR.2019 11:07:51

802.11n-HT20: Band Edge, Left Side




Date: 30.APR.2019 11:19:10

802.11n-HT20: Band Edge, Right Side




Date: 30.APR.2019 11:16:45

BLE: Band Edge, Left Side



Date: 5.APR.2019 17:21:01

BLE: Band Edge, Right Side



Date: 5.APR.2019 17:21:45


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	52~55 %
ATM Pressure:	100.9~101.0 kPa


The testing was performed by Kieroy Luo from 2019-04-05 to 2019-04-30.

EUT operation mode: Transmitting

Test Result: Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	6.13	≤ 8
Middle	2437	4.79	≤ 8
High	2462	4.23	≤ 8
802.11g mode			
Low	2412	-11.90	≤ 8
Middle	2437	-10.43	≤ 8
High	2462	-13.24	≤ 8
802.11n-HT20 mode			
Low	2412	-12.68	≤ 8
Middle	2437	-11.26	≤ 8
High	2462	-13.07	≤ 8
BLE mode			
Low	2402	-12.68	≤ 8
Middle	2440	-11.14	≤ 8
High	2480	-12.63	≤ 8

Power Spectral Density, 802.11b Low Channel




Date: 30.APR.2019 11:52:51

Power Spectral Density, 802.11b Middle Channel




Date: 30.APR.2019 11:54:56

Power Spectral Density, 802.11b High Channel




Date: 30.APR.2019 11:57:21

Power Spectral Density, 802.11g Low Channel




Date: 30.APR.2019 12:03:27

Power Spectral Density, 802.11g Middle Channel




Date: 30.APR.2019 12:02:20

Power Spectral Density, 802.11g High Channel




Date: 30.APR.2019 12:00:47

Power Spectral Density, 802.11n-HT20 Low Channel




Date: 30.APR.2019 12:04:27

Power Spectral Density, 802.11n-HT20 Middle Channel




Date: 30.APR.2019 12:05:52

Power Spectral Density, 802.11n-HT20 High Channel




Date: 30.APR.2019 12:07:19

Power Spectral Density, BLE Low Channel




Date: 5.APR.2019 17:23:49

Power Spectral Density, BLE Middle Channel



Date: 5.APR.2019 17:23:28

Power Spectral Density, BLE High Channel



Date: 5.APR.2019 17:23:03

***** END OF REPORT *****