



BUREAU
VERITAS

Test Report No.: FS160901N007

RF EXPOSURE REPORT

| | |
|-----------|---|
| Applicant | TP-LINK TECHNOLOGIES CO., LTD. |
| Address | Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China |

| | |
|-------------------------------------|---|
| Manufacturer or Supplier | TP-LINK TECHNOLOGIES CO., LTD. |
| Address | Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China |
| Product | 300Mbps Wireless N Outdoor Access Point |
| Brand Name | TP-LINK |
| Model | EAP110-Outdoor |
| Additional Model & Model Difference | N/A |
| Date of tests | Sep. 01, 2016 ~ Oct. 10, 2016 |

FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

| | |
|--|--|
| Tested by Harry Li Project Engineer/ EMC Department | Approved by Glyn He Supervisor / EMC Department |
| | |

Date: Oct. 13, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



BUREAU
VERITAS

Test Report No.: FS160901N007

Table of Contents

| | |
|---|---|
| RELEASE CONTROL RECORD | 3 |
| 1. CERTIFICATION..... | 4 |
| 2. RF EXPOSURE LIMIT | 5 |
| 3. MPE CALCULATION FORMULA..... | 5 |
| 4. CLASSIFICATION | 5 |
| 5. ANTENNA GAIN | 6 |
| 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER..... | 6 |



**BUREAU
VERITAS** Test Report No.: FS160901N007

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|--------------|-------------------|---------------|
| FS160901N007 | Original release | Oct. 13, 2016 |



BUREAU
VERITAS

Test Report No.: FS160901N007

1. CERTIFICATION

PRODUCT: 300Mbps Wireless N Outdoor Access Point

BRAND NAME: TP-LINK

MODEL NO.: EAP110-Outdoor

ADDITIONAL MODEL: N/A

FCC ID: TE7EAP110OD

TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: TP-LINK TECHNOLOGIES CO., LTD.

TESTED DATE: Oct. 10, 2016

STANDARDS: FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1



BUREAU
VERITAS Test Report No.: FS160901N007

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| FREQUENCY RANGE (MHz) | ELECTRIC FIELD STRENGTH (V/m) | MAGNETIC FIELD STRENGTH (A/m) | POWER DENSITY (mW/cm ²) | AVERAGE TIME (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE | | | | |
| 300-1500 | ... | ... | F/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



BUREAU
VERITAS

Test Report No.: FS160901N007

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

| Transmitter Circuit | Peak Gain (dBi) | Total Gain (dBi) | Antenna Type |
|---------------------|-----------------|------------------|----------------|
| Chain 0 | 5 | 8.01 | Dipole Antenna |
| Chain 1 | 5 | | Dipole Antenna |

Note: Total Gain=3.2+10log(N=2)=5+(3.01)=8.01dBi

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

| FREQUENCY BAND (MHz) | MAX POWER (mW) | ANTENNA GAIN (dBi) | DISTANCE (cm) | POWER DENSITY (mW/cm ²) | LIMIT (mW/cm ²) |
|----------------------|----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| WLAN 2.4GHz | 737.987 | 5 | 20 | 0.928 | 1.0 |

--- END ---