

FCC RF EXPOSURE REPORT

FCC ID: TE7EAP225WALL

Project No. : 1805C099
Equipment : AC1200 Wireless MU-MIMO Wall Plate Access Point
Test Model : EAP225-Wall
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
**Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4)
Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China**

**According: : FCC Guidelines for Human Exposure IEEE C95.1
& FCC Part 2.1091**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

1. CERTIFICATION

Equipment : AC1200 Wireless MU-MIMO Wall Plate Access Point
Brand Name : Omada
Test Model : EAP225-Wall
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
Manufacturer : TP-Link Technologies Co., Ltd.
Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology
Park,Shennan Rd, Nanshan, Shenzhen,China
Date of Test : Jun. 01, 2018 ~ Jul. 31, 2018
Test Sample : Engineering Sample No.: D180504296

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-3-1805C099) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP according to the ISO-17025 quality assessment standard and technical standard(s).

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

For 2.4G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PIFA	N/A	2
2	N/A	N/A	PIFA	N/A	2

Note:

This EUT supports MIMO 2X2, any transmit signals are correlated with each other, so Directional gain = $G_{ANT} + 10\log(N)$ dBi, that is Directional gain = $2 + 10\log(2)$ dBi = 5.01.

For 5G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PIFA	N/A	3
2	N/A	N/A	PIFA	N/A	3

Note:

(1) This EUT supports MIMO 2X2, any transmit signals are correlated with each other, so Directional gain = $G_{ANT} + 10\log(N)$ dBi, that is Directional gain = $3 + 10\log(2)$ dBi = 6.01; So, the UNII-1, UNII-3 output power limit is $30 - 6.01 + 6 = 29.99$. The UNII-1 power density limit is $17 - 6.01 + 6 = 16.99$, the UNII-3 power density limit is $30 - 6.01 + 6 = 29.99$.

(2) Beamforming Gain: 3.01 dBi, Directional gain = $3 + 10\log(2)$ dBi = 6.01. Then, the UNII-1, UNII-3 output power limit is $30 - 6.01 + 6 = 29.99$. The UNII-1 power density limit is $17 - 6.01 + 6 = 16.99$, the UNII-3 power density limit is $30 - 6.01 + 6 = 29.99$.

3. TEST RESULTS

2.4G WIFI

Antenna Gain (dBi)	Antenna Gain (numeric)	AVG Output Power (dBm)	AVG Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.01	3.1696	21.92	155.5966	0.09816	1	Complies

5G Band UNII-1

Antenna Gain (dBi)	Antenna Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
6.01	3.9902	22.12	162.9296	0.12940	1	Complies

5G Band UNII-1 with Beamforming

Antenna Gain (dBi)	Antenna Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
6.01	3.9902	21.88	154.1700	0.12245	1	Complies

5G Band UNII-3

Antenna Gain (dBi)	Antenna Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
6.01	3.9902	22.65	184.0772	0.14620	1	Complies

5G Band UNII-3 with Beamforming

Antenna Gain (dBi)	Antenna Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
6.01	3.9902	21.76	149.9685	0.11911	1	Complies

For the max simultaneous transmission MPE:

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4G	5G			
0.09816	0.14620	0.24436	1	Complies

Note: the calculated distance is 20 cm.