

FCC RF EXPOSURE REPORT

FCC ID: TE7KP200

Project No. : 1808C015
Equipment : Smart Wi-Fi Power Outlet
Test Model : KP200
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4)
Central Science and Technology Park, Shennan
Rd, Nanshan, Shenzhen, China

According: : FCC Guidelines for Human Exposure IEEE C95.1
& FCC Part 2.1091

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

1. CERTIFICATION

Equipment : Smart Wi-Fi Power Outlet
Brand Name : tp-link
Test Model : KP200
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
Manufacturer : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Factory : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Date of Test : Aug. 03, 2018 ~ Aug. 24, 2018
Test Sample : Engineering Sample No.: D180806505

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1808C015) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of A2LA according to the ISO-17025 quality assessment standard and technical standard(s).

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:


S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		N/A	PCB	I-PEX	2.71

3. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	AVG Output Power (dBm)	AVG Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.71	1.8664	20.87	122.1800	0.04538897	1	Complies

Note: the calculated distance is 20 cm.

End of Test Report