

MEASUREMENT REPORT

FCC PART 15.407 WLAN 802.11a/n/ac

FCC ID: TE7RE450V2

APPLICANT: TP-Link Technologies Co., Ltd.

Application Type: Certification

Product: AC1750 Wi-Fi Range Extender

Model No.: RE450

Brand Name: TP-Link

FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Rule Part(s): Part 15.407

Test Procedure(s): ANSI C63.10-2013, KDB 789033 D02v01r04,
KDB 662911 D01v02r01, KDB 644545 D03v01

Test Date: May 02 ~ 25, 2017

Reviewed By : *Paddy Chen*
(Paddy Chen)

Approved By : *Chenz Ker*
(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v01r04. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1706TW0118-U2	Rev. 01	Initial report	06-25-2017	Valid

CONTENTS

Description	Page
§2.1033 General Information	6
1. INTRODUCTION	7
1.1. Scope	7
1.2. MRT Test Location	7
2. PRODUCT INFORMATION	8
2.1. Equipment Description.....	8
2.2. Product Specification Subjective to this Report.....	8
2.3. Working Frequencies for this report	9
2.4. Description of Available Antennas	10
2.5. Description of Antenna RF Port	11
2.6. Test Mode	11
2.7. Description of Test Software	12
2.8. Device Capabilities	14
2.9. Test Configuration	16
2.10. EMI Suppression Device(s)/Modifications	16
2.11. Labeling Requirements.....	16
3. DESCRIPTION OF TEST	17
3.1. Evaluation Procedure	17
3.2. AC Line Conducted Emissions	17
3.3. Radiated Emissions	18
4. ANTENNA REQUIREMENTS.....	19
5. TEST EQUIPMENT CALIBRATION DATE	20
6. MEASUREMENT UNCERTAINTY	21
7. TEST RESULT	22
7.1. Summary	22
7.2. 26dB Bandwidth Measurement.....	23
7.2.1. Test Limit	23
7.2.2. Test Procedure used.....	23
7.2.3. Test Setting.....	23
7.2.4. Test Setup	23
7.2.5. Test Result.....	24
7.3. 6dB Bandwidth Measurement.....	37
7.3.1. Test Limit	37

7.3.2. Test Procedure used.....	37
7.3.3. Test Setting.....	37
7.3.4. Test Setup	37
7.3.5. Test Result.....	38
7.4. Output Power Measurement	43
7.4.1. Test Limit	43
7.4.2. Test Procedure Used	43
7.4.3. Test Setting.....	43
7.4.4. Test Setup	43
7.4.5. Test Result.....	44
7.5. Transmit Power Control	48
7.5.1. Test Limit	48
7.5.2. Test Procedure Used	48
7.5.3. Test Setting.....	48
7.5.4. Test Setup	48
7.5.5. Test Result.....	49
7.6. Power Spectral Density Measurement	51
7.6.1. Test Limit	51
7.6.2. Test Procedure Used	51
7.6.3. Test Setting.....	51
7.6.4. Test Setup	52
7.6.5. Test Result.....	53
7.7. Frequency Stability Measurement.....	89
7.7.1. Test Limit	89
7.7.2. Test Procedure Used	89
7.7.3. Test Setup	89
7.7.4. Test Result.....	90
7.8. Radiated Spurious Emission Measurement	91
7.8.1. Test Limit	91
7.8.2. Test Procedure Used	91
7.8.3. Test Setting.....	91
7.8.4. Test Setup	92
7.8.5. Test Result.....	95
7.9. Radiated Restricted Band Edge Measurement	155
7.9.1. Test Limit	155
7.9.2. Test Result.....	157
7.10. AC Conducted Emissions Measurement.....	271
7.10.1. Test Limit	271
7.10.2. Test Procedure	271

7.10.3. Test Setup	272
7.10.4. Test Result.....	273
8. CONCLUSION.....	275

§2.1033 General Information

Applicant:	TP-Link Technologies Co., Ltd.
Applicant Address:	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Manufacturer:	TP-Link Technologies Co., Ltd.
Manufacturer Address:	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Test Site:	MRT Technology (Taiwan) Co., Ltd
Test Site Address:	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT Registration No.:	153292
FCC Rule Part(s):	Part 15.407
Model No.:	RE450
Test Device Serial No.:	N/A ☐ Production ☒ Pre-Production ☐ Engineering

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Fuxing Rd., Taoyuan, Taiwan (R.O.C)

- MRT facility is a FCC registered (Reg. No. 153292) test facility with the site description report on file and is designated by the FCC as an Accredited Test Film.
- MRT facility is an IC registered (MRT Reg. No. 21723-1) test laboratory with the site description on file at Industry Canada.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (TAF) under the American Association for Laboratory Accreditation Program (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC, Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	AC1750 Wi-Fi Range Extender
Model No.:	RE450
Brand Name:	TP-Link
Wi-Fi Specification:	802.11a/b/g/n/ac

2.2. Product Specification Subjective to this Report

Frequency Range:	802.11a/n-HT20/ac-VHT20: 5180~5320MHz, 5500~5580, 5660~5700MHz, 5745~5825MHz 802.11n-HT40/ac-VHT40: 5190~5310MHz, 5510~5550MHz, 5670MHz, 5755~5795MHz 802.11ac-VHT80: 5210MHz, 5290MHz, 5530MHz, 5775MHz
Channel Number:	802.11a/ n-HT20/ac-VHT20: 21 802.11a/ n-HT20/ac-VHT40: 9 802.11ac-VHT80: 4
Type of Modulation:	802.11a/n/ac: OFDM
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 450Mbps 802.11ac: up to 1299.9Mbps
Maximum Average Output Power:	802.11a: 26.07dBm 802.11n-HT20: 26.07dBm 802.11n-HT40: 24.59dBm 802.11ac-VHT20: 25.58dBm 802.11ac-VHT40: 24.30dBm 802.11ac-VHT80: 23.54dBm

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this Report

802.11a/n-HT20/ ac-VHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	149	5745 MHz	153	5765 MHz
157	5785 MHz	161	5805 MHz	165	5825 MHz

802.11n-HT40/ ac-VHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550 MHz
134	5670 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
155	5775 MHz	--	--	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	TX Paths	Max Antenna Gain (dBi)	CDD Directional Gain (dBi)	
				For Power	For PSD
Omni-Directional	2412 ~ 2462	3	2.0	2.0	6.77
	5150 ~ 5850	3	2.5	2.5	7.27


Note: The EUT supports Cyclic Delay Diversity (CDD) technology for 802.11a/b/g/n/ac mode, and the transmitter output signal is correlated.

For CDD transmissions, directional gain is calculated as follows, $N_{ANT} = 3$, $N_{SS} = 1$.

Three antennas have the same gain, G_{ANT} , Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,
Array Gain = $10 \log (N_{ANT} / N_{SS})$ dB = 4.77;
- For power measurements on IEEE 802.11 devices,
Array Gain = 0 dB for $N_{ANT} \leq 4$;

2.5. Description of Antenna RF Port

Antenna RF Port						
--	2.4GHz RF Port			5GHz RF Port		
Software Control Port	Chain 0	Chain 1	Chain 2	Chain 0	Chain 1	Chain 2
 The photograph shows the antenna RF port assembly. It features a green PCB with a silver shield. Red labels with arrows point to specific components: '2.4GHz_Chain 1/ 5GHz_Chain 1' points to a component on the left, '2.4GHz_Chain 2/ 5GHz_Chain 0' points to a component in the middle, and '2.4GHz_Chain 0/ 5GHz_Chain 2' points to a component on the right. A yellow SMA connector is visible on the left side of the assembly.						

2.6. Test Mode

Test Mode	Mode 1: Transmit by 802.11a
	Mode 2: Transmit by 802.11n-HT20
	Mode 3: Transmit by 802.11n-HT40
	Mode 4: Transmit by 802.11ac-VHT20
	Mode 5: Transmit by 802.11ac-VHT40
	Mode 6: Transmit by 802.11ac-VHT80

2.7. Description of Test Software

The test utility software used during testing was “CART”, and the version was 4.9.

Power Parameter Value

Test Mode	Test Channel No.	Test Frequency (MHz)	Power Parameter Value
802.11a	36	5180	15.5
	40	5200	20.0
	48	5240	20.0
	52	5260	15.5
	60	5300	15.5
	64	5320	15.5
	100	5500	14.5
	116	5580	15.0
	140	5700	16.5
	149	5745	20.0
	157	5785	20.0
	165	5825	20.0
802.11 n-HT20	36	5180	14.5
	40	5200	20.0
	48	5240	20.0
	52	5260	15.0
	60	5300	16.0
	64	5320	15.5
	100	5500	14.5
	116	5580	15.0
	140	5700	16.0
	149	5745	20.0
	157	5785	20.0
	165	5825	20.0

Test Mode	Test Channel No.	Test Frequency (MHz)	Power Parameter Value
802.11n-HT40	38	5190	14.5
	46	5230	20.0
	54	5270	19.0
	62	5310	16.5
	102	5510	13.5
	110	5550	19.0
	134	5670	17.5
	151	5755	20.0
	159	5795	20.0
802.11ac-VHT20	36	5180	14.5
	40	5200	20.0
	48	5240	20.0
	52	5260	15.5
	60	5300	15.5
	64	5320	15.5
	100	5500	14.0
	116	5580	15.0
	140	5700	16.5
	149	5745	20.0
	157	5785	20.0
	165	5825	20.0
802.11ac-VHT40	38	5190	14.5
	46	5230	20.0
	54	5270	19.5
	62	5310	16.5
	102	5510	13.5
	110	5550	19.0
	134	5670	17.5
	151	5755	20.0
	159	5795	20.0
802.11ac-VHT80	42	5210	13.0
	58	5290	15.0
	106	5530	11.5
	155	5775	20.0


2.8. Device Capabilities

This device contains the following capabilities:


2.4GHz WLAN (DTS) and 5GHz WLAN (NII)

Note: 5GHz (NII) operation is possible in 20MHz, 40MHz and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = average per the guidance of Section B)2)b) of KDB 789033 D02v01r04. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:


Test Mode	Duty Cycle
802.11a	95.94 %
802.11n-HT20	96.11 %
802.11n-HT40	92.85 %
802.11ac-VHT20	96.15 %
802.11ac-VHT40	91.96 %
802.11ac-VHT80	87.01 %




802.11n-HT40




802.11ac-VHT20



802.11ac-VHT40



802.11ac-VHT80



2.9. Test Configuration

The **AC1750 Wi-Fi Range Extender** was tested per the guidance of KDB 789033 D02v01r04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.10. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.11. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 789033 D02v01r04 were used in the measurement of the **AC1750 Wi-Fi Range Extender**.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.10.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **AC1750 Wi-Fi Range Extender** is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **AC1750 Wi-Fi Range Extender** unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2018/03/17
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2018/03/23
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2018/03/23
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2018/06/09

Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2018/03/02
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2018/03/16
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2018/04/06
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2018/04/06
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2018/04/06
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2018/04/06
Broadband Hornantenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2018/04/06
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2018/04/06
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2018/06/09

Conducted Test Equipment - SR1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2017/07/11
PSA Series Spectrum Analyzer	Agilent	E4447A	MRTTWA00060	1 year	2017/12/11
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2018/03/18
Programmable Temperature & Humidity Chamber	TEN BILLION	TTH-B3UP	MRTTWA00036	1 year	2018/05/11
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2018/06/09

Software	Version	Function
EMI Software	V3	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement - SR2
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: 3.46dB
Radiated Emission Measurement - AC1
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 40GHz: 4.76dB
Output Power - SR1
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.13dB
Power Spectrum Density - SR1
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.15dB
Occupied Bandwidth - SR1
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.28%

7. TEST RESULT

7.1. Summary

Product Name: AC1750 Wi-Fi Range Extender
FCC ID: TE7RE450V2
FCC Classification: Unlicensed National Information Infrastructure (UNII)
Data Rate / MCS 6Mbps for 802.11a & MCS0 for 802.11n-HT20MHz
Tested: MCS0 for 802.11n-HT40MHz & MCS0 for 802.11ac-VHT20MHz
MCS0 for 802.11ac-VHT40MHz & MCS0 for 802.11ac-VHT80MHz

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section 7.2
15.407(e)	6dB Bandwidth	$\geq 500\text{kHz}$		Pass	Section 7.3
15.407(a)(1)(ii), (2), (3)	Maximum Conducted Output Power	$\leq 30\text{ dBm U-NII-1 \& U-NII-3}$ $\leq 24\text{ dBm U-NII-2}$		Pass	Section 7.4
15.407(h)(1)	Transmit Power Control	$\leq 24\text{ dBm}$		Pass	Section 7.5
15.407(a)(1)(ii), (2), (3), (5)	Peak Power Spectral Density	$\leq 17\text{ dBm/MHz U-NII-1}$ $\leq 11\text{ dBm/MHz U-NII-2}$ $\leq 30\text{ dBm/500kHz U-NII-3}$		Pass	Section 7.6
15.407(g)	Frequency Stability	N/A		Pass	Section 7.7
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	$\leq -27\text{dBm/MHz EIRP}$ Detail see section 7.8	Radiated	Pass	Section 7.8 & 7.9
15.205, 15.209 15.407(b)(5), (6), (7)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.10

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) Test Items "26dB Bandwidth" & "99% Bandwidth" & "6dB Bandwidth" & "Frequency Stability" have been assessed MIMO transmission, and showed the worst single test data in this report.

7.2. 26dB Bandwidth Measurement

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

KDB 789033 D02v01r04 - Section C.1

7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. $VBW \geq 3 \times RBW$.
4. Detector = Peak.
5. Trace mode = max hold.

7.2.4. Test Setup



7.2.5. Test Result


Product	AC1750 Wi-Fi Range Extender	Temperature	25°C
Test Engineer	Kevin Ker	Relative Humidity	54%
Test Site	SR1	Test Date	2017/05/13

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Chain 0 / Chain 0 + 1 + 2					
802.11a	6Mbps	36	5180	21.92	16.66
802.11a	6Mbps	40	5200	37.58	18.76
802.11a	6Mbps	48	5240	34.97	17.85
802.11a	6Mbps	52	5260	21.80	16.66
802.11a	6Mbps	60	5300	20.69	16.62
802.11a	6Mbps	64	5320	21.21	16.64
802.11a	6Mbps	100	5500	21.27	16.60
802.11a	6Mbps	116	5580	20.78	16.67
802.11a	6Mbps	140	5700	20.91	16.55
802.11a	6Mbps	149	5745	38.56	18.14
802.11a	6Mbps	157	5785	38.61	18.69
802.11a	6Mbps	165	5825	38.06	19.78
802.11n-HT20	MCS0	36	5180	21.77	17.77
802.11n-HT20	MCS0	40	5200	36.15	18.77
802.11n-HT20	MCS0	48	5240	33.84	18.47
802.11n-HT20	MCS0	52	5260	21.75	17.76
802.11n-HT20	MCS0	60	5300	21.96	17.80
802.11n-HT20	MCS0	64	5320	22.52	17.77
802.11n-HT20	MCS0	100	5500	22.04	17.82
802.11n-HT20	MCS0	116	5580	21.77	17.78
802.11n-HT20	MCS0	140	5700	22.40	17.76
802.11n-HT20	MCS0	149	5745	39.04	18.63
802.11n-HT20	MCS0	157	5785	39.78	18.96
802.11n-HT20	MCS0	165	5825	39.60	19.79


Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Chain 0 / Chain 0 + 1 + 2					
802.11n-HT40	MCS0	38	5190	43.83	36.33
802.11n-HT40	MCS0	46	5230	68.65	37.10
802.11n-HT40	MCS0	54	5270	49.09	36.70
802.11n-HT40	MCS0	62	5310	44.25	36.58
802.11n-HT40	MCS0	102	5510	45.28	36.62
802.11n-HT40	MCS0	110	5550	71.82	36.91
802.11n-HT40	MCS0	134	5670	43.85	36.36
802.11n-HT40	MCS0	151	5755	77.06	37.71
802.11n-HT40	MCS0	159	5795	78.13	38.22
802.11ac-VHT20	MCS0	36	5180	21.34	17.81
802.11ac-VHT20	MCS0	40	5200	39.07	18.79
802.11ac-VHT20	MCS0	48	5240	37.24	18.75
802.11ac-VHT20	MCS0	52	5260	21.54	17.76
802.11ac-VHT20	MCS0	60	5300	22.09	17.74
802.11ac-VHT20	MCS0	64	5320	22.36	17.79
802.11ac-VHT20	MCS0	100	5500	21.64	17.84
802.11ac-VHT20	MCS0	116	5580	22.16	17.81
802.11ac-VHT20	MCS0	140	5700	22.11	17.78
802.11ac-VHT20	MCS0	149	5745	38.82	18.66
802.11ac-VHT20	MCS0	157	5785	37.51	18.84
802.11ac-VHT20	MCS0	165	5825	39.64	19.51
802.11ac-VHT40	MCS0	38	5190	44.13	36.38
802.11ac-VHT40	MCS0	46	5230	67.27	36.97
802.11ac-VHT40	MCS0	54	5270	70.57	36.77
802.11ac-VHT40	MCS0	62	5310	44.93	36.54
802.11ac-VHT40	MCS0	102	5510	43.59	36.60
802.11ac-VHT40	MCS0	110	5550	71.12	36.96
802.11ac-VHT40	MCS0	134	5670	44.10	36.43
802.11ac-VHT40	MCS0	151	5755	69.53	37.33
802.11ac-VHT40	MCS0	159	5795	77.57	38.02
802.11ac-VHT80	MCS0	42	5210	85.09	75.80
802.11ac-VHT80	MCS0	58	5290	82.49	75.68
802.11ac-VHT80	MCS0	106	5530	85.39	76.04
802.11ac-VHT80	MCS0	155	5775	145.2	77.35

802.11a 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)



Channel 60 (5300MHz)



Channel 64 (5320MHz)




802.11a 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT20 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)



Channel 60 (5300MHz)




Channel 64 (5320MHz)




802.11n-HT20 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT40 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 38 (5190MHz)




Channel 46 (5230MHz)




Channel 54 (5270MHz)




Channel 62 (5310MHz)



Channel 102 (5510MHz)




Channel 110 (5550MHz)




802.11n-HT40 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 134 (5670MHz)



Channel 151 (5755MHz)




Channel 159 (5795MHz)




802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)



Channel 60 (5300MHz)




Channel 64 (5320MHz)




802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth - Chain 0 / Chain 0 + 1 + 2


Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)



Channel 165 (5825MHz)

