



A Test Lab Techno Corp.

Changan Lab : N o. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C)
Tel : 886-3-271-0188 / Fax : 886-3-271-0190



MPE Report

Test Report No.	:	1511FS13-01
Applicant	:	TP-LINK TECHNOLOGIES CO., LTD.
Address	:	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China
Product Type	:	300Mbps Wireless N ADSL2+ Modem Router
Trade Name	:	TP-LINK
Model Number	:	TD-W8960N
Date of Received	:	Oct. 21, 2015
Test Period	:	Nov. 05, 2015
Date of Issued	:	Dec. 31, 2015
Test Specification	:	ANSI / IEEE Std.C95.1-1992 / IEEE Std. 1528-2013 47 CFR § 2.1091 47 CFR § 1.1310
Location of Test Lab.	:	Chang-an Lab.

1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By : Bill Hu
(Bill Hu)

Tested By : Sky Chou
(Sky Chou)



Contents

1.	Description of Equipment under Test (EUT).....	3
2.	Human Exposure Assessment.....	4
3.	RF Output Power	5
4.	Test Result	6



1. Description of Equipment under Test (EUT)

Applicant	TP-LINK TECHNOLOGIES CO., LTD. Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China				
Manufacturer	TP-LINK TECHNOLOGIES CO., LTD. Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China				
Product Type	300Mbps Wireless N ADSL2+ Modem Router				
Trade Name	TP-LINK				
Model Number	TD-W8960N				
FCC ID	TE7TDW8960NV7				
Frequency Range	IEEE 802.11b / 802.11g / 802.11n 2.4GHz 20MHz : 2412 - 2462 MHz IEEE 802.11n 2.4GHz 40MHz : 2422 - 2452 MHz				
Transmit Power (conducted power)	IEEE 802.11b :	0.070	W /	18.44	dBm
	IEEE 802.11g :	0.152	W /	21.81	dBm
	IEEE 802.11n 2.4GHz 20MHz :	0.151	W /	21.79	dBm
	IEEE 802.11n 2.4GHz 40MHz :	0.156	W /	21.94	dBm
Antenna Type	Omni Directional Antenna				
Antenna Gain	3.7 dBi				
Antenna Delivery	IEEE 802.11b: 1TX+1RX IEEE 802.11g, IEEE 802.11n 2.4GHz 20MHz / 40MHz: 2TX+2RX				
Temperature Range	0~ 40°C				
RF Evaluation	0.081 mW/cm ²				

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 & 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR §1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. " This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.



3. RF Output Power

Band	Date Rate	CH	Frequency (MHz)	Average Conducted power (dBm)		
				ANT-0	ANT-1	ANT-0+1
IEEE 802.11b	1M	1	2412.0	18.40	18.22	---
		6	2437.0	18.44	18.28	---
		11	2462.0	17.34	17.11	---
	2M	6	2437.0	18.42	18.25	---
	5.5M	6	2437.0	18.41	18.21	---
	11M	6	2437.0	18.38	18.19	---
IEEE 802.11g	6M	1	2412.0	10.75	11.17	13.98
		6	2437.0	19.03	18.56	21.81
		11	2462.0	8.92	9.37	12.16
	9M	6	2437.0	18.97	18.49	21.75
	12M	6	2437.0	19.00	18.53	21.78
	18M	6	2437.0	19.02	18.47	21.76
	24M	6	2437.0	18.96	18.43	21.71
	36M	6	2437.0	18.88	18.51	21.71
	48M	6	2437.0	18.92	18.45	21.70
	54M	6	2437.0	18.99	18.48	21.75
IEEE 802.11n 2.4GHz 20MHz	13M	1	2412.0	10.48	11.36	13.95
		6	2437.0	18.84	18.13	21.51
		11	2462.0	10.46	11.14	13.82
	26M	6	2437.0	18.79	18.10	21.47
	39M	6	2437.0	18.76	18.66	21.72
	52M	6	2437.0	18.75	18.71	21.74
	78M	6	2437.0	18.71	18.77	21.75
	104M	6	2437.0	18.69	18.75	21.73
	117M	6	2437.0	18.77	18.79	21.79
	130M	6	2437.0	18.65	18.72	21.70
IEEE 802.11n 2.4GHz 40MHz	27M	3	2422.0	7.89	8.32	11.12
		6	2437.0	19.13	18.72	21.94
		9	2452.0	7.73	8.24	11.00
	54M	6	2437.0	18.95	18.66	21.82
	81M	6	2437.0	19.01	18.63	21.83
	108M	6	2437.0	19.04	18.55	21.81
	162M	6	2437.0	19.06	18.59	21.84
	216M	6	2437.0	19.03	18.62	21.84
	243M	6	2437.0	19.07	18.53	21.82
	270M	6	2437.0	19.00	18.70	21.86

4. Test Result

Band	Data Rate	Frequency (MHz)	Limit (mw/cm ²)	Distance (cm) [R]	Max Tune-up power (dBm) [P]	ANT Gain (dBi)	Numeric Gain [G] (dBi)	Duty Cycle	[P] x [G] With Duty Cycle (mW) [TP]	Power Density [S] (mw/cm ²)
IEEE 802.11b	1 M	2412	1.000	20	18.90	3.70	2.34	1	181.64	0.036
		2437	1.000	20	18.90	3.70	2.34	1	181.64	0.036
		2462	1.000	20	18.90	3.70	2.34	1	181.64	0.036
IEEE 802.11g	6 M	2412	1.000	20	14.20	3.70	2.34	1	61.55	0.012
		2437	1.000	20	22.30	3.70	2.34	1	397.39	0.079
		2462	1.000	20	12.40	3.70	2.34	1	40.66	0.008
IEEE 802.11n 2.4GHz 20MHz	13 M	2412	1.000	20	14.20	3.70	2.34	1	61.55	0.012
		2437	1.000	20	22.00	3.70	2.34	1	370.87	0.074
		2462	1.000	20	14.30	3.70	2.34	1	62.98	0.013
IEEE 802.11n 2.4GHz 40MHz	27M	2422	1.000	20	11.60	3.70	2.34	1	33.82	0.007
		2437	1.000	20	22.40	3.70	2.34	1	406.65	0.081
		2452	1.000	20	11.50	3.70	2.34	1	33.05	0.007

Note:

1. The Numeric Gain calculated by $10^{(\text{ant. Gain(dBi)} / 10)}$.
2. Each band max power which perform MPE of any configurations.
3. The MPE results are evaluated by lowest data rate for wlan
4. The device operating IEEE 802.11b mode is Diversity with transmit signals to 1TX.
5. The device operating IEEE 802.11g& IEEE 802.11n mode is MIMO with transmit signals to 2TX.