

MPE CALCULATION

For *HYUNDAI MOBIS CO., LTD* - ; Model: AC1B0DKAN
FCC ID: TQ8-AC1B0KDAN

| | |
|---|---|
| RF Exposure Requirements: | 47 CFR §1.1307(b) |
| RF Radiation Exposure Limits: | 47 CFR §1.1310 |
| RF Radiation Exposure Guidelines: | FCC OST/OET Bulletin Number 65 / 47 CFR §2.1091 |
| EUT Frequency Band: | 2402 – 2480 MHz |
| Limits for General Population/Uncontrolled Exposure in the band of: | 1500 – 100,000 MHz |
| Power Density Limit: | 1.0mW/ cm ² ; |

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Low Channel (2402 MHz): Power =-0.14 dBm, Antenna Gain =1.07 dBi, Prediction distance 20cm

S = 0.0002 mW/cm²

Result

The Above Result had shown that Device complied with 1.0 mW/cm² Power density requirement for distance of 20cm.

Completed By : Jong Suk LEE

Date : July 25, 2011