

TEST REPORT

of

FCC Part 15 Subpart E §15.407

FCC ID: TQ8-ADC10SXFN

1. Equipment Under Test : DISPLAY CAR SYSTEM
2. Model Name : ADC10SXFN
3. Variant Model Name(s) : Refer to the page 4
4. Applicant : Hyundai Mobis Co., Ltd.
5. Manufacturer : Hyundai Mobis Co., Ltd.
6. Date of Receipt : 2020.01.03
7. Date of Test(s) : 2020.01.26 ~ 2020.03.02
8. Date of Issue : 2020.03.18

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.

Tested by:



Jinhyoung Cho

Technical
Manager:



Jungmin Yang

SGS Korea Co., Ltd. Gunpo Laboratory

INDEX

Table of contents

1. General Information -----	3
2. Transmitter Radiated Spurious Emissions -----	11
3. 26 dB Bandwidth & 99 % Bandwidth -----	48
4. 6 dB Bandwidth -----	70
5. Maximum Conducted Output Power -----	77
6. Peak Power Spectral Density -----	86
7. Antenna Requirement -----	111

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : Hyundai Mobis Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977

Contact Person : Choe, Seung-hoon

Phone No. : +82 31 260 0098

1.3. Details of Manufacturer

Company : Same as applicant

Address : Same as applicant

1.4. Description of EUT

Kind of Product	DISPLAY CAR SYSTEM
Model Name	ADC10SXFN
Variant Model Names	ADC10SXGG, ADC10SXGN, ADC10SXGL, ADC11SXGG, DA331SXGG, ADC10SXMG, DA340SXGG, DA341SXGG
Power Supply	DC 14.4 V
Frequency Range	5 180 MHz ~ 5 240 MHz (Band 1: 11a/n_HT20, 11ac_VHT20) 5 190 MHz ~ 5 230 MHz (Band 1: 11n_HT40, 11ac_VHT40) 5 210 MHz (Band 1: 11ac_VHT80) 5 260 MHz ~ 5 320 MHz (Band 2A: 11a/n_HT20, 11ac_VHT20) 5 270 MHz ~ 5 310 MHz (Band 2A: 11n_HT40, 11ac_VHT40) 5 290 MHz (Band 2A: 11ac_VHT80) 5 500 MHz ~ 5 720 MHz (Band 2C: 11a/n_HT20, 11ac_VHT20) 5 510 MHz ~ 5 710 MHz (Band 2C: 11n_HT40, 11ac_VHT40) 5 530 MHz ~ 5 690 MHz (Band 2C: 11ac_VHT80) 5 745 MHz ~ 5 825 MHz (Band 3: 11a/n_HT20, 11ac_VHT20) 5 755 MHz ~ 5 795 MHz (Band 3: 11n_HT40, 11ac_VHT40) 5 775 MHz (Band 3: 11ac_VHT80)
Modulation Technique	OFDM
Number of Channels	4 channels (Band 1: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 1: 11n_HT40, 11ac_VHT40) 1 channel (Band 1: 11ac_VHT80) 4 channels (Band 2A: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 2A: 11n_HT40, 11ac_VHT40) 1 channel (Band 2A: 11ac_VHT80) 9 channels (Band 2C: 11a/n_HT20, 11ac_VHT20) 4 channels (Band 2C: 11n_HT40, 11ac_VHT40) 2 channels (Band 2C: 11ac_VHT80) 5 channels (Band 3: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 3: 11n_HT40, 11ac_VHT40) 1 channel (Band 3: 11ac_VHT80)
Antenna Type	Pattern antenna
Antenna Gain	5 150 MHz ~ 5 250 MHz: -0.61 dBi 5 250 MHz ~ 5 350 MHz: -0.18 dBi 5 470 MHz ~ 5 725 MHz: -0.77 dBi 5 725 MHz ~ 5 850 MHz: -0.18 dBi

1.5. Declaration by the Manufacturer

- The EUT is a slave without radar detection and TPC.
- The EUT is not supported TDWR(5.6 - 5.65 GHz) band.

1.6. Automatically Discontinue Transmission

1.6.1. Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operating failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

1.6.2. Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

1.7. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	Agilent	E8257D	MY51501169	Nov. 21, 2019	Annual	Nov. 21, 2020
Signal Generator	R&S	SMBV100A	255834	Jun. 10, 2019	Annual	Jun. 10, 2020
Spectrum Analyzer	R&S	FSV30	103453	Nov. 06, 2019	Annual	Nov. 06, 2020
Spectrum Analyzer	Agilent	N9030A	US51350132	Nov. 15, 2019	Annual	Nov. 15, 2020
Power Meter	Anritsu	ML2495A	1223004	Jun. 05, 2019	Annual	Jun. 05, 2020
Power Sensor	Anritsu	MA2411B	1207272	Jun. 05, 2019	Annual	Jun. 05, 2020
Attenuator	AEROFLEX / INMET	40AH2W-10	40G-3	Jun. 20, 2019	Annual	Jun. 20, 2020
Low Pass Filter	Mini-Circuits	NLP-1200+	V9500401023-2	Jun. 05, 2019	Annual	Jun. 05, 2020
High Pass Filter	Wainwright Instrument GmbH	WHKX6.0/18G-10SS	51	Jun. 07, 2019	Annual	Jun. 07, 2020
High Pass Filter	Wainwright Instrument GmbH	WHNX7.5/26.5G-6SS	15	Jun. 07, 2019	Annual	Jun. 07, 2020
DC Power Supply	R&S	HMP2020	020089489	May 21, 2019	Annual	May 21, 2020
Preamplifier	MITEQ Inc.	JS44-18004000-35-8P	1546891	May 13, 2019	Annual	May 13, 2020
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 22, 2019	Biennial	Aug. 22, 2021
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	396	Mar. 21, 2019	Biennial	Mar. 21, 2021
Horn Antenna	R&S	HF906	100326	Feb. 14, 2020	Annual	Feb. 14, 2021
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA 9170	BBHA9170431	Sep. 10, 2018	Biennial	Sep. 10, 2020
Test Receiver	R&S	ESU26	100109	Feb. 18, 2020	Annual	Feb. 18, 2021
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/383 30516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/383 30516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	SUCOFLEX	104 (3 m)	MY3258414	Jan. 28, 2020	Semi-annual	Jul. 28, 2020
Coaxial Cable	SUCOFLEX	104 (10 m)	MY3145814	Jan. 28, 2020	Semi-annual	Jul. 28, 2020
Coaxial Cable	Rosenberger	LA1-C006-1500	131014 01/20	Feb. 13, 2020	Semi-annual	Aug. 13, 2020

1.8. Summary of Test Result

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15 Subpart E		
Section	Test Item(s)	Result
15.205(a) 15.209(a) 15.407(b)(1) 15.407(b)(2) 15.407(b)(3) 15.407(b)(4)	Transmitter Radiated Spurious Emissions	Complied
15.407(a)	26 dB Bandwidth & 99 % Bandwidth	Complied
15.407(e)	6 dB Bandwidth	Complied
15.407(a)(1) 15.407(a)(2) 15.407(a)(3)	Maximum Conducted Output Power	Complied
15.407(a)(1) 15.407(a)(2) 15.407(a)(3)	Peak Power Spectral Density	Complied
15.207	AC Power Line Conducted Emission	N/A ¹⁾

Note;

- 1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

1.9. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 were used in the measurement of the DUT.

1.10. Sample Calculation

Where relevant, the following sample calculation is provided:

1.10.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.10.2. Radiation Test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)

1.11. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL000414	2020.03.18	Initial

1.12. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
RF Output Power	± 0.34 dB
Occupied Bandwidth	± 9.66 kHz
Power Spectral Density	± 0.41 dB
Radiated Emission, 9 kHz to 30 MHz	± 3.59 dB
Radiated Emission, below 1 GHz	± 5.88 dB
Radiated Emission, above 1 GHz	± 5.94 dB

Uncertainty figures are valid to a confidence level of 95 %.

1.13. Information of Variant Models

	Model Name	BT/WIFI	Broadcast Freq.	DRM	Arkamys	HD	Ecall	RDS	RBDS	MIC type
Basic Model	ADC10SXFN	BT/WIFI	NA	-	-	O	-	-	O	OHCL
Variant Models	ADC10SXGG	BT/WIFI	General	-	-	-	-	-	-	OHCL
	ADC10SXGN	BT/WIFI	NA	-	-	-	-	-	-	OHCL
	ADC10SXGL	BT/WIFI	Columbia	-	-	-	-	-	-	OHCL
	ADC11SXGG	BT/WIFI	General	-	-	-	-	O	-	OHCL
	DA331SXGG	BT	General	-	-	-	-	O	-	OHCL
	ADC10SXMG	BT	General	-	-	-	O	O	-	OHCL
	DA340SXGG	BT/WIFI	General	-	-	-	-	-	-	OHCL
	DA341SXGG	BT/WIFI	General	-	-	-	-	O	-	OHCL

1.14. Duty Cycle of EUT

Regarding to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, II.B, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.

Set RBW ≥ EBW if possible; otherwise, set RBW to the largest available value, Set VBW ≥ RBW.

Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.


Mode	Data Rate (Mbps)	Duty Cycle (%)	Correction Factor (dB)
11a	6 Mbps	95.39	0.20
11n_HT20	MCS0	90.48	0.43
11ac_VHT40	MCS0	90.41	0.44
11ac_VHT80	MCS0	82.06	0.86

Remark;


- As measured duty cycles of EUT, all of mode and data rate keep constant period and are converted to log scale (power averaging) to compensate correction factor to result of average test items.
- Duty Cycle (%) = (Tx on time / Tx on + off time) x 100
- Correction Factor (dB) = 10 log (1 / Duty Cycle)

- Test plots


802.11a




802.11n_HT20



802.11ac_VHT40



802.11ac_VHT80




2. Transmitter Radiated Spurious Emissions


2.1. Test Setup

2.1.1. Transmitter radiated spurious emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



2.2. Limit

According to § 15.407(b)

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dB m/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dB m/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dB m/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dB m/MHz at the band edge.

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (Meters)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.3. Test Procedures

Radiated spurious emissions from the EUT were measured according to the dictates in section G of KDB 789033 D02 General UNII Test Procedures New Rules v02r01 and ANSI C63.10-2013.

2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note;

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

- II.G.4. Unwanted emissions measurements below 1 GHz.

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

- II.G.5. Unwanted maximum emissions measurements above 1 GHz.

Maximum emission levels are measured by setting the analyzer as follows:

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = Peak, Sweep time = auto, Trace mode= Max hold.

- II.G.6. Average unwanted emissions measurements above 1 GHz.

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = power averaging (rms), Averaging type = power averaging (rms), Sweep time = auto, Perform a trace average of at least 100 traces If the transmission is continuous, If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle. For example, with 50 % duty cycle, at least 200 traces shall be averaged.

If tests are performed with the EUT transmitting at a duty cycle less than 98 %, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle. The correction factor is computed as follows:

- If power averaging (rms) mode was used in II.G.6.c)(iv), the correction factor is $10 \log (1/x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50 %, then 3 dB must be added to the measured emission levels.

- Definition of the test orthogonal plan for EUT was described in the test setup photo.

The test orthogonal plan of EUT is **X – axis** during radiation test.

2.4. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

2.4.1. Radiated Spurious Emission below 1 000 MHz


The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
151.01	40.80	Peak	V	13.90	-25.20	29.50	43.50	14.00
151.01	38.40	Peak	H	13.90	-25.20	27.10	43.50	16.40
352.53	32.30	Peak	H	20.95	-24.76	28.49	46.00	17.51
503.36	31.80	Peak	H	23.07	-24.39	30.48	46.00	15.52
920.70	34.60	Peak	V	28.30	-22.05	40.85	46.00	5.15

Remark;

- Spurious emissions for all channels and modes were investigated and almost the same below 1 GHz.
- Reported spurious emissions are in **11n HT20 (Band 2A) / MCS0 / Low channel** as worst case among other modes.
- Radiated spurious emission measurement as below.
 (Actual = Reading + AF + AMP + CL)
- According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

- Test plot



2.4.2. Radiated Spurious Emission above 1 000 MHz

802.11a (Band 1)_6 Mbps

A. Low Channel (5 180 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 500.00	38.29	Peak	V	31.80	-33.56	-	36.53	74.00	37.47
*4 500.00	29.25	Average	V	31.80	-33.56	0.20	27.69	54.00	26.31
*5 148.06	42.39	Peak	V	33.30	-32.67	-	43.02	74.00	30.98
*5 147.27	34.17	Average	V	33.30	-32.67	0.20	35.00	54.00	19.00
*5 150.00	42.28	Peak	V	33.30	-32.67	-	42.91	74.00	31.09
*5 150.00	34.22	Average	V	33.30	-32.67	0.20	35.05	54.00	18.95

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 240 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11a (Band 2A)_6 Mbps

A. Low Channel (5 260 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 300 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 320 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*5 350.00	39.52	Peak	V	33.70	-32.44	-	40.78	74.00	33.22
*5 350.00	31.21	Average	V	33.70	-32.44	0.20	32.67	54.00	21.33
*5 387.43	41.62	Peak	V	33.63	-32.41	-	42.84	74.00	31.16
*5 352.91	31.47	Average	V	33.69	-32.44	0.20	32.92	54.00	21.08
*5 460.00	37.61	Peak	V	33.74	-32.21	-	39.14	74.00	34.86
*5 460.00	29.51	Average	V	33.74	-32.21	0.20	31.24	54.00	22.76

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11a (Band 2C)_6 Mbps

A. Low Channel (5 500 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	35.69	Peak	V	33.90	-32.44	-	37.15	74.00	36.85
*5 350.00	27.36	Average	V	33.90	-32.44	0.20	29.02	54.00	24.98
*5 459.38	41.86	Peak	V	33.90	-32.21	-	43.55	74.00	30.45
*5 459.64	31.76	Average	V	33.90	-32.21	0.20	33.65	54.00	20.35
*5 460.00	40.29	Peak	V	33.90	-32.21	-	41.98	74.00	32.02
*5 460.00	31.86	Average	V	33.90	-32.21	0.20	33.75	54.00	20.25

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 580 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 720 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11a (Band 3)_6 Mbps

A. Low Channel (5 745 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 624.06	40.61	Peak	H	33.70	-32.16		42.15	68.23	26.08
5 689.80	40.29	Peak	H	33.86	-32.09		42.06	97.68	55.62
5 706.80	41.71	Peak	H	33.90	-32.08		43.53	107.13	63.60
5 720.00	40.59	Peak	H	33.90	-32.11		42.38	110.83	68.45

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 785 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 825 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 851.96	42.27	Peak	H	34.01	-31.94		44.34	117.76	73.42
5 865.97	41.87	Peak	H	34.10	-31.97		44.00	107.76	63.76
5 884.82	40.85	Peak	H	34.21	-31.98		43.08	97.96	54.88
5 958.57	40.29	Peak	H	34.40	-31.87		42.82	68.33	25.51

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11n_HT20 (Band 1)_MCS0

A. Low Channel (5 180 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	37.50	Peak	V	31.80	-33.56	-	35.74	74.00	38.26
*4 500.00	29.28	Average	V	31.80	-33.56	0.43	27.95	54.00	26.05
*5 147.27	43.64	Peak	V	33.30	-32.67	-	44.27	74.00	29.73
*5 148.06	34.26	Average	V	33.30	-32.67	0.43	35.32	54.00	18.68
*5 150.00	42.16	Peak	V	33.30	-32.67	-	42.79	74.00	31.21
*5 150.00	34.35	Average	V	33.30	-32.67	0.43	35.41	54.00	18.59

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 240 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11n_HT20 (Band 2A)_MCS0

A. Low Channel (5 260 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 300 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 320 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*5 350.00	38.60	Peak	V	33.70	-32.44	-	39.86	74.00	34.14
*5 350.00	31.15	Average	V	33.70	-32.44	0.43	32.84	54.00	21.16
*5 351.71	42.06	Peak	V	33.70	-32.44	-	43.32	74.00	30.68
*5 350.27	31.44	Average	V	33.70	-32.44	0.43	33.13	54.00	20.87
*5 460.00	36.71	Peak	V	33.74	-32.21	-	38.24	74.00	35.76
*5 460.00	29.07	Average	V	33.74	-32.21	0.43	31.03	54.00	22.97

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11n_HT20 (Band 2C)_MCS0

A. Low Channel (5 500 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	37.33	Peak	V	33.90	-32.44	-	38.79	74.00	35.21
*5 350.00	27.23	Average	V	33.90	-32.44	0.43	29.12	54.00	24.88
*5 459.38	41.32	Peak	V	33.90	-32.21	-	43.01	74.00	30.99
*5 456.26	31.12	Average	V	33.90	-32.21	0.43	33.24	54.00	20.76
*5 460.00	39.38	Peak	V	33.90	-32.21	-	41.07	74.00	32.93
*5 460.00	31.22	Average	V	33.90	-32.21	0.43	33.34	54.00	20.66

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 580 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 720 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11n_HT20 (Band 3)_MCS0

A. Low Channel (5 745 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 602.76	39.77	Peak	H	33.70	-32.19	41.28	68.23	26.95
5 676.29	40.80	Peak	H	33.81	-32.10	42.51	87.68	45.17
5 701.07	40.98	Peak	H	33.90	-32.07	42.81	105.53	62.72
5 722.77	40.45	Peak	H	33.90	-32.11	42.24	117.14	74.90

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 785 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 825 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 851.96	41.86	Peak	H	34.01	-31.94	43.93	117.76	73.83
5 857.01	41.39	Peak	H	34.04	-31.95	43.48	110.26	66.78
5 879.76	40.12	Peak	H	34.18	-31.98	42.32	101.71	59.39
5 946.39	39.90	Peak	H	34.39	-31.92	42.37	68.23	25.86

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT40 (Band 1)_MCS0

A. Low Channel (5 190 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	36.90	Peak	V	31.80	-33.56	-	35.14	74.00	38.86
*4 500.00	29.79	Average	V	31.80	-33.56	0.44	28.47	54.00	25.53
*4 590.08	40.22	Peak	V	31.70	-33.60	-	38.32	74.00	35.68
*5 148.06	30.48	Average	V	33.30	-32.67	0.44	31.55	54.00	22.45
*5 150.00	38.99	Peak	V	33.30	-32.67	-	39.62	74.00	34.38
*5 150.00	30.26	Average	V	33.30	-32.67	0.44	31.33	54.00	22.67

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 230 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT40 (Band 2A)_MCS0

A. Low Channel (5 270 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 310 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	40.25	Peak	V	33.70	-32.44	-	41.51	74.00	32.49
*5 350.00	32.10	Average	V	33.70	-32.44	0.44	33.80	54.00	20.20
*5 350.99	41.86	Peak	V	33.70	-32.44	-	43.12	74.00	30.88
*5 351.71	32.27	Average	V	33.70	-32.44	0.44	33.97	54.00	20.03
*5 460.00	36.34	Peak	V	33.74	-32.21	-	37.87	74.00	36.13
*5 460.00	29.08	Average	V	33.74	-32.21	0.44	31.05	54.00	22.95

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT40 (Band 2C)_MCS0

A. Low Channel (5 510 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*5 350.00	36.33	Peak	V	33.90	-32.44	-	37.79	74.00	36.21
*5 350.00	27.11	Average	V	33.90	-32.44	0.44	29.01	54.00	24.99
*5 448.20	41.35	Peak	V	33.90	-32.22	-	43.03	74.00	30.97
*5 458.86	30.97	Average	V	33.90	-32.21	0.44	33.10	54.00	20.90
*5 460.00	38.75	Peak	V	33.90	-32.21	-	40.44	74.00	33.56
*5 460.00	30.76	Average	V	33.90	-32.21	0.44	32.89	54.00	21.11

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 550 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 710 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT40 (Band 3)_MCS0

A. Low Channel (5 755 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 600.51	40.46	Peak	H	33.70	-32.19		41.97	68.23	26.26
5 671.99	40.91	Peak	H	33.79	-32.10		42.60	84.50	41.90
5 713.35	42.50	Peak	H	33.90	-32.10		44.30	108.97	64.67
5 722.77	41.71	Peak	H	33.90	-32.11		43.50	117.14	73.64

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 795 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 854.49	39.82	Peak	H	34.03	-31.94		41.91	111.99	70.08
5 868.96	40.32	Peak	H	34.11	-31.97		42.46	106.92	64.46
5 883.21	40.36	Peak	H	34.20	-31.98		42.58	99.15	56.57
5 937.20	40.71	Peak	H	34.37	-31.93		43.15	68.23	25.08

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT80 (Band 1)_MCS0

A. Middle Channel (5 210 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 500.00	38.03	Peak	V	31.80	-33.56	-	36.27	74.00	37.73
*4 500.00	29.32	Average	V	31.80	-33.56	0.86	28.42	54.00	25.58
*5 145.69	45.96	Peak	V	33.30	-32.67	-	46.59	74.00	27.41
*5 148.06	36.42	Average	V	33.30	-32.67	0.86	37.91	54.00	16.09
*5 150.00	45.28	Peak	V	33.30	-32.67	-	45.91	74.00	28.09
*5 150.00	36.87	Average	V	33.30	-32.67	0.86	38.36	54.00	15.64

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT80 (Band 2A)_MCS0

A. Middle Channel (5 290 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*5 350.00	42.80	Peak	V	33.70	-32.44	-	44.06	74.00	29.94
*5 350.00	34.38	Average	V	33.70	-32.44	0.86	36.50	54.00	17.50
*5 351.95	47.28	Peak	V	33.70	-32.44	-	48.54	74.00	25.46
*5 350.99	35.18	Average	V	33.70	-32.44	0.86	37.30	54.00	16.70
*5 460.00	37.12	Peak	V	33.74	-32.21	-	38.65	74.00	35.35
*5 460.00	29.46	Average	V	33.74	-32.21	0.86	31.85	54.00	22.15

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT80 (Band 2C)_MCS0

A. Low Channel (5 530 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	36.34	Peak	V	33.90	-32.44	-	37.80	74.00	36.20
*5 350.00	26.94	Average	V	33.90	-32.44	0.86	29.26	54.00	24.74
*5 456.26	43.72	Peak	V	33.90	-32.21	-	45.41	74.00	28.59
*5 458.08	33.03	Average	V	33.90	-32.21	0.86	35.58	54.00	18.42
*5 460.00	41.58	Peak	V	33.90	-32.21	-	43.27	74.00	30.73
*5 460.00	32.04	Average	V	33.90	-32.21	0.86	34.59	54.00	19.41

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 690 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

802.11ac_VHT80 (Band 3)_MCS0

A. Middle Channel (5 775 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 634.92	40.76	Peak	V	33.70	-32.14	42.32	68.23	25.91
5 692.67	40.62	Peak	V	33.87	-32.08	42.41	99.80	57.39
5 703.93	41.40	Peak	V	33.90	-32.08	43.22	106.33	63.11
5 723.80	40.38	Peak	V	33.90	-32.11	42.17	119.49	77.32
5 852.65	39.33	Peak	V	34.02	-31.94	41.41	116.19	74.78
5 866.66	40.46	Peak	V	34.10	-31.97	42.59	107.56	64.97
5 890.33	40.96	Peak	V	34.24	-32.00	43.20	93.88	50.68
5 963.17	40.25	Peak	V	34.40	-31.85	42.80	68.38	25.58

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

Remark;


1. “*” means the restricted band.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using Peak / average detector mode if frequency was in restricted band. Otherwise the frequency was out of restricted band, only peak detector should be used.
3. Actual = Reading + AF + AMP + CL + (DF).
4. If frequency was out of restricted band, the calculation method for peak limit is same as below.

$$68.23 \text{ dB}\mu\text{V/m} = \text{EIRP} - 20 \log(d) + 104.77 = -27 - 20 \log(3) + 104.77$$
5. In case of the emissions within $\pm 75 \text{ MHz}$ from band edge of band 3, limit should be adjusted to emission mask of 15.407(4)(i).
6. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
7. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.


- Test plots

OFDM: 802.11a (6 Mbps)


Low channel Band edge (Peak) - Band 1




Low channel Band edge (Average) - Band 1




High channel Band edge (Peak) - Band 2A




High channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



Low channel Band edge (Peak) - Band 3




High channel Band edge (Peak) - Band 3




OFDM: 802.11n20_HT20 (MCS0)


Low channel Band edge (Peak) - Band 1




Low channel Band edge (Average) - Band 1




High channel Band edge (Peak) - Band 2A




High channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



Low channel Band edge (Peak) - Band 3




High channel Band edge (Peak) - Band 3




OFDM: 802.11ac_VHT40 (MCS0)


Low channel Band edge (Peak) - Band 1




Low channel Band edge (Average) - Band 1




High channel Band edge (Peak) - Band 2A




High channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



Low channel Band edge (Peak) - Band 3




High channel Band edge (Peak) - Band 3




OFDM: 802.11ac_VHT80 (MCS0)


Middle channel Band edge (Peak) - Band 1




Middle channel Band edge (Average) - Band 1




Middle channel Band edge (Peak) - Band 2A




Middle channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



Middle channel Band edge (Peak) - Band 3



Middle channel Band edge (Peak) - Band 3



3. 26 dB Bandwidth & 99 % Bandwidth

3.1. Test Setup



3.2. Limit

None; for reporting purpose only.

3.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

3.3.1. 26 dB Bandwidth

1. This measurement settings are specified in section II.C.1 of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = approximately 1 % of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

3.2.2. 99 % Bandwidth

1. This measurement settings are specified in section II.D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set center frequency to the nominal EUT channel center frequency.
3. Set span = 1.5 times to 5.0 times the OBW.
4. Set RBW = 1 % to 5 % of the OBW.
5. Set VBW $\geq 3 \times$ RBW.
6. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
7. Use the 99 % power bandwidth function of the instrument (if available).
8. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % occupied bandwidth is the difference between these two frequencies.

In the result,

- DFS requirements are not applicable in the 5 150 MHz ~ 5 250 MHz.

Remark;

In case of band crossing channels 138, 142 and 144, the measurement is complied with section III.A of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

3.4. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

Test mode: 11a

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 180	36	6	21.201	-
	5 220	44		21.129	-
	5 240	48		20.839	17.019
U-NII 2A	5 260	52		20.984	-
	5 300	60		21.056	-
	5 320	64		21.056	-
U-NII 2C	5 500	100		21.201	-
	5 580	116		21.056	-
	5 720	144		21.056	-
U-NII 3	5 745	149		20.839	-
	5 785	157		21.129	-
	5 825	165		21.056	-

Test mode: 11n_HT20

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 180	36	MCS0	21.418	-
	5 220	44		21.563	-
	5 240	48		21.780	18.119
U-NII 2A	5 260	52		21.563	-
	5 300	60		21.418	-
	5 320	64		21.346	-
U-NII 2C	5 500	100		21.635	-
	5 580	116		21.491	-
	5 720	144		21.491	-
U-NII 3	5 745	149		21.491	-
	5 785	157		21.418	-
	5 825	165		21.418	-

Test mode: 11ac_VHT40

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 190	38	MCS0	40.289	-
	5 230	46		40.058	36.237
U-NII 2A	5 270	54		40.289	-
	5 310	62		40.058	-
U-NII 2C	5 510	102		40.289	-
	5 550	110		40.174	-
	5 710	142		40.289	-
U-NII 3	5 755	151		40.174	-
	5 795	159		40.289	-

Test mode: 11ac_VHT80

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 210	42	MCS0	82.431	75.716
U-NII 2A	5 290	58		81.968	-
U-NII 2C	5 530	106		82.200	-
	5 690	138		82.200	-
U-NII 3	5 775	155		81.968	-

Band-crossing channel


Mode	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)
11a	5 720	144	6	15.536
11n_HT20	5 720	144	MCS0	15.651
11ac_VHT40	5 710	142	MCS0	35.029
11ac_VHT80	5 690	138	MCS0	75.984

- Test plots


26 dB Bandwidth

802.11a (Band 1)


Low Channel
(5 180 MHz)



Middle Channel
(5 220 MHz)




High Channel
(5 240 MHz)




802.11a (Band 2A)


Low Channel
(5 260 MHz)



Middle Channel
(5 300 MHz)




High Channel
(5 320 MHz)




802.11a (Band 2C)


Low Channel
(5 500 MHz)



Middle Channel
(5 580 MHz)




High Channel
(5 720 MHz)




802.11a (Band 3)


Low Channel
(5 745 MHz)



Middle Channel
(5 785 MHz)




High Channel
(5 825 MHz)




802.11n_HT20 (Band 1)

Low Channel (5 180 MHz)


Low Channel
(5 180 MHz)



Middle Channel
(5 220 MHz)




High Channel
(5 240 MHz)




802.11n_HT20 (Band 2A)


Low Channel
(5 260 MHz)



Middle Channel
(5 300 MHz)




High Channel
(5 320 MHz)




802.11n_HT20 (Band 2C)


Low Channel
(5 500 MHz)



Middle Channel
(5 580 MHz)




High Channel
(5 720 MHz)




802.11n_HT20 (Band 3)


Low Channel
(5 745 MHz)



Middle Channel
(5 785 MHz)




High Channel
(5 825 MHz)




802.11ac_VHT40 (Band 1)

Low Channel
(5 190 MHz)




High Channel
(5 230 MHz)




802.11ac_VHT40 (Band 2A)

Low Channel
 (5 270 MHz)




High Channel
 (5 310 MHz)




802.11ac_VHT40 (Band 2C)


Low Channel
(5 510 MHz)



Middle Channel
(5 550 MHz)




High Channel
(5 710 MHz)




802.11ac_VHT40 (Band 3)

Low Channel
(5 755 MHz)




High Channel
(5 795 MHz)




802.11ac_VHT80 (Band 1)

Middle Channel
(5 210 MHz)




802.11ac_VHT80 (Band 2A)

Middle Channel
(5 290 MHz)




802.11ac_VHT80 (Band 2C)

Low Channel
(5 530 MHz)




High Channel
(5 690 MHz)



802.11ac_VHT80 (Band 3)


Middle Channel
(5 775 MHz)



99 % Bandwidth


802.11a

High Channel (5 240 MHz)




802.11n_HT20 (Band 1)

High Channel (5 240 MHz)




802.11ac_VHT40 (Band 1)

High Channel (5 230 MHz)




802.11ac_VHT80 (Band 1)

Middle Channel (5 210 MHz)




Band-crossing channels


802.11a (5 720 MHz)



802.11n_HT20 (5 720 MHz)



802.11ac_VHT40 (5 710 MHz)



802.11ac_VHT80 (5 690 MHz)

