

## FCC/IC TEST REPORT

Test report No.: EMC- FCC- R0095  
FCC ID: TQ8-AM110TFGG  
IC: 5074A-AM110TFGG  
Type of equipment: DIGITAL CAR AUDIO SYSTEM  
Basic Model Name: AM110TFGG  
Variant Model name: AM110TFGN, AM110TFGE, AM110TFGL  
Applicant: Hyundai Mobis Co., Ltd.  
Max.RF Output Power: 3.09 dBm  
FCC Rule Part(s): FCC Part 15 Subpart C 15.247  
IC Rule: RSS-210, RSS-GEN  
Frequency Range: 2 402 MHz ~ 2 480 MHz  
Test result: Complied

The above equipment was tested by EMC compliance Testing Laboratory for compliance with the requirements of FCC Rules and Regulations.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of test: February 18, 2013 ~ February 26, 2013

Issued date: March 4, 2013



Tested by:

SON, MIN GI



Approved by:

KIM, CHANG MIN

## [ Contents ]

|  |           |
|--|-----------|
| <b>1. Client information.....</b>                            | <b>3</b>  |
| <b>2. Laboratory information .....</b>                       | <b>4</b>  |
| <b>3. Description of E.U.T.....</b>                          | <b>5</b>  |
| 3.1 Basic description.....                                   | 5         |
| 3.2 General description .....                                | 5         |
| 3.3 Test frequency.....                                      | 6         |
| 3.4 Test Voltage .....                                       | 6         |
| <b>4. Summary of test results.....</b>                       | <b>7</b>  |
| 4.1 Standards & results .....                                | 7         |
| 4.2 Uncertainty .....  | 7         |
| <b>5. Test results .....</b>                                 | <b>8</b>  |
| 5.1 Antenna Requirement.....                                 | 8         |
| 5.2 Maximum Peak Output Power .....                          | 9         |
| 5.3 Carrier Frequency Separation .....                       | 14        |
| 5.4 20 dB Channel Bandwidth .....                            | 19        |
| 5.5 Number of Hopping Channels .....                         | 24        |
| 5.6 Time of Occupancy(Dwell Time) .....                      | 28        |
| 5.7 Spurious Emission, Band edge, and Restricted bands ..... | 33        |
| 5.8 Receiver Spurious Emissions .....                        | 53        |
| 5.9 RF Exposure.....   | 60        |
| <b>6. Test equipment used for test .....</b>                 | <b>61</b> |

**Appendix 1 Test setup photos**

**Appendix 2 External photos of EUT**

**Appendix 3 Internal photos of EUT**

**Appendix 4 Block diagram**

**Appendix 5 Schematics**

**Appendix 6 User manual**

**Appendix 7 Part list**

**Appendix 8 Layout diagram**

**Appendix 9 Antenna Specification**

## 1. Client information

**Applicant:** Hyundai Mobis Co., Ltd.  
**Address:** 80-9, Mabook-dong, Giheung-gu, Yongin-shi, Gyunggi-do, Korea (446-912)  
**Telephone number:** +82-31-260-0092  
**Facsimile number** +82-31-899-1788  
**Contact person:** Jong Tae Kim / dounu@mobil.co.kr

**Manufacturer:** Hyundai Mobis Co., Ltd.  
**Address :** 723, Mundeok-Ri, Munbaek-Myeon, Jincheon-Gun, Chungcheongbuk-Do, 365-862 Korea

## 2. Laboratory information

### Address

EMC Compliance Ltd.  
480-5 Shin-dong, Yeongtong-gu, Suwon-city, Gyunggi-do, 443-390, Korea  
Telephone Number: 82 31 336 9919 Facsimile Number: 82 31 336 4767

### Certificate

CBTL Testing Laboratory, KOLAS NO.: 231  
FCC Filing No.: 508785  
VCCI Registration No.: C-1713, R-1606, T-258  
IC Recognition No.: 8035A-2

### SITE MAP



### 3. Description of E.U.T.

#### 3.1 Basic description

|                                 |   |
|---------------------------------|---|
| <b>Applicant :</b>              | Hyundai Mobis Co., Ltd.   |
| <b>Address of Applicant:</b>    | 80-9, Mabook-dong, Giheung-gu, Yongin-shi, Gyunggi-do, Korea (446-912)        |
| <b>Manufacturer:</b>            | Hyundai Mobis Co., Ltd.   |
| <b>Address of Manufacturer:</b> | 723, Mundok-Ri, Munbaek-Myeon, Jincheon-Gun, Chungcheongbuk-Do, 365-862 Korea |
| <b>Type of equipment:</b>       | DIGITAL CAR AUDIO SYSTEM  |
| <b>Basic Model:</b>             | AM110TFGG   |
| <b>Variant Model:</b>           | AM110TFGN, AM110TFGE, AM110TFGL*  |
| <b>Serial number:</b>           | Proto Type  |

\* Variant model names are different only for the marketing area, and all model names are electrically identical in construction, radio characteristics, and features.

#### 3.2 General description

|                           |  |
|---------------------------|--|
| <b>Frequency Range</b>    | 2 402 MHz ~ 2 480 MHz  |
| <b>Type of Modulation</b> | Modulation technologies: FHSS<br>Modulation : GFSK, $\pi/4$ DQPSK, 8DPSK |
| <b>Number of Channels</b> | 79 channels  |
| <b>Type of Antenna</b>    | Integral   |
| <b>Antenna Gain</b>       | 3.5 dBi  |
| <b>Transmit Power</b>     | 3.09 dBm   |
| <b>Power supply</b>       | 14.4 V DC  |

### 3.3 Test frequency

|                         | <b>Frequency</b> |
|-------------------------|------------------|
| <b>Low frequency</b>    | <b>2 402 MHz</b> |
| <b>Middle frequency</b> | <b>2 441 MHz</b> |
| <b>High frequency</b>   | <b>2 480 MHz</b> |

### 3.4 Test Voltage

| <b>mode</b>             | <b>Voltage</b>   |
|-------------------------|------------------|
| <b>Norminal voltage</b> | <b>DC 14.4 V</b> |

#### ※ 15.247 Requirements for Bluetooth transmitter

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - 1) This system is hopping pseudo-randomly.
  - 2) Each frequency is used equally on the average by each transmitter.
  - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
  - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

## 4. Summary of test results

### 4.1 Standards & results

| FCC Rule   | IC Rule  | Parameter                                    | Report Section | Test Result |
|--|--|--|----------------|-------------|
| 15.203,<br>15.247(b)(4)  | RSS-GEN, 7.1.2                                   | Antenna Requirement                          | 5.1            | C           |
| 15.247(b)(1),<br>(4)   | RSS-210, A8.4(2)                                 | Maximum Peak Output Power                    | 5.2            | C           |
| 15.247(a)(1)   | RSS-210, A8.1(b)                                 | Carrier Frequency Separation                 | 5.3            | C           |
| 15.247(a)(1)   | RSS-210, A8.1(a)                                 | 20dB Channel Bandwidth                       | 5.4            | C           |
| -  | RSS-210, A1.1                                    | Occupied Bandwidth                           | 5.4            | C           |
| 15.247(a)(iii)<br>15.247(b)(1)   | RSS-210, A8.1(d)                                 | Number of Hopping Channel                    | 5.5            | C           |
| 15.247(a) (iii)  | RSS-210, A8.1(d)                                 | Time of Occupancy(Dwell Time)                | 5.6            | C           |
| 15.247(d),<br>15.205(a),<br>15.209(a)                                      | RSS-210, A8.5<br>RSS-210, A2.9<br>RSS-GEN, 7.2.3 | Spurious Emission, BandEdge, Restricted Band | 5.7            | C           |
| -  | RSS-GEN, 4.10                                    | Receiver Spurious Emissions                  | 5.8            | C           |
| 15.247(i),<br>1.1307(b)(1)   | -  | RF Exposure                                  | 5.10           | C           |
| Note: C=complies<br>NC= Not complies<br>NT=Not tested<br>NA=Not Applicable |  |  |                |             |

\* The method of measurement used to test this DSS device is FCC Public Notice DA 00-705

\* The general test methods used to test this device is ANSI C63.4 2003 (or 2009, or ANSI C63.10 2009)

### 4.2 Uncertainty

| Measurement Item     | Combined Standard Uncertainty Uc   | Expanded Uncertainty U = KUc (K = 2)   |
|----------------------|--|--|
| Conducted RF power   | ± 0.29 dB  | ± 0.58 dB  |
| Radiated disturbance | 30 MHz ~ 300 MHz : + 2.43 dB, - 2.44 dB<br>300 MHz ~ 1 000 MHz : + 2.49 dB, - 2.50 dB<br>1 GHz ~ 6 GHz : + 3.10 dB, - 3.10 dB<br>6 GHz ~ 18 GHz : + 3.21 dB, - 3.27 dB | 30 MHz ~ 300 MHz : + 4.86 dB, - 4.88 dB<br>300 MHz ~ 1 000 MHz : + 4.98 dB, - 4.99 dB<br>1 GHz ~ 6 GHz : + 6.19 dB, - 6.20 dB<br>6 GHz ~ 18 GHz : + 6.41 dB, - 6.53 dB |

## 5. Test results

### 5.1 Antenna Requirement

#### 5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 5.1.2 Result

-Complied

The transmitter has an integral dipole antenna. type of antenna.  
The directional gain of the antenna is 3.5 dBi.

## 5.2 Maximum Peak Output Power

### 5.2.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 5.2.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW > the 20 dB bandwidth of the emission being measured  $VBW \geq RBW$  Sweep = auto Detector function = peak Trace = max hold
5. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
6. Repeat above procedures until all frequencies measured were complete.

### 5.2.3 Test Result

-Complied

- GFSK

| Channel | Frequency (MHz) | Result (dBm) | Limit (dBm) | Margin (dB) |
|---------|-----------------|--------------|-------------|-------------|
| Low     | 2 402           | 1.73         | 30.00       | 28.27       |
| Middle  | 2 441           | 1.77         | 30.00       | 28.23       |
| High    | 2 480           | 2.18         | 30.00       | 27.82       |

-  $\pi/4$ DQPSK

| Channel | Frequency (MHz) | Result (dBm) | Limit (dBm) | Margin (dB) |
|---------|-----------------|--------------|-------------|-------------|
| Low     | 2 402           | 2.72         | 30.00       | 27.28       |
| Middle  | 2 441           | 2.67         | 30.00       | 27.33       |
| High    | 2 480           | 2.82         | 30.00       | 27.18       |

- 8DPSK

| Channel | Frequency (MHz) | Result (dBm) | Limit (dBm) | Margin (dB) |
|---------|-----------------|--------------|-------------|-------------|
| Low     | 2 402           | 2.87         | 30.00       | 27.13       |
| Middle  | 2 441           | 2.85         | 30.00       | 27.15       |
| High    | 2 480           | <b>3.09</b>  | 30.00       | 26.91       |

NOTE:


1. Since the directional gain of the integral antenna declared by the manufacturer ( $G_{ANT} = 3.5$  dBi) does not exceed 6.0 dBi, there was no need to reduce the output power.
2. We took the insertion loss of the cable loss into consideration within the measuring instrument.

## 5.2.4 Test Plot


Figure 1. Plot of the Maximum Peak Output Power (Conducted)

- GFSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




-  $\pi/4$ DQPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




- 8DPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)



Highest Channel  
(2 480 MHz)



## 5.3 Carrier Frequency Separation

### 5.3.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

### 5.3.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface.
4. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels  
Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span Video (or Average) Bandwidth (VBW)  $\geq$  RBW Sweep = auto Detector function = peak Trace = max hold
5. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
6. Repeat above procedures until all frequencies measured were complete.

### 5.3.3 Test Result

-Complied

- GFSK

| Channel | Carrier frequency separation(MHz) | Limit  |
|---------|-----------------------------------|--|
| Low     | 0.999                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |
| Middle  | 1.002                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |
| High    | 1.005                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |

-  $\pi/4$ DQPSK

| Channel | Carrier frequency separation(MHz) | Limit  |
|---------|-----------------------------------|--|
| Low     | 1.005                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |
| Middle  | 1.002                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |
| High    | 1.002                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |

- 8DPSK

| Channel | Carrier frequency separation(MHz) | Limit  |
|---------|-----------------------------------|--|
| Low     | 0.996                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |
| Middle  | 0.996                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |
| High    | 1.002                             | $\geq 25$ kHz or two-thirds of the 20 dB bandwidth |


NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

### 5.3.4 Test Plot


Figure 2. Plot of the Carrier Frequency Separation (Conducted)

- GFSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




-  $\pi/4$ DQPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




- 8DPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)



Highest Channel  
(2 480 MHz)



## 5.4 20 dB Channel Bandwidth

### 5.4.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

### 5.4.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer as follows: Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel RBW  $\geq$  1% of the 20 dB bandwidth VBW  $\geq$  RBW Sweep = auto Detector function = peak Trace = max hold
5. Set a reference level on it equal to the highest peak value.
6. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
7. Repeat above procedures until all frequencies measured were complete..

### 5.4.3 Test Result

-Complied

- GFSK

| Channel | 20dB Channel Bandwidth(MHz) | Carrier frequency Separation(MHz) | Occupied Bandwidth (99% BW)(MHz) |
|---------|-----------------------------|-----------------------------------|----------------------------------|
| Low     | 0.935                       | 0.999                             | 0.874                            |
| Middle  | 0.933                       | 1.002                             | 0.874                            |
| High    | 0.934                       | 1.005                             | 0.861                            |

-  $\pi/4$ DQPSK

| Channel | 20dB Channel Bandwidth(MHz) | Carrier frequency Separation(MHz) | Occupied Bandwidth (99% BW)(MHz) |
|---------|-----------------------------|-----------------------------------|----------------------------------|
| Low     | 1.268                       | 1.005                             | 1.192                            |
| Middle  | 1.277                       | 1.002                             | 1.212                            |
| High    | 1.317                       | 1.002                             | 1.206                            |

- 8DPSK


| Channel | 20dB Channel Bandwidth(MHz) | Carrier frequency Separation(MHz) | Occupied Bandwidth (99% BW)(MHz) |
|---------|-----------------------------|-----------------------------------|----------------------------------|
| Low     | 1.289                       | 0.996                             | 1.226                            |
| Middle  | 1.283                       | 0.996                             | 1.223                            |
| High    | 1.298                       | 1.002                             | 1.219                            |

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.


#### 5.4.4 Test Plot

Figure 3. Plot of the 20dB Channel Bandwidth/ Occupied Bandwidth (Conducted)


- GFSK  
Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441MHz)




Highest Channel  
(2 480 MHz)




-  $\pi/4$ DQPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




- 8DPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)



Highest Channel  
(2 480 MHz)



## 5.5 Number of Hopping Channels

### 5.5.1 Regulation

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 5.5.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set the hopping function enabled by controlling it via UART interface.
4. Set the spectrum analyzer as follows: Span = the frequency band of operation RBW  $\geq$  1% of the span VBW  $\geq$  RBW Sweep = auto Detector function = peak Trace = max hold
5. Record the number of hopping channels.

### 5.5.3 Test Result

-Complied  
- GFSK

| Frequency         | Number of hopping channel | Limit     |
|-------------------|---------------------------|-----------|
| 2 402 – 2 480 MHz | 79                        | $\geq$ 15 |


- 8DPSK/  $\pi$ /4DQPSK

| Frequency         | Number of hopping channel | Limit     |
|-------------------|---------------------------|-----------|
| 2 402 – 2 480 MHz | 79                        | $\geq$ 15 |


### 5.5.4 Test Plot

Figure 4. Plot of the Number of Hopping Channels (Conducted)


- GFSK



-  $\pi/4$ DQPSK



- 8DPSK



## 5.6 Time of Occupancy(Dwell Time)

### 5.6.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 5.6.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface.
4. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel RBW = 1 MHz VBW  $\geq$  RBW Sweep = as necessary to capture the entire dwell time per hopping channel Detector function = peak Trace = max hold
5. Measure the dwell time using the marker-delta function.
6. Repeat above procedures until all frequencies measured were complete.
7. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

### 5.6.3 Test Result

-Complied

- GFSK

| Channel | Reading[ms] | Hopping rate[hop/s] | Number of Channels | Actual[s] | Limit[s] |
|---------|-------------|---------------------|--------------------|-----------|----------|
| Low     | 2.900       | 266.667             | 79                 | 0.309     | 0.40     |
| Middle  | 2.900       | 266.667             | 79                 | 0.309     | 0.40     |
| High    | 2.900       | 266.667             | 79                 | 0.309     | 0.40     |

-  $\pi/4$ DQPSK

| Channel | Reading[ms] | Hopping rate[hop/s] | Number of Channels | Actual[s] | Limit[s] |
|---------|-------------|---------------------|--------------------|-----------|----------|
| Low     | 2.905       | 266.667             | 79                 | 0.310     | 0.40     |
| Middle  | 2.905       | 266.667             | 79                 | 0.310     | 0.40     |
| High    | 2.905       | 266.667             | 79                 | 0.310     | 0.40     |

- 8DPSK

| Channel | Reading[ms] | Hopping rate[hop/s] | Number of Channels | Actual[s] | Limit[s] |
|---------|-------------|---------------------|--------------------|-----------|----------|
| Low     | 2.905       | 266.667             | 79                 | 0.310     | 0.40     |
| Middle  | 2.905       | 266.667             | 79                 | 0.310     | 0.40     |
| High    | 2.905       | 266.667             | 79                 | 0.310     | 0.40     |

**Actual = Reading × (Hopping rate / Number of channels) × Test period**

**Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds]**

NOTE:


1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

### 5.6.4 Test Plot


Figure 5. Plot of the Time of Occupancy (Conducted)

- GFSK


Lowest Channel  
(2 402 MHz)




Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




-  $\pi/4$ DQPSK  
Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)




Highest Channel  
(2 480 MHz)




- 8DPSK


Lowest Channel  
(2 402 MHz)



Middle Channel  
(2 441 MHz)



Highest Channel  
(2 480 MHz)



## 5.7 Spurious Emission, Band edge, and Restricted bands

### 5.7.1 Regulation

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency (MHz) | Field strength ( $\mu$ V/m @ 3m) | Field strength (dB $\mu$ V/m @ 3m) |
|-----------------|----------------------------------|------------------------------------|
| 30–88           | 100                              | 40.0                               |
| 88–216          | 150                              | 43.5                               |
| 216–960         | 200                              | 46.0                               |
| Above 960       | 500                              | 54.0                               |

According to §15.109(a), for an unintentional device, except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the above table.

\*\* The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector and above 1000 MHz are based on the average value of measured emissions.

## 5.7.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

- 1) Band-edge Compliance of RF Conducted Emissions
- 2)

1. Set the spectrum analyzer as follows:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation  
RBW  $\geq$  1% of the span  
VBW  $\geq$  RBW  
Sweep = auto  
Detector function = peak  
Trace = max hold

2. Allow the trace to stabilize. Set the marker on the emission at the band-edge, or on the highest modulation product outside of the band, if this level is greater than that at the band-edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
3. Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

### 2) Spurious RF Conducted Emissions:

1. Set the spectrum analyzer as follows:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.  
Typically, several plots are required to cover this entire span.

RBW = 100 kHz  
VBW  $\geq$  RBW  
Sweep = auto  
Detector function = peak  
Trace = max hold

2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.  
a 4  $\times$  4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
5. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

3) Spurious Radiated Emissions:

1. The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
2. The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
3. The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 kHz to 30 MHz using the loop antenna, and from 30 to 1000 MHz using the TRILOG broadband antenna, and from 1000 MHz to 26500 MHz using the horn antenna.
4. To obtain the final measurement data, the EUT was arranged on a turntable situated on a 4 × 4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
5. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

### 5.7.3 Test Result

-complied

1. Band edge compliance of RF Conducted Emissions was shown in figure 6.
2. Band edge compliance of RF Radiated Emissions was shown in figure 7.
3. Spurious RF conducted Emissions were shown in the Figure 8.

Note: We took the insertion loss of the cable into consideration within the measuring instrument.

4. Measured value of the Field strength of spurious Emissions (Radiated)

- GFSK

Low channel (2 402 MHz)

| Frequency<br>[MHz]                             | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 30 MHz</b> |                                |      |                     |                |                      |                     |                |
| Below<br>30.000                                | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Quasi-Peak DATA. Emissions below 1GHz</b>   |                                |      |                     |                |                      |                     |                |
| 36.01  | 120                            | V    | 41.6                | -14.4          | 27.2                 | 40.0                | 12.8           |
| 149.37   | 120                            | V    | 41.9                | -11.1          | 30.8                 | 43.5                | 12.7           |
| 159.98   | 120                            | V    | 43.5                | -11.0          | 32.5                 | 43.5                | 11.0           |
| 360.04   | 120                            | H    | 36.7                | -6.7           | 30.0                 | 46.0                | 16.0           |
| 480.08   | 120                            | H    | 32.7                | -3.3           | 29.4                 | 46.0                | 16.6           |
| 600.00   | 120                            | H    | 31.4                | 0.2            | 31.6                 | 46.0                | 14.4           |
| Above<br>600.000                               | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Peak DATA. Emissions above 1GHz</b>         |                                |      |                     |                |                      |                     |                |
| 2 352.24                                       | 1 000                          | V    | 47.9                | -1.2           | 46.7                 | 74.0                | 27.3           |
| 2809.75  | 1 000                          | V    | 56.2                | -0.5           | 55.7                 | 74.0                | 18.3           |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Average DATA. Emissions above 1GHz</b>      |                                |      |                     |                |                      |                     |                |
| 2 352.24                                       | 1 000                          | V    | 33.4                | -1.2           | 32.2                 | 54.0                | 21.8           |
| 2 809.75                                       | 1 000                          | V    | 36.8                | -0.5           | 36.3                 | 54.0                | 17.7           |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |

**Middle channel (2 441 MHz)**

| Frequency<br>[MHz]                             | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 30 MHz</b> |                                |      |                     |                |                      |                     |                |
| Below<br>30.000                                | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Quasi-Peak DATA. Emissions below 1GHz</b>   |                                |      |                     |                |                      |                     |                |
| 36.01  | 120                            | V    | 43.9                | -14.4          | 29.5                 | 40.0                | 10.5           |
| 149.37   | 120                            | V    | 41.9                | -11.1          | 30.8                 | 43.5                | 12.7           |
| 159.98   | 120                            | V    | 41.5                | -11.0          | 30.5                 | 43.5                | 13.0           |
| 360.04   | 120                            | H    | 37.9                | -6.7           | 31.2                 | 46.0                | 14.8           |
| 480.08   | 120                            | H    | 32.6                | -3.3           | 29.3                 | 46.0                | 16.7           |
| 600.00   | 120                            | H    | 31.4                | 0.2            | 31.6                 | 46.0                | 14.4           |
| Above<br>500.000                               | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Peak DATA. Emissions above 1GHz</b>         |                                |      |                     |                |                      |                     |                |
| 2 809.75                                       | 1 000                          | V    | 56.3                | -0.5           | 55.8                 | 74.0                | 18.2           |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Average DATA. Emissions above 1GHz</b>      |                                |      |                     |                |                      |                     |                |
| 2 809.75                                       | 1 000                          | V    | 49.6                | -0.5           | 49.1                 | 54.0                | 4.9            |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |

**High channel (2 480 MHz)**

| Frequency<br>[MHz]                             | Receiver<br>Bandwidth<br>[kHz] | Pol.<br>[V/H] | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|---------------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 30 MHz</b> |                                |               |                     |                |                      |                     |                |
| Below<br>30.000                                | Not<br>Detected                | -             | -                   | -              | -                    | -                   | -              |
|  |                                |               |                     |                |                      |                     |                |
| <b>Quasi-Peak DATA. Emissions below 1GHz</b>   |                                |               |                     |                |                      |                     |                |
| 36.01  | 120                            | V             | 43.6                | -14.4          | 29.2                 | 40.0                | 10.8           |
| 149.37   | 120                            | V             | 43.0                | -11.1          | 31.9                 | 43.5                | 11.6           |
| 159.98   | 120                            | V             | 41.5                | -11.0          | 30.5                 | 43.5                | 13.0           |
| 360.04   | 120                            | H             | 36.3                | -6.7           | 29.6                 | 46.0                | 16.4           |
| 480.08   | 120                            | H             | 32.7                | -3.3           | 29.4                 | 46.0                | 16.6           |
| 600.00   | 120                            | H             | 31.4                | 0.2            | 31.6                 | 46.0                | 14.4           |
| Above<br>600.000                               | Not<br>Detected                | -             | -                   | -              | -                    | -                   | -              |
| <b>Peak DATA. Emissions above 1GHz</b>         |                                |               |                     |                |                      |                     |                |
| 2 483.50                                       | 1 000                          | V             | 57.6                | -1.0           | 56.6                 | 74.0                | 17.4           |
| 2 809.75                                       | 1 000                          | V             | 56.5                | -0.5           | 56.0                 | 74.0                | 18.0           |
| Above<br>3 000.00                              | Not<br>Detected                | -             | -                   | -              | -                    | -                   | -              |
|  |                                |               |                     |                |                      |                     |                |
| <b>Average DATA. Emissions above 1GHz</b>      |                                |               |                     |                |                      |                     |                |
| 2 483.50                                       | 1 000                          | V             | 40.7                | -1.0           | 39.7                 | 54.0                | 14.3           |
| 2 809.75                                       | 1 000                          | V             | 51.3                | -0.5           | 50.8                 | 54.0                | 3.2            |
| Above<br>3 000.00                              | Not<br>Detected                | -             | -                   | -              | -                    | -                   | -              |
|  |                                |               |                     |                |                      |                     |                |

- 8DPSK

**Low channel (2 402 MHz)**

| Frequency<br>[MHz]                             | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 30 MHz</b> |                                |      |                     |                |                      |                     |                |
| Below<br>30.000                                | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Quasi-Peak DATA. Emissions below 1GHz</b>   |                                |      |                     |                |                      |                     |                |
| 35.94  | 120                            | V    | 45.6                | -14.4          | 31.2                 | 40.0                | 8.8            |
| 76.20  | 120                            | H    | 52.3                | -16.2          | 36.1                 | 40.0                | 3.9            |
| 84.44  | 120                            | V    | 52.8                | -17.5          | 35.3                 | 40.0                | 4.7            |
| 152.71   | 120                            | V    | 45.6                | -11.0          | 34.6                 | 43.5                | 8.9            |
| 255.89   | 120                            | H    | 36.7                | -10.2          | 26.5                 | 46.0                | 19.5           |
| 297.72   | 120                            | H    | 37.6                | -8.6           | 29.0                 | 46.0                | 17.0           |
| 360.04   | 120                            | H    | 44.9                | -6.7           | 38.2                 | 46.0                | 7.8            |
| 479.96   | 120                            | H    | 39.3                | -3.3           | 36.0                 | 46.0                | 10.0           |
| Above<br>500.000                               | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Peak DATA. Emissions above 1GHz</b>         |                                |      |                     |                |                      |                     |                |
| 2 387.92                                       | 1 000                          | V    | 48.4                | -1.2           | 47.2                 | 74.0                | 26.8           |
| 2 809.75                                       | 1 000                          | V    | 55.2                | -0.5           | 54.7                 | 74.0                | 19.3           |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Average DATA. Emissions above 1GHz</b>      |                                |      |                     |                |                      |                     |                |
| 2 350.64                                       | 1 000                          | V    | 33.7                | -1.2           | 32.5                 | 54.0                | 21.5           |
| 2 809.75                                       | 1 000                          | V    | 49.6                | -0.5           | 49.1                 | 54.0                | 4.9            |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |

**Middle channel (2 441 MHz)**

| Frequency<br>[MHz]                             | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 30 MHz</b> |                                |      |                     |                |                      |                     |                |
| Below<br>30.000                                | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Quasi-Peak DATA. Emissions below 1GHz</b>   |                                |      |                     |                |                      |                     |                |
| 35.94  | 120                            | V    | 43.3                | -14.4          | 28.9                 | 40.0                | 11.1           |
| 51.22  | 120                            | V    | 38.6                | -12.9          | 25.7                 | 40.0                | 14.3           |
| 135.25   | 120                            | V    | 43.5                | -12.3          | 31.2                 | 43.5                | 12.3           |
| 151.37   | 120                            | V    | 45.1                | -11.1          | 34.0                 | 43.5                | 9.5            |
| Above<br>200.000                               | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Peak DATA. Emissions above 1GHz</b>         |                                |      |                     |                |                      |                     |                |
| 2 809.75                                       | 1 000                          | V    | 55.9                | -0.5           | 55.4                 | 74.0                | 18.6           |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Average DATA. Emissions above 1GHz</b>      |                                |      |                     |                |                      |                     |                |
| 2 809.75                                       | 1 000                          | V    | 49.2                | -0.5           | 48.7                 | 54.0                | 5.3            |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |

**High channel (2 480 MHz)**

| Frequency<br>[MHz]                             | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 30 MHz</b> |                                |      |                     |                |                      |                     |                |
| Below<br>30.000                                | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Quasi-Peak DATA. Emissions below 1GHz</b>   |                                |      |                     |                |                      |                     |                |
| 31.33  | 120                            | V    | 38.3                | -14.9          | 23.4                 | 40.0                | 16.6           |
| 35.94  | 120                            | V    | 46.6                | -14.4          | 32.2                 | 40.0                | 7.8            |
| 38.73  | 120                            | V    | 41.2                | -14.1          | 27.1                 | 40.0                | 12.9           |
| 44.31  | 120                            | V    | 36.1                | -13.4          | 22.7                 | 40.0                | 17.3           |
| 52.80  | 120                            | V    | 35.5                | -12.9          | 22.6                 | 40.0                | 17.4           |
| 84.68  | 120                            | V    | 42.5                | -17.5          | 25.0                 | 40.0                | 15.0           |
| 135.25   | 120                            | V    | 44.7                | -12.3          | 32.4                 | 43.5                | 11.1           |
| 152.22   | 120                            | V    | 45.6                | -11.0          | 34.6                 | 43.5                | 8.9            |
| 240.01   | 120                            | V    | 35.8                | -11.2          | 24.6                 | 46.0                | 21.4           |
| 359.92   | 120                            | V    | 38.7                | -6.7           | 32.0                 | 46.0                | 14.0           |
| Above<br>500.000                               | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Peak DATA. Emissions above 1GHz</b>         |                                |      |                     |                |                      |                     |                |
| 2 483.50                                       | 1 000                          | V    | 54.0                | -1.0           | 53.0                 | 74.0                | 21.0           |
| 2 809.75                                       | 1 000                          | V    | 56.1                | -0.5           | 55.6                 | 74.0                | 18.4           |
| Above<br>3000.00                               | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
| <b>Average DATA. Emissions above 1GHz</b>      |                                |      |                     |                |                      |                     |                |
| 2 483.50                                       | 1 000                          | V    | 39.7                | -1.0           | 38.7                 | 54.0                | 15.3           |
| 2 809.75                                       | 1 000                          | V    | 49.2                | -0.5           | 48.7                 | 54.0                | 5.3            |
| Above<br>3 000.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |

**Factor(dB) = ANT Factor + Amp Gain + Cable Loss**

**Margin (dB) = Limit - Result**

**[Result = Reading - Factor]**

1. H = Horizontal, V = Vertical Polarization

2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss

\* The spurious emission at the frequency does not fall in the restricted bands.

\*\* The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.


NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.

### 5.7.4 Test Plot


Figure 6. Plot of the Band Edge (Conducted)

- GFSK without Hopping

Lowest Channel  
(2 402 MHz)




Highest Channel  
(2 480 MHz)




- GFSK with Hopping

Lowest Channel  
(2 402 MHz)




Highest Channel  
(2 480 MHz)




-  $\pi/4$ DQPSK (without Hopping)

Lowest Channel  
(2 402 MHz)




Highest Channel  
(2 480 MHz)




-  $\pi/4$ DQPSK (with Hopping)

Lowest Channel  
(2 402 MHz)




Highest Channel  
(2 480 MHz)




- 8DPSK (without Hopping)

Lowest Channel  
(2 402 MHz)




Highest Channel  
(2 480 MHz)




- 8DPSK (with Hopping)

Lowest Channel  
(2 402 MHz)




Highest Channel  
(2 480 MHz)




### 5.7.4 Test Plot (Continue)

Figure 7. Plot of the Band Edge (Radiated)  
- GFSK


Lowest Channel(2 402 MHz): PEAK




Lowest Channel(2 402 MHz): AVERAGE



Highest Channel(2480 MHz): PEAK




Highest Channel(2480 MHz): AVERAGE




## - 8DPSK

-worst case


### Lowest Channel(2 402 MHz): PEAK



### Lowest Channel(2 402 MHz): AVERAGE



### Highest Channel(2480 MHz): PEAK



### Highest Channel(2480 MHz): AVERAGE






Figure 8. Plot of the Spurious RF conducted emissions  
- GFSK


Lowest Channel(2 402 MHz):30 MHz ~ 12 GHz




Lowest Channel(2 402 MHz):12 GHz ~ 25 GHz




Middle Channel(2 441 MHz): 30 MHz ~ 12 GHz




Middle Channel(2 441 MHz): 12 GHz ~ 25 GHz



Highest Channel(2 480 MHz): 30 MHz ~ 12 GHz




Highest Channel(2 480 MHz): 12 GHz ~ 25 GHz




-  $\pi/4$ DQPSK

Lowest Channel(2 402 MHz):30 MHz ~ 12 GHz




Copyright 2000-2004 Agilent Technologies

Middle Channel(2 441 MHz): 30 MHz ~ 12 GHz




Copyright 2000-2004 Agilent Technologies

Highest Channel(2 480 MHz): 30 MHz ~ 12 GHz




Copyright 2000-2004 Agilent Technologies

Lowest Channel(2 402 MHz):12 GHz ~ 25 GHz




Copyright 2000-2004 Agilent Technologies

Middle Channel(2 441 MHz): 12 GHz ~ 25 GHz



Copyright 2000-2004 Agilent Technologies


Highest Channel(2 480 MHz): 12 GHz ~ 25 GHz




Copyright 2000-2004 Agilent Technologies

- 8DPSK


Lowest Channel(2 402 MHz):30 MHz ~ 12 GHz




Lowest Channel(2 402 MHz):12 GHz ~ 25 GHz




Middle Channel(2 441 MHz): 30 MHz ~ 12 GHz




Middle Channel(2 441 MHz): 12 GHz ~ 25 GHz



Highest Channel(2 480 MHz): 30 MHz ~ 12 GHz



Highest Channel(2 480 MHz): 12 GHz ~ 25 GHz



## 5.8 Receiver Spurious Emissions

### 5.8.1 Regulation

The receiver shall be operated in the normal receive mode near the mid-point of the band in which the receiver is designed to operate.

Radiated emission measurements are to be performed on a test site registered with Industry Canada. As an alternative, the conducted measurement method may be used when the antenna is detachable. In such a case, the receiver spurious signal may be measured at the antenna port.

If the receiver is super-regenerative, stabilize it by coupling to it an unmodulated carrier on the receiver frequency (antenna conducted measurement) or by transmitting an unmodulated carrier on the receiver frequency from an antenna in the proximity of the receiver (radiated measurement). Taking care not to overload the receiver, vary the amplitude and frequency of the stabilizing signal to obtain the highest level of the spurious emissions from the receiver.

For either method, the search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is higher, to at least 3 times the highest tuneable or local oscillator frequency, whichever is higher, without exceeding 40 GHz.

For emissions below 1000 MHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. As an alternative to CISPR quasi-peak measurement, compliance with the emission limit can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization as required, with an equal or greater measurement bandwidth relative to the applicable CISPR quasi-peak bandwidth.

Above 1000 MHz, measurements shall be performed using an average detector with a minimum resolution bandwidth of 1 MHz.

### 5.8.2 Measurement Procedure

Radiated spurious emission measurements shall be performed with the receiver antenna connected to the receiver antenna terminals.

Spurious emissions from receivers shall not exceed the radiated limits shown in the table below:

| Frequency<br>(MHz) | Field Strength<br>(microvolts/m at 3 metres)* |
|--------------------|---|
| 30-88              | 100   |
| 88-216             | 150   |
| 216-960            | 200   |
| Above 960          | 500   |

\*Measurements for compliance with limits in the above table may be performed at distances other than 3 metres, in accordance with Section 7.2.7.

### 5.8.3 Test Result

-Complied

- GFSK

#### Low channel (2 402 MHz)

| Frequency<br>[MHz]                           | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 1GHz</b> |                                |      |                     |                |                      |                     |                |
| 51.77  | 120                            | V    | 29.5                | -12.9          | 16.6                 | 40.0                | 23.4           |
| 150.36                                       | 120                            | V    | 44.5                | -11.1          | 33.4                 | 43.5                | 10.1           |
| 599.63                                       | 120                            | H    | 18.9                | 0.2            | 19.1                 | 46.0                | 26.9           |
| Above<br>600.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |

#### Peak DATA. Emissions above 1GHz

|                   |                 |   |      |      |      |      |      |
|-------------------|-----------------|---|------|------|------|------|------|
| 2 809.75          | 1 000           | V | 55.6 | -0.5 | 55.1 | 74.0 | 18.9 |
| Above<br>3 000.00 | Not<br>Detected | - | -    | -    | -    | -    | -    |
|                   |                 |   |      |      |      |      |      |

#### Average DATA. Emissions above 1GHz

|                   |                 |   |      |      |      |      |     |
|-------------------|-----------------|---|------|------|------|------|-----|
| 2 809.75          | 1 000           | V | 51.2 | -0.5 | 50.7 | 54.0 | 3.3 |
| Above<br>3 000.00 | Not<br>Detected | - | -    | -    | -    | -    | -   |
|                   |                 |   |      |      |      |      |     |

**Middle channel (2 441 MHz)**

| Frequency<br>[MHz]                           | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 1GHz</b> |                                |      |                     |                |                      |                     |                |
| 36.01  | 120                            | V    | 43.9                | -14.4          | 29.5                 | 40.0                | 10.5           |
| 149.37                                       | 120                            | V    | 41.9                | -11.1          | 30.8                 | 43.5                | 12.7           |
| 159.98                                       | 120                            | V    | 43.2                | -11.0          | 32.2                 | 43.5                | 11.3           |
| 360.04                                       | 120                            | H    | 36.7                | -6.7           | 30.0                 | 46.0                | 16.0           |
| 480.08                                       | 120                            | H    | 32.7                | -3.3           | 29.4                 | 46.0                | 16.6           |
| 600.00                                       | 120                            | H    | 31.4                | 0.2            | 31.6                 | 46.0                | 14.4           |
| Above<br>300.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Peak DATA. Emissions above 1GHz</b>       |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 55.6                | -0.5           | 55.1                 | 74.0                | 18.9           |
| Above<br>3 000.00                            | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Average DATA. Emissions above 1GHz</b>    |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 51.1                | -0.5           | 50.6                 | 54.0                | 3.4            |
| Above<br>3 000.00                            | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |

**High channel (2 480 MHz)**

| Frequency<br>[MHz]                           | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 1GHz</b> |                                |      |                     |                |                      |                     |                |
| 36.01  | 120                            | V    | 42.6                | -14.4          | 28.2                 | 40.0                | 11.8           |
| 149.37                                       | 120                            | V    | 41.9                | -11.1          | 30.8                 | 43.5                | 12.7           |
| 159.98                                       | 120                            | V    | 41.6                | -11.0          | 30.6                 | 43.5                | 12.9           |
| 360.04                                       | 120                            | H    | 36.9                | -6.7           | 30.2                 | 46.0                | 15.8           |
| 480.08                                       | 120                            | H    | 32.9                | -3.3           | 29.6                 | 46.0                | 16.4           |
| 600.00                                       | 120                            | H    | 31.4                | 0.2            | 31.6                 | 46.0                | 14.4           |
| Above<br>600.000                             | Not<br>Detected                |      |                     |                |                      |                     |                |
| <b>Peak DATA. Emissions above 1GHz</b>       |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 56.0                | -0.5           | 55.5                 | 74.0                | 18.5           |
| Above<br>3 000.00                            | Not<br>Detected                |      |                     |                |                      |                     |                |
| <b>Average DATA. Emissions above 1GHz</b>    |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 49.7                | -0.5           | 49.2                 | 54.0                | 4.8            |
| Above<br>3 000.00                            | Not<br>Detected                |      |                     |                |                      |                     |                |

Factor(dB) = ANT Factor + Amp Gain + Cable Loss

Margin (dB) = Limit - Result

[Result = Reading - Factor]

1. H = Horizontal, V = Vertical Polarization

2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss

\* The spurious emission at the frequency does not fall in the restricted bands.

\*\* The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.

NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.

- 8DPSK  
**Low channel (2 402 MHz)**

| Frequency<br>[MHz]                           | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 1GHz</b> |                                |      |                     |                |                      |                     |                |
| 35.94  | 120                            | V    | 45.7                | -14.4          | 31.3                 | 40.0                | 8.7            |
| 51.22  | 120                            | V    | 38.7                | -12.9          | 25.8                 | 40.0                | 14.2           |
| 135.25                                       | 120                            | V    | 44.0                | -12.3          | 31.7                 | 43.5                | 11.8           |
| 151.37                                       | 120                            | V    | 45.8                | -11.1          | 34.7                 | 43.5                | 8.8            |
| 360.41                                       | 120                            | H    | 43.0                | -6.7           | 36.3                 | 46.0                | 9.7            |
| Above<br>500.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Peak DATA. Emissions above 1GHz</b>       |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 55.4                | -0.5           | 54.9                 | 74.0                | 19.1           |
| Above<br>3 000.00                            | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Average DATA. Emissions above 1GHz</b>    |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 49.4                | -0.5           | 48.9                 | 54.0                | 5.1            |
| Above<br>3 000.00                            | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |

**Middle channel (2 441 MHz)**

| Frequency<br>[MHz]                           | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 1GHz</b> |                                |      |                     |                |                      |                     |                |
| 35.94  | 120                            | V    | 48.0                | -14.4          | 33.6                 | 40.0                | 6.4            |
| 152.34                                       | 120                            | V    | 45.1                | -11.0          | 34.1                 | 43.5                | 9.4            |
| 241.58                                       | 120                            | V    | 44.0                | -11.1          | 32.9                 | 46.0                | 13.1           |
| Above<br>500.00                              | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Peak DATA. Emissions above 1GHz</b>       |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 55.4                | -0.5           | 54.9                 | 74.0                | 19.1           |
| Above<br>3 000.00                            | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |
| <b>Average DATA. Emissions above 1GHz</b>    |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 48.9                | -0.5           | 48.4                 | 54.0                | 5.6            |
| Above<br>3 000.00                            | Not<br>Detected                | -    | -                   | -              | -                    | -                   | -              |
|  |                                |      |                     |                |                      |                     |                |

**High channel (2 480 MHz)**

| Frequency<br>[MHz]                           | Receiver<br>Bandwidth<br>[kHz] | Pol. | Reading<br>[dB(µV)] | Factor<br>[dB] | Result<br>[dB(µV/m)] | Limit<br>[dB(µV/m)] | Margin<br>[dB] |
|--|--------------------------------|------|---------------------|----------------|----------------------|---------------------|----------------|
| <b>Quasi-Peak DATA. Emissions below 1GHz</b> |                                |      |                     |                |                      |                     |                |
| 30.36  | 120                            | V    | 47.4                | -14.9          | 32.5                 | 40.0                | 7.5            |
| 35.94  | 120                            | V    | 45.7                | -14.4          | 31.3                 | 40.0                | 8.7            |
| 51.83  | 120                            | V    | 38.8                | -12.9          | 25.9                 | 40.0                | 14.1           |
| 78.86  | 120                            | V    | 40.7                | -16.7          | 24.0                 | 40.0                | 16.0           |
| 152.34                                       | 120                            | V    | 45.6                | -11.0          | 34.6                 | 43.5                | 8.9            |
| 360.04                                       | 120                            | H    | 41.5                | -6.7           | 34.8                 | 46.0                | 11.2           |
| 480.08                                       | 120                            | H    | 37.2                | -3.3           | 33.9                 | 46.0                | 12.1           |
| Above<br>500.000                             | Not<br>Detected                |      |                     |                |                      |                     |                |
|  |                                |      |                     |                |                      |                     |                |
| <b>Peak DATA. Emissions above 1GHz</b>       |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 55.7                | -0.5           | 55.2                 | 74.0                | 18.8           |
| Above<br>3 000.00                            | Not<br>Detected                |      |                     |                |                      |                     |                |
|  |                                |      |                     |                |                      |                     |                |
| <b>Average DATA. Emissions above 1GHz</b>    |                                |      |                     |                |                      |                     |                |
| 2 809.75                                     | 1 000                          | V    | 51.5                | -0.5           | 51.0                 | 54.0                | 3.0            |
| Above<br>3 000.00                            | Not<br>Detected                |      |                     |                |                      |                     |                |
|  |                                |      |                     |                |                      |                     |                |

**Factor(dB) = ANT Factor + Amp Gain + Cable Loss**

**Margin (dB) = Limit - Result**

**[Result = Reading - Factor]**

1. H = Horizontal, V = Vertical Polarization

2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss

\* The spurious emission at the frequency does not fall in the restricted bands.

\*\* The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.

NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.

## 5.9 RF Exposure

### 5.9.1 Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

| Frequency Range                                       | Electric Field Strength [V/m] | Magnetic Field Strength [A/m] | Power Density [mW/cm <sup>2</sup> ] | Averaging Time [minute] |
|---|-------------------------------|-------------------------------|-------------------------------------|-------------------------|
| Limits for General Population / Uncontrolled Exposure |                               |                               |                                     |                         |
| 0.3 ~ 1.34  | 614                           | 1.63                          | *(100)                              | 30                      |
| 1.34 ~ 30   | 824 /f                        | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                      |
| 30 ~ 300  | 27.5                          | 0.073                         | 0.2                                 | 30                      |
| 300 ~ 1500  | /                             | /                             | f/1500                              | 30                      |
| 1500 ~ 15000  | /                             | /                             | 1.0                                 | 30                      |

f=frequency in MHz, \* = plane-wave equivalent power density

#### MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S=power density [mW/cm<sup>2</sup>]

P=Power input to antenna [mW]

G=Power gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the center of radiation of the antenna [cm]

|   |   |
|---|---|
| EUT: Maximum peak output power = 2.04 [mW](= 3.09 dBm)<br>Antenna gain=2.239(= 3.5 [dBi]) |   |
| 100 mW, at 20 cm from an antenna 6[dBi]   | $S = PG/4\pi R^2 = 100 \times 3.98 / (4 \times \pi \times 400)$<br>$= 0.0792 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$ |
| 2.04 mW, at 20 cm from an antenna 2.239 [dBi]   | $S = PG/4\pi R^2 = 0.000\ 91 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$   |
| 2.04 mW, at 2.5 cm from an antenna 2.239 [dBi]  | $S = PG/4\pi R^2 = 0.058\ 06 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$   |

### 5.9.2 RF Exposure Compliance Issue

The information should be included in the user's manual:


This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

## 6. Test equipment used for test


|                                     | Description             | Manufacture       | Model No. | Serial No.  | Next Cal Date. |
|-------------------------------------|-------------------------|-------------------|-----------|-------------|----------------|
| <input type="checkbox"/>            | Temp & humidity chamber | taekwang          | TK-04     | TK001       | 13.12.07       |
| <input type="checkbox"/>            | Temp & humidity chamber | taekwang          | TK-500    | TK002       | 13.09.03       |
| <input type="checkbox"/>            | Frequency Counter       | HP                | 53150A    | US39250565  | 13.09.04       |
| <input checked="" type="checkbox"/> | Spectrum Analyzer       | Agilent           | E4440A    | MY44303500  | 13.06.27       |
| <input checked="" type="checkbox"/> | Spectrum Analyzer       | R & S             | FSP40     | 100209      | 13.06.27       |
| <input type="checkbox"/>            | Modulation Analyzer     | HP                | 8901B     | 3538A05527  | 13.10.25       |
| <input type="checkbox"/>            | Audio Analyzer          | HP                | 8903B     | 3729A19213  | 13.10.23       |
| <input type="checkbox"/>            | AC Power Supply         | KIKUSUI           | PCR2000W  | GB001619    | 13.10.23       |
| <input type="checkbox"/>            | DC Power Supply         | Tektronix         | PS2520G   | TW50517     | 13.02.06       |
| <input checked="" type="checkbox"/> | DC Power Supply         | Tektronix         | PS2521G   | TW53135     | 13.10.23       |
| <input type="checkbox"/>            | Dummy Load              | BIRD              | 8141      | 7560        | 13.09.09       |
| <input type="checkbox"/>            | Dummy Load              | BIRD              | 8401-025  | 799         | 13.09.09       |
| <input checked="" type="checkbox"/> | EMI Test Receiver       | R&S               | ESCI      | 100001      | 13.11.06       |
| <input type="checkbox"/>            | Attenuator              | HP                | 8494A     | 2631A09825  | 12.10.24       |
| <input type="checkbox"/>            | Attenuator              | HP                | 8496A     | 3308A16640  | 12.10.24       |
| <input type="checkbox"/>            | Attenuator              | R&S               | RBS1000   | D67079      | 12.10.24       |
| <input type="checkbox"/>            | WIDEBAND POWER SENSOR   | R & S             | NRP-Z81   | 100677      | 13.05.04       |
| <input checked="" type="checkbox"/> | LOOP Antenna            | EMCO              | EMCO6502  | 9205-2745   | 13.05.22       |
| <input checked="" type="checkbox"/> | BILOG Antenna           | Schwarzbeck       | VULB 9168 | 375         | 13.09.21       |
| <input checked="" type="checkbox"/> | HORN Antenna            | ETS               | 3115      | 00086706    | 13.11.21       |
| <input checked="" type="checkbox"/> | HORN Antenna            | ETS               | 3115      | 00062589    | 13.09.06       |
| <input checked="" type="checkbox"/> | HORN Antenna            | ETS               | 3116      | 00086632    | 13.11.15       |
| <input checked="" type="checkbox"/> | HORN Antenna            | ETS               | 3116      | 00086632    | 13.11.15       |
| <input checked="" type="checkbox"/> | Amplifier               | SONOMA INSTRUMENT | 310N      | 293004      | 13.11.06       |
| <input checked="" type="checkbox"/> | PREAMPLIFIER            | AGILENT           | 8449B     | 3008A01802  | 13.05.08       |
| <input checked="" type="checkbox"/> | Signal Generator        | R & S             | SMR40     | 100007      | 13.06.27       |
| <input checked="" type="checkbox"/> | Power Divider           | Weinschel         | 1580-1    | NX380       | 13.09.09       |
| <input type="checkbox"/>            | Power Divider           | Weinschel         | 1594      | 671         | 13.09.10       |
| <input checked="" type="checkbox"/> | Bluetooth tester        | Tescom            | TC3000A   | 3000A310047 | 13.04.06       |

## Appendix 1. Test Setup Photos

Below 30MHz



Above 30MHz



Above 1GHz

