

MPE TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-AN243HGAN

Equipment Under Test : DIGITAL CAR AVN SYSTEM

Model Name : AN243HGAN

Serial No. : N/A

Applicant : Hyundai MOBIS Co., Ltd.

Manufacturer : Hyundai MOBIS Co., Ltd.

Date of Test(s) : 2013.02.12 ~ 2013.02.20

Date of Issue : 2013.02.21

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date:

2013.02.21

Harim Lee

Approved By:



Date:

2013.02.21

Denny Ham

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory)

18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.ee.sgs.com/korea

INDEX

	<u>Table of Contents</u>	Page
1. General Information -----		3
2. RF Exposure Evaluation -----		4

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.ee.sgs.com/korea

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 3FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040 (Lab)
- Wireless Div. 1FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040 (Chamber)

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 428 5700

FAX : +82 31 427 2371

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 80-9, Mabook-Dong, Giheung-Gu Yongin-Shi, Gyunggi-Do, 446-912, South Korea

Contact Person : Kim, Jong-Tae

Phone No. : +82 31 260 0092

1.3. Description of EUT

Kind of Product	DIGITAL CAR AVN SYSTEM
Model Name	AN243HGAN
Serial Number	N/A
Power Supply	DC 14.4 V (Used on vehicle battery)
Frequency Range	2 402 MHz ~ 2 480 MHz
Modulation Technique	GFSK, π/4DQPSK, 8DPSK
Number of Channels	79
Antenna Type	PCB + Cable Assembly Antenna
Antenna Gain	1.0 dB i

1.4. Test report revision

Revision	Report number	Description
0	F690501/RF-RTL006286	Initial

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.ee.sgs.com/korea

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational /Control Exposures				
300 – 1 500	--	--	F/300	6
1 500 – 100 000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300 – 1 500	--	--	F/1500	6
<u>1 500 – 100 000</u>	--	--	<u>1</u>	<u>30</u>

2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

FHSS: GFSK

Channel	Channel Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
Low	2 402	-0.17	1.00	47	0.000 113	1
Middle	2 441	-0.57	1.00	47	0.000 103	1
High	2 480	-1.39	1.00	47	0.000 085	1

FHSS: 8DPSK

Channel	Channel Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
Low	2 402	-1.17	1.00	47	0.000 090	1
Middle	2 441	-1.92	1.00	47	0.000 076	1
High	2 480	-2.91	1.00	47	0.000 060	1

Note :

1. The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm² .