

TEST REPORT

of

FCC Part 15 Subpart E §15.407

FCC ID: TQ8-AT140C2AN

Equipment Under Test : DISPLAY AUDIO SYSTEM

Model Name : AT140C2AN

Applicant : Hyundai MOBIS Co., Ltd.

Manufacturer : Hyundai MOBIS Co., Ltd.

Date of Test(s) : 2015.01.30 ~ 2015.03.10

Date of Issue : 2015.03.10

In the configuration tested, the EUT complied with the standards specified above.

Tested By:


Jungmin Yang

Date:

2015.03.10

Approved By:


Hyunchae You

Date:

2015.03.10

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Table of contents

1. General information -----	3
2. Transmitter radiated spurious emissions -----	6
3. 26 dB Bandwidth & 99 % Bandwidth-----	26
4. 6 dB Bandwidth -----	53
5. Output power -----	61
6. Peak power spectral density -----	72

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General information

1.1 Testing laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 435-837

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : + 82 31 688 0901

Fax No. : + 82 31 688 0921

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, 135-977, Korea

Contact Person : Choi, Seung-Hoon

Phone No. : + 82 31 260 0098

1.3. Description of EUT

Kind of Product	DISPLAY AUDIO SYSTEM
Model Name	AT140C2AN
Power Supply	DC 14.4 V (Vehicle Battery)
Frequency Range	2 402 MHz ~ 2 480 MHz (BT), 2 412 MHz ~ 2 462 MHz (11b/g/n_HT20), 5 745 MHz ~ 5 825 MHz (Band 3: 11a/n_HT20, 11ac_VHT20), 5 755 MHz ~ 5 795 MHz (Band 3: 11n_HT40, 11ac_VHT40), 5 775 MHz (Band 3: 11ac_VHT80), 5 180 MHz ~ 5 240 MHz (Band 1: 11a/n_HT20, 11ac_VHT20), 5 190 MHz ~ 5 230 MHz (Band 1: 11n_HT40, 11ac_VHT40), 5 210 MHz (Band 1: 11ac_VHT80), 5 260 MHz ~ 5 320 MHz (Band 2A: 11a/n_HT20, 11ac_VHT20), 5 270 MHz ~ 5 310 MHz (Band 2A: 11n_HT40, 11ac_VHT40), 5 290 MHz (Band 2A: 11ac_VHT80), 5 500 MHz ~ 5 700 MHz (Band 2C: 11a/n_HT20, 11ac_VHT20), 5 510 MHz ~ 5 670 MHz (Band 2C: 11n_HT40, 11ac_VHT40), 5 530 MHz (Band 2C: 11ac_VHT80)
Modulation Technique	DSSS, OFDM, GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels	79 channel (BT), 11 channel (11b/g/n_HT20), 5 channel (Band 3: 11a/n_HT20, 11ac_VHT20), 2 channel (Band 3: 11n_HT40, 11ac_VHT40), 1 channel (Band 3: 11ac_VHT80), 4 channel (Band 1: 11a/n_HT20, 11ac_VHT20), 2 channel (Band 1: 11n_HT40, 11ac_VHT40), 1 channel (Band 1: 11ac_VHT80), 4 channel (Band 2A: 11a/n_HT20, 11ac_VHT20), 2 channel (Band 2A: 11n_HT40, 11ac_VHT40), 1 channel (Band 2A: 11ac_VHT80), 8 channel (Band 2C: 11a/n_HT20, 11ac_VHT20), 3 channel (Band 2C: 11n_HT40, 11ac_VHT40), 1 channel (Band 2C: 11ac_VHT80)
Operation Temperature	-20 °C ~ 70 °C
Antenna Type	Internal type
Antenna Gain	2 402 MHz ~ 2 480 MHz: 2.29 dB i, 2 412 MHz ~ 2 472 MHz: -0.09 dB i, 5 180 MHz ~ 5 320 MHz: 4.77 dB i, 5 500 MHz ~ 5 700 MHz: 1.68 dB i, 5 745 MHz ~ 5 805 MHz: 2.78 dB i

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.4. Declaration by the manufacturer

- Client without Radar Detection and TPC.
- EUT is not supported TDWR(5.6-5.65 GHz) band.

1.5. Test equipment list

Equipment	Manufacturer	Model	S/N	Cal Date	Cal Interval	Cal Due.
Signal Generator	R&S	SMR40	100272	Jul. 18, 2014	Annual	Jul. 18, 2015
Signal Generator	R&S	SMBV100A	255834	Jun. 25, 2014	Annual	Jun. 25, 2015
Spectrum Analyzer	Agilent	N9030A	US51350132	Sep. 24, 2014	Annual	Sep. 24, 2015
Attenuator	MCLI	FAS-23-20	23834	Jun. 20, 2014	Annual	Jun. 20, 2015
Band Reject Filter	Wainwright	WRCJV5150/5350-5130/ 5370-50/16SS	1	Sep. 24, 2014	Annual	Sep. 24, 2015
Band Reject Filter	Wainwright	WRCJV5470/5725-5450/ 5745-50/20SS	1	Sep. 24, 2014	Annual	Sep. 24, 2015
High Pass Filter	Wainwright	WHK6.0/18G-10SS	11	Jun. 10, 2014	Annual	Jun. 10, 2015
High Pass Filter	Wainwright	WHK7.5/26.5G-6SS	11	Jun. 10, 2014	Annual	Jun. 10, 2015
Low Pass Filter	Mini circuits	NLP-1200+	V8979400903-2	Mar. 21, 2014	Annual	Mar. 21, 2015
Power Meter	Anritsu	ML2495A	1223004	Jun. 10, 2014	Annual	Jun. 10, 2015
Power Sensor	Anritsu	MA2411B	1207272	Jun. 10, 2014	Annual	Jun. 10, 2015
DC Power Supply	Agilent	U8002A	MY50060028	Mar. 27, 2014	Annual	Mar. 27, 2015
Preamplifier	H.P.	8447F	2944A03909	Aug. 27, 2014	Annual	Aug. 27, 2015
Preamplifier	R&S	SCU 18	10117	Dec. 26, 2014	Annual	Dec. 26, 2015
Preamplifier	MITEQ Inc.	JS44-18004000-35-8P	1546891	Apr. 28, 2014	Annual	Apr. 28, 2015
Bilog Antenna	SCHWARZBECK MESSELEKTRONIK	VULB9163	396	Jun. 07, 2013	Biennial	Jun. 07, 2015
Loop Antenna	R&S	HFH2-Z2	100118	Jul. 12, 2013	Biennial	Jul. 12, 2015
Horn Antenna	R&S	HF906	100326	Dec. 10, 2013	Biennial	Dec. 10, 2015
Horn Antenna	SCHWARZBECK MESSELEKTRONIK	BBHA9170	BBHA9170431	May 15, 2014	Biennial	May 15, 2016
Test Receiver	R&S	ESU26	100109	Mar. 04, 2014	Annual	Mar. 04, 2015
Antenna Master	INN-CO	MM4000	N/A	N/A	N/A	N.C.R.
Turn Table	INN-CO	DS 1200 S	N/A	N/A	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N/A	N/A	N.C.R.

► Support equipment

Description	Manufacturer	Model	Serial Number
N/A	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.6. Summary of test result

The EUT has been tested according to the following specifications:

APPLIED STANDARD:FCC Part15 subpart E		
Section in FCC 15	Test Item	Result
15.205(a) 15.209(a) 15.407(b)(1) 15.407(b)(2) 15.407(b)(3) 15.407(b)(4)	Transmitter radiated spurious emissions and Conducted spurious emission	Complied
15.407(a)	26 dB Bandwidth	Complied
15.407(e)	6 dB Bandwidth	Complied
15.407(a)(1) 15.407(a)(2) 15.407(a)(3)	Output power	Complied
15.407(a)(1) 15.407(a)(2) 15.407(a)(3)	Peak power spectral density	Complied

1.7. Test Procedure(s)

The measurement procedures described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2003) and the guidance provided in KDB 789033 D02 v01 were used in the measurement of the DUT.

1.8. Sample calculation

Where relevant, the following sample calculation is provided:

1.8.1. Conducted test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.8.2. Radiation test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB) + Cable loss (dB) - amplifier (dB)

1.9. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL008456	2015.02.27	Initial
1	F690501/RF-RTL008456-1	2015.03.10	Add 99 % bandwidth test result


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. Transmitter radiated spurious emissions and conducted spurious emission


2.1. Test setup

2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.2. Limit

For transmitters operating in the 5.15 ~ 5.25 GHz band: All emissions outside of the 5.15 ~ 5.35 GHz band shall not exceed an e.i.r.p. of -27 m/MHz.

For transmitters operating in the 5.25 ~ 5.35 GHz band: All emissions outside of the 5.15 ~ 5.35 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.

For transmitters operating in the 5.47 ~ 5.725 GHz band: All emissions outside of the 5.47 ~ 5.725 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.

For transmitters operating in the 5.725 ~ 5.785 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dB m/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dB m/MHz.

According to § 15.209(a), Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Distance (Meters)	Field Strength (dBμV/m)	Field Strength (μV/m)
0.009 – 0.490	300	20 log (2 400/F(kHz))	2 400/F(kHz)
0.490 – 1.705	30	20 log (24 000/F(kHz))	24 000/F(kHz)
1.705 – 30.0	30	29.54	30
30 - 88	3	40.0	100**
88 – 216	3	43.5	150**
216 – 960	3	46.0	200**
Above 960	3	54.0	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.3. Test procedures

Radiated spurious emissions from the EUT were measured according to the dictates in section G of KDB 789033 D02 v01 and ANSI C63.4 2003.

The emissions of the configuration that produced the worst case emissions are reported in this section.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3.1. Test procedures for radiated spurious emissions

2.3.1.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.1.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE;

- The measurements for below 1 GHz refer to section II.G.4.
Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.
- The measurements for above 1 GHz II.G.5.
Peak emission levels are measured by setting the analyzer as follows:
Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = Peak, Sweep time = auto, Trace mode= Max hold
- The measurements for above 1 GHz II.G.6.
Average emission levels are measured by setting the analyzer as follows:
Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = RMS, Averaging type = power(i.e., RMS), Sweep time = auto, Trace mode= trace average of at least 100 traces. If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle.
If duty cycle < 98 percent, a correction factor shall be added to the measurement results.
- Voltage averaging mode was used above the correction factor is 20 log (1/x), where x is the duty cycle.
- Test orthogonal plan of EUT is X-axis during radiation test.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4. Test result

Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

2.4.1. Spurious radiated emission

The frequency spectrum from 9 kHz to 1 000 MHz was investigated.

Radiated Emissions			Ant.	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
61.51	37.86	Peak	V	12.51	-26.77	23.60	40.00	16.40
81.01	41.27	Peak	V	9.59	-26.56	24.30	40.00	15.70
135.00	40.99	Peak	H	10.06	-26.05	25.00	43.50	18.50
160.02	40.90	Peak	H	9.98	-25.78	25.10	43.50	18.40
251.65	39.06	Peak	V	13.91	-24.97	28.00	46.00	18.00
560.02	40.74	Peak	V	18.75	-25.19	34.30	46.00	11.70
Above 600.00	Not detected	-	-	-	-	-	-	-

Remark:

1. Spurious emissions for all channels and modes were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **11a / 6 Mbps / 36 channel** as worst case among other modes.
3. Radiated spurious emission measurement as below
(Actual = Reading + Antenna Factor + Amp + CL)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4.2. Spurious radiated emission for above 1 GHz

802.11a (Band 1)_6 Mbps

A. Low Channel (5 180 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	9.08	Peak	V	32.20	8.67	-	49.95	74.00	24.05
*4 500.00	-1.25	Average	V	32.20	8.67	0.63	40.25	54.00	13.75
*4 985.55	13.18	Peak	V	33.43	8.88	-	55.49	74.00	18.51
*4 985.55	1.32	Average	V	33.43	8.88	0.63	44.26	54.00	9.74
*5 150.00	10.39	Peak	V	33.43	9.32	-	53.14	74.00	20.86
*5 150.00	-0.48	Average	V	33.43	9.32	0.63	42.90	54.00	11.10

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 361.19	35.95	Peak	H	37.74	-28.89	-	44.80	68.23	23.43
Above 10 400.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 437.36	35.06	Peak	H	37.66	-29.03	-	43.69	68.23	24.54
Above 10 500.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 240 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 478.33	36.48	Peak	H	37.66	-29.05	-	45.09	68.23	23.14
Above 10 500.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 2A)_6 Mbps

A. Low Channel (5 260 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 521.72	36.73	Peak	H	37.66	-28.95	-	45.44	68.23	22.79
Above 10 600.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 300 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*10 602.18	37.25	Peak	H	37.78	-28.54	-	46.49	74.00	27.51
*10 602.18	25.74	Average	H	37.78	-28.54	0.63	35.61	54.00	18.39
Above 10 700.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 320 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	9.28	Peak	V	33.75	9.32	-	52.35	74.00	21.65
*5 350.00	-0.75	Average	V	33.75	9.32	0.63	42.95	54.00	11.05
*5 377.72	12.69	Peak	V	33.86	9.43	-	55.98	74.00	18.02
*5 377.72	0.91	Average	V	33.76	9.33	0.63	44.63	54.00	9.37
*5 460.00	10.96	Peak	V	34.29	9.12	-	54.37	74.00	19.63
*5 460.00	-0.54	Average	V	34.29	9.12	0.63	43.50	54.00	10.50

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*10 637.65	37.29	Peak	H	37.83	-28.33	-	46.79	74.00	27.21
*10 637.65	24.48	Average	H	37.83	-28.33	0.63	34.61	54.00	19.39
Above 10 700.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 2C)_6 Mbps

A. Low Channel (5 500 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	10.54	Peak	V	33.75	9.32	-	53.61	74.00	20.39
*5 350.00	0.09	Average	V	33.75	9.32	0.63	43.79	54.00	10.21
*5 449.11	13.56	Peak	V	34.20	9.07	-	56.83	74.00	17.17
*5 449.11	0.88	Average	V	34.20	9.07	0.63	44.78	54.00	9.22
*5 460.00	10.76	Peak	V	34.29	9.12	-	54.17	74.00	19.83
*5 460.00	-0.48	Average	V	34.29	9.12	0.63	43.56	54.00	10.44

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 003.13	36.19	Peak	H	38.20	-27.13	-	47.26	74.00	26.74
*11 003.13	25.16	Average	H	38.20	-27.13	0.63	36.86	54.00	17.14
Above 11 100.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 580 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 160.29	36.20	Peak	H	38.18	-28.31	-	46.07	74.00	27.93
*11 160.29	24.50	Average	H	38.18	-28.31	0.63	35.00	54.00	19.00
Above 11 200.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 700 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 398.90	36.18	Peak	H	38.25	-28.35	-	46.08	74.00	27.92
*11 398.90	24.54	Average	H	38.25	-28.35	0.63	35.07	54.00	18.93
Above 11 400.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 3)_6 Mbps

A. Low Channel (5 745 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 708.13	13.72	Peak	V	34.10	9.35	-	57.17	68.23	11.06
5 723.27	20.37	Peak	V	34.12	9.43	-	63.92	78.23	14.31

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 490.88	36.20	Peak	H	38.49	-29.04	-	45.65	74.00	28.35
*11 490.88	24.94	Average	H	38.49	-29.04	0.63	35.02	54.00	18.98
Above 11 500.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 785 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 574.15	35.81	Peak	H	38.55	-28.88	-	45.48	74.00	28.52
*11 574.15	24.73	Average	H	38.55	-28.88	0.63	35.03	54.00	18.97
Above 11 600.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 825 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 851.05	18.47	Peak	V	34.14	9.54	-	62.15	78.23	16.08
5 861.11	13.91	Peak	V	34.21	9.69	-	57.81	68.23	10.42

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 650.25	36.31	Peak	H	38.46	-28.41	-	46.36	74.00	27.64
*11 650.25	24.48	Average	H	38.46	-28.41	0.63	35.16	54.00	18.84
Above 11 700.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 1)_MCS0

A. Low Channel (5 180 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	8.79	Peak	V	32.20	8.67	-	49.66	74.00	24.34
*4 500.00	-1.59	Average	V	32.20	8.67	0.72	40.00	54.00	14.00
*5 135.70	13.75	Peak	V	33.38	9.21	-	56.34	74.00	17.66
*5 135.70	1.38	Average	V	33.38	9.21	0.72	44.69	54.00	9.31
*5 150.00	10.09	Peak	V	33.43	9.32	-	52.84	74.00	21.16
*5 150.00	-0.48	Average	V	33.43	9.32	0.72	42.99	54.00	11.01

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 356.38	36.96	Peak	H	37.73	-28.88	-	45.81	68.23	22.42
Above 10 400.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 440.81	36.38	Peak	H	37.66	-29.03	-	45.01	68.23	23.22
Above 10 500.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 240 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 479.44	37.44	Peak	H	37.66	-29.05	-	46.05	68.23	22.18
Above 10 500.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 2A)_MCS0

A. Low Channel (5 260 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 517.65	36.91	Peak	H	37.67	-28.97	-	45.61	68.23	22.62
Above 10 600.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 300 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*10 600.47	37.17	Peak	H	37.78	-28.55	-	46.40	74.00	27.60
*10 600.47	25.88	Average	H	37.78	-28.55	0.72	35.83	54.00	18.17
Above 10 700.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 320 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	9.27	Peak	V	33.75	9.32	-	52.34	74.00	21.66
*5 350.00	0.13	Average	V	33.75	9.32	0.72	43.92	54.00	10.08
*5 357.92	12.63	Peak	V	33.77	9.35	-	55.75	74.00	18.25
*5 357.92	1.02	Average	V	33.77	9.35	0.72	44.86	54.00	9.14
*5 460.00	11.07	Peak	V	34.29	9.12	-	54.48	74.00	19.52
*5 460.00	-0.23	Average	V	34.29	9.12	0.72	43.90	54.00	10.10

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*10 639.09	36.66	Peak	H	37.83	-28.32	-	46.17	74.00	27.83
*10 639.09	24.78	Average	H	37.83	-28.32	0.72	35.01	54.00	18.99
Above 10 700.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 2C)_MCS0

A. Low Channel (5 500 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	9.45	Peak	V	33.75	9.32	-	52.52	74.00	21.48
*5 350.00	-0.83	Average	V	33.75	9.32	0.72	42.96	54.00	11.04
*5 380.03	12.22	Peak	V	33.87	9.43	-	55.52	74.00	18.48
*5 380.03	0.87	Average	V	33.87	9.43	0.72	44.89	54.00	9.11
*5 460.00	9.77	Peak	V	34.29	9.12	-	53.18	74.00	20.82
*5 460.00	-0.39	Average	V	34.29	9.12	0.72	43.74	54.00	10.26

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*10 998.46	37.26	Peak	H	38.20	-27.12	-	48.34	74.00	25.66
*10 998.46	24.21	Average	H	38.20	-27.12	0.72	36.01	54.00	17.99
Above 11 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 580 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 157.07	36.13	Peak	H	38.18	-28.27	-	46.04	74.00	27.96
*11 157.07	24.63	Average	H	38.18	-28.27	0.72	35.26	54.00	18.74
Above 11 200.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 700 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 399.12	35.78	Peak	H	38.25	-28.35	-	45.68	74.00	28.32
*11 399.12	24.32	Average	H	38.25	-28.35	0.72	34.94	54.00	19.06
Above 11 400.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 3)_MCS0

A. Low Channel (5 745 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 713.77	16.42	Peak	V	34.11	9.38	-	59.91	68.23	8.32
5 724.36	25.96	Peak	V	34.13	9.44	-	69.53	78.23	8.70

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 488.24	36.30	Peak	H	38.49	-29.02	-	45.77	74.00	28.23
*11 488.24	24.82	Average	H	38.49	-29.02	0.72	35.01	54.00	18.99
Above 11 500.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 785 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 568.55	36.45	Peak	H	38.57	-28.90	-	46.12	74.00	27.88
*11 568.55	24.80	Average	H	38.57	-28.90	0.72	35.19	54.00	18.81
Above 11 600.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 825 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 854.40	20.45	Peak	V	34.17	9.59	-	64.21	78.23	14.02
5 866.48	14.90	Peak	V	34.21	9.76	-	58.87	68.23	9.36

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 651.78	36.00	Peak	H	38.48	-28.40	-	46.08	74.00	27.92
*11 651.78	24.81	Average	H	38.48	-28.40	0.72	35.61	54.00	18.39
Above 11 700.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 1)_MCS0

A. Low Channel (5 190 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	9.68	Peak	V	32.20	8.67	-	50.55	74.00	23.45
*4 500.00	-1.27	Average	V	32.20	8.67	1.72	41.32	54.00	12.68
*5 145.45	13.10	Peak	V	33.42	9.29	-	55.81	74.00	18.19
*5 145.45	1.48	Average	V	33.42	9.29	1.72	45.91	54.00	8.09
*5 150.00	9.72	Peak	V	33.43	9.32	-	52.47	74.00	21.53
*5 150.00	-0.52	Average	V	33.43	9.32	1.72	43.95	54.00	10.05

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 380.33	37.39	Peak	H	37.73	-28.95	-	46.17	68.23	22.06
Above 10 400.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 230 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 460.17	37.04	Peak	H	37.70	-29.05	-	45.69	68.23	22.54
Above 10 500.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802. 11n_HT40 (Band 2A)_MCS0

A. Low Channel (5 270 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
10 540.28	36.27	Peak	H	37.72	-28.85	-	45.14	68.23	23.09
Above 10 600.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 310 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	9.94	Peak	V	33.75	9.32	-	53.01	74.00	20.99
*5 350.00	-0.26	Average	V	33.75	9.32	1.72	44.53	54.00	9.47
*5 353.41	13.03	Peak	V	33.76	9.33	-	56.12	74.00	17.88
*5 353.41	0.89	Average	V	33.76	9.33	1.72	45.70	54.00	8.30
*5 460.00	10.46	Peak	V	34.29	9.12	-	53.87	74.00	20.13
*5 460.00	0.14	Average	V	34.29	9.12	1.72	45.27	54.00	8.73

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*10 615.12	36.83	Peak	H	37.80	-28.46	-	46.17	74.00	27.83
*10 615.12	25.47	Average	H	37.80	-28.46	1.72	36.53	54.00	17.47
Above 10 700.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802. 11n_HT40 (Band 2C)_MCS0

A. Low Channel (5 510 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	11.13	Peak	V	33.75	9.32	-	54.20	74.00	19.80
*5 350.00	-0.03	Average	V	33.75	9.32	1.72	44.76	54.00	9.24
*5 455.16	12.93	Peak	V	34.25	9.09	-	56.27	74.00	17.73
*5 455.16	0.81	Average	V	34.25	9.09	1.72	45.87	54.00	8.13
*5 460.00	10.40	Peak	V	34.29	9.12	-	53.81	74.00	20.19
*5 460.00	-0.37	Average	V	34.29	9.12	1.72	44.76	54.00	9.24

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 016.74	35.45	Peak	H	38.25	-27.19	-	46.51	74.00	27.49
*11 016.74	23.70	Average	H	38.25	-27.19	1.72	36.48	54.00	17.52
Above 11 100.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 550 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 095.77	35.88	Peak	H	38.20	-27.55	-	46.53	74.00	27.47
*11 095.77	24.49	Average	H	38.20	-27.55	1.72	36.86	54.00	17.14
Above 11 100.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 670 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 341.12	35.36	Peak	H	38.26	-28.87	-	44.75	74.00	29.25
*11 341.12	22.88	Average	H	38.26	-28.87	1.72	33.99	54.00	20.01
Above 11 400.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 3)_MCS0

A. Low Channel (5 755 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 712.75	20.92	Peak	V	34.11	9.37	-	64.40	68.23	3.83
5 724.47	26.17	Peak	V	34.13	9.44	-	69.74	78.23	8.49

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 510.44	36.51	Peak	H	38.52	-29.08	-	45.95	74.00	28.05
*11 510.44	24.23	Average	H	38.52	-29.08	1.72	35.39	54.00	18.61
Above 11 600.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 795 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 851.40	16.11	Peak	V	34.15	9.55	-	59.81	78.23	18.42
5 869.18	12.95	Peak	V	34.21	9.80	-	56.96	68.23	11.27

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 592.69	35.87	Peak	H	38.59	-28.83	-	45.63	74.00	28.37
*11 592.69	24.40	Average	H	38.59	-28.83	1.72	35.88	54.00	18.12
Above 11 600.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11ac_VHT80 (Band 1)_MCS0

A. Middle Channel (5 210 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 500.00	9.90	Peak	V	32.20	8.67	-	50.77	74.00	23.23
*4 500.00	-1.77	Average	V	32.20	8.67	3.22	42.32	54.00	11.68
*5 142.85	14.58	Peak	V	33.42	9.27	-	57.27	74.00	16.73
*5 142.85	2.32	Average	V	33.42	9.27	3.22	48.23	54.00	5.77
*5 150.00	11.31	Peak	V	33.43	9.32	-	54.06	74.00	19.94
*5 150.00	-0.66	Average	V	33.43	9.32	3.22	45.31	54.00	8.69

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
10 421.60	36.92	Peak	H	37.70	-29.03	-	45.59	68.23	22.64
Above 10 500.00	Not detected	-	-	-	-	-	-	-	-

802. 11ac_VHT80 (Band 2A)_MCS0

A. Middle Channel (5 290 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*5 350.00	9.29	Peak	V	33.75	9.32	-	52.36	74.00	21.64
*5 350.00	-0.83	Average	V	33.75	9.32	3.22	45.46	54.00	8.54
*5 370.57	13.46	Peak	V	33.82	9.40	-	56.68	74.00	17.32
*5 370.57	0.98	Average	V	33.82	9.40	3.22	47.42	54.00	6.58
*5 460.00	9.43	Peak	V	34.29	9.12	-	52.84	74.00	21.16
*5 460.00	-0.22	Average	V	34.29	9.12	3.22	46.41	54.00	7.59

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
10 579.26	37.32	Peak	H	37.76	-28.65	-	46.43	68.23	21.80
Above 10 600.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802. 11ac_VHT80 (Band 2C)_MCS0

A. Middle Channel (5 530 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*5 350.00	9.93	Peak	V	33.75	9.32	-	53.00	74.00	21.00
*5 350.00	-0.17	Average	V	33.75	9.32	3.22	46.12	54.00	7.88
*5 413.14	12.45	Peak	V	34.03	9.39	-	55.87	74.00	18.13
*5 413.14	0.76	Average	V	34.03	9.39	3.22	47.40	54.00	6.60
*5 460.00	9.24	Peak	V	34.29	9.12	-	52.65	74.00	21.35
*5 460.00	-0.14	Average	V	34.29	9.12	3.22	46.49	54.00	7.51

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*11 056.68	36.09	Peak	H	38.23	-27.37	-	46.95	74.00	27.05
*11 056.68	24.52	Average	H	38.23	-27.37	3.22	38.60	54.00	15.40
Above 11 100.00	Not detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11ac_VHT80 (Band 3)_MCS0

A. Low Channel (5 775 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 710.83	17.98	Peak	V	34.11	9.36	-	61.45	68.23	6.78
5 715.71	20.97	Peak	V	34.11	9.39	-	64.47	78.23	13.76
5 851.99	17.86	Peak	V	34.15	9.56	-	61.57	78.23	16.66
5 860.44	15.10	Peak	V	34.21	9.68	-	58.99	68.23	9.24

Radiated Emissions			Ant.	Correction Factors			Total	FCC Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*11 548.44	36.41	Peak	H	38.54	-28.96	-	45.99	74.00	28.01
*11 548.44	24.16	Average	H	38.54	-28.96	3.22	36.96	54.00	17.04
Above 11 600.00	Not detected	-	-	-	-	-	-	-	-

Remark:

1. "*" means the restricted band.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using Peak / average detector mode if frequency was in restricted band. Otherwise the frequency was out of restricted band, only peak detector should be used.
3. Band edge measurement
(Actual = Reading + Antenna Factor + CL + Duty cycle)
4. Radiated spurious emission measurement
(Actual = Reading + Antenna Factor + Amp + CL + Duty cycle)
5. If frequency was out of restricted band, the calculation method for peak limit is same as below:

$$68.23 \text{ dB}\mu\text{V/m} = \text{EIRP} - 20 \log(d) + 104.77 = -27 - 20 \log(3) + 104.77$$
6. In case of the frequency between 5 715 MHz ~ 5 725 MHz and 5 850 MHz ~ 5 860 MHz the limit is determined as 78.23 dBμV/m.

$$78.23 \text{ dB}\mu\text{V/m} = \text{EIRP} - 20 \log(d) + 104.77 = -17 - 20 \log(3) + 104.77$$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. 26 dB Bandwidth & 99 % Bandwidth

3.1. Test setup



3.2. Test procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

3.2.1. 26 dB Bandwidth

1. This measurement settings are specified in section C.1 of KDB 789033 D02 v01.
2. Set RBW: approximately 1 % of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

3.2.2. 99 % Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % occupied bandwidth is the difference between these two frequencies.

In the result,

- DFS requirements are not applicable in the 5 150 MHz - 5 250 MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.3. Test result

Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

3.3.1. 26 dB Bandwidth & 99 % Bandwidth


Band	Mode	Frequency (MHz)	Ch.	Data Rate	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	11a	5 180	36	6	21.40	-
		5 220	44	6	21.64	-
		5 240	48	6	21.76	16.93
	11n_HT20	5 180	36	MCS0	21.68	-
		5 220	44	MCS0	21.88	-
		5 240	48	MCS0	21.88	18.09
	11n_HT40	5 190	38	MCS0	39.84	-
		5 230	46	MCS0	39.60	-
	11ac_VHT80	5 210	42	MCS0	81.60	75.69
U-NII 2A	11a	5 260	52	6	21.76	-
		5 300	60	6	21.68	-
		5 320	64	6	21.80	-
	11n_HT20	5 260	52	MCS0	21.56	-
		5 300	60	MCS0	21.88	-
		5 320	64	MCS0	22.08	-
	11n_HT40	5 270	54	MCS0	39.84	-
		5 310	62	MCS0	39.84	-
	11ac_VHT80	5 290	58	MCS0	81.76	-
	U-NII 2C	11a	5 500	100	6	21.32
5 580			116	6	21.52	-
5 700			140	6	21.20	-
11n_HT20		5 500	100	MCS0	21.52	-
		5 580	116	MCS0	21.44	-
		5 700	140	MCS0	21.76	-
11n_HT40		5 510	102	MCS0	39.68	-
		5 550	110	MCS0	39.84	-
		5 670	134	MCS0	39.60	-
11ac_VHT80		5 530	106	MCS0	80.64	-
U-NII 3	11a	5 745	149	6	21.40	-
		5 785	157	6	21.28	-
		5 825	165	6	21.20	-
	11n_HT20	5 745	149	MCS0	21.80	-
		5 785	157	MCS0	21.56	-
		5 825	165	MCS0	21.36	-
	11n_HT40	5 755	151	MCS0	39.84	-
		5 795	159	MCS0	39.52	-
	11ac_VHT80	5 775	155	MCS0	80.96	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

26 dB Bandwidth

802.11a (Band 1)

Low Channel (5 180 MHz)




Middle Channel (5 220 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 2A)

Low Channel (5 260 MHz)



Middle Channel (5 300 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 2C)

Low Channel (5 500 MHz)




Middle Channel (5 580 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 700 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 3)

Low Channel (5 745 MHz)




Middle Channel (5 785 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel (5 825 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 1)

Low Channel (5 180 MHz)



Middle Channel (5 220 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 2A)

Low Channel (5 260 MHz)




Middle Channel (5 300 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 2C)

Low Channel (5 500 MHz)




Middle Channel (5 580 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 700 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 3)

Low Channel (5 745 MHz)



Middle Channel (5 785 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 825 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 1)

Low Channel (5 190 MHz)




High Channel (5 230 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 2A)

Low Channel (5 270 MHz)




High Channel (5 310 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 2C)

Low Channel (5 510 MHz)




Middle Channel (5 550 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 670 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 3)

Low Channel (5 755 MHz)



Middle Channel (5 795 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11ac_VHT80 (Band 1)

Middle Channel (5 210 MHz)



802.11ac_VHT80 (Band 2A)


Middle Channel (5 290 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


802.11ac_VHT80 (Band 2C)

Middle Channel (5 530 MHz)



802.11ac_VHT80 (Band 3)

Middle Channel (5 775 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

99 % Bandwidth


802.11a (Band 1)

High Channel (5 240 MHz)




802.11n_HT20 (Band 1)

High Channel (5 240 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11ac_VHT20 (Band 1) Middle Channel (5 210 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4. 6 dB bandwidth

4.1. Test setup



4.2. Limit

Within the 5.725 – 5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

4.3. Test procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

1. This measurement settings are specified in section C.2 of KDB 789033 D02 v01.
2. Set RBW: 100 kHz.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.4. Test result


Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

Band	Mode	Frequency (MHz)	Ch.	Data Rate	6 dB Bandwidth (MHz)
U-NII 3	11a	5 745	149	6	16.40
		5 785	157	6	16.40
		5 825	165	6	16.36
	11n_HT20	5 745	149	MCS0	17.60
		5 785	157	MCS0	17.64
		5 825	165	MCS0	17.64
	11n_HT40	5 755	151	MCS0	36.40
		5 795	159	MCS0	36.40
	11ac_VHT80	5 775	155	MCS0	76.16

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 3)

Low Channel (5 745 MHz)




Middle Channel (5 785 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 825 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 3)

Low Channel (5 745 MHz)




Middle Channel (5 785 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 825 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 3)

Low Channel (5 755 MHz)




High Channel (5 795 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


802.11ac_VHT80 (Band 3) Middle Channel (5 775 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4. Output power

4.1. Test setup



4.2. Limit

FCC 15.407 (a)(1)(iv)

For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dB i. In addition, the maximum power spectral density shall not exceed 11 dB m in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dB i are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB i.

(a)(2)

For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dB m 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dB m in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dB i are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB i.

(a)(3)

For the band 5.725 - 5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dB m in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dB i are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB i. However, fixed point-to point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dB i without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.3. Test procedure

1. This measurement settings are specified in section E.3.a of KDB 789033 D02 v01.
2. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.
 - The EUT is configured to transmit continuously or to transmit with a consistent duty cycle.
 - At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
3. If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in section II.B.
4. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
5. Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.4. Test result

Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

- 11a

Band	Power	Frequency (MHz)	Conducted Power (dB m)							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
U-NII 1	Mea. average	5 180	11.95	11.73	11.41	11.07	10.71	10.53	10.26	10.08
	Result		12.27	12.24	12.07	11.99	11.85	12.14	12.34	12.23
	Mea. average	5 220	11.70	11.51	11.32	11.01	10.82	10.63	10.17	9.96
	Result		12.02	12.02	11.98	11.93	11.96	12.24	12.25	12.11
	Mea. average	5 240	11.78	11.50	11.26	11.02	10.83	10.52	10.36	10.05
	Result		12.10	12.01	11.92	11.94	11.97	12.13	12.44	12.20
U-NII 2A	Mea. average	5 260	13.52	13.29	13.01	12.87	12.62	12.30	11.79	11.65
	Result		13.84	13.80	13.67	13.79	13.76	13.91	13.87	13.80
	Mea. average	5 300	13.48	13.21	12.98	12.80	12.67	12.31	11.82	11.72
	Result		13.80	13.72	13.64	13.72	13.81	13.92	13.90	13.87
	Mea. average	5 320	13.59	13.25	12.98	12.81	12.71	12.31	11.82	11.72
	Result		13.91	13.76	13.64	13.73	13.85	13.92	13.90	13.87
U-NII 2C	Mea. average	5 500	10.41	10.26	10.05	9.84	9.75	9.55	9.20	8.83
	Result		10.73	10.77	10.71	10.76	10.89	11.16	11.28	10.98
	Mea. average	5 580	10.43	10.21	9.89	9.64	9.56	9.32	9.09	8.64
	Result		10.75	10.72	10.55	10.56	10.70	10.93	11.17	10.79
	Mea. average	5 700	10.74	10.43	10.21	10.08	9.91	9.64	9.35	9.06
	Result		11.06	10.94	10.87	11.00	11.05	11.25	11.43	11.21
U-NII 3	Mea. average	5 745	10.70	10.46	10.21	10.06	9.95	9.71	9.43	8.96
	Result		11.02	10.97	10.87	10.98	11.09	11.32	11.51	11.11
	Mea. average	5 785	10.94	10.65	10.39	10.21	10.12	10.00	9.67	9.16
	Result		11.26	11.16	11.05	11.13	11.26	11.61	11.75	11.31
	Mea. average	5 825	10.71	10.44	10.05	9.91	9.84	9.60	9.31	8.88
	Result		11.03	10.95	10.71	10.83	10.98	11.21	11.39	11.03

Band	Conducted Power Limit (dB m)					
	Frequency (MHz)	Fixed Limit (dB m)	26 dB BW (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
U-NII 1	5 180	24				
	5 220	24				
	5 240	24				
U-NII 2A	5 260	24	21.76	24.38	4.77	24
	5 300	24	21.68	24.36	4.77	24
	5 320	24	21.80	24.38	4.77	24
U-NII 2C	5 500	24	21.32	24.29	1.68	24
	5 580	24	21.52	24.33	1.68	24
	5 700	24	21.20	24.26	1.68	24
U-NII 3	5 745	30				
	5 785	30				
	5 825	30				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Mode	Duty cycle							
	Data Rate [Mbps]							
11a	6	9	12	18	24	36	48	54
Duty Cycle (%)	93	89	86	81	77	69	62	61
Correction factor (dB)	0.32	0.51	0.66	0.92	1.14	1.61	2.08	2.15

Remark:

1. Result (dB m) = Average (dB m) + Correction factor (dB)
2. Duty cycle (%) = (Tx on time / Tx on + off time) x 100
3. Correction factor (dB) = 10 log (1/duty cycle (ms))

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

- 11n_HT20

Band	Power	Frequency (MHz)	Conducted Power (dB m)							
			Data Rate [MCS]							
			0	1	2	3	4	5	6	7
U-NII 1	Mea. average	5 180	11.85	11.43	11.09	10.81	10.67	10.55	10.36	9.93
	Result		12.21	12.09	12.01	12.00	12.34	12.56	12.51	12.22
	Mea. average	5 220	11.70	11.36	11.05	10.74	10.41	10.26	10.05	9.71
	Result		12.06	12.02	11.97	11.93	12.08	12.27	12.20	12.00
	Mea. average	5 240	11.55	11.36	11.05	10.77	10.48	10.26	10.06	9.96
	Result		11.91	12.02	11.97	11.96	12.15	12.27	12.21	12.25
U-NII 2A	Mea. average	5 260	13.34	13.11	12.94	12.62	12.20	11.88	11.70	11.55
	Result		13.70	13.77	13.86	13.81	13.87	13.89	13.85	13.84
	Mea. average	5 300	13.45	13.21	12.98	12.55	12.22	11.91	11.74	11.54
	Result		13.81	13.87	13.90	13.74	13.89	13.92	13.89	13.83
	Mea. average	5 320	13.50	13.21	12.97	12.67	12.22	11.87	11.60	11.52
	Result		13.86	13.87	13.89	13.86	13.89	13.88	13.75	13.81
U-NII 2C	Mea. average	5 500	10.57	10.40	10.12	9.70	9.26	9.05	8.81	8.64
	Result		10.93	11.06	11.04	10.89	10.93	11.06	10.96	10.93
	Mea. average	5 580	10.36	10.09	9.74	9.52	9.25	9.06	8.77	8.52
	Result		10.72	10.75	10.66	10.71	10.92	11.07	10.92	10.81
	Mea. average	5 700	10.77	10.46	10.05	9.77	9.53	9.21	9.06	8.90
	Result		11.13	11.12	10.97	10.96	11.20	11.22	11.21	11.19
U-NII 3	Mea. average	5 745	10.86	10.61	10.31	10.06	9.78	9.60	9.24	9.00
	Result		11.22	11.27	11.23	11.25	11.45	11.61	11.39	11.29
	Mea. average	5 785	10.94	10.71	10.36	10.08	9.63	9.55	9.26	9.14
	Result		11.30	11.37	11.28	11.27	11.30	11.56	11.41	11.43
	Mea. average	5 825	10.50	10.31	10.07	9.74	9.45	9.26	9.05	8.86
	Result		10.86	10.97	10.99	10.93	11.12	11.27	11.20	11.15

Band	Conducted Power Limit (dB m)					
	Frequency (MHz)	Fixed Limit (dB m)	26 dB BW (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
U-NII 1	5 180	24				
	5 220	24				
	5 240	24				
U-NII 2A	5 260	24	21.56	24.34	4.77	24
	5 300	24	21.88	24.40	4.77	24
	5 320	24	22.08	24.44	4.77	24
U-NII 2C	5 500	24	21.52	24.33	1.68	24
	5 580	24	21.44	24.31	1.68	24
	5 700	24	21.76	24.38	1.68	24
U-NII 3	5 745	30				
	5 785	30				
	5 825	30				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Mode	Duty cycle							
	Data Rate [MCS]							
11n_HT20	0	1	2	3	4	5	6	7
Duty Cycle (%)	92	86	81	76	68	63	61	59
Correction factor (dB)	0.36	0.66	0.92	1.19	1.67	2.01	2.15	2.29

Remark:

1. Result (dB m) = Average (dB m) + Correction factor (dB)
2. Duty cycle (%) = (Tx on time / Tx on + off time) x 100
3. Correction factor (dB) = 10 log (1/duty cycle (ms))

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

- 11n_HT40

Band	Power	Frequency (MHz)	Conducted Power (dB m)							
			Data Rate [MCS]							
			0	1	2	3	4	5	6	7
U-NII 1	Mea. average	5 190	12.69	12.30	11.74	11.18	10.42	9.82	9.59	9.20
	Result		13.55	13.85	13.89	13.86	13.89	13.91	13.991	13.89
	Mea. average	5 230	12.48	12.05	11.71	11.25	10.40	9.77	9.50	9.17
	Result		13.34	13.60	13.86	13.93	13.87	13.86	13.82	13.86
U-NII 2A	Mea. average	5 270	13.00	12.34	11.77	11.22	10.41	9.80	9.36	9.10
	Result		13.86	13.89	13.92	13.90	13.88	13.89	13.68	13.79
	Mea. average	5 310	13.02	12.36	11.74	11.16	10.42	9.65	9.26	9.03
	Result		13.88	13.91	13.89	13.84	13.89	13.74	13.58	13.72
U-NII 2C	Mea. average	5 510	11.01	10.64	10.32	9.84	9.15	9.00	8.55	8.36
	Result		11.87	12.19	12.47	12.52	12.62	13.09	12.87	13.05
	Mea. average	5 550	10.77	10.22	9.87	9.51	9.07	8.86	8.50	8.25
	Result		11.63	11.77	12.02	12.19	12.54	12.95	12.82	12.94
	Mea. average	5 670	10.48	10.11	9.87	9.40	8.73	8.30	8.04	7.86
	Result		11.34	11.66	12.02	12.08	12.20	12.39	12.36	12.55
U-NII 3	Mea. average	5 755	11.30	11.00	10.55	10.14	9.65	9.37	9.04	8.77
	Result		12.16	12.55	12.70	12.82	13.12	13.46	13.36	13.46
	Mea. average	5 795	11.07	10.70	10.33	9.87	9.43	9.30	8.96	8.66
	Result		11.93	12.25	12.48	12.55	12.90	13.39	13.28	13.35

Band	Conducted Power Limit (dB m)					
	Frequency (MHz)	Fixed Limit (dB m)	26 dB BW (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
U-NII 1	5 190	24				
	5 230	24				
U-NII 2A	5 270	24	39.84	27.00	4.77	24
	5 310	24	39.84	27.00	4.77	24
U-NII 2C	5 510	24	39.68	26.99	1.68	24
	5 550	24	39.84	27.00	1.68	24
	5 670	24	39.60	26.98	1.68	24
U-NII 3	5 755	30				
	5 795	30				

Mode	Duty cycle							
	Data Rate [MCS]							
11n_HT40	0	1	2	3	4	5	6	7
Duty Cycle (%)	82	70	61	54	45	39	37	34
Correction factor (dB)	0.86	1.55	2.15	2.68	3.47	4.09	4.32	4.69

Remark:

- Result (dB m) = Average (dB m) + Correction factor (dB)
- Duty cycle (%) = (Tx on time / Tx on + off time) x 100
- Correction factor (dB) = 10 log (1/duty cycle (ms))

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

- 11ac_VHT20

Band	Power	Frequency (MHz)	Conducted Power (dB m)								
			Data Rate [MCS]								
			0	1	2	3	4	5	6	7	8
U-NII 1	Mea. average	5 180	11.84	11.35	11.02	10.84	10.75	10.53	10.29	10.04	9.92
	Result		12.20	12.01	11.94	12.03	12.42	12.54	12.44	12.33	12.44
	Mea. average	5 220	11.66	11.34	11.10	10.84	10.60	10.56	10.29	9.99	9.80
	Result		12.02	12.00	12.02	12.03	12.27	12.57	12.44	12.28	12.32
	Mea. average	5 240	11.77	11.49	11.21	10.80	10.54	10.36	10.05	9.80	9.71
	Result		12.13	12.15	12.13	11.99	12.21	12.37	12.20	12.09	12.23
U-NII 2A	Mea. average	5 260	13.50	13.21	12.98	12.58	12.24	11.89	11.77	11.61	11.36
	Result		13.86	13.87	13.90	13.77	13.91	13.90	13.92	13.90	13.88
	Mea. average	5 300	13.49	13.22	12.94	12.54	12.20	11.87	11.72	11.60	11.38
	Result		13.85	13.88	13.86	13.73	13.87	13.88	13.87	13.89	13.90
	Mea. average	5 320	13.55	13.21	12.90	12.67	12.21	11.88	11.67	11.52	11.40
	Result		13.91	13.87	13.82	13.86	13.88	13.89	13.82	13.81	13.92
U-NII 2C	Mea. average	5 500	10.46	10.24	10.08	9.66	9.26	9.11	8.87	8.69	8.60
	Result		10.82	10.90	11.00	10.85	10.93	11.12	11.02	10.98	11.12
	Mea. average	5 580	10.41	10.22	9.89	9.61	9.19	8.99	8.77	8.61	8.44
	Result		10.77	10.88	10.81	10.80	10.86	11.00	10.92	10.90	10.96
	Mea. average	5 700	10.70	10.44	10.09	9.71	9.54	9.34	9.10	8.89	8.80
	Result		11.06	11.10	11.01	10.90	11.21	11.35	11.25	11.18	11.32
U-NII 3	Mea. average	5 745	10.90	10.54	10.23	9.94	9.71	9.55	9.21	9.05	8.96
	Result		11.26	11.20	11.15	11.13	11.38	11.56	11.36	11.34	11.48
	Mea. average	5 785	10.84	10.67	10.26	10.04	9.69	9.50	9.35	9.19	8.95
	Result		11.20	11.33	11.18	11.23	11.36	11.51	11.50	11.48	11.47
	Mea. average	5 825	10.65	10.51	10.20	9.87	9.54	9.26	9.10	8.83	8.60
	Result		11.01	11.17	11.12	11.06	11.21	11.27	11.25	11.12	11.12

Band	Conducted Power Limit (dB m)					
	Frequency (MHz)	Fixed Limit (dB m)	26 dB BW (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
U-NII 1	5 180	24				
	5 220	24				
	5 240	24				
U-NII 2A	5 260	24	21.76	24.38	4.77	24
	5 300	24	21.60	24.34	4.77	24
	5 320	24	21.40	24.30	4.77	24
U-NII 2C	5 500	24	21.40	24.30	1.68	24
	5 580	24	21.56	24.34	1.68	24
	5 700	24	21.48	24.32	1.68	24
U-NII 3	5 745	30				
	5 785	30				
	5 825	30				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Mode	Duty cycle								
	Data Rate [MCS]								
11ac VHT20	0	1	2	3	4	5	6	7	8
Duty Cycle (%)	92	86	81	76	68	63	61	59	56
Correction factor (dB)	0.36	0.66	0.92	1.19	1.67	2.01	2.15	2.29	2.52

Remark:

1. Result (dB m) = Average (dB m) + Correction factor (dB)
2. Duty cycle (%) = (Tx on time / Tx on + off time) x 100
3. Correction factor (dB) = 10 log (1/duty cycle (ms))

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

- 11ac_VHT40

Band	Power	Frequency (MHz)	Conducted Power (dB m)									
			Data Rate [MCS]									
			0	1	2	3	4	5	6	7	8	9
U-NII 1	Mea. average	5 190	12.60	12.05	11.62	11.10	10.38	9.79	9.51	9.20	8.96	8.52
	Result		13.46	13.60	13.77	13.78	13.85	13.88	13.83	13.89	13.91	13.90
	Mea. average	5 230	12.48	12.06	11.62	11.21	10.40	9.80	9.49	9.11	8.96	8.50
	Result		13.34	13.61	13.77	13.89	13.87	13.89	13.81	13.80	13.91	13.88
U-NII 2A	Mea. average	5 270	13.04	12.36	11.66	11.12	10.46	9.80	9.33	9.10	8.88	8.51
	Result		13.90	13.91	13.81	13.80	13.93	13.89	13.65	13.79	13.83	13.89
	Mea. average	5 310	13.03	12.25	11.73	11.10	10.41	9.62	9.29	9.10	8.77	8.50
	Result		13.89	13.80	13.88	13.78	13.88	13.71	13.61	13.79	13.72	13.88
U-NII 2C	Mea. average	5 510	10.80	10.62	10.20	9.74	9.22	9.05	8.67	8.46	8.31	8.20
	Result		11.66	12.17	12.35	12.42	12.69	13.14	12.99	13.15	13.26	13.58
	Mea. average	5 550	10.80	10.29	9.87	9.45	8.97	8.71	8.49	8.24	8.02	7.91
	Result		11.66	11.84	12.02	12.13	12.44	12.80	12.81	12.93	12.97	13.29
	Mea. average	5 670	10.38	10.08	9.66	9.27	8.78	8.49	8.21	7.90	7.82	7.70
	Result		11.24	11.63	11.81	11.95	12.25	12.58	12.53	12.59	12.77	13.08
U-NII 3	Mea. average	5 755	11.25	10.89	10.37	10.01	9.57	9.40	9.11	8.89	8.70	8.57
	Result		12.11	12.44	12.52	12.69	13.04	13.49	13.43	13.58	13.65	13.95
	Mea. average	5 795	11.18	10.84	10.36	9.94	9.42	9.26	9.00	8.74	8.56	8.44
	Result		12.04	12.39	12.51	12.62	12.89	13.35	13.32	13.43	13.51	13.82

Band	Conducted Power Limit (dB m)					
	Frequency (MHz)	Fixed Limit (dB m)	26 dB BW (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
U-NII 1	5 190	24				
	5 230	24				
U-NII 2A	5 270	24	39.44	26.96	4.77	24
	5 310	24	39.84	27.00	4.77	24
U-NII 2C	5 510	24	39.52	26.97	1.68	24
	5 550	24	39.68	26.99	1.68	24
	5 670	24	39.76	26.99	1.68	24
U-NII 3	5 755	30				
	5 795	30				

Mode	Duty cycle									
	Data Rate [MCS]									
11ac_VHT40	0	1	2	3	4	5	6	7	8	9
Duty Cycle (%)	82	70	61	54	45	39	37	34	32	29
Correction factor (dB)	0.86	1.55	2.15	2.68	3.47	4.09	4.32	4.69	4.95	5.38

Remark:

1. Result (dB m) = Average (dB m) + Correction factor (dB)
2. Duty cycle (%) = (Tx on time / Tx on + off time) x 100
3. Correction factor (dB) = 10 log (1/duty cycle (ms))

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

- 11ac_VHT80

Band	Power	Frequency (MHz)	Conducted Power (dB m)									
			Data Rate [MCS]									
			0	1	2	3	4	5	6	7	8	9
U-NII 1	Mea. Average	5 210	11.35	7.75	10.40	9.77	8.60	8.01	7.73	7.29	7.01	6.66
	Result		12.96	13.77	13.87	13.86	13.83	13.86	13.75	13.87	13.59	13.65
U-NII 2A	Mea. Average	5 290	12.18	7.80	10.39	9.69	8.64	8.01	7.44	7.16	7.00	6.79
	Result		13.79	13.82	13.86	13.78	13.87	13.86	13.46	13.74	13.58	13.78
U-NII 2C	Mea. Average	5 530	9.94	7.55	9.21	8.64	7.99	7.66	7.43	7.21	7.10	6.87
	Result		11.55	13.57	12.68	12.73	13.22	13.51	13.45	13.79	13.68	13.86
U-NII 3	Mea. Average	5 775	10.28	7.82	9.26	8.44	8.00	7.95	7.65	7.28	7.14	6.90
	Result		11.89	13.84	12.73	12.53	13.23	13.80	13.67	13.86	13.72	13.89

Band	Conducted Power Limit (dB m)					
	Frequency (MHz)	Fixed Limit (dB m)	26 dB BW (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
U-NII 1	5 210	24				
U-NII 2A	5 290	24	81.76	30.13	4.77	24
U-NII 2C	5 530	24	80.64	30.07	1.68	24
U-NII 3	5 775	30				

Mode	Duty cycle									
	Data Rate [MCS]									
11ac_VHT80	0	1	2	3	4	5	6	7	8	9
Duty Cycle (%)	69	25	45	39	30	26	25	22	22	20
Correction factor (dB)	1.61	6.02	3.47	4.09	5.23	5.85	6.02	6.58	6.58	6.99

Remark:

1. Result (dB m) = Average (dB m) + Correction factor (dB)
2. Duty cycle (%) = (Tx on time / Tx on + off time) x 100
3. Correction factor (dB) = 10 log (1/duty cycle (ms))

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5. Peak power spectral density

5.1. Test setup



5.2. Limit

FCC 15.407 (a)(1)(iv)

For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(a)(2)

For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm $10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(a)(3)

For the band 5.725 - 5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5.3. Test procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

1. This measurement settings are specified in section F of KDB 789033 D02 v01.
2. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
3. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
4. Make the following adjustments to the peak value of the spectrum, if applicable:
 - a) **If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.**
 - b) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
5. The result is the Maximum PSD over 1 MHz reference bandwidth.
6. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth ($< 1 \text{ MHz}$, or $< 500 \text{ kHz}$) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
 - a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
 - b) Set $\text{VBW} \geq 3 \text{ RBW}$.
 - c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500 \text{ kHz}/\text{RBW})$ to the measured result, whereas RBW ($< 500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 - d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1 \text{ MHz}/\text{RBW})$ to the measured result, whereas RBW ($< 1 \text{ MHz}$) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 - e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW=100 kHz is available on nearly all spectrum analyzers.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5.4. Test result


Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

Band	Mode	Frequency (MHz)	Ch.	Data Rate	Measured PPSD (dB m)	Duty Factor (dB)	Final PPSD (dB m)	Limit (dB m/MHz)
U-NII 1	11a	5 180	36	6	-4.78	0.32	-4.46	11
		5 220	44	6	-5.87	0.32	-5.55	11
		5 240	48	6	-5.60	0.32	-5.28	11
	11n_HT20	5 180	36	MCS0	-5.13	0.36	-4.77	11
		5 220	44	MCS0	-6.31	0.36	-5.95	11
		5 240	48	MCS0	-5.99	0.36	-5.63	11
	11n_HT40	5 190	38	MCS0	-7.76	0.86	-6.90	11
		5 230	46	MCS0	-8.46	0.86	-7.60	11
	11ac_VHT80	5 210	42	MCS0	-11.97	1.61	-10.36	11
U-NII 2A	11a	5 260	52	6	-4.29	0.32	-3.97	11
		5 300	60	6	-5.25	0.32	-4.93	11
		5 320	64	6	-5.23	0.32	-4.91	11
	11n_HT20	5 260	52	MCS0	-4.60	0.36	-4.24	11
		5 300	60	MCS0	-5.60	0.36	-5.24	11
		5 320	64	MCS0	-5.62	0.36	-5.26	11
	11n_HT40	5 270	54	MCS0	-7.74	0.86	-6.88	11
		5 310	62	MCS0	-8.35	0.86	-7.49	11
	11ac_VHT80	5 290	58	MCS0	-12.11	1.61	-10.50	11
U-NII 2C	11a	5 500	134	6	-10.03	0.32	-9.71	11
		5 580	106	6	-9.86	0.32	-9.54	11
		5 700	140	6	-9.48	0.32	-9.16	11
	11n_HT20	5 500	100	MCS0	-10.63	0.36	-10.27	11
		5 580	116	MCS0	-10.05	0.36	-9.69	11
		5 700	140	MCS0	-10.04	0.36	-9.68	11
	11n_HT40	5 510	102	MCS0	-14.14	0.86	-13.28	11
		5 550	110	MCS0	-13.61	0.86	-12.75	11
	11ac_VHT80	5 670	134	MCS0	-12.78	0.86	-11.92	11
U-NII 3	11a	5 530	106	MCS0	-17.57	1.61	-15.96	11
		5 745	149	6	-10.95	0.32	-10.63	30
		5 785	157	6	-11.41	0.32	-11.09	30
	11n_HT20	5 825	165	6	-10.50	0.32	-10.18	30
		5 745	149	MCS0	-11.48	0.36	-11.12	30
		5 785	157	MCS0	-11.49	0.36	-11.13	30
		5 825	165	MCS0	-10.86	0.36	-10.50	30
	11n_HT40	5 755	151	MCS0	-14.14	0.86	-13.28	30
		5 795	159	MCS0	-14.29	0.86	-13.43	30
	11ac_VHT80	5 775	155	MCS0	-17.88	1.61	-16.27	30


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 1)

Low Channel (5 180 MHz)




Middle Channel (5 220 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 2A)

Low Channel (5 260 MHz)




Middle Channel (5 300 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 2C)

Low Channel (5 500 MHz)




Middle Channel (5 580 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 700 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11a (Band 3)

Low Channel (5 745 MHz)




Middle Channel (5 785 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 825 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 1)

Low Channel (5 180 MHz)




Middle Channel (5 220 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 2A)

Low Channel (5 260 MHz)




Middle Channel (5 300 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 2C)

Low Channel (5 500 MHz)




Middle Channel (5 580 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel (5 700 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT20 (Band 3)

Low Channel (5 745 MHz)



Middle Channel (5 785 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel (5 825 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 1)

Low Channel (5 190 MHz)




High Channel (5 230 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 2A)

Low Channel (5 270 MHz)




High Channel (5 310 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 2C)

Low Channel (5 510 MHz)




Middle Channel (5 550 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel (5 670 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

802.11n_HT40 (Band 3)

Low Channel (5 755 MHz)



High Channel (5 795 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


802.11ac_VHT80 (Band 1)

Middle Channel (5 210 MHz)



802.11ac_VHT80 (Band 2A)


Middle Channel (5 290 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


802.11ac_VHT80 (Band 2C)

Middle Channel (5 530 MHz)



802.11ac_VHT80 (Band 3)

Middle Channel (5 775 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.