

# TEST REPORT

of

FCC Part 15 Subpart E §15.407  
 IC RSS-247 Issue 2 and RSS-Gen Issue 5


FCC ID: TQ8-ATC41GWAN  
 IC Certification: 5074A-ATC41GWKN

1. Equipment Under Test : DIGITAL CAR AVN SYSTEM
2. Model Name : FCC: ATC41GWAN  
 : IC: ATC41GWKN
3. Variant Model Name(s) : Refer to the page 3
4. Applicant : Hyundai Mobis Co., Ltd.
5. Manufacturer : Hyundai Mobis Co., Ltd.
6. Date of Receipt : 2020.02.19
7. Date of Test(s) : 2020.03.09 ~ 2020.04.09
8. Date of Issue : 2020.04.27

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.

Tested by:

  
 Jinhyoung Cho

Technical  
 Manager:

  
 Hyunchae You

**SGS Korea Co., Ltd. Gunpo Laboratory**

# INDEX

## Table of contents

|                                                  |     |
|--------------------------------------------------|-----|
| 1. General Information -----                     | 3   |
| 2. Transmitter Radiated Spurious Emissions ----- | 12  |
| 3. 26 dB Bandwidth & 99 % Bandwidth -----        | 50  |
| 4. 6 dB Bandwidth -----                          | 84  |
| 5. Maximum Conducted Output Power -----          | 91  |
| 6. Peak Power Spectral Density -----             | 104 |
| 7. Antenna Requirement -----                     | 130 |

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

### 1.2. Details of Applicant

Applicant : Hyundai Mobis Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977

Contact Person : Choe, Seung-hoon

Phone No. : +82 31 260 0098

### 1.3. Details of Manufacturer

Company : Same as applicant

Address : Same as applicant

#### 1.4. Description of EUT

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Kind of Product</b>         | DIGITAL CAR AVN SYSTEM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>FCC Model Name</b>          | ATC41GWAN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>IC Model Name</b>           | ATC41GWKN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>FCC Variant Model Names</b> | ATC40GWAN, ATC40GXAN, ATC41GXAN, ATC42GXAN, ATC43GXAN, ATC40HPAN, ATC41HPAN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>IC Variant Model Names</b>  | ATC40GWKN, ATC40HPKN, ATC41HPKN, VT260GXKN, VT261GXKN, VT262GXKN, VT263GXKN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Power Supply</b>            | DC 14.4 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Frequency Range</b>         | 5 180 MHz ~ 5 240 MHz (Band 1: 11a/n_HT20, 11ac_VHT20)<br>5 190 MHz ~ 5 230 MHz (Band 1: 11n_HT40, 11ac_VHT40)<br>5 210 MHz (Band 1: 11ac_VHT80)<br>5 260 MHz ~ 5 320 MHz (Band 2A: 11a/n_HT20, 11ac_VHT20)<br>5 270 MHz ~ 5 310 MHz (Band 2A: 11n_HT40, 11ac_VHT40)<br>5 290 MHz (Band 2A: 11ac_VHT80)<br>5 500 MHz ~ 5 720 MHz (Band 2C: 11a/n_HT20, 11ac_VHT20)<br>5 510 MHz ~ 5 710 MHz (Band 2C: 11n_HT40, 11ac_VHT40)<br>5 530 MHz ~ 5 690 MHz (Band 2C: 11ac_VHT80)<br>5 745 MHz ~ 5 825 MHz (Band 3: 11a/n_HT20, 11ac_VHT20)<br>5 755 MHz ~ 5 795 MHz (Band 3: 11n_HT40, 11ac_VHT40)<br>5 775 MHz (Band 3: 11ac_VHT80) |
| <b>Modulation Technique</b>    | OFDM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Number of Channels</b>      | 4 channels (Band 1: 11a/n_HT20, 11ac_VHT20)<br>2 channels (Band 1: 11n_HT40, 11ac_VHT40)<br>1 channel (Band 1: 11ac_VHT80)<br>4 channels (Band 2A: 11a/n_HT20, 11ac_VHT20)<br>2 channels (Band 2A: 11n_HT40, 11ac_VHT40)<br>1 channel (Band 2A: 11ac_VHT80)<br>9 channels (Band 2C: 11a/n_HT20, 11ac_VHT20)<br>4 channels (Band 2C: 11n_HT40, 11ac_VHT40)<br>2 channels (Band 2C: 11ac_VHT80)<br>5 channels (Band 3: 11a/n_HT20, 11ac_VHT20)<br>2 channels (Band 3: 11n_HT40, 11ac_VHT40)<br>1 channel (Band 3: 11ac_VHT80)                                                                                                    |
| <b>Antenna Type</b>            | Pattern antenna                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Antenna Gain</b>            | 5 180 MHz ~ 5 240 MHz: 0.59 dB i<br>5 260 MHz ~ 5 320 MHz: 2.00 dB i<br>5 500 MHz ~ 5 720 MHz: 4.58 dB i<br>5 745 MHz ~ 5 825 MHz: 4.19 dB i                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## **1.5. Declaration by the Manufacturer**

- The EUT is a slave without radar detection and TPC.
- The EUT is not supported TDWR(5.6 - 5.65 GHz) band.

## **1.6. Automatically Discontinue Transmission**

### **1.6.1. Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operating failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **1.6.2. Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

## 1.7. Test Equipment List

| Equipment                | Manufacturer                | Model                                | S/N                    | Cal. Date     | Cal. Interval | Cal. Due      |
|--------------------------|-----------------------------|--------------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator         | R&S                         | SMR40                                | 100272                 | Jun. 07, 2019 | Annual        | Jun. 07, 2020 |
| Signal Generator         | R&S                         | SMBV100A                             | 255834                 | Jun. 10, 2019 | Annual        | Jun. 10, 2020 |
| Spectrum Analyzer        | R&S                         | FSV30                                | 103101                 | Jun. 05, 2019 | Annual        | Jun. 05, 2020 |
| Spectrum Analyzer        | Agilent                     | N9030A                               | US51350132             | Nov. 15, 2019 | Annual        | Nov. 15, 2020 |
| Power Meter              | Anritsu                     | ML2495A                              | 1223004                | Jun. 05, 2019 | Annual        | Jun. 05, 2020 |
| Power Sensor             | Anritsu                     | MA2411B                              | 1207272                | Jun. 05, 2019 | Annual        | Jun. 05, 2020 |
| Attenuator               | AEROFLEX / INMET            | 40AH2W-10                            | 40G-3                  | Jun. 20, 2019 | Annual        | Jun. 20, 2020 |
| Low Pass Filter          | Mini-Circuits               | NLP-1200+                            | V 9500401023-2         | Jun. 05, 2019 | Annual        | Jun. 05, 2020 |
| High Pass Filter         | Wainwright Instrument GmbH  | WHKX6.0/18G-10SS                     | 51                     | Jun. 07, 2019 | Annual        | Jun. 07, 2020 |
| High Pass Filter         | Wainwright Instrument GmbH  | WHNX7.5/26.5G-6SS                    | 15                     | Jun. 07, 2019 | Annual        | Jun. 07, 2020 |
| DC Power Supply          | Agilent                     | U8002A                               | MY53150029             | Jun. 10, 2019 | Annual        | Jun. 10, 2020 |
| Signal Conditioning Unit | R&S                         | SCU-18                               | 10117                  | Jun. 12, 2019 | Annual        | Jun. 12, 2020 |
| Preamplifier             | MITEQ Inc.                  | JS44-18004000-35-8P                  | 1546891                | May 13, 2019  | Annual        | May 13, 2020  |
| Loop Antenna             | Schwarzbeck Mess-Elektronik | FMZB 1519                            | 1519-039               | Aug. 22, 2019 | Biennial      | Aug. 22, 2021 |
| Bilog Antenna            | Schwarzbeck Mess-Elektronik | VULB 9163                            | 396                    | Mar. 21, 2019 | Biennial      | Mar. 21, 2021 |
| Horn Antenna             | R&S                         | HF906                                | 100326                 | Feb. 14, 2020 | Annual        | Feb. 14, 2021 |
| Horn Antenna             | Schwarzbeck Mess-Elektronik | BBHA 9170                            | BBHA9170431            | Sep. 10, 2018 | Biennial      | Sep. 10, 2020 |
| Test Receiver            | R&S                         | ESU26                                | 100109                 | Feb. 18, 2020 | Annual        | Feb. 18, 2021 |
| Turn Table               | Innco systems GmbH          | DS 1200 S                            | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Controller               | Innco systems GmbH          | CONTROLLER CO3000-4P                 | CO3000/963/383 30516/L | N.C.R.        | N/A           | N.C.R.        |
| Antenna Mast             | Innco systems GmbH          | MA4640-XP-ET                         | MA4640/536/383 30516/L | N.C.R.        | N/A           | N.C.R.        |
| Anechoic Chamber         | SY Corporation              | L × W × H<br>(9.6 m × 6.4 m × 6.6 m) | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Coaxial Cable            | SUCOFLEX                    | 104 (3 m)                            | MY3258414              | Jan. 28, 2020 | Semi-annual   | Jul. 28, 2020 |
| Coaxial Cable            | SUCOFLEX                    | 104 (10 m)                           | MY3145814              | Jan. 28, 2020 | Semi-annual   | Jul. 28, 2020 |
| Coaxial Cable            | Rosenberger                 | LA1-C006-1500                        | 131014 07/20           | Feb. 23, 2020 | Semi-annual   | Aug. 23, 2020 |

## 1.8. Summary of Test Result

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 15 Subpart E, IC RSS-247 Issue 2, RSS-Gen Issue 5           |                                                                                                                                 |                                         |                   |
|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-------------------|
| Section in FCC                                                                         | Section in IC                                                                                                                   | Test Item(s)                            | Result            |
| 15.205(a)<br>15.209(a)<br>15.407(b)(1)<br>15.407(b)(2)<br>15.407(b)(3)<br>15.407(b)(4) | RSS-Gen Issue 5 8.9<br>RSS-247 Issue 2 6.2.1.2<br>RSS-247 Issue 2 6.2.2.2<br>RSS-247 Issue 2 6.2.3.2<br>RSS-247 Issue 2 6.2.4.2 | Transmitter Radiated Spurious Emissions | Complied          |
| 15.407(a)                                                                              | RSS-Gen Issue 5 6.7                                                                                                             | 26 dB Bandwidth & 99 % Bandwidth        | Complied          |
| 15.407(e)                                                                              | RSS-247 Issue 2 6.2.4.1                                                                                                         | 6 dB Bandwidth                          | Complied          |
| 15.407(a)(1)<br>15.407(a)(2)<br>15.407(a)(3)                                           | RSS-247 Issue 2 6.2.1.1<br>RSS-247 Issue 2 6.2.2.1<br>RSS-247 Issue 2 6.2.3.1<br>RSS-247 Issue 2 6.2.4.1                        | Maximum Conducted Output Power          | Complied          |
| 15.407(a)(1)<br>15.407(a)(2)<br>15.407(a)(3)                                           | RSS-247 Issue 2 6.2.1.1<br>RSS-247 Issue 2 6.2.2.1<br>RSS-247 Issue 2 6.2.3.1<br>RSS-247 Issue 2 6.2.4.1                        | Peak Power Spectral Density             | Complied          |
| 15.207                                                                                 | RSS-Gen Issue 5 8.8                                                                                                             | AC Power Line Conducted Emission        | N/A <sup>1)</sup> |

**Note;**

- 1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

## 1.9. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 were used in the measurement of the DUT.

## 1.10. Sample Calculation

Where relevant, the following sample calculation is provided:

### 1.10.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

### 1.10.2. Radiation Test

Field strength level (dB $\mu$ V/m) = Measured level (dB $\mu$ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)

## 1.11. Test Report Revision

| Revision | Report Number        | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0        | F690501-RF-RTL000593 | 2020.04.27    | Initial     |

## 1.12. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter                          | Uncertainty    |
|------------------------------------|----------------|
| RF Output Power                    | $\pm 0.34$ dB  |
| Occupied Bandwidth                 | $\pm 9.66$ kHz |
| Power Spectral Density             | $\pm 0.61$ dB  |
| Radiated Emission, 9 kHz to 30 MHz | $\pm 3.59$ dB  |
| Radiated Emission, below 1 GHz     | $\pm 5.88$ dB  |
| Radiated Emission, above 1 GHz     | $\pm 5.94$ dB  |

Uncertainty figures are valid to a confidence level of 95 %.

### 1.13. Information of Variant Models

| Model Names    |     |           | Description |                 |      |        |     |    |            |
|----------------|-----|-----------|-------------|-----------------|------|--------|-----|----|------------|
|                |     |           | Local       | BT / WiFi / LTE | UI   | Camera | SXM | HD | FM/AM Code |
| Basic Model    | FCC | ATC41GWAN | U.S.A       | BT, WiFi, LTE   | GEN  | SVM    | O   | O  | A2         |
|                | IC  | ATC41GWKN | Canada      | BT, WiFi, LTE   | GEN  | SVM    | O   | O  | A2         |
| Variant Models | FCC | ATC40GWAN | U.S.A       | BT, WiFi, LTE   | GEN  | RVM    | O   | O  | A2         |
|                |     | ATC40GXAN | U.S.A       | BT, WiFi, LTE   | HEV  | RVM    | O   | O  | A2         |
|                |     | ATC41GXAN | U.S.A       | BT, WiFi, LTE   | HEV  | SVM    | O   | O  | A2         |
|                |     | ATC42GXAN | U.S.A       | BT, WiFi, LTE   | PHEV | RVM    | O   | O  | A2         |
|                |     | ATC43GXAN | U.S.A       | BT, WiFi, LTE   | PHEV | SVM    | O   | O  | A2         |
|                |     | ATC40HPAN | U.S.A       | BT, WiFi, LTE   | GEN  | RVM    | O   | O  | A2         |
|                |     | ATC41HPAN | U.S.A       | BT, WiFi, LTE   | GEN  | SVM    | O   | O  | A2         |
|                | IC  | ATC40GWKN | Canada      | BT, WiFi, LTE   | GEN  | RVM    | O   | O  | A2         |
|                |     | ATC40HPKN | Canada      | BT, WiFi, LTE   | GEN  | RVM    | O   | O  | A2         |
|                |     | ATC41HPKN | Canada      | BT, WiFi, LTE   | GEN  | SVM    | O   | O  | A2         |
|                |     | VT260GXKN | Canada      | BT, WiFi, LTE   | HEV  | RVM    | O   | O  | A2         |
|                |     | VT261GXKN | Canada      | BT, WiFi, LTE   | HEV  | SVM    | O   | O  | A2         |
|                |     | VT262GXKN | Canada      | BT, WiFi, LTE   | PHEV | RVM    | O   | O  | A2         |

| BAND | CODE | FREQUENCY RANGE | STEP    | LOCAL  |
|------|------|-----------------|---------|--------|
| FM   | A2   | 87.5-107.9 MHz  | 200 kHz | NA/GEN |
| AM   |      | 530-1 710 kHz   | 10 kHz  |        |

### 1.14. Duty Cycle of EUT

Regarding to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, II.B, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.

Set RBW ≥ EBW if possible; otherwise, set RBW to the largest available value, Set VBW ≥ RBW.

Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.


| Mode       | Data Rate (Mbps) | Duty Cycle (%) | Correction Factor (dB) |
|------------|------------------|----------------|------------------------|
| 11a        | 6                | 93.42          | 0.30                   |
| 11n_HT20   | MCS0             | 93.03          | 0.31                   |
| 11n_HT40   | MCS0             | 86.80          | 0.61                   |
| 11ac_VHT80 | MCS0             | 76.39          | 1.17                   |

#### Remark;


- As measured duty cycles of EUT, all of mode and data rate keep constant period and are converted to log scale (power averaging) to compensate correction factor to result of average test items.
- Duty Cycle (%) = (Tx on time / Tx on + off time) x 100
- Correction Factor (dB) = 10 log (1 / Duty Cycle)

#### - Test plots


802.11a




802.11n\_HT20



802.11n\_HT40



802.11ac\_VHT80




## 2. Transmitter Radiated Spurious Emissions


### 2.1. Test Setup

#### 2.1.1. Transmitter radiated spurious emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



## 2.2. Limit

### 2.2.1. FCC

According to § 15.407(b)

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
  - (i) All emissions shall be limited to a level of -27 dB m/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dB m/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dB m/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dB m/MHz at the band edge.

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency<br>(MHz) | Field Strength<br>( $\mu\text{V/m}$ ) | Measurement Distance<br>(Meters) |
|--------------------|---------------------------------------|----------------------------------|
| 0.009-0.490        | 2 400/F(kHz)                          | 300                              |
| 0.490-1.705        | 24 000/F(kHz)                         | 30                               |
| 1.705-30.0         | 30                                    | 30                               |
| 30-88              | 100**                                 | 3                                |
| 88-216             | 150**                                 | 3                                |
| 216-960            | 200**                                 | 3                                |
| Above 960          | 500                                   | 3                                |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

**2.2.2. IC**

According to RSS-247 Issue 2,

**6.2.1.2 Frequency band 5 150-5 250 MHz**

For transmitters with operating frequencies in the band 5 150-5 250 MHz, all emissions outside the band 5 150-5 350 MHz shall not exceed -27 dB m/MHz e.i.r.p. Any unwanted emissions that fall into the band 5 250-5 350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5 % of the occupied bandwidth (i.e. 99% bandwidth), above 5 250 MHz. The 26 dB bandwidth may fall into the 5 250-5 350 MHz band; however, if the occupied bandwidth also falls within the 5 250- 5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5 250-5 350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5 250-5 350 MHz band.

**6.2.2.2 Frequency band 5 250-5 350 MHz**

Devices shall comply with the following:

a) All emissions outside the band 5 250-5 350 MHz shall not exceed -27 dBm/MHz e.i.r.p.; or

b) All emissions outside the band 5 150-5 350 MHz shall not exceed -27 dBm/MHz e.i.r.p. and its power shall comply with the spectral power density for operation within the band 5 150-5 250 MHz. The device, except devices installed in vehicles, shall be labelled or include in the user manual the following text "for indoor use only."

**6.2.3.2 Frequency band 5 470-5 600 MHz and 5 650-5 725 MHz**

Emissions outside the band 5 470-5 725 MHz shall not exceed -27 dB m/MHz e.i.r.p. However, devices with bandwidth overlapping the band edge of 5 725 MHz can meet the emission limit of -27 dB m/MHz e.i.r.p. at 5 850 MHz instead of 5 725 MHz.

**6.2.4.2 Frequency band 5 725-5 850 MHz**

Devices operating in the band 5 725-5 850 MHz with antenna gain greater than 10 dBi can have unwanted emissions that comply with either the limits in this section or in section 5.5 until six (6) months after the publication date of this standard for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2018.

Devices operating in the band 5 725-5 850 MHz with antenna gain of 10 dBi or less can have unwanted emissions that comply with either the limits in this section or in section 5.5 until April 1, 2018 for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2020.

Devices operating in the band 5 725-5 850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;

b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;

c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and

d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

## 2.3. Test Procedures

Radiated spurious emissions from the EUT were measured according to the dictates in section G of KDB 789033 D02 General UNII Test Procedures New Rules v02r01 and ANSI C63.10-2013.

### 2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

### 2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**Note;**

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

- II.G.4. Unwanted emissions measurements below 1 GHz.

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

- II.G.5. Unwanted maximum emissions measurements above 1 GHz.

Peak emission levels are measured by setting the analyzer as follows:

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = Peak, Sweep time = auto, Trace mode = Max hold.

- II.G.6. Average unwanted emissions measurements above 1 GHz.

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = power averaging (rms), Averaging type = power averaging (rms), Sweep time = auto, Perform a trace average of at least 100 traces. If the transmission is continuous, If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle. For example, with 50 % duty cycle, at least 200 traces shall be averaged.

If tests are performed with the EUT transmitting at a duty cycle less than 98 %, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle. The correction factor is computed as follows:

- If power averaging (rms) mode was used in II.G.6.c)(iv), the correction factor is  $10 \log (1/x)$ , where x is the duty cycle. For example, if the transmit duty cycle was 50 %, then 3 dB must be added to the measured emission levels.

- Definition of the test orthogonal plan for EUT was described in the test setup photo.

The test orthogonal plan of EUT is **X – axis** during radiation test.

## 2.4. Test Result

Ambient temperature : (23 ± 1) °C  
 Relative humidity : 47 % R.H.

### 2.4.1. Radiated Spurious Emission below 1 000 MHz


The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.

| Radiated Emissions |                |             | Ant. | Correction Factors |               | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP + CL (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 30.97              | 47.00          | Peak        | V    | 15.30              | -26.71        | <b>35.59</b>    | 40.00          | 4.41        |
| 118.76             | 37.70          | Peak        | H    | 15.62              | -25.31        | 28.01           | 43.50          | 15.49       |
| 138.40             | 46.60          | Peak        | V    | 14.10              | -25.25        | 35.45           | 43.50          | 8.05        |
| 163.38             | 39.80          | Peak        | V    | 14.44              | -25.19        | 29.05           | 43.50          | 14.45       |
| 201.45             | 36.50          | Peak        | V    | 16.88              | -25.10        | 28.28           | 43.50          | 15.22       |
| 314.45             | 34.50          | Peak        | H    | 19.39              | -24.87        | 29.02           | 46.00          | 16.98       |
| Above 400.00       | Not Detected   | -           | -    | -                  | -             | -               | -              | -           |

#### Remark;

- Spurious emissions for all channels and modes were investigated and almost the same below 1 GHz.
- Reported spurious emissions are in **11a (Band 1) / 6 Mbps / Middle channel** as worst case among other modes.
- Radiated spurious emission measurement as below.  
 (Actual = Reading + AF + AMP + CL)
- According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

#### - Test plot



## 2.4.2. Radiated Spurious Emission above 1 000 MHz

### 802.11a (Band 1)\_6 Mbps

#### A. Low Channel (5 180 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *4 500.00          | 38.84                | Peak        | H    | 32.10              | -33.56      | -       | 37.38                 | 74.00                | 36.62       |
| *4 500.00          | 29.95                | Average     | H    | 32.10              | -33.56      | 0.30    | 28.79                 | 54.00                | 25.21       |
| *5 139.38          | 45.86                | Peak        | H    | 33.48              | -32.68      | -       | 46.66                 | 74.00                | 27.34       |
| *5 148.06          | 37.46                | Average     | H    | 33.50              | -32.67      | 0.30    | 38.59                 | 54.00                | 15.41       |
| *5 150.00          | 45.63                | Peak        | H    | 33.50              | -32.67      | -       | 46.46                 | 74.00                | 27.54       |
| *5 150.00          | 37.15                | Average     | H    | 33.50              | -32.67      | 0.30    | 38.28                 | 54.00                | 15.72       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

#### B. Middle Channel (5 220 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

#### C. High Channel (5 240 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

**802.11a (Band 2A)\_6 Mbps**

A. Low Channel (5 260 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (5 300 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (5 320 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *5 350.00          | 40.46          | Peak        | H    | 33.90              | -32.44      | -       | 41.92           | 74.00          | 32.08       |
| *5 350.00          | 34.01          | Average     | H    | 33.90              | -32.44      | 0.30    | 35.77           | 54.00          | 18.23       |
| *5 355.30          | 44.03          | Peak        | H    | 33.91              | -32.43      | -       | 45.51           | 74.00          | 28.49       |
| *5 353.39          | 34.41          | Average     | H    | 33.91              | -32.44      | 0.30    | <b>36.18</b>    | 54.00          | 17.82       |
| *5 460.00          | 38.06          | Peak        | H    | 33.90              | -32.21      | -       | 39.75           | 74.00          | 34.25       |
| *5 460.00          | 30.01          | Average     | H    | 33.90              | -32.21      | 0.30    | 32.00           | 54.00          | 22.00       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**802.11a (Band 2C)\_6 Mbps**

A. Low Channel (5 500 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *5 350.00          | 38.20          | Peak        | H    | 33.90              | -32.44      | -       | 39.66           | 74.00          | 34.34       |
| *5 350.00          | 29.99          | Average     | H    | 33.90              | -32.44      | 0.30    | 31.75           | 54.00          | 22.25       |
| *5 459.09          | 44.73          | Peak        | H    | 33.90              | -32.21      | -       | 46.42           | 74.00          | 27.58       |
| *5 456.23          | 35.41          | Average     | H    | 33.90              | -32.21      | 0.30    | <b>37.40</b>    | 54.00          | 16.60       |
| *5 460.00          | 44.00          | Peak        | H    | 33.90              | -32.21      | -       | 45.69           | 74.00          | 28.31       |
| *5 460.00          | 34.93          | Average     | H    | 33.90              | -32.21      | 0.30    | 36.92           | 54.00          | 17.08       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (5 580 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (5 720 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**802.11a (Band 3)\_6 Mbps**

A. Low Channel (5 745 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 5 649.05           | 42.51          | Peak        | V    | 34.00              | -32.13      |         | <b>44.38</b>    | 68.23          | 23.85       |
| 5 698.40           | 44.75          | Peak        | V    | 34.10              | -32.07      |         | 46.78           | 104.04         | 57.26       |
| 5 700.45           | 45.45          | Peak        | V    | 34.10              | -32.07      |         | 47.48           | 105.35         | 57.87       |
| 5 722.37           | 44.79          | Peak        | V    | 34.06              | -32.11      |         | 46.74           | 116.23         | 69.49       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (5 785 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (5 825 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 5 850.81           | 44.78          | Peak        | V    | 34.30              | -31.94      |         | 47.14           | 120.38         | 73.24       |
| 5 855.40           | 44.72          | Peak        | V    | 34.31              | -31.95      |         | 47.08           | 110.72         | 63.64       |
| 5 888.49           | 43.28          | Peak        | V    | 34.38              | -32.00      |         | 45.66           | 95.24          | 49.58       |
| 5 937.89           | 40.72          | Peak        | V    | 34.55              | -31.94      |         | 43.33           | 68.23          | 24.90       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**802.11n\_HT20 (Band 1)\_MCS0**

A. Low Channel (5 180 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *4 500.00          | 38.00          | Peak        | H    | 32.10              | -33.56      | -       | 36.54           | 74.00          | 37.46       |
| *4 500.00          | 30.07          | Average     | H    | 32.10              | -33.56      | 0.31    | 28.92           | 54.00          | 25.08       |
| *5 142.53          | 46.03          | Peak        | H    | 33.49              | -32.67      | -       | 46.85           | 74.00          | 27.15       |
| *5 148.06          | 37.15          | Average     | H    | 33.50              | -32.67      | 0.31    | 38.29           | 54.00          | 15.71       |
| *5 150.00          | 45.62          | Peak        | H    | 33.50              | -32.67      | -       | 46.45           | 74.00          | 27.55       |
| *5 150.00          | 37.48          | Average     | H    | 33.50              | -32.67      | 0.31    | <b>38.62</b>    | 54.00          | 15.38       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (5 220 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (5 240 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

### 802.11n\_HT20 (Band 2A)\_MCS0

#### A. Low Channel (5 260 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

#### B. Middle Channel (5 300 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

#### C. High Channel (5 320 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *5 350.00          | 42.11          | Peak        | H    | 33.90              | -32.44      | -       | 43.57           | 74.00          | 30.43       |
| *5 350.00          | 33.12          | Average     | H    | 33.90              | -32.44      | 0.31    | 34.89           | 54.00          | 19.11       |
| *5 358.66          | 44.06          | Peak        | H    | 33.92              | -32.43      | -       | 45.55           | 74.00          | 28.45       |
| *5 353.63          | 34.17          | Average     | H    | 33.91              | -32.44      | 0.31    | <b>35.95</b>    | 54.00          | 18.05       |
| *5 460.00          | 36.84          | Peak        | H    | 33.90              | -32.21      | -       | 38.53           | 74.00          | 35.47       |
| *5 460.00          | 30.61          | Average     | H    | 33.90              | -32.21      | 0.31    | 32.61           | 54.00          | 21.39       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

### 802.11n\_HT20 (Band 2C)\_MCS0

#### A. Low Channel (5 500 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *5 350.00          | 38.60                | Peak        | H    | 33.90              | -32.44      | -       | 40.06                 | 74.00                | 33.94       |
| *5 350.00          | 29.22                | Average     | H    | 33.90              | -32.44      | 0.31    | 30.99                 | 54.00                | 23.01       |
| *5 454.16          | 44.78                | Peak        | H    | 33.90              | -32.21      | -       | 46.47                 | 74.00                | 27.53       |
| *5 459.09          | 34.89                | Average     | H    | 33.90              | -32.21      | 0.31    | <b>36.89</b>          | 54.00                | 17.11       |
| *5 460.00          | 41.46                | Peak        | H    | 33.90              | -32.21      | -       | 43.15                 | 74.00                | 30.85       |
| *5 460.00          | 34.88                | Average     | H    | 33.90              | -32.21      | 0.31    | 36.88                 | 54.00                | 17.12       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

#### B. Middle Channel (5 580 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

#### C. High Channel (5 720 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

**802.11n\_HT20 (Band 3)\_MCS0**

A. Low Channel (5 745 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |    | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|----|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 5 645.57           | 41.75          | Peak        | V    | 34.00              | -32.14      |    | <b>43.61</b>    | 68.23          | 24.62       |
| 5 696.15           | 44.95          | Peak        | V    | 34.09              | -32.08      |    | 46.96           | 102.38         | 55.42       |
| 5 715.20           | 44.39          | Peak        | V    | 34.07              | -32.10      |    | 46.36           | 109.48         | 63.12       |
| 5 722.57           | 44.62          | Peak        | V    | 34.05              | -32.11      |    | 46.56           | 116.69         | 70.13       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (5 785 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (5 825 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |    | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|----|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 5 853.34           | 43.95          | Peak        | V    | 34.31              | -31.94      |    | 46.32           | 114.61         | 68.29       |
| 5 868.04           | 44.40          | Peak        | V    | 34.34              | -31.97      |    | 46.77           | 107.18         | 60.41       |
| 5 876.54           | 44.59          | Peak        | V    | 34.35              | -31.98      |    | 46.96           | 104.09         | 57.13       |
| 5 973.05           | 41.01          | Peak        | V    | 34.60              | -31.80      |    | 43.81           | 68.49          | 24.68       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**802.11n\_HT40 (Band 1)\_MCS0**

A. Low Channel (5 190 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *4 500.00          | 38.42                | Peak        | H    | 32.10              | -33.56      | -       | 36.96                 | 74.00                | 37.04       |
| *4 500.00          | 30.28                | Average     | H    | 32.10              | -33.56      | 0.61    | 29.43                 | 54.00                | 24.57       |
| *5 148.06          | 47.32                | Peak        | H    | 33.50              | -32.67      | -       | 48.15                 | 74.00                | 25.85       |
| *5 148.06          | 37.15                | Average     | H    | 33.50              | -32.67      | 0.61    | 38.59                 | 54.00                | 15.41       |
| *5 150.00          | 47.13                | Peak        | H    | 33.50              | -32.67      | -       | 47.96                 | 74.00                | 26.04       |
| *5 150.00          | 37.81                | Average     | H    | 33.50              | -32.67      | 0.61    | <b>39.25</b>          | 54.00                | 14.75       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

B. High Channel (5 230 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

**802.11n\_HT40 (Band 2A)\_MCS0**

A. Low Channel (5 270 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

B. High Channel (5 310 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *5 350.00          | 44.15                | Peak        | H    | 33.90              | -32.44      | -       | 45.61                 | 74.00                | 28.39       |
| *5 350.00          | 34.51                | Average     | H    | 33.90              | -32.44      | 0.61    | 36.58                 | 54.00                | 17.42       |
| *5 350.27          | 44.97                | Peak        | H    | 33.90              | -32.44      | -       | 46.43                 | 74.00                | 27.57       |
| *5 350.75          | 34.58                | Average     | H    | 33.90              | -32.44      | 0.61    | <b>36.65</b>          | 54.00                | 17.35       |
| *5 460.00          | 38.60                | Peak        | H    | 33.90              | -32.21      | -       | 40.29                 | 74.00                | 33.71       |
| *5 460.00          | 30.10                | Average     | H    | 33.90              | -32.21      | 0.61    | 32.40                 | 54.00                | 21.60       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

**802.11n\_HT40 (Band 2C)\_MCS0**

A. Low Channel (5 510 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *5 350.00          | 37.19          | Peak        | H    | 33.90              | -32.44      | -       | 38.65           | 74.00          | 35.35       |
| *5 350.00          | 30.21          | Average     | H    | 33.90              | -32.44      | 0.61    | 32.28           | 54.00          | 21.72       |
| *5 457.27          | 44.09          | Peak        | H    | 33.90              | -32.21      | -       | 45.78           | 74.00          | 28.22       |
| *5 457.79          | 35.14          | Average     | H    | 33.90              | -32.21      | 0.61    | 37.44           | 54.00          | 16.56       |
| *5 460.00          | 43.77          | Peak        | H    | 33.90              | -32.21      | -       | 45.46           | 74.00          | 28.54       |
| *5 460.00          | 35.32          | Average     | H    | 33.90              | -32.21      | 0.61    | <b>37.62</b>    | 54.00          | 16.38       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (5 550 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (5 710 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**802.11n\_HT40 (Band 3)\_MCS0**

**A. Low Channel (5 755 MHz)**

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| 5 644.54           | 43.42                | Peak        | V    | 34.00              | -32.14      |         | <b>45.28</b>          | 68.23                | 22.95       |
| 5 696.56           | 45.38                | Peak        | V    | 34.09              | -32.08      |         | 47.39                 | 102.68               | 55.29       |
| 5 719.29           | 47.65                | Peak        | V    | 34.06              | -32.11      |         | 49.60                 | 110.63               | 61.03       |
| 5 720.11           | 46.11                | Peak        | V    | 34.06              | -32.11      |         | 48.06                 | 111.08               | 63.02       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

**B. High Channel (5 795 MHz)**

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| 5 851.50           | 42.19                | Peak        | V    | 34.30              | -31.94      |         | 44.55                 | 118.81               | 74.26       |
| 5 870.57           | 42.69                | Peak        | V    | 34.34              | -31.97      |         | 45.06                 | 106.47               | 61.41       |
| 5 876.31           | 41.88                | Peak        | V    | 34.35              | -31.98      |         | 44.25                 | 104.26               | 60.01       |
| 5 970.98           | 42.09                | Peak        | V    | 34.60              | -31.82      |         | 44.87                 | 68.47                | 23.60       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

### 802.11ac\_VHT80 (Band 1)\_MCS0

A. Middle Channel (5 210 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *4 500.00          | 39.77                | Peak        | H    | 32.10              | -33.56      | -       | 38.31                 | 74.00                | 35.69       |
| *4 500.00          | 30.31                | Average     | H    | 32.10              | -33.56      | 1.17    | 30.02                 | 54.00                | 23.98       |
| *5 140.17          | 49.70                | Peak        | H    | 33.48              | -32.68      | -       | 50.50                 | 74.00                | 23.50       |
| *5 148.06          | 39.33                | Average     | H    | 33.50              | -32.67      | 1.17    | 41.33                 | 54.00                | 12.67       |
| *5 150.00          | 49.30                | Peak        | H    | 33.50              | -32.67      | -       | 50.13                 | 74.00                | 23.87       |
| *5 150.00          | 39.49                | Average     | H    | 33.50              | -32.67      | 1.17    | <b>41.49</b>          | 54.00                | 12.51       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

### 802.11ac\_VHT80 (Band 2A)\_MCS0

A. Middle Channel (5 290 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *5 350.00          | 41.40                | Peak        | H    | 33.90              | -32.44      | -       | 42.86                 | 74.00                | 31.14       |
| *5 350.00          | 33.37                | Average     | H    | 33.90              | -32.44      | 1.17    | 36.00                 | 54.00                | 18.00       |
| *5 370.65          | 44.64                | Peak        | H    | 33.94              | -32.42      | -       | 46.16                 | 74.00                | 27.84       |
| *5 350.51          | 33.80                | Average     | H    | 33.90              | -32.44      | 1.17    | <b>36.43</b>          | 54.00                | 17.57       |
| *5 460.00          | 37.77                | Peak        | H    | 33.90              | -32.21      | -       | 39.46                 | 74.00                | 34.54       |
| *5 460.00          | 30.64                | Average     | H    | 33.90              | -32.21      | 1.17    | 33.50                 | 54.00                | 20.50       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

**802.11ac\_VHT80 (Band 2C)\_MCS0**

A. Low Channel (5 530 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *5 350.00          | 38.48          | Peak        | H    | 33.90              | -32.44      | -       | 39.94           | 74.00          | 34.06       |
| *5 350.00          | 30.59          | Average     | H    | 33.90              | -32.44      | 1.17    | 33.22           | 54.00          | 20.78       |
| *5 456.75          | 51.87          | Peak        | H    | 33.90              | -32.21      | -       | 53.56           | 74.00          | 20.44       |
| *5 459.09          | 40.43          | Average     | H    | 33.90              | -32.21      | 1.17    | <b>43.29</b>    | 54.00          | 10.71       |
| *5 460.00          | 49.32          | Peak        | H    | 33.90              | -32.21      | -       | 51.01           | 74.00          | 22.99       |
| *5 460.00          | 40.16          | Average     | H    | 33.90              | -32.21      | 1.17    | 43.02           | 54.00          | 10.98       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. High Channel (5 690 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**802.11ac\_VHT80 (Band 3)\_MCS0**

A. Middle Channel (5 775 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 5 638.81           | 45.63          | Peak        | V    | 34.00              | -32.15      | <b>47.48</b>    | 68.23          | 20.75       |
| 5 652.12           | 45.62          | Peak        | V    | 34.00              | -32.13      | 47.49           | 69.80          | 22.31       |
| 5 718.27           | 45.87          | Peak        | V    | 34.06              | -32.11      | 47.82           | 110.34         | 62.52       |
| 5 721.96           | 45.42          | Peak        | V    | 34.06              | -32.11      | 47.37           | 115.30         | 67.93       |
| 5 854.26           | 42.19          | Peak        | V    | 34.31              | -31.94      | 44.56           | 112.51         | 67.95       |
| 5 865.51           | 43.11          | Peak        | V    | 34.33              | -31.97      | 45.47           | 107.88         | 62.41       |
| 5 877.92           | 43.10          | Peak        | V    | 34.36              | -31.98      | 45.48           | 103.07         | 57.59       |
| 5 928.01           | 42.09          | Peak        | V    | 34.51              | -31.95      | 44.65           | 68.23          | 23.58       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |


**Remark;**

1. “\*” means the restricted band.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using Peak / average detector mode if frequency was in restricted band. Otherwise the frequency was out of restricted band, only peak detector should be used.
3. Actual = Reading + AF + AMP + CL + (DF).
4. If frequency was out of restricted band, the calculation method for peak limit is same as below.  
 $68.23 \text{ dB}\mu\text{V/m} = \text{EIRP} - 20 \log(d) + 104.77 = -27 - 20 \log(3) + 104.77$
5. In case of the emissions within  $\pm 75 \text{ MHz}$  from band edge of band 3, limit should be adjusted to emission mask of 15.407(4)(i).
6. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
7. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.


## - Test plots

### OFDM: 802.11a (6 Mbps)


#### Low channel Band edge (Peak) - Band 1




#### Low channel Band edge (Average) - Band 1




High channel Band edge (Peak) - Band 2A




High channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



## Low channel Band edge (Peak) - Band 3




## High channel Band edge (Peak) - Band 3




## OFDM: 802.11n\_HT20 (MCS0)


### Low channel Band edge (Peak) - Band 1




### Low channel Band edge (Average) - Band 1




## High channel Band edge (Peak) - Band 2A




## High channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



## Low channel Band edge (Peak) - Band 3




## High channel Band edge (Peak) - Band 3




## OFDM: 802.11n\_HT40 (MCS0)


### Low channel Band edge (Peak) - Band 1




### Low channel Band edge (Average) - Band 1




## High channel Band edge (Peak) - Band 2A




## High channel Band edge (Average) - Band 2A




Low channel Band edge (Peak) - Band 2C




Low channel Band edge (Average) - Band 2C



## Low channel Band edge (Peak) - Band 3




## High channel Band edge (Peak) - Band 3




## OFDM: 802.11ac\_VHT80 (MCS0)


### Middle channel Band edge (Peak) - Band 1




### Middle channel Band edge (Average) - Band 1



Middle channel Band edge (Peak) - Band 2A




Middle channel Band edge (Average) - Band 2A




## Low channel Band edge (Peak) - Band 2C



## Low channel Band edge (Average) - Band 2C



Middle channel Band edge (Peak) - Band 3



Middle channel Band edge (Peak) - Band 3

