

# TEST REPORT

of

FCC Part 15 Subpart C §15.209  
IC RSS-210 Issue 11 and RSS-Gen Issue 5

FCC ID: TQ8-BDC-4E07  
IC Certification: 5074A-BDC4E07

Equipment Under Test : SMART KEY ECU

Model Name : BDC-4E07

Variant Model Name(s) : BDC-4E08

Applicant : FCC: HYUNDAI MOBIS CO., LTD.  
: IC: Hyundai MOBIS Co., Ltd

Manufacturer : Hyundai Mobis Co., Ltd.

Date of Receipt : 2024.12.09

Date of Test(s) : 2025.01.07 ~ 2025.02.05

Date of Issue : 2025.02.17

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Ethan Lim

Technical  
Manager:



Jinyoung Cho

## SGS Korea Co., Ltd. Gunpo Laboratory

# INDEX

<u>Table of Contents</u>	<u>Page</u>
1. General Information -----	3
2. Field Strength of Fundamental and Spurious Emission-----	7
3. 20 dB Bandwidth -----	15
4. Occupied Bandwidth-----	16

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

### 1.2. Details of Applicant

FCC Applicant : HYUNDAI MOBIS CO., LTD.  
FCC Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977  
IC Applicant : Hyundai MOBIS Co., Ltd  
IC Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977  
Contact Person : Choe, Seung-hoon  
Phone No. : +82 31 260 2767

### 1.3. Details of Manufacturer

Company : Hyundai Mobis Co., Ltd  
Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977

### 1.4. Description of EUT

<b>Kind of Product</b>		SMART KEY ECU
<b>Model Name</b>		BDC-4E07
<b>Variant Model</b>		BDC-4E08
<b>Serial Number</b>		001
<b>Power Supply</b>		DC 12.0 V
<b>Frequency Range</b>		Tx: 125.00 kHz, Rx: 433.92 MHz
<b>Antenna Type</b>	<b>TX</b>	Coil Antenna
	<b>RX</b>	Rod Antenna
<b>Antenna Part Number</b>		95425-BE000
<b>H/W Version</b>		A.00
<b>S/W Version</b>		A.00
<b>FVIN</b>		N/A

## 1.5. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	R&S	SMBV100A	259067	Jun. 19, 2024	Annual	Jun. 19, 2025
DC Power Supply	R&S	HMP2020	102130	May 02, 2024	Annual	May 02, 2025
Spectrum Analyzer	R&S	FSV30	103210	Mar. 27, 2024	Annual	Mar. 27, 2025
EMI TEST RECEIVER	R&S	ESW44	101767	Oct. 24, 2024	Annual	Oct. 24, 2025
Loop Antenna	Schwarzbeck Mess-Elektronik	HFRAE 5161	5161-028	Nov. 06, 2024	Annual	Nov. 06, 2025
Amplifier	H.P.	8447F	2944A03909	Aug. 09, 2024	Annual	Aug. 09, 2025
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 21, 2023	Biennial	Aug. 21, 2025
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	9163-396	Apr. 02, 2024	Biennial	Apr. 02, 2026
EMI Test Receiver	R&S	ESU26	100109	Jan. 13, 2025	N/A	Jan. 13, 2026
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/3 8330516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/3 8330516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	SENSORVIEW	NMST-13A26-NMST-5 m	TPC24021900 04	Oct. 04, 2024	Semi-annual	Apr. 04, 2025
Coaxial Cable	SENSORVIEW	NMST-13A26-NMST-10 m	TPC24021900 01	Oct. 04, 2024	Semi-annual	Apr. 04, 2025
Coaxial Cable	RADIALL	TESTPRO 3	182287	Oct. 11, 2024	Semi-annual	Apr. 11, 2025

**Note:**

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

## 1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

<b>Applied standard: FCC Part 15 Subpart C, IC RSS-210 Issue 11, RSS-Gen Issue 5</b>			
<b>Section in FCC</b>	<b>Section in IC</b>	<b>Test Item(s)</b>	<b>Result</b>
15.209	RSS-210 Issue 11, 8.3, RSS-Gen Issue 5, 8.9	Radiated emission, Spurious Emission and Field Strength of Fundamental	Pass
2.1049	-	20 dB Bandwidth	Pass
-	RSS-Gen Issue 5 6.7	Occupied Bandwidth	Pass
15.207	RSS-Gen Issue 5 8.8	AC Power Line Conducted Emission	N/A <sup>1)</sup>

**Note:**

- 1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

## 1.7. Sample Calculation

Where relevant, the following sample calculation is provided:

Field strength level (dB $\mu$ V/m) = Measured level (dB $\mu$ V) + Antenna factor (dB) + Cable loss (dB)

## 1.8. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

<b>Parameter</b>		<b>Uncertainty</b>
20 dB Bandwidth		0.01 kHz
Occupied Bandwidth		0.01 kHz
Radiated Emission, 9 kHz to 30 MHz	H	3.40 dB
	V	3.40 dB
Radiated Emission, below 1 GHz	H	4.60 dB
	V	5.00 dB

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence.

### 1.9. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL005754	2025.02.17	Initial

### 1.10. Description of Variant Model

Model name		Description
Basic Model	BDC-4E07	- Representative production model - External type received antenna
Variant Model	BDC-4E08	- All internals are the same, but receiver antenna is integrated.


**Note:**

The all the test were performed with basic model.


## 2. Field Strength of Fundamental and Spurious Emission

### 2.1. Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission below 30 MHz.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz.



## 2.2. Limits

### 2.2.1. FCC

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meter)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

According to §15.209(d), The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1 000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

## 2.2.2. IC

According to RSS-Gen Issue 5, 8.9.

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

**Table 5 - General field strength limits at frequencies above 30 MHz**

Frequency (MHz)	Field Strength ( $\mu$ V/m at 3 m)
30-88	100
88-216	150
216-960	200
Above 960	500

**Table 6 - General field strength limits at frequencies below 30 MHz**

Frequency	Magnetic Field Strength (H-Field) ( $\mu$ A/m)	Measurement Distance (m)
9-490 kHz <sup>1</sup>	6.37/F (F in kHz)	300
490-1 705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

According to RSS-210 Issue 11, 8.3.

Transmitters whose wanted and unwanted emissions fall within the general field strength limits specified in RSS-Gen may operate licence exempt in any of the frequency bands, other than the restricted frequency bands, other than the restricted frequency bands listed in RSS-Gen and the TV bands 54-72 MHz, 76-88 MHz, 174-216 MHz and 470-602 MHz, and shall be certified under RSS-210. Under no circumstances shall the level of any unwanted emissions exceed the level of the fundamental emissions.

## 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013.

### 2.3.1. Test Procedures for emission from 9 kHz to 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.
5. To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is X – axis during radiation test.

### 2.3.2. Test Procedures for emission from 30 MHz to 1 000 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.

## 2.4. Field Strength of Fundamental Test Result

Ambient temperature :  $(23 \pm 1)^\circ\text{C}$

Relative humidity : 47 % R.H.


The following table shows the highest level of radiated emissions on between polarizations of horizontal and vertical.

Radiated Emissions			Ant.	Correction Factors		Total		Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	Cable (dB)	Actual (dB $\mu$ V/m) at 3 m	Actual (dB $\mu$ V/m) at 300 m	Limit (dB $\mu$ V/m) at 300 m	Margin (dB)
0.125	54.80	Average	H	18.20	0.05	73.05	-6.95	25.67	32.62

### Remark;

1. According to §15.31(f)(2), 300 m Result (dB $\mu$ V/m) = 3 m Result (dB $\mu$ V/m) - 40log (300/3) (dB $\mu$ V/m).
2. According to §15.209(d), the measurements were tested by using Quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1 000 MHz in these three bands on measurements employing an average detector.
3. The limit above was calculated based on table of §15.209(a).
4. According to ANSI C63.10: 2013, For measurement below 30 MHz conversion factor from E-field to H-field is considered as free-space impedance [1  $\mu$ V/m = (1/377  $\Omega$ )  $\times$  1  $\mu$ A/m] The FCC limits are same to the IC limits.
5. Actual (dB $\mu$ V/m) at 3 m = Reading (dB $\mu$ V) + AF (dB/m) + CL (dB).

### - Test plot



## 2.5. Spurious Emission Test Result

Ambient temperature : (23 ± 1) °C

Relative humidity : 47 % R.H.

The following table shows the highest level of radiated emissions on between polarizations of horizontal and vertical.

### Below 30 MHz

Radiated Emissions			Ant.	Correction Factors		Total		Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB $\mu$ V/m) at 3 m	Actual (dB $\mu$ V/m) at 300 m or 30 m	Limit (dB $\mu$ V/m) at 300 m or 30 m	Margin (dB)
0.019	33.80	Average	V	18.73	0.03	52.56	-27.44	42.03	69.47
0.069	33.00	Average	V	18.29	0.04	51.33	-28.67	30.83	59.50
1.613	31.60	Quasi Peak	V	18.52	0.62	50.74	<b>10.74</b>	23.45	12.71
13.777	14.50	Quasi Peak	V	18.92	0.60	34.02	-5.98	29.54	35.52

### Above 30 MHz


Radiated Emissions			Ant.	Correction Factors (dB/m)	Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.		Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
377.62	32.14	Quasi Peak	V	-4.33	27.81	46.00	18.19
Above 400.00	Not detected	-	-	-	-	-	-

**Remark;**


1. According to §15.31(f)(2)
  - 300 m Result (dB $\mu$ V/m) = 3 m Result (dB $\mu$ V/m) - 40log (300/3) (dB $\mu$ V/m)
  - 30 m Result (dB $\mu$ V/m) = 3 m Result (dB $\mu$ V/m) - 40log (30/3) (dB $\mu$ V/m)
2. According to field strength table of general requirement in §15.209(a), field strength limits below 1.705 MHz were calculated as below.
  - 9 kHz to 490 kHz: 20log (2 400 / F (kHz)) at 300 m (dB $\mu$ V/m)
  - 490 kHz to 1 705 kHz: 20log (24 000 / F (kHz)) at 30 m (dB $\mu$ V/m)
3. According to §15.209(d), the measurements were tested by using Quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1 000 MHz in these three bands on measurements employing an average detector.
4. According to ANSI C63.10: 2013, For measurement below 30 MHz.  
conversion factor from E-field to H-field is considered as free-space impedance [1  $\mu$ V/m = (1/377  $\Omega$ )  $\times$  1  $\mu$ A/m]  
The FCC limits are same to the IC limits.
5. The limit above was calculated based on table of §15.209 (a).
6. Test from 30 MHz to 1 000 MHz was performed using the software of ELEKTRAT(V5.02) from Rohde & Schwarz GmbH & Co. KG.
7. Actual (dB $\mu$ V/m) at 3 m were calculated as below.
  - Below 30 MHz : Reading (dB $\mu$ V) + AF (dB/m) + CL (dB)
  - Above 30 MHz : Actual = Reading + Correction (Correction = Antenna Factor + AMP Factor + Cable Loss)
8. Above 30 MHz, According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

**- Test plots**

**Below 30 MHz**




**Above 30 MHz**



### 3. 20 dB Bandwidth

#### 3.1. Test Setup



#### 3.2. Limit

None; for reporting purposes only

#### 3.3. Test Procedure

- Span = set to capture all products of the modulation process, including the emission skirts.  
RBW = 200 Hz, VBW = 200 Hz, Sweep = auto, Detector = peak, Trace = max hold.
- The marker-to-peak function to set the mark to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is 20 dB bandwidth of the emission.


#### 3.4. Test Result

Ambient temperature :  $(23 \pm 1)^\circ\text{C}$

Relative humidity : 47 % R.H.


Frequency (kHz)	20 dB Bandwidth (kHz)	Limit
125	0.829	Reporting proposed only

#### - Test plot



## 4. Occupied Bandwidth

### 4.1. Test Setup



### 4.2. Limit

None; for reporting purposes only

### 4.3. Test Procedure

1. Set the spectrum analyzer as Span = set to capture all products of the modulation process, including the emission skirts, RBW = 200 Hz, VBW = 200 Hz, Detector = peak, Trace mode = max hold.
2. Measure lowest and highest frequencies are placed in a running sum until 0.5 % and 99.5 % of the total is reached.
3. Record the SPAN between the lowest and the highest frequencies for the 99 % occupied bandwidth.


### 4.4. Test Result

Ambient temperature :  $(23 \pm 1)^\circ\text{C}$

Relative humidity : 47 % R.H.

Frequency (kHz)	Occupied Bandwidth (kHz)	Limit
125	16.488	Reporting proposed only

#### - Test plot



- End of the Test Report -