

RF EXPOSURE REPORT

Equipment under test Wireless Phone Charger

Model name D7F76-AC000

FCC ID TQ8-D7F76AC000

Applicant Hyundai Mobis Co., Ltd.

Manufacturer DONGYANG E&P Inc.

Date of test(s) 2019.10.07~2019.10.17

Date of issue 2019.10.17

Issued to

Hyundai Mobis Co., Ltd.

203, Teheran-Ro, Gangnam-gu,
Seoul, 135-977, Korea

Tel: +82-31-260-0098 / Mobile: +82-10-8845-0683



Issued by

KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea

473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea

Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
Won-Jun Sim Test engineer	Hyeon-Su Jang Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



Revision history

Revision	Date of issue	Test report No.	Description
-	2019.10.17	KES-RF-19T0155	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration.....	4
1.3.	Test frequency	4
1.4.	Test mode	4
1.5.	Information about derivative model.....	5
1.6.	Device modifications	5
1.7.	Accessory information	5
2.	Environmental evaluation and exposure limit.....	6
2.1.	Test Setup	7
2.2.	Test results.....	9
	- E-Field Strength at 10 cm from each edges the EUT	9
	- H-Field Strength at 10 cm from each edges the EUT	9
	Appendix A. Measurement equipment	10
	Appendix B. Test setup photo.....	11



1. General information

Applicant Hyundai Mobis Co., Ltd.
Applicant address 203, Teheran-Ro, Gangnam-Gu, Seoul, 135-977, Korea
Test site KES Co., Ltd.
Test site address 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s): Part 15C
FCC ID: TQ8-D7F76AC000
Test device serial No. ☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test Wireless Phone Charger
Frequency 0.110 MHz ~ 0.205 MHz
Modulation type AM
Model: D7F76-AC000
Antenna specification Internal type(Coil antenna)
Power source DC 12V

1.2. Test configuration

The **Hyundai Mobis Co.,Ltd. Wireless Phone Charger FCC ID: TQ8-D7F76AC000** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15C
ANSI C63.10-2013
KDB 680106 D01 V03

1.3. Test frequency

		Frequency Range
Power source	DC 12 V	0.110 MHz ~ 0.205 MHz

1.4. Test mode

Mode	Description
Charging mode With Client device	100% full charging of Battery.
	Less than 50% of Battery
	Less than 1% of Battery



1.5. Information about derivative model

N/A

1.6. Device modifications

N/A

1.7. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

2. Environmental evaluation and exposure limit

Limits for Maximum Permissible Exposure (MPE)

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.


TABLE 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational / Control Exposures				
0.3 - 3.0	614	1.63	*(100)	6
3.0 - 30	1842/f	4.89/f	*(900/f ²)	6
30 - 300	61.4	0.613	1.0	6
300 - 1 500			f/300	6
1 500 - 100 000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
<u>0.3-1.34</u>	<u>614</u>	<u>1.63</u>	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1 500			f/1 500	30
1 500 - 100 000			1.0	30

Note.

1. f= frequency in MHz
2. “*” means Plane-wave equivalent power density

2.1. Test Setup



1. The test was performed on 360° turn table in anechoic chamber.
2. The probe was placed at distance 15 cm or 20 cm which is between the edge of the charger and the geometric center of the probe.
3. The highest emission level was recorded and compared with limit as soon as measurement of each point ; A, B, C, D, E were completed.
4. Point F is highest measured field from moving the probe around the device at distance 15 cm.
5. The EUT was measured according to the KDB 680106 D01v03.

Note.

Equipment Approval Considerations item 5.b) of KDB 680106 D01 v03.

- a) Power transfer frequency is less than 1 MHz.
 - The device operates at a frequency of 110 kHz to 205 kHz.
- b) Output power from each primary coil is less than or equal to 15 watts.
 - Output power from each primary coil : 15 watts.
- c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
 - The transfer system including a charging system with single coil. .
- d) Client device is placed directly in contact with the transmitter.
 - Client device is placed directly.
- e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
 - The device is a mobile device.
- f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50 % of the MPE limit.
 - Refer to following test results.
The EUT H-Field Strength levels at 15 cm < 50 % of the MPE H-Field Strength limit 1.63 A/m
0.069 A/m (Max) < 0.815 A/m

2.2. Test results

- E-Field Strength from each edges the EUT

Test Mode		Point A (V/m)	Point B (V/m)	Point C (V/m)	Point D (V/m)	Point E (V/m)	Point F (V/m)
Charging mode	Less than 1% of Battery	0.433	0.721	0.433	0.413	0.422	0.393
	Less than 50% of Battery	0.428	0.718	0.431	0.408	0.435	0.376
	100% full charging of Battery.	0.431	0.717	0.451	0.420	0.418	0.388

- H-Field Strength from each edges the EUT

Test Mode		Point A (A/m)	Point B (A/m)	Point C (A/m)	Point D (A/m)	Point E (A/m)	Point F (A/m)
Charging mode	Less than 1% of Battery	0.064	0.052	0.069	0.055	0.053	0.067
	Less than 50% of Battery	0.066	0.052	0.067	0.053	0.050	0.062
	100% full charging of Battery.	0.068	0.054	0.066	0.054	0.052	0.064

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Isotropic electric Field Probe	ETS LINDGREN	HI-6105	00151770	1 year	202.06.14
Exposure Level Meter	Narda	ELT-400	N-0538	1 year	2019.11.12

Peripheral device






Device	Manufacturer	Model No.	Note
Client device	Samsung	SM-N950N	Mobile Phone

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr






Appendix B. Test setup photo

E-Field	
Position A	Position B
	
Position C	Position D
	
Position E	
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr

H-Field	
Position A	Position B
	
Position C	Position D
	
Position E	
	

The end of test report.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr