



# TEST REPORT

FCC BT Test for DA351I6MG  
Certification

**APPLICANT**

Hyundai Mobis Co., Ltd

**REPORT NO.**

HCT-RF-2503-FC050

**DATE OF ISSUE**

March 13, 2025

Tested by  
Kyung Jun Woo



Technical Manager  
Jong Seok Lee



Accredited by KOLAS, Republic of KOREA

**HCT CO., LTD.**  
*BongJai Huh*  
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea  
Tel. +82 31 645 6300 Fax. +82 31 645 6401

# TEST REPORT

**REPORT NO.**  
HCT-RF-2503-FC050

**DATE OF ISSUE**  
March 13, 2025

<b>Applicant</b>	<b>Hyundai Mobis Co., Ltd</b> 203, Teheran-ro, Gangnam-gu, Seoul, Republic of Korea
<b>Product Name</b>	DISPLAY CAR SYSTEM
<b>Model Name</b>	DA351I6MG
<b>FCC ID</b>	TQ8-DA351I6MG
<b>FCC Classification</b>	FCC Part 15 Spread Spectrum Transmitter
<b>Date of Test</b>	February 14, 2025 ~ March 13, 2025
<b>Test Standard Used</b>	FCC Rule Part(s): Part 15 subpart C 15.247
<b>Location of Test</b>	<input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing Lab (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
<b>Test Results</b>	PASS

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	March 13, 2025	Initial Release

## Notice

### Content

#### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked \*.

Information provided by the applicant is marked \*\*.

Test results provided by external providers are marked \*\*\*.

When confirmation of authenticity of this test report is required, please contact [www.hct.co.kr](http://www.hct.co.kr)

This test report provides test result(s) under the scope accredited by the Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA.

(KOLAS (KS Q ISO/IEC 17025) Accreditation No. KT197)

This test report provides test result(s) under the lab's valid Scope of Accreditation by A2LA (American Association for Laboratory Accreditation), signatory of the ILAC-MRA.

(A2LA (ISO/IEC 17025) Certificate No. 4114.01)

## CONTENTS

1. EUT DESCRIPTION	5
2. Requirements for Bluetooth transmitter(15.247)	6
3. TEST METHODOLOGY	6
EUT CONFIGURATION	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES	7
4. INSTRUMENT CALIBRATION	7
5. FACILITIES AND ACCREDITATIONS	7
FACILITIES	7
EQUIPMENT	7
6. ANTENNA REQUIREMENTS	8
7. MEASUREMENT UNCERTAINTY	9
8. DESCRIPTION OF TESTS	10
9. SUMMARY OF TEST RESULTS	29
10. TEST RESULT	30
10.1 PEAK POWER	30
10.2 BAND EDGES	32
10.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99 % BW)	34
10.4 NUMBER OF HOPPING FREQUENCY	37
10.5 TIME OF OCCUPANCY (DWELL TIME)	39
10.6 SPURIOUS EMISSIONS	41
10.6.1 CONDUCTED SPURIOUS EMISSIONS	41
10.6.2 RADIATED SPURIOUS EMISSIONS	42
10.6.3 RADIATED RESTRICTED BAND EDGES	49
11. LIST OF TEST EQUIPMENT	51
12. ANNEX A_ TEST SETUP PHOTO	53

**1. EUT DESCRIPTION**

<b>Model</b>	DA351I6MG
<b>Additional Model</b>	DA350I6NG ,DA351I6NG ,DA352I6NG ,DA350I6GG ,DA351I6GG ,DA352I6GG ,DA350I6GN ,DA350I6GP ,DA350I6MG ,DA360I6GG ,DA361I6GG ,DA360I6GN ,DA360I6GP ,DA350I6GG ,DA351I6GG ,DA350I6GN ,DA361I6GG ,DA360I6GN
<b>EUT Type</b>	DISPLAY CAR SYSTEM
<b>Power Supply</b>	DC 14.4 V
<b>Frequency Range</b>	2 402 MHz - 2 480 MHz
<b>Max. RF Output Power</b>	1.326 dBm (1.36 mW)
<b>BT Operating Mode</b>	Normal, EDR, AFH
<b>Modulation Type</b>	GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR)
<b>Modulation Technique</b>	FHSS
<b>Number of Channels</b>	79 Channels, Minimum 20 Channels(AFH)
<b>Antenna Specification</b>	Type: Pattern Antenna Peak Gain: -0.18 dBi
<b>Serial number</b>	Conducted : MMA240730050 Radiated : MMA240730045

This device supports simultaneous transmission operation.

Simultaneous transmission Scenario	2.4 GHz WiFi	5 GHz WiFi	BT	Test Case
Bluetooth + 2.4 GHz WiFi	on	-	on	Scenario1
Bluetooth + 5 GHz WiFi	-	on	on	Scenario2

## 2. Requirements for Bluetooth transmitter(15.247)

This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:

- 1) This system is hopping pseudo-randomly.
- 2) Each frequency is used equally on the average by each transmitter.
- 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
- 4) The receiver shifts frequencies in synchronization with the transmitted signals.
  - 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
  - 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

## 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Device (ANSI C63.10-2013, KDB 558074) is used in the measurement of the test device.

### EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### GENERAL TEST PROCEDURES

#### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and average detector modes.

### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1 GHz. Above 1 GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1 GHz. For average measurements above 1 GHz, the analyzer was set to peak detector and add the DCCF calculations.

### **DESCRIPTION OF TEST MODES**

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

### **4. INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

### **5. FACILITIES AND ACCREDITATIONS**

#### **FACILITIES**

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated March 11, 2024 (Registration Number: KR0032).

#### **EQUIPMENT**

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## **6. ANTENNA REQUIREMENTS**

### **According to FCC 47 CFR § 15.203:**

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of § 15.203

## 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ kHz)
X dB, 99% Bandwidth	95 (Confidence level about 95 %, $k=2$ )
Frequency stability	28 (Confidence level about 95 %, $k=2$ )
Carrier Frequency Separation	
Number of Hopping Frequencies	49 (Confidence level about 95 %, $k=2$ )
Time of Occupancy	

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.98 (Confidence level about 95 %, $k=2$ )
Conducted Output Power(Signal Analyzer)	0.68 (Confidence level about 95 %, $k=2$ )
Power Spectral Density	1.03 (Confidence level about 95 %, $k=2$ )
Conducted Spurious Emissions	0.70 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$ )

## 8. DESCRIPTION OF TESTS


### 8.1. Conducted Maximum Peak Output Power

#### Limit

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 W.  
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 W.
2. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

#### Test Configuration



#### Test Procedure

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.5 in ANSI 63.10-2013& Procedure 9(b) in KDB 558074 v05r02)


- 1) Span: approximately 5 times the 20 dB bandwidth, centered on a hopping channel
- 2) RBW> the 20 dB bandwidth of the emission being measured
- 3) VBW  $\geq$  RBW
- 4) Sweep = Auto
- 5) Detector = Peak
- 6) Trace = Max hold

## 8.2. Conducted Band Edge(Out of Band Emissions)

### Limit

According to § 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration



### Test Procedure

This test is performed with hopping off and hopping on.

The Spectrum Analyzer is set to (6.10.4 in ANSI 63.10-2013& Procedure 8.5 and 8.6 in KDB 558074 v05r02)


- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: Coupled.
- 5) RBW: 100 kHz
- 6) VBW: 300 kHz
- 7) Detector: Peak
- 8) Trace: Max hold

### 8.3. Frequency Separation & 20 dB Bandwidth

#### Limit

According to § 15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Test Configuration



#### Test Procedure(Frequency Separation)

The Channel Separation test is performed with hopping on.

And the 20 dB Bandwidth test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.2 in ANSI 63.10-2013& Procedure 9(b) in KDB 558074 v05r02)

- 1) Span: Wide enough to capture the peaks of two adjacent channels
- 2) RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3) VBW  $\geq$  RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) All the trace to stabilize.
- 8) Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

**Test Procedure (20 dB Bandwidth)**

And the 20 dB Bandwidth test is performed with hopping off.

The Spectrum Analyzer is set to (6.9.2 in ANSI 63.10-2013)


- 1) Span: Set between two times and five times the OBW
- 2) RBW: 1 % to 5 % of the OBW.
- 3) VBW  $\geq$  3 x RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) All the trace to stabilize.

#### 8.4. Number of Hopping Frequencies

##### Limit

According to § 15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

##### Test Configuration



##### Test Procedure

The Bluetooth frequency hopping function of the EUT was enabled.

The Spectrum Analyzer is set to (7.8.3 in ANSI 63.10-2013& Procedure 9(b) in KDB 558074 v05r02)


- 1) Span: the frequency band of operation
- 2) RBW: To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 3) VBW  $\geq$  RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) Allow the trace to stabilize.

## 8.5. Time of Occupancy

### Limit

According to § 15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### Test Configuration



### Test Procedure

This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.4 in ANSI 63.10-2013& Procedure 9(b) in KDB 558074 v05r02)

- 1) Span: Zero span, centered on a hopping channel
- 2) RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where T is the expected dwell time per channel.
- 3) Sweep = as necessary to capture the entire dwell time per hopping channel
- 4) Detector: Peak
- 5) Trace: Max hold

The marker-delta function was used to determine the dwell time.

**Sample Calculation**

The following calculation process is not relevant to our measurement results. It is just an example.

**(1) Non-AFH Mode**

- DH 5 (GFSK) :  $2.890 \times (1600/6)/79 \times 31.6 = 308.27$  (ms)
- 2-DH 5 ( $\pi/4$ DQPSK) :  $2.890 \times (1600/6)/79 \times 31.6 = 308.27$  (ms)
- 3-DH 5 (8DPSK) :  $2.890 \times (1600/6)/79 \times 31.6 = 308.27$  (ms)

**(2) AFH Mode**

- DH 5 (GFSK) :  $2.890 \times (800/6)/20 \times 8.0 = 154.13$  (ms)
- 2-DH 5 ( $\pi/4$ DQPSK) :  $2.890 \times (800/6)/20 \times 8.0 = 154.13$  (ms)
- 3-DH 5 (8DPSK) :  $2.890 \times (800/6)/20 \times 8.0 = 154.13$  (ms)

Note :

DH5 Packet need 5 time slot for transmitting and 1 time slot for receiving.

Then the system makes worst case 1600/6 hops per second with 79 channels. So the system have each channel 3.3755 times per second and so for 31.6 seconds the system have 106.667 times of appearance.

Each tx-time per appearance of DH5 is 2.890 ms.


Dwell time = Tx-time x 106.667 = 308.27 (ms)

## 8.6. Conducted Spurious Emissions

### Limit

Conducted > 20 dBc

### Test Configuration



### Test Procedure

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer.

The Spectrum Analyzer is set to (7.8.8 in ANSI 63.10-2013& Procedure 8.5 and 8.6 in KDB 558074 v05r02)

- 1) Span:30 MHz to 10 times the operating frequency in GHz.
- 2) RBW: 100 kHz
- 3) VBW: 300 kHz
- 4) Sweep: Coupled
- 5) Detector: Peak

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

This test is performed with hopping off.

**Factors for frequency**

Freq(MHz)	Factor(dB)
30	16.70
100	16.77
200	16.80
300	16.78
400	16.89
500	16.97
600	17.00
700	17.14
800	17.26
900	17.36
1000	17.38
2000	17.38
2400	<b>17.42</b>
2500	<b>17.42</b>
3000	17.64
4000	18.08
5000	19.16
6000	19.16
7000	19.24
8000	19.25
9000	19.29
10000	19.36
11000	19.35
12000	19.38
13000	19.40
14000	19.53
15000	19.48
16000	19.54
17000	19.58
18000	19.62
19000	19.68
20000	19.72
21000	19.74
22000	19.78
23000	19.85
24000	19.89
25000	19.90
26000	19.94

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Attenuator + Cable loss(2 EA) + EUT loss(0.5 dB) + Splitter loss(6 dB)


### 8.7. Radiated Test

#### Limit


Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

#### Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



#### Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor( $0.009\text{ MHz} - 0.490\text{ MHz}$ ) =  $40\log(3\text{ m}/300\text{ m}) = - 80\text{ dB}$   
Measurement Distance : 3 m
7. Distance Correction Factor( $0.490\text{ MHz} - 30\text{ MHz}$ ) =  $40\log(3\text{ m}/30\text{ m}) = - 40\text{ dB}$

Measurement Distance : 3 m

#### 8. Spectrum Setting

- Frequency Range = 9 kHz ~ 30 MHz
- Detector = Peak
- Trace = Max hold
- RBW = 9 kHz
- VBW  $\geq$  3 x RBW

9. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

#### KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

#### Test Procedure of Radiated spurious emissions(Below 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. The Hybrid antenna was placed at a location 3m from the EUT, which is varied from 1m to 4m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

#### 6. Spectrum Setting

##### (1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Max hold
- RBW = 100 kHz
- VBW  $\geq$  3 x RBW

##### (2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

※In general, (1) is used mainly

7. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L)

8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions

from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

#### **Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Max hold
    - RBW = 1 MHz
    - VBW  $\geq$  3 x RBW
  - (2) Measurement Type(Average):
    - Average value of pulsed emissions
    - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determine from the peak field strength after correcting for the worst-case duty cycle as described in Number.14
      - ◆ Duty Cycle Correction(AFH) =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -24.7314 dB
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
11. Distance extrapolation factor =  $20\log(\text{test distance} / \text{specific distance})$  (dB)
12. Total(Measurement Type : Peak)  
= Measured Value(Peak) + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – Amp Gain(A.G)  
Total(Measurement Type : Average)  
= Measured Value(Peak) + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) - Amp Gain(A.G)  
+ D.C.C.F(AFH)

**13. Duty Cycle Correction Factor (79 channel hopping)**

- a. Time to cycle through all channels =  $\Delta t = \tau$  [ms] x 79 channels = 229.100 ms, where  $\tau$  = pulse width
- b.  $100 \text{ ms} / \Delta t$  [ms] = H  $\rightarrow$  Round up to next highest integer, H ' = 1
- c. Worst Case Dwell Time =  $\tau$  [ms] x H ' = 2.9 ms
- d. Duty Cycle Correction =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -30.752 dB

**14. Duty Cycle Correction Factor (AFH mode – minimum channel number case - 20 channels)**

- a. Time to cycle through all channels =  $\Delta t = \tau$  [ms] x 20 channels = 58.00 ms, where  $\tau$  = pulse width
- b.  $100 \text{ ms} / \Delta t$  [ms] = H  $\rightarrow$  Round up to next highest integer, H ' = 2
- c. Worst Case Dwell Time =  $\tau$  [ms] x H ' = 5.800 ms
- d. Duty Cycle Correction (AFH) =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -24.7314 dB

**Test Procedure of Radiated Restricted Band Edge**

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.

**8. Spectrum Setting****(1) Measurement Type (Peak):**

- Detector = Peak
- Trace = Max hold
- RBW = 1 MHz
- VBW  $\geq 3 \times$  RBW

**(2) Measurement Type (Average):**

- Average value of pulsed emissions
  - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determine from the peak field strength after correcting for the worst-case duty cycle as described in Number.13
- ◆ Duty Cycle Correction (AFH) =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -24.7314 dB

9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

10. Distance extrapolation factor =  $20\log(\text{test distance} / \text{specific distance})$  (dB)

11. Total

(1) Measurement(Peak)

= Measured Value(Peak)

(2) Measurement(Avg)

= Measured Value(Peak) + D.C.C.F(AFH)

- We apply to the offset in range 1 GHz - 18 GHz

- The offset = Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

## 12. Duty Cycle Correction Factor (79 channel hopping)

- a. Time to cycle through all channels=  $\Delta t = \tau$  [ms] x 79 channels = 229.100 ms, where  $\tau$  = pulse width
- b. 100 ms/  $\Delta t$  [ms] = H  $\rightarrow$  Round up to next highest integer, H ' =1
- c. Worst Case Dwell Time =  $\tau$  [ms] x H ' = 2.9 ms
- d. Duty Cycle Correction =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -30.752 dB

## 13. Duty Cycle Correction Factor(AFH mode – minimum channel number case - 20 channels)

- a. Time to cycle through all channels=  $\Delta t = \tau$  [ms] x 20 channels = 58.00 ms, where  $\tau$  = pulse width
- b. 100 ms/  $\Delta t$  [ms] = H  $\rightarrow$  Round up to next highest integer, H ' = 2
- c. Worst Case Dwell Time =  $\tau$  [ms] x H ' = 5.800 ms
- d. Duty Cycle Correction(AFH) =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -24.7314 dB

## 8.8. AC Power line Conducted Emissions

### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 <sup>(a)</sup>	56 to 46 <sup>(a)</sup>
0.50 to 5	56	46
5 to 30	60	50

<sup>(a)</sup>Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

### Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.
5. The EUT is the device operating below 30MHz.
  - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
  - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

### Sample Calculation

Quasi-peak(Final Result) = Measured Value + Correction Factor

## 8.9. Worst case configuration and mode

### Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone, Stand alone+ Shark Antenna
  - Worstcase : Stand alone+ Shark Antenna
2. EUT Axis
  - Radiated Spurious Emissions : X
  - Radiated Restricted Band Edge : X
3. All data rate of operation were investigated and the test results are worst case in highest datarate of each mode.
  - GFSK : DH5
  - $\pi/4$ DQPSK : 2-DH5
  - 8DPSK : 3-DH5
4. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
  - Position : Horizontal, Vertical, Parallel to the ground plane
5. DA351I6MG, Additional Models were tested and the worst case results are reported.  
(Worst case : DA351I6MG)

### AC Power line Conducted Emissions

1. We don't perform powerline conducted emission test. The device only employ battery power for operation.

### Conducted test

1. The EUT was configured with data rate of highest power.
  - GFSK : DH5
  - $\pi/4$ DQPSK : 2-DH5
  - 8DPSK : 3-DH5
2. AFH & Non-AFH were tested and the worst case results are reported.  
(Worst case : Non-AFH)
3. DA351I6MG, Additional Models were tested and the worst case results are reported.  
(Worst case : DA351I6MG)

**Radiated test(Simultaneous transmission Scenario)**

1. All modes of operation were investigated and the worst case configuration results are reported.

- Mode : Stand alone, Stand alone+ Shark Antenna

- Worstcase : Stand alone+ Shark Antenna

2. EUT Axis

- Radiated Spurious Emissions : X

3. All of Simultaneous transmission Scenario were investigated and the worst case configuration results are reported.

Simultaneous transmission Scenario	2.4 GHz WiFi	5 GHz WiFi	BT	Test Case
Bluetooth + 2.4 GHz WiFi	on	-	on	Scenario1
Bluetooth + 5 GHz WiFi	-	on	on	Scenario2

4. The Simultaneous transmission mode test investigated both intermodulation and radiated spurious emissions. And the worst results were reported.

- Worst result: Radiated spurious emissions

- Intermodulation: No signals are generated.

- Radiated spurious emissions: cf. Section 10.6.2

Scenario	Description	Bluetooth Emission	2.4 GHz Emission
1	Antenna	BT ANT	WLAN ANT
	Channel	78	1
	Data Rate	1 Mbps	1 Mbps
	Mode	GFSK	802.11b

Note : DTS Simultaneous transmission Scenario Data refer to [DTS] Test Report

Scenario	Description	Bluetooth Emission	5 GHz Emission
2	Antenna	BT ANT	WLAN ANT
	Channel	78	100
	Data Rate	1 Mbps	6 Mbps
	Mode	GFSK	802.11a

Note : UNII Simultaneous transmission Scenario Data refer to [UNII] Test Report

**9. SUMMARY OF TEST RESULTS**

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	§ 15.247(a)(1)	N/A	Conducted	PASS
Occupied Bandwidth	N/A	N/A		N/A
Conducted Maximum Peak Output Power	§ 15.247(b)(1)	<0.125 W		PASS
Carrier Frequency Separation	§ 15.247(a)(1)	>25 kHz or >2/3 of the 20 dB BW		PASS
Number of Hopping Frequencies	§ 15.247(a)(1)(iii)	≥ 15		PASS
Time of Occupancy	§ 15.247(a)(1)(iii)	<400 ms		PASS
Conducted Spurious Emissions	§ 15.247(d)	> 20 dB for all out-of band emissions		PASS
Band Edge (Out of Band Emissions)	§ 15.247(d)	> 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	§ 15.207(a)	cf. Section 8.8		N/A (Note1)
Radiated Spurious Emissions	§ 15.247(d), 15.205, 15.209	cf. Section 8.7	Radiated	PASS
Radiated Restricted Band Edge	§ 15.247(d), 15.205, 15.209	cf. Section 8.7		PASS

**Note**

1. The device only employ battery power for operation.

**10. TEST RESULT****10.1 PEAK POWER**

Channel	Frequency (MHz)	Output Power (GFSK)		Limit (mW)
		(dBm)	(mW)	
Ch. 0	2402	0.569	1.14	125
Ch. 39	2441	1.326	1.36	
Ch. 78	2480	1.042	1.27	

Channel	Frequency (MHz)	Output Power (8DPSK)		Limit (mW)
		(dBm)	(mW)	
Ch. 0	2402	-1.892	0.65	125
Ch. 39	2441	-0.766	0.84	
Ch. 78	2480	-0.769	0.84	

Channel	Frequency (MHz)	Output Power ( $\pi/4$ DQPSK)		Limit (mW)
		(dBm)	(mW)	
Ch. 0	2402	-2.348	0.58	125
Ch. 39	2441	-1.209	0.76	
Ch. 78	2480	-1.201	0.76	

## TEST PLOTS(Peak Power)


### Note:

In order to simplify the report, attached plots were only the worst case channel.

GFSK : Peak Power (Ch. 39)



8DPSK : Peak Power (Ch. 39)



$\pi/4$ DQPSK : Peak Power (Ch. 78)



**10.2 BAND EDGES****Without hopping**

Outside Frequency Band	GFSK (dB)	8DPSK (dB)	$\pi/4$ DQPSK (dB)	Limit (dBc)
Lower	47.937	42.680	41.692	20
Upper	48.712	43.662	43.990	

**With hopping**

Outside Frequency Band	GFSK (dB)	8DPSK (dB)	$\pi/4$ DQPSK (dB)	Limit (dBc)
Lower	47.366	41.762	41.359	20
Upper	48.401	43.285	43.448	


█ TEST PLOTS(BAND EDGES)

Note :


In order to simplify the report, attached plots were only the worst case mode.

**Without hopping**

**π/4DQPSK Band Edge(Ch. 0)**




**8DPSK Band Edge(Ch. 78)**




**-With hopping**

**π/4DQPSK Band Edge(Ch. 0)**



**8DPSK Band Edge(Ch. 78)**



**10.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99 % BW)**

99% BW (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
Ch. 0	997.6	1347	1361
Ch. 39	1004	1347	1362
Ch. 78	979.4	1343	1354

20dB Bandwidth (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
Ch. 0	908.74	1223.7	1221.1
Ch. 39	906.89	1223.9	1219.3
Ch. 78	907.90	1222.2	1217.7



Channel Separation (kHz)			Limit
GFSK	8DPSK	$\pi/4$ DQPSK	(kHz)
998	994	991	>25 kHz or >2/3 of the 20 dB BW

## □ TEST PLOTS(Channel Separation)

Test Plot (GFSK)



Test Plot (8DPSK)


 Test Plot ( $\pi/4$ DQPSK)


TEST PLOTS(20 dB Bandwidth & 99% OBW)


**Note:**

In order to simplify the report, attached plots were only the widest 20 dB BW channel.


GFSK 20 dB BW & 99% OBW (Ch. 39)



8DPSK 20 dB BW & 99% OBW (Ch. 39)



$\pi/4$ DQPSK 20 dB BW & 99% OBW (Ch. 39)



**10.4 NUMBER OF HOPPING FREQUENCY**

Result (No. of CH)			Limit
GFSK	8DPSK	$\pi/4$ DQPSK	
79	79	79	>15

**Note :**

In case of AFH mode, minimum number of hopping channels is 20.

□ TEST PLOTS (NUMBER OF HOPPING FREQUENCY)



**10.5 TIME OF OCCUPANCY (DWELL TIME)**

Pulse Time (ms)	Channel	GFSK	8DPSK	$\pi/4$ DQPSK
	Ch. 0	2.885	2.890	2.890
	Ch. 39	2.890	2.895	2.890
	Ch. 78	2.890	2.890	2.890

**Non-AFH Mode**

Total of Dwell (ms)	Channel	GFSK	8DPSK	$\pi/4$ DQPSK	Period Time (s)	Limit (ms)
	Ch. 0	307.73	308.27	308.27	31.6	400
	Ch. 39	308.27	308.80	308.27	31.6	
	Ch. 78	308.27	308.27	308.27	31.6	

**AFH Mode**

Total of Dwell (ms)	Channel	GFSK	8DPSK	$\pi/4$ DQPSK	Period Time (s)	Limit (ms)
	Ch. 0	153.87	154.13	154.13	8	400
	Ch. 39	154.13	154.40	154.13	8	
	Ch. 78	154.13	154.13	154.13	8	

## █ TEST PLOTS(Dwell Time)


### Note:

In order to simplify the report, attached plots were only the lowest channel.


GFSK : Dwell Time(Ch. 0)



8DPSK : Dwell Time(Ch. 0)



π/4DQPSK : Dwell Time(Ch. 0)




## 10.6 SPURIOUS EMISSIONS

### 10.6.1 CONDUCTED SPURIOUS EMISSIONS

#### █ TEST PLOTS (Worst case : GFSK \_CH.39)

##### Spurious Emission (30 MHz – 26.5 GHz)



#### Note:

1. In order to simplify the report, attached plots were only the worst case channel and data rate.
2. Limit: -20.131 dBm

### 10.6.2 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30 MHz

Frequency	Measured Value	A.F+C.L+D.F	POL	Total	Limit	Margin
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]

No Critical peaks found

Note:

1. The Measured of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor =  $40\log(\text{specific distance} / \text{test distance})$  (dB)
3. Limit line = Specific Limits (dB $\mu$ V) + Distance extrapolation factor
4. Radiated test is performed with hopping off.

Frequency Range : Below 1 GHz

Frequency	Measured Value	A.F+C.L	POL	Total	Limit	Margin
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]

No Critical peaks found

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
2. Radiated test is performed with hopping off.

## Frequency Range : Above 1 GHz

CH 0	2402	MHz	Mode :			Normal(GFSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4804	43.92	3.16	V	0.00	47.08	73.98	26.90	PK
4804	43.92	3.16	V	-24.73	22.35	53.98	31.63	AV
7206	42.00	9.93	V	0.00	51.93	73.98	22.05	PK
7206	42.00	9.93	V	-24.73	27.20	53.98	26.78	AV
4804	44.47	3.16	H	0.00	47.63	73.98	26.35	PK
4804	44.47	3.16	H	-24.73	22.90	53.98	31.08	AV
7206	42.04	9.93	H	0.00	51.97	73.98	22.01	PK
7206	42.04	9.93	H	-24.73	27.24	53.98	26.74	AV
CH 39	2441	MHz	Mode :			Normal(GFSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4882	42.59	4.11	V	0.00	46.70	73.98	27.28	PK
4882	42.59	4.11	V	-24.73	21.97	53.98	32.01	AV
7323	42.39	10.60	V	0.00	52.99	73.98	20.99	PK
7323	42.39	10.60	V	-24.73	28.26	53.98	25.72	AV
4882	42.71	4.11	H	0.00	46.82	73.98	27.16	PK
4882	42.71	4.11	H	-24.73	22.09	53.98	31.89	AV
7323	42.43	10.60	H	0.00	53.03	73.98	20.95	PK
7323	42.43	10.60	H	-24.73	28.30	53.98	25.68	AV
CH 78	2480	MHz	Mode :			Normal(GFSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4960	43.71	2.88	V	0.00	46.59	73.98	27.39	PK
4960	43.71	2.88	V	-24.73	21.86	53.98	32.12	AV
7440	41.86	11.34	V	0.00	53.20	73.98	20.78	PK
7440	41.86	11.34	V	-24.73	28.46	53.98	25.52	AV
4960	43.73	2.88	H	0.00	46.61	73.98	27.37	PK
4960	43.73	2.88	H	-24.73	21.88	53.98	32.10	AV
7440	41.95	11.34	H	0.00	53.29	73.98	20.69	PK
7440	41.95	11.34	H	-24.73	28.55	53.98	25.43	AV

CH 0	2402	MHz	Mode :			EDR ( $\pi/4$ DQPSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4804	43.67	3.16	V	0.00	46.83	73.98	27.15	PK
4804	43.67	3.16	V	-24.73	22.10	53.98	31.88	AV
7206	40.92	9.93	V	0.00	50.85	73.98	23.13	PK
7206	40.92	9.93	V	-24.73	26.12	53.98	27.86	AV
4804	43.67	3.16	H	0.00	46.83	73.98	27.15	PK
4804	43.67	3.16	H	-24.73	22.10	53.98	31.88	AV
7206	40.92	9.93	H	0.00	50.85	73.98	23.13	PK
7206	40.92	9.93	H	-24.73	26.12	53.98	27.86	AV
CH 39	2441	MHz	Mode :			EDR ( $\pi/4$ DQPSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4882	42.28	4.11	V	0.00	46.39	73.98	27.59	PK
4882	42.28	4.11	V	-24.73	21.66	53.98	32.32	AV
7323	41.93	10.60	V	0.00	52.53	73.98	21.45	PK
7323	41.93	10.60	V	-24.73	27.80	53.98	26.18	AV
4882	42.49	4.11	H	0.00	46.60	73.98	27.38	PK
4882	42.49	4.11	H	-24.73	21.87	53.98	32.11	AV
7323	42.05	10.60	H	0.00	52.65	73.98	21.33	PK
7323	42.05	10.60	H	-24.73	27.92	53.98	26.06	AV
CH 78	2480	MHz	Mode :			EDR ( $\pi/4$ DQPSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4960	42.58	2.88	V	0.00	45.46	73.98	28.52	PK
4960	42.58	2.88	V	-24.73	20.73	53.98	33.25	AV
7440	41.66	11.34	V	0.00	53.00	73.98	20.98	PK
7440	41.66	11.34	V	-24.73	28.26	53.98	25.72	AV
4960	42.96	2.88	H	0.00	45.84	73.98	28.14	PK
4960	42.96	2.88	H	-24.73	21.11	53.98	32.87	AV
7440	41.76	11.34	H	0.00	53.10	73.98	20.88	PK
7440	41.76	11.34	H	-24.73	28.36	53.98	25.62	AV

CH 0	2402	MHz	Mode :			EDR (8DPSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4804	44.01	3.16	V	0.00	47.17	73.98	26.81	PK
4804	44.01	3.16	V	-24.73	22.44	53.98	31.54	AV
7206	41.17	9.93	V	0.00	51.10	73.98	22.88	PK
7206	41.17	9.93	V	-24.73	26.37	53.98	27.61	AV
4804	44.12	3.16	H	0.00	47.28	73.98	26.70	PK
4804	44.12	3.16	H	-24.73	22.55	53.98	31.43	AV
7206	41.21	9.93	H	0.00	51.14	73.98	22.84	PK
7206	41.21	9.93	H	-24.73	26.41	53.98	27.57	AV

CH 39	2441	MHz	Mode :			EDR (8DPSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4882	42.11	4.11	V	0.00	46.22	73.98	27.76	PK
4882	42.11	4.11	V	-24.73	21.49	53.98	32.49	AV
7323	41.98	10.60	V	0.00	52.58	73.98	21.40	PK
7323	41.98	10.60	V	-24.73	27.85	53.98	26.13	AV
4882	42.15	4.11	H	0.00	46.26	73.98	27.72	PK
4882	42.15	4.11	H	-24.73	21.53	53.98	32.45	AV
7323	42.14	10.60	H	0.00	52.74	73.98	21.24	PK
7323	42.14	10.60	H	-24.73	28.01	53.98	25.97	AV

CH 78	2480	MHz	Mode :			EDR (8DPSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4960	42.99	2.88	V	0.00	45.87	73.98	28.11	PK
4960	42.99	2.88	V	-24.73	21.14	53.98	32.84	AV
7440	41.75	11.34	V	0.00	53.09	73.98	20.89	PK
7440	41.75	11.34	V	-24.73	28.35	53.98	25.63	AV
4960	43.21	2.88	H	0.00	46.09	73.98	27.89	PK
4960	43.21	2.88	H	-24.73	21.36	53.98	32.62	AV
7440	41.85	11.34	H	0.00	53.19	73.98	20.79	PK
7440	41.85	11.34	H	-24.73	28.45	53.98	25.53	AV

**[Simultaneous transmission Scenario]**Scenario 1

Bluetooth DH5\_Ch.78 + WLAN 2.4 GHz 802.11b\_Ch. 1

CH 78	2480	MHz	Mode :			Normal(GFSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4960	43.59	2.88	V	0.00	46.47	73.98	27.51	PK
4960	43.59	2.88	V	-24.73	21.74	53.98	32.24	AV
7440	41.79	11.34	V	0.00	53.13	73.98	20.85	PK
7440	41.79	11.34	V	-24.73	28.39	53.98	25.59	AV
4960	43.74	2.88	H	0.00	46.62	73.98	27.36	PK
4960	43.74	2.88	H	-24.73	21.89	53.98	32.09	AV
7440	41.97	11.34	H	0.00	53.31	73.98	20.67	PK
7440	41.97	11.34	H	-24.73	28.57	53.98	25.41	AV

Scenario 2


Bluetooth DH5\_Ch.78 + WLAN 5 GHz 802.11a\_Ch. 100

CH 78	2480	MHz	Mode :			Normal(GFSK)		
Frequency	Measured value	A.F+C.L-A.G+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
4960	43.58	2.88	V	0.00	46.46	73.98	27.52	PK
4960	43.58	2.88	V	-24.73	21.73	53.98	32.25	AV
7440	41.99	11.34	V	0.00	53.33	73.98	20.65	PK
7440	41.99	11.34	V	-24.73	28.59	53.98	25.39	AV
4960	43.76	2.88	H	0.00	46.64	73.98	27.34	PK
4960	43.76	2.88	H	-24.73	21.91	53.98	32.07	AV
7440	42.12	11.34	H	0.00	53.46	73.98	20.52	PK
7440	42.12	11.34	H	-24.73	28.72	53.98	25.26	AV

**□ Test Plots**

**Note:** Plot of worst case was only reported.


Radiated Spurious Emissions plot – Average &amp; Peak Result (GFSK, Ch.78 3rd Harmonic, X-H)



**[Simultaneous transmission Scenario]**Scenario 1


Bluetooth DH5\_Ch.78 + WLAN 2.4 GHz 802.11b\_Ch. 1

Radiated Spurious Emissions plot – Peak &amp; Average Result (GFSK, Ch.78 3rd Harmonic, X-H)

Scenario 2

Bluetooth DH5\_Ch.78 + WLAN 5 GHz 802.11a\_Ch. 100

Radiated Spurious Emissions plot – Peak &amp; Average Result (GFSK, Ch.78 3rd Harmonic, X-H)



**10.6.3 RADIATED RESTRICTED BAND EDGES**

Normal(GFSK)	Channel	CH. 0, CH. 78		Channel Frequency		2402 MHz, 2480 MHz		
Frequency	Measured Value	A.F+C.L+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
2390.0	55.39	0.00	H	0.00	55.39	73.98	18.59	PK
2390.0	55.39	0.00	H	-24.73	30.66	53.98	23.32	AV
2483.5	55.50	0.00	H	0.00	55.50	73.98	18.48	PK
2483.5	55.50	0.00	H	-24.73	30.77	53.98	23.21	AV


EDR( $\pi/4$ DQPSK)	Channel	CH. 0, CH. 78		Channel Frequency		2402 MHz, 2480 MHz		
Frequency	Measured Value	A.F+C.L+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
2390.0	55.71	0.00	H	0.00	55.71	73.98	18.27	PK
2390.0	55.71	0.00	H	-24.73	30.98	53.98	23.00	AV
2483.5	54.95	0.00	H	0.00	54.95	73.98	19.03	PK
2483.5	54.95	0.00	H	-24.73	30.22	53.98	23.76	AV

EDR(8DPSK)	Channel	CH. 0, CH. 78		Channel Frequency		2402 MHz, 2480 MHz		
Frequency	Measured Value	A.F+C.L+D.F	ANT. POL	Duty Cycle Correction	Total	Limit	Margin	Measurement Type
[MHz]	[dB $\mu$ V]	[dB/m]	[H/V]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
2390.0	55.01	0.00	H	0.00	55.01	73.98	18.97	PK
2390.0	55.01	0.00	H	-24.73	30.28	53.98	23.70	AV
2483.5	56.08	0.00	H	0.00	56.08	73.98	17.90	PK
2483.5	56.08	0.00	H	-24.73	31.35	53.98	22.63	AV

**□ Test Plots**

Radiated Restricted Band Edges plot – Average &amp; Peak Result (8DPSK, Ch.78, X-H)

**Note:**

Plot of worst case was only reported.

**11. LIST OF TEST EQUIPMENT****Conducted Test**

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
LISN	ENV216	Rohde & Schwarz	102245	07/17/2025	Annual
EMI Test Receiver	ESR	Rohde & Schwarz	101910	07/02/2025	Annual
Temperature Chamber	SU-642	ESPEC	93022487	06/27/2025	Annual
Signal Analyzer	N9030A	Keysight	MY55410508	08/23/2025	Annual
Power Measurement Set	OSP 120	Rohde & Schwarz	100935	08/01/2025	Annual
Power Meter	N1911A	Agilent	MY45100523	02/21/2026	Annual
Power Sensor	N1921A	Agilent	MY57820067	02/04/2026	Annual
Directional Coupler	87300B	Agilent	3116A03621	10/21/2025	Annual
Power Splitter	11667B	Hewlett Packard	10545	01/23/2026	Annual
DC Power Supply	E3632A	Agilent	KR75305528	12/24/2025	Annual
Attenuator(10 dB)(DC-26.5 GHz)	8493C-010	Agilent	08285	05/28/2025	Annual
Attenuator(20 dB)	18N-20dB	Rohde & Schwarz	8	02/18/2026	Annual
Software	EMC32	Rohde & Schwarz	N/A	N/A	N/A
FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	HCT CO., LTD.	N/A	N/A	N/A
Bluetooth Tester	CBT	Rohde & Schwarz	100752	12/27/2025	Annual

**Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

**Radiated Test**

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
Controller(Antenna mast)	CO3000	Innco system	CO3000-4p	N/A	N/A
Antenna Position Tower	MA4640/800-XP-EP	Innco system	S3AM	07/30/2025	Annual
Controller	EM2090	Emco	060520	N/A	N/A
Turn Table	N/A	Ets	N/A	N/A	N/A
Amp & Filter Bank Switch Controller	FBSM-01A	TNM system	0	N/A	N/A
Loop Antenna	FMZB 1513	Rohde & Schwarz	1513-333	03/07/2026	Biennial
Hybrid Antenna	VULB 9168	Schwarzbeck	9168-0895	08/28/2026	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-1191	11/07/2025	Biennial
Horn Antenna(15 GHz ~ 40 GHz)	BBHA9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Band Reject Filter	WRCJV2400/2483.5-2370/2520-60/12SS	Wainwright Instruments	2	12/26/2025	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	5	06/04/2025	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	6	06/04/2025	Annual
Band Reject Filter	WRCJV5100/5850-40/50-8EEK	Wainwright Instruments	1	01/09/2026	Annual
RF Switching System	FBSR-03A (3G HPF+LNA)	T&M SYSTEM	S3L1	10/31/2025	Annual
RF Switching System	FBSR-03A (10dB ATT+LNA)	T&M SYSTEM	S3L2	10/31/2025	Annual
RF Switching System	FBSR-03A (7G HPF+LNA)	T&M SYSTEM	S3L3	10/31/2025	Annual
RF Switching System	FBSR-03A (3dB ATT+LNA)	T&M SYSTEM	S3L4	10/31/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
Bluetooth Tester	TC-3000C	TESCOM	3000C000175	03/19/2025	Annual
Spectrum Analyzer	FSV40 (9 kHz ~ 40 GHz)	Rohde & Schwarz	100900	08/27/2025	Annual

**Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

**12. ANNEX A\_ TEST SETUP PHOTO**

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2503-FC050-P