



HCT CO., LTD.

CERTIFICATE OF COMPLIANCE

FCC PART 15.247 Certification

Applicant Name:
HYUNDAI MOBIS CO., LTD.

Address:
80-9, MABOOK-RI, GUSEONG-EUP,
YONGIN-SHI, GYUNGGI-DO, 449-912 SOUTH KOREA

Date of Issue:
June 16, 2010
Location:
HCT CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,
Kyungki-do, Korea
Test Report No.: HCTR1006FR12
HCT FRN: 0005866421
IC Recognition No.: 5944A-1

FCC ID	:TQ8-PA710RBLSBT
IC ID	:5074A-PA710RBCASBT
APPLICANT	:HYUNDAI MOBIS CO., LTD.

FCC Model(s): PA710RBLSBT
IC Model(s): PA710RBCASBT
EUT Type: CAR AUDIO
Max. RF Output Power: 2.73 dBm(1.87 mW)
Frequency Range: 2402 - 2480 MHz (Bluetooth)
Modulation type GFSK(Normal), PSK(EDR)
FCC Classification: FCC Part 15 Frequency Hopping Spread Spectrum Transceiver
FCC Rule Part(s): Part 15 subpart C 15.247
IC Rule : RSS-210 Issue 7 (June 2007) , RSS-GEN Issue 2(June 2007)
IC Registration No. : 5944A-1

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.862


Report prepared by
: Jong Seok Lee
Test Engineer of RF Team


Approved by
: Sang Jun Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1006FR12	June 16, 2010	First Approval Report

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT



Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
4. INSTRUMENT CALIBRATION	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	6
7. SUMMARY OF TEST RESULTS	7
8. FCC PART 15.247 REQUIREMENTS	8
8.1 PEAK POWER	8
8.2 BAND EDGES MEASUREMENT	12
8.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)	15
8.4 NUMBER OF HOPPING FREQUENCY	20
8.5 TIME OF OCCUPANCY (DWELL TIME)	23
8.6 SPURIOUS EMISSIONS	27
8.6.1 CONDUCTED SPURIOUS MEASUREMENT	27
8.6.2 RADIATED SPURIOUS EMISSIONS	34
8.6.3 RECEIVER SPURIOUS EMISSIONS	42
8.6.4 RADIATED RESTRICTED BAND EDGE MEASUREMENTS	43
8.7 POWERLINE CONDUCTED EMISSIONS	44
9. LIST OF TEST EQUIPMENT	45

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



1. GENERAL INFORMATION

Applicant Name: HYUNDAI MOBIS CO., LTD.
Address: 80-9, MABOOK-RI, GUSEONG-EUP,
YONGIN-SHI, GYUNGGI-DO, 449-912 SOUTH KOREA
FCC ID: TQ8-PA710RBLSBT
IC ID: 5074A-PA710RBCASBT
EUT: CAR AUDIO
Model name(s): PA710RBLSBT
Date(s) of Tests: June 08, 2010 ~ June 09, 2010
Contact Person: Name: Seung Keun, Jeon
Phone #: +82-31-288-5232
Fax #: +82-31-899-1788
Place of Tests: HCT CO., LTD.,
San 136-1 Ami-ri, Bubal-eup, Icheon-si, Kyungki-do, Korea
(IC Recognition No. : 5944A-1)

2. EUT DESCRIPTION

Product	CAR AUDIO
FCC Model Name	PA710RBLSBT
IC Model Name	PA710RBCASBT
Power Supply	DC 12 V
Frequency Range	2402 - 2480 MHz (Bluetooth)
Transmit Power	2.73 dBm(1.87 mW)
Modulation Type	GFSK(Normal), PSK(EDR)
Modulation Technique	FHSS
Number of Channels	79Channels
Antenna Specification	Manufacturer: Auto Industrial Co., Ltd. Antenna type: Chip Antenna Peak Gain : -5.47 dBi

* 15.247 Requirements for Bluetooth transmitter

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
 - 1) This system is hopping pseudorandomly.
 - 2) Each frequency is used equally on the average by each transmitter.
 - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
 - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz(ANSI C63.4-2003) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" were used in the measurement of the **HYUNDAI MOBIS CO., LTD.** .

CAR AUDIO FCC ID: TQ8-PA710RBLASBT

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLASBT	IC : 5074A-PA710RBCASBT



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



7. SUMMARY OF TEST RESULTS

Test Description	IC Part Section(s)	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	RSS-210, A8.1(a)	§15.247(a)(1)(ii) or (iii)	NA	CONDUCTED	PASS
Occupied Bandwidth	RSS-210, A1.1.3		NA		PASS
Conducted Maximum Peak Output Power	RSS-210, A8.4(2)	§15.247(b)(1)	< 1 Watts		PASS
Carrier Frequency Separation	RSS-210, A8.1(b)	§15.247(a)(1)	>25 kHz or >2/3 of the 20dB BW		PASS
Number of Hopping Frequencies	RSS-210, A8.1(d)	§15.247(a)(1)(iii)	>15		PASS
Time of Occupancy	RSS-210, A8.1(d)	§15.247(a)(1)(iii)	<400 ms		PASS
Conducted Spurious Emissions	RSS-210, A 8.5 RSS-GEN, Section 7.2.3	§15.247(d)	< 20 dB for all out-of band emissions		PASS
Band Edge(Out of Band Emissions)	RSS-210, A 8.5	§15.247(d)	< 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	RSS-GEN, Section 7.2.2	§15.207(a)	cf. Section 8.7		PASS
Radiated Spurious Emissions	RSS-210, A2.9, A 8.5	§15.247(d), 15.205, 15.209	cf. Section 8.6.2	RADIATED	PASS
Radiated Restricted Band Edge	RSS-210, A2.9, A 8.5	§15.247(d), 15.205, 15.209	cf. Section 8.6.4		PASS
Receiver Spurious Emissions	RSS-GEN, Section 7.2.3	§15.109	cf. Section 8.6.3		PASS

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

8. FCC PART 15.247 REQUIREMENTS


8.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode.

1. Span = 2 MHz (GFSK) / 5 MHz (8DPSK)
2. RBW = 1 MHz (GFSK) / 3 MHz (8DPSK)
3. VBW = 1 MHz (GFSK) / 3 MHz (8DPSK)
4. Sweep = auto
5. Packet type= DH5 (GFSK) / 3-DH5 (8DPSK)

TEST RESULTS


No non-compliance noted

Test Data


Channel	Frequency (MHz)	Output Power(GFSK)		Output Power(8DPSK)		Limit (W)	Result
		(dBm)	(mW)	(dBm)	(mW)		
Low	2402	2.73	1.87	2.57	1.81	1	PASS
Mid	2441	1.85	1.53	1.69	1.48		PASS
High	2480	0.73	1.18	0.53	1.13		PASS

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT	

Test Plots (GFSK)
Peak Power (Low-CH)




Test Plots (GFSK)
Peak Power (Mid-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK)
Peak Power (High-CH)




Test Plots (8DPSK)
Peak Power (Low-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT


Test Plots (8DPSK)

Peak Power (Mid-CH)



Test Plots (8DPSK)

Peak Power (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

8.2 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Configuration



TEST PROCEDURE

The spectrum analyzer is set to :


1. Span = 8 MHz
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Sweep = auto
5. Detector Mode = Peak

TEST RESULTS


See attached.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK)
Band Edges (Low-CH)




Test Plots (GFSK)
Band Edges (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (8DPSK)
Band Edges (Low-CH)



Test Plots (8DPSK)
Band Edges (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

8.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)

LIMIT

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Configuration



TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 3 MHz
2. RBW = 30 kHz
3. VBW = 100 kHz
4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

TEST RESULTS

No non-compliance noted

Test Data


Channel Separation (kHz)		20dB Bandwidth (kHz)			Limit (kHz)	Result
GFSK	8DPSK	Channel	GFSK	8DPSK		
1000	1000	Low CH	934.1	1272.0	>25 or >2/3 of the 20dB BW	Pass
		Middle CH	926.4	1276.0		
		High CH	928.3	1278.0		

Occupied Bandwidth (99% BW)


99% BW (kHz)			Result
Channel	GFSK	8DPSK	
Low CH	853.5	1172.8	Pass
Middle CH	856.3	1169.9	
High CH	852.9	1170.3	

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK)
Channel Separation




Test Plots (8DPSK)
Channel Separation



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (Low-CH)



Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT


Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)



Test Plots (8DPSK)


20 dB Bandwidth & Occupied Bandwidth (Low-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT


Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)



Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

8.4 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

Test Configuration



TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

1. Span = the frequency band of operation (Start = 2400 MHz, Stop = 2483.5 MHz)
2. RBW = 300 kHz
3. VBW = 300 kHz
4. Sweep = auto

The trace was allowed to stabilize.

TEST RESULTS

No non-compliance noted


Test Data

Result (No. of CH)		Limit	Result
GFSK	8DPSK		
79	79	>15	Pass

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT


Test Plots (GFSK)

Number of Channels (2.4 GHz - 2.441 GHz)



Test Plots (GFSK)


Number of Channels (2.441 GHz - 2.4835 GHz)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT


Test Plots (8DPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



Test Plots (8DPSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

8.5 TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

Test Configuration



TEST PROCEDURE

EUT was set to transmit the longest packet type (DH5)

1. Span = zero span
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

TEST RESULTS

See the table.

DH 5(The longest packet type for GFSK)

$$\text{CH Mid : } 2.9 * (1600/6)/79 * 31.6 = 309.33 \text{ (ms)}$$


3-DH 5(The longest packet type for 8DPSK)

$$\text{CH Mid : } 2.91 * (1600/6)/79 * 31.6 = 310.4 \text{ (ms)}$$


Channel	Pulse Time (ms)		Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result
	GFSK	8DPSK	GFSK	8DPSK			
Low	2.90	2.91	309.33	310.40	31.6	400	PASS
Mid	2.90	2.91	309.33	310.40	31.6		PASS
High	2.90	2.91	309.33	310.40	31.6		PASS

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT				www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID :	IC :	
HCTR1006FR12	June 16, 2010	CAR AUDIO	TQ8-PA710RBLSBT	5074A-PA710RBCASBT	

Test Plots (GFSK)
Dwell Time (Low-CH)




Test Plots (GFSK)
Dwell Time (Mid-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK)
Dwell Time (High-CH)




Test Plots (8DPSK)
Dwell Time (Low-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT


Test Plots (8DPSK)

Dwell Time (Mid-CH)



Test Plots (8DPSK)

Dwell Time (High-CH)




8.6 SPURIOUS EMISSIONS

8.6.1 CONDUCTED SPURIOUS MEASUREMENT

LIMIT : §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


TEST RESULTS

No non-compliance noted


FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)
Spurious Emission (Low-CH)




Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)
Spurious Emission (Mid-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)
Spurious Emission (High-CH)




Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)
Spurious Emission (Low-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT



Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)
Spurious Emission (Mid-CH)




Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)
Spurious Emission (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID :	IC :
HCTR1006FR12	June 16, 2010	CAR AUDIO	TQ8-PA710RBLBSBT	5074A-PA710RBCASBT

Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)
Spurious Emission (Low-CH)




Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)
Spurious Emission (Mid-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)
Spurious Emission (High-CH)




Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)
Spurious Emission (Low-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT

Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)
Spurious Emission (Mid-CH)



Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)
Spurious Emission (High-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT



8.6.2 RADIATED SPURIOUS EMISSIONS

LIMIT : §15.247(d), §15.205, §15.209


1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLB	IC : 5074A-PA710RBCASBT

Test Configuration

Below 30 MHz




30 MHz - 1 GHz



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO		FCC ID : TQ8-PA710RBLASBT	IC : 5074A-PA710RBCASBT	

Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO		FCC ID : TQ8-PA710RBLBSBT	IC : 5074A-PA710RBCASBT	



TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO		FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode (Channel : 2402)

Frequency MHz	Reading dBuV	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
113.42	13.00	10.40	2.50	H	25.90	43.5	17.6
238.55	11.81	10.80	3.70	V	26.31	46.0	19.7
474.26	9.48	16.50	5.10	V	31.08	46.0	14.9
479.11	9.66	16.60	5.20	V	31.46	46.0	14.5
886.51	5.05	22.30	7.20	H	34.55	46.0	11.5

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT	



Above 1 GHz

Operation Mode: CH Low(GFSK)

Frequency [MHz]	Reading dBuV	*A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804	49.86	-6.08	H	43.78	74	30.22	PK
4804	34.34	-6.08	H	28.26	54	25.74	AV
7206	49.16	1.28	H	50.44	74	23.56	PK
7206	34.38	1.28	H	35.66	54	18.34	AV
4804	49.48	-6.08	V	43.40	74	30.60	PK
4804	34.36	-6.08	V	28.28	54	25.72	AV
7206	48.93	1.28	V	50.21	74	23.79	PK
7206	34.35	1.28	V	35.63	54	18.37	AV

* A-F: ANTENNA FACTOR

C-L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.
5. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



Operation Mode: CH Mid(GFSK)

Frequency [MHz]	Reading dBuV	※A.F+CL-AMP GAIN. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4882	48.17	-5.81	H	42.36	74	31.64	PK
4882	34.76	-5.81	H	28.95	54	25.05	AV
7323	48.56	1.65	H	50.21	74	23.79	PK
7323	34.30	1.65	H	35.95	54	18.05	AV
4882	48.76	-5.81	V	42.95	74	31.05	PK
4882	34.78	-5.81	V	28.97	54	25.03	AV
7323	48.67	1.65	V	50.32	74	23.68	PK
7323	34.28	1.65	V	35.93	54	18.07	AV

※ A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.
5. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



Operation Mode: CH High(GFSK)

Frequency [MHz]	Reading dBuV	*A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960	49.03	-5.53	H	43.50	74	30.50	PK
4960	34.00	-5.53	H	28.47	54	25.53	AV
7440	49.83	2.03	H	51.86	74	22.14	PK
7440	35.43	2.03	H	37.46	54	16.54	AV
4960	48.11	-5.53	V	42.58	74	31.42	PK
4960	34.08	-5.53	V	28.55	54	25.45	AV
7440	49.24	2.03	V	51.27	74	22.73	PK
7440	35.38	2.03	V	37.41	54	16.59	AV

* A.F: ANTENNA FACTOR

C.L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.
5. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



8.6.3 RECEIVER SPURIOUS EMISSIONS

FCC Rule(s)	§15.109 (see Table Below)	
Test Requirements:	Emission Level shall not exceed §15.109 limits	
Operating conditions:	Under normal test conditions	
Method of testing:	Radiated	
S/A. Settings:	F < 1 GHz: RBW: 120 kHz, VBW: 300 kHz (Quasi Peak)	
Mode of operation:	F > 1 GHz: RBW: 1 MHz, VBW: 1 MHz (Peak)	
Receive		
Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30 – 88	100 (40 dBuV)	3
88 - 216	150 (43.5 dBuV))	3
216 – 960	200 (46 dBuV)	3
Above 960	500 (54 dBuV)	3

Operation Mode: Receive:

30 MHz ~ 1 GHz

Frequency MHz	Reading dBuV	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
113.42	11.87	10.40	2.50	H	24.77	43.5	18.7
238.55	10.88	10.80	3.70	V	25.38	46.0	20.6
474.26	8.60	16.50	5.10	V	30.20	46.0	15.8
479.11	9.77	16.60	5.20	V	31.57	46.0	14.4
867.11	5.15	22.00	7.10	H	34.25	46.0	11.8

Above 1 GHz

Frequency MHz	Reading dBuV	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
No Critical peaks found							

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLASBT	IC : 5074A-PA710RBCASBT	



8.6.4 RADIATED RESTRICTED BAND EDGE MEASUREMENTS

Test Requirements and limit, §15.247(d), §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode	GFSK(Normal)						
Operating Frequency	2402 MHz, 2480 MHz						
Channel No	CH 0, CH 78						

Frequency [MHz]	Reading dBuV	*A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2340.38	51.17	-12.54	V	38.63	74	35.37	PK
2340.38	36.49	-12.54	V	23.95	54	30.05	AV
2366.54	50.91	-12.43	H	38.48	74	35.52	PK
2366.54	36.53	-12.43	H	24.10	54	29.90	AV
2490.16	51.49	-11.89	V	39.60	74	34.40	PK
2490.16	36.55	-11.89	V	24.66	54	29.34	AV
2491.49	50.63	-11.89	H	38.74	74	35.26	PK
2491.49	36.18	-11.89	H	24.29	54	29.71	AV

* A-F: ANTENNA FACTOR

C-L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW=1 MHz, VBW= 10 Hz.
2. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLBTS	IC : 5074A-PA710RBCASBT



8.7 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

Note : We don't perform powerline conducted emission test. Because this EUT use with vehicle.

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT



9. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESH2-Z5/ LISN	Annual	03/24/2011	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	Annual	03/05/2011	100329
Schwarzbeck	VULB 9160/ TRILOG Antenna	Biennial	12/18/2010	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	Annual	10/30/2010	375.8810.352
MITEQ	AMF-6D-001180-35-20P/AMP	Annual	05/20/2011	990893
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	09/23/2011	296
Rohde & Schwarz	FSP30 / Spectrum Analyzer	Annual	03/25/2011	839117/011
Agilent	E4440A / Spectrum Analyzer	Annual	06/09/2011	US45303008
Agilent	E4416A /Power Meter	Annual	01/14/2011	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	07/28/2010	MY4442009
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	06/29/2010	1
Hewlett Packard	11636B/Power Divider	Annual	12/24/2010	11377
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	01/08/2011	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	12/01/2010	010002156287001199
TESCOM	TC-3000A / BLUETOOTH TESTER	Annual	01/11/2011	3000A490112
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	06/22/2010	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/13/2012	9009-2536

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1006FR12	Date of Issue: June 16, 2010	EUT Type: CAR AUDIO	FCC ID : TQ8-PA710RBLSBT	IC : 5074A-PA710RBCASBT