

Report No

EG0094-1

FCC ID: TW6AG-007-NMFA IC: 6304A-AG007

'	
Client	Hyde Park Electronics, LLC
Phone Fax	937-252-2121 937-258-5830
FRN	0014406581
Models	AG-007-NMFA
FCC ID IC #	TW6AG-007-NMFA 6304A-AG007
Emissions Designator	K1D
Equipment Type Equipment Code	Low Power Communications Device Transmitter DXX
Results	As detailed within this report
Prepared by	Josh LeBlanc – Test Engineer
Authorized by	Michael Buchholz – EMC Manager
Issue Date	3/6/06
Conditions of issue	This Test Report is issued subject to the conditions stated in 'terms and conditions' section of this report

Summary	
Product Description (Transmitter)	
Test Methodology	
Statement of Conformity	
EUT Configuration	
Spurious and Harmonic Radiated Emissions	
Occupied Bandwidth	
Fundamental Field Strength	
Test Equipment Used	
Terms and Conditions	
A2LA Accreditation	

Summary

This report is an application for certification of a transmitter operating pursuant to 47 CFR 15.249 and RSS-210. The product covered by this report is the AG-007-NMFA. It is a wireless proximity sensor that has a transmitter and receiver operating at 916.5MHz.

Product Description (Transmitter)

MN: AG-007-NMFA SN: Test sample 1 Power Source: 3.6V DC battery

Test Methodology

Radiated emissions testing was performed according to the procedures specified in ANSI C63.4 (2003). The EUT was maximized around all three orthogonal axes. The EUT has an integrated internal antenna which can not be maximized separately. The standard test voltage was 3.6VDC. The EUT is battery powered with no provisions for connection to the AC mains. A fresh battery was used for all testing. The ambient environmental conditions were as follows:

Date	Temperature	Humidity
1/30/06	23.6°C	22%

Frequency range investigated:	30 MHz- 9.165 GHz

Measurement Distance:		
Frequency (MHz)	Distance (m)	Comments
AC conducted 0.15 – 30MHz	-	N/A
Fundamental 916.5MHz	3 m	Radiated
Spurious & harmonics 30 – 9165 MHz	3 m	Radiated

All readings are peak unless otherwise noted.

Statement of Conformity

The AG-007-NMFA has been found to conform with the following parts of the 47 CFR, RSS-GEN, and RSS-210 as detailed below:

RSS- GEN	RSS-210	47 CFR	Comments
5.3		Part # 15.15(b)	The product contains no user accessible controls that increase transmission power above allowable levels.
5.2		15.19	The label is shown in the label exhibit.
7.1.5		15.21	Information to the user is shown in the instruction manual exhibit.
		15.27	No special accessories are required for compliance.
		15.31(e)	A fresh battery was used for testing.
4.4.1			99% Occupied Bandwidth
7.1.4		15.203	The device uses an integrated internal antenna.
7.1.4		15.204	See attached documentation describing the antenna.
7.2.3	2.2 2.6	15.205 15.209	The fundamental is not in a restricted band and the spurious emissions in the restricted bands comply with the general emission limits of 15.209.
7.2.2		15.207	The EUT is battery powered with no capability of being connected to the AC mains.
	A2.9	15.249(a)	The EUT meets the field strength limit of 50mV/m (94dBµV/m) at the fundamental, and 500µV/m (54dBµV/m) at the harmonics.
7.2.3		15.249 (d)	Spurious emissions meet the general radiated emissions limits of section 15.209.
7.2.3		15.249 (e)	Spurious emissions found above 1GHz meet the limits of 15.209.

Modifications required for compliance:

No modifications were required.

EUT Configuration

EUT Configuration

Work Order: G0094

Company: Hyde Park Electronics
Company Address: 1875 Founders Drive

Dayton, OH 45420-4017

Contact: Dane Hanby

MN SN

EUT: AG-007-NMFA Test Sample 1 & 2

EUT Description: wireless proximity sensor

EUT Max Frequency: 916.5MHz

Support Equipment:MNSNMillennial Net gatewayGW-5209-1/2-ASMnot labeled

EUT Cables: Qty Shielded? Length Ferrites

none

Unpopulated EUT Ports: Qty Reason

none

Software / Operating Mode Description:

The EUT tested in RX, TX and Standby modes.

Curtis-Straus LLC • 527 Great Road • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

Spurious and Harmonic Radiated Emissions

FCC part 15.249(a), (d), (e) & RSS-210 sections 2.2 and 2.6


Spurious	s Radiate	ed Emis	ssions	Table					Curtis-St	raus LLC
Date:	Date: 30-Jan-06			Company:	Hyde Pa	rk Electron	١	Vork Order:	G0094	
Engineer:	Josh LeBland	;		EUT Desc:	AG-007-	NMFA				
	Freque	ncy Range:	30-9165M	Hz			Mea	surement Distance:	3 m	
Notes:	Black Horn, v RX, TX,and S		, emir-high	#2 used ab	ove 1GH	z		EUT Max Freq:	916.5MHz	
Antenna			Preamp	Antenna	Cable	Adjusted			FCC Class I	3
Polarization	Frequency	Reading	Factor	Factor	Factor	Reading		Limit	Margin	Result
(H / V)	(MHz)	(dBµV)	(dB)	(dB/m)	(dB)	(dBµV/m)		(dBµV/m)	(dB)	(Pass/Fail)
V	46.2	29.6	21.2	10.4	0.7	19.5		40.0	-20.5	Pass
V	114.2	33.4	21.2	13.0	1.2	26.4		43.5	-17.1	Pass
V	126.9	29.0	21.0	14.5	1.3	23.8		43.5	-19.7	Pass
V	148.55	32.3	20.9	13.0	1.4	25.8		43.5	-17.7	Pass
V	155.65	30.9	20.9	12.7	1.5	24.2		43.5	-19.3	Pass
V	245.1	29.9	21.1	12.3	1.9	23.0		46.0	-23.0	Pass
Table	e Result:	Pass	by	-17.1	dB			Worst Freq:	114.2	MHz
Test Site:	"F"	Pre-Amp:	Black	Cable:	EMIR-0		Analyzer: Green	Antenna:	Red-White	

Date:	30-Jan-06			Company:	Hyde Pa	ark Electroni			W	ork Order:	G0094	
Engineer:	Josh LeBland	• • •										
	Freque	ncy Range:	Harmonics	5					Measuremer	nt Distance:	3 m	
Notes:	Black Horn, V	Vhite pream	o, and EMIF	R-High #2 u	sed abov	re 2GHz.			EU	Γ Max Freq:	916.5MHz	
Antenna			Preamp	Antenna	Cable	Adjusted				F	CC Class I	3
Polarization	Frequency	Reading	Factor	Factor	Factor	Reading	Limit	Margin	Result	Limit	Margin	Result
(H / V)	(MHz)	(dBµV)	(dB)	(dB/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(Pass/Fail)	(dBµV/m)	(dB)	(Pass/Fai
		33.9	15.9	30.1	7.4	55.5				74.0	-18.5	Pass
Hpk	1833.0	33.9										
Hpk Havg	1833.0 1833.0	21.8	15.9	30.1	7.4	43.4				54.0	-10.6	Pass
•				30.1 31.0	7.4 2.5	43.4 48.7				54.0 74.0	-10.6 -25.3	Pass Pass
Havg	1833.0	21.8	15.9			-						
Havg Vpk Vavg	1833.0 2749.65	21.8 34.3	15.9 19.1	31.0	2.5 2.5	48.7				74.0	-25.3	Pass Pass

Sample Calculation:

Adjusted Reading = Reading - Pre Amp_(factor) + Antenna_(factor) + Cable_(factor)

Bandedge Plot



Limit line = Limit + Pre Amp_(factor) - Antenna_(factor) - Cable_(factor)


Conclusion: The EUT meets the limits at the band edges.

<u>Curtis-Straus</u> LLC • 527 Great Road • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

Occupied Bandwidth

RSS-GEN section 4.4.1

*** Agilent** 13:31:52 Jan 30, 2006



Occupied Bandwidth 665.0969 kHz

Осс ВW % Рыг 99.00 % ж dB -26.00 dB

Transmit Freq Error 47.965 kHz Occupied Bandwidth 938.996 kHz*

Fundamental Field Strength

FCC part 15.249(a) & RSS-210 section A2.9

Fundam	ental										Curtis-St	raus LLC
Date:	30-Jan-06		Company: Hyde Park Electronics Work Order: G00									G0094
Engineer:	Josh LeBland	:	EUT Desc: AG-007-NMFA									
	Frequency Range: 916.5MHz Measurement Distance: 3 m											
Notes:												
Antenna			Preamp	Antenna	Cable	Adjusted				F	CC Class I	В
Antenna Polarization	Frequency	Reading	Preamp Factor	Antenna Factor	Cable Factor	Adjusted Reading	Limit	 Margin	Result	Limit	CC Class I	B Result
	Frequency (MHz)	Reading (dBµV)					Limit (dBµV/m)		Result (Pass/Fail)			
Polarization			Factor	Factor	Factor	Reading		Margin		Limit	Margin	Result
Polarization (H / V) H	(MHz)	(dBµV)	Factor (dB)	Factor (dB/m)	Factor (dB) 4.5	Reading (dBµV/m)	(dBµV/m)	Margin (dB)	(Pass/Fail)	Limit (dBµV/m)	Margin (dB)	Result (Pass/Fail) Pass

Sample Calculation:

Adjusted Reading = Reading - Pre Amp_(factor) + Antenna_(factor) + Cable_(factor)

Test Equipment Used

							RE\	. 12-JAN	-2006	
SPECTRUM ANALYZEF RECEIVERS	RS/ RAI	NGE	MN	MFR	SN	I	ASSET	Сат	Γ	CALIBRATION DUE
GREEN	9kHz-2	26.5GHz 8593E		HP	3829A0	3618	00143	I		21-NOV-2006
OPEN AREA TEST S	F	CC CODE		IC CODE	VCC	CODE	Сат	(CALIBRATION DUE	
SITE F			93448		IC 2762-F	R-1	1688	II	C	4-APR-2007
PREAMPS / ATTENUATORS , FILTERS	/ RANGE	M	1N	MFR	SN	ASSET		Сат		CALIBRATION DUE
BLACK White	0.01-2000MHz 1-20GHz		000-LN C-12A	C-S C-S	N/A 426643	00799 00760		II II	-	25-AUG-2006 04-AUG-2006
ANTENNAS	RANGE	MN	M	¶FR	SN	ASSET	CA T	CA	LIBRA	ATION DUE
RED-WHITE BILOG BLACK HORN	30-2000MHz 1-18GHz	JB1 3115		JNOL //CO	A091604-1 9703-5148	01105 00056	II I	_		P-2006 N-2007
METEOROLOGICAL	METERS	M	N	ı	MFR	SN	Ass	ET (Сат	CALIBRATIO N DUE
TEMP./HUMIDITY/ATM. PRI	ESSURE GAUGE	7400 PER	CEPTION II	С	AVIS	N/A	009	65	II	08-FEB- 2007
TEMPERATURE /HUMIC	DITY GAUGE	THG	-912	Н	UGER	4000562	007	89	I	01-FEB- 2007
Weather Clock (Pres	SSURE ONLY)	BAS	928	OREGO	N SCIENTIFIC	C3166-1	008	31	I	02-FEB- 2007

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

FCC ID: TW6AG-007-NMFA REPORT: EG0094-1 IC: 6304A-AG007

Terms and Conditions

Paragraph 1. SERVICES. LABORATORY will:

Use the degree of care and skill ordinarily exercised by and consistent with the standards of the profession.

Perform all technical services in substantial accordance with the generally accepted laboratory principles and practices.

Retain all pertinent records relating to the services performed for a period of three (3) years following submission of the report describing such services, during which period the records will be made available to CLIENT upon reasonable request.

Paragraph 2. CLIENT'S RESPONSIBILITIES. CLIENT or his authorized representative will:

Provide LABORATORY with all plans, schematics, specifications, addenda, change orders, drawings and other information for the proper performance of technical services.

- Designate a person to act as CLIENT's representative with respect to LABORATORY's services to be performed on behalf of the CLIENT; such person or firm to have complete authority to transmit instructions, receive information and data, interpret and define CLIENT's policies and decisions with respect to the LABORATORY's work on behalf of the CLIENT and to order, at CLIENT's expense, such technical services as may be required.
- Designate a person who is authorized to receive copies of LABORATORY's reports.

Undertake the following:

- (a) Secure and deliver to LABORATORY, without cost to LABORATORY, preliminary representative samples of the
- equipment proposed to require technical services, together with any relevant data.
 (b) Furnish such labor and equipment needed by LABORATORY to handle samples at the LABORATORY and to facilitate the specified technical services.

Paragraph 3. GENERAL CONDITIONS:

LABORATORY, by the performance of services covered hereunder, does not in any way assume any of those duties or responsibilities customarily vested in the CLIENT, its employees, or any other party, agency or authority.

LABORATORY shall not be responsible for acts of omissions of any other party or parties involved in the design, manufacture or maintenance of the equipment or the failure of any employee, contractor or subcontractor to undertake any aspect of equipment's design, manufacture or maintenance.

LABORATORY is not authorized to revoke, alter, release, enlarge or release any requirement of the equipment's design, manufacture or maintenance unless specifically authorized by CLIENT or his authorized representative.

THE ONLY WARRANTY MADE BY LABORATORY IN CONNECTION WITH ITS SERVICE PERFORMED HEREUNDER IS THAT IT WILL USE THAT DEGREE OF CARE AND SKILL AS SET FORTH IN PARAGRAPH 1 ABOVE. NO OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE OR INTENDED FOR SERVICES PROVIDED HEREUNDER.

Where the LABORATORY indicates that additional testing is advisable to obtain more valid or useful data, and where such testing has not been authorized, CLIENT agrees to view such test reports as inconclusive and preliminary.

The LABORATORY will supply technical service and prepare a report based solely on the sample submitted to the LABORATORY by the CLIENT. The CLIENT understands that application of the data to other devices is highly speculative

and should be applied with extreme caution.

The LABORATORY agrees to exercise ordinary care in receiving, preserving and shipping (F.O.B. Littleton, MA) any sample to be tested, but assumes no responsibility for damages, either direct or consequential, which arise from loss, damage or destruction of the samples due to the act of examination, modification or testing, or technical services or circumstances beyond LÄBORATORY's control.

The LABORATORY will hold samples for thirty (50) days after tests are completed, or until the CLIENT's outstanding debts to the LABORATORY are satisfied, whichever is later.

The CLIENT recognizes that generally accepted error variances apply and agrees to consider such error variances in its use of test data.

3.10 It is agreed between LABORATORY and CLIENT that no distribution of any tests, reports or analysis other than that described below shall be made to any third party without the prior written consent of both parties unless such distribution is mandated by operation of law. It is agreed that tests, reports, or analysis results may be disclosed to third party auditors of the laboratory at the laboratory facility in the course of accreditation maintenance audits. No reference to reports or technical services of the LABORATORY shall be made in any advertising or promotional literature without the express written permission of the LABORATORY.

5.11 The CLIENT acknowledges that all employees of LABORATORY operate under employment contracts with the LABORATORY and CLIENT agrees not to solicit employment of such employees or to solicit information related to other clients from said employees.

3.12 In recognition of the relative risks and benefits of the project to both CLIENT and LABORATORY, the risks have been allocated such that the CLIENT agrees, to the fullest extent permitted by law, to limit the liability of the LABORATORY to the CLIENT for any and all claims, losses, costs, damages of any nature whatsoever or claims expenses from any cause or cause including attorneys' fees and costs and expert witness fees and costs, so that the total aggregate liability of the LABORATORY to the CLIENT shall not exceed \$100,000, or the LABORATORY'S total fee for services rendered on this project, whichever is greater. It is intended that this limitation apply to any and all liability or cause of action however alleged or arising, unless otherwise prohibited by law.

Paragraph 4. INSURANCE:

LABORATORY shall secure and maintain throughout the full period of the services provided to the CLIENT adequate insurance to protect it from claims under applicable Workmen's Compensation Acts and also shall maintain one million dollars of general liability coverage to cover claims for bodily injury, death or property damage as may arise from the performance of its services.

The CLIENT hereby warrants that it has sufficient insurance to protect its employees adequately under applicable Workmen's

Compensation Acts and for bodily injury, death, or property damage.

4.5 No insurance of whatever kind or type, which may be carried by either party is to be considered as in any way limiting any other party's responsibility for damages resulting from their operations or for furnishing work and materials.

Paragraph 5. PAYMENT:

- CLIENT shall pay to LABORATORY such fees for services as previously agreed, orally or in writing, within 30 days of presentment of a bill for such services performed. In the event CLIENT ordered, orally or in writing, services but such services were not assigned a rate for billing, such services shall be billed at the LABORATORY's reasonable and customary rate.
- CLIENT shall be responsible for all shipping, customs and other expenses related to services provided by LABORATORY to the CLIENT, and shall fully insure any test sample or other equipment provided to LABORATORY by the CLIENT.
- Amounts overdue from CLIENT to LABORATORY shall be charged interest at a rate of 11/2% per month.

Paragraph 6. ISO/IEC GUIDE 17025 ADDITIONS:

- CLIENT agrees that this test report will not be reproduced except in full, without written approval from the LABORATORY. CLIENT agrees that this test report shall not be used to claim product endorsement by A2LA or ANSI or any agency of the U.S. 6.2
- CLIENT agrees that test results presented herein relate only to the sample tested by the LABORATORY.

A2LA Accreditation

AZLA ACCI		Г	
SCOPE OF ACCI	REDITATION TO ISO/IEC 17025-1999	EN 55011 1991, 1998	Limits and methods of measurement of radio disturbance characteristics of industrial, scientific and medical (ISM) radio-
	CURTIS-STRAUS ¹ 527 Great Road	SABS CISPR 11:1997	frequency equipment. Industrial, scientific and medical (ISM) radio-frequency equipment – Electromagnetic disturbance characteristics Limits and methods of
Barry Or	Littleton, MA 01460 uinlan Phone: 978-486-8880	Canada ICES-001 1998	measurement Industrial, scientific and medical radio frequency generators
2) Q		CNS13803	Industrial, Scientific and Medical Instrument
Valid until: February 28, 2006	ELECTRICAL Certificate Number: 1627.01	AS/NZS 2064: 1997	Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio- frequency equipment.
In recognition of the successful completion of	f the A2LA evaluation process, accreditation is granted to this	CSA C108.8 – M1983	Electromagnetic Emission from Data Processing Equipment and Electronic Office Machines
Safety tests:	agnetic Compatibility (EMC), Telecommunications, and Product	CISPR 13:1996, 1998, 2001	Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment.
Electrostatic Discharge testing; Electrical Fast Immunity testing; Lightning Immunity testing	netic fields); Conducted emissions testing (voltage and current); t Transient testing; Radiated Immunity testing; Conducted g; Voltage Dips, Interrupts and Voltage Variations testing; Magnetic "requency Edulity measurements; Longitudinal Induction	EN 55013: 1990, 2001 EN 55013 Amend 12 1994	Sound and television broadcast receivers and associated equipment: Electromagnetic compatibility. Part 1: Specification for limits and methods of measurement of radio disturbance characteristics of broadcast receivers and associated equipment. Limits and methods of measurement of radio disturbance
	cight flicker testing; Low frequency disturbance voltage testing;		characteristics of broadcast receivers and associated equipment. Amendment 12
EMC Standards	Title	SABS CISPR 13: 1996	Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment.
Emissions CISPR 22 1997 with amendments 1 and 2	Limits and methods of measurement of radio disturbance	CNS 13439 AS/NZS 1053: 1999	Broadcast receiver and associated equipment Limits and methods of measurement of radio interference characteristics of sound and
	characteristics of information technology equipment.		television broadcast receivers and associated equipment.
CNS13438 1994 EN55022:1994 and 1998	Limits and methods of measurement of radio interference characteristics of information technology equipment. Limits and methods of measurement of radio disturbance	CISPR 14 1993 (except discontinuous disturbances)	Limits and methods of measurement of radio disturbance characteristics of electrical motor- operated and thermal appliances for household and similar purposes, electric tools and electric apparatus.
SABS CISPR 22:1997	characteristics of information technology equipment. Information technology equipment – Radio disturbance	EN 55014 1993, 1997 discontinuous disturbances)	Limits and methods of measurement of radio disturbance (except characteristics of electrical motor- operated and thermal appliances for
Canada ICES-003 1997	characteristics – Limits and methods of measurement Digital apparatus	and the same of th	household and similar purposes, electric tools and similar electric apparatus.
AS/NZS 3548 1995	Australian/New Zealand Standard Limits and methods of measurement of radio disturbance characteristics of information technology equipment	AS/NZS 1044: 1995 discontinuous disturbances)	apparatus. Limits and methods of measurement of radio disturbance (except characteristics of electrical motor- operated and thermal appliances for household and similar purposes, electric tools and similar electric
CISPR 11 1990, 1997, 1999	Limits and methods of measurement of electromagnetic		apparatus.
	disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment.	Immunity	
		CNS13783-1 SABS CISPR 14-1 1993	Household Electrical Appliances Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 1: Emission –
¹ Note: This accreditation covers testing perfolocated at 168 Ayer Rd, Littleton, MA 01460	rmed at the laboratory listed above and the satellite facility	SABS CISPR 14-2 1997 + A1:2001	Product family standard Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 2: Immunity - Product family standard
(A2LA Cert. No. 1627-01) 1/31/06	Page 1 of 11	(A2LA Cert. No. 1627-01) 1/31/06	Page 2 of 11
CISPR 14-2 1996, 1997 + A1:2001	Immunity requirements for household appliances, tools and	EN 61000-6-1: 1997, 2001	Electromagnetic Compatibility (EMC)- Part 6: Generic standards-
CISPR 20: 1995, 2002 with amendment 3 characteristics (associated group only)	similar apparatus. Limits and methods of measurement of immunity of sound and television broadcast receivers and associated	EN 61000-6-2: 1998, 2001	Section 1: Immunity for residential, commercial and light-industrial environments Electromagnetic Compatibility (EMC)- Part 6: Generic standards-
EN 55020: 1995, 2002	equipment. Electromagnetic immunity of broadcast receivers and	EN 50091-2 1996	Section 2: Immunity for industrial environments Specification for Uninterruptible Power Systems (UPS). Part 2: EMC
(associated group only) CISPR 24	Associated equipment. Information technology equipment – Immunity characteristics –	EN 55024 1998	requirements Information technology equipment – Immunity Characteristics –
SABS CISPR 24 1997	Limits and methods of measurement Information technology equipment – Immunity characteristics –	Limits EN 55103-1 1997	and methods of measurement. Electromagnetic Compatibility – Product family standard for audio,
AS/NZS 3200.1.2: 1995	Limits and methods of measurement Approval and test specification – Medical electrical Equipment – General requirements for safety – Collateral Standard:	EN 55103-2 1997	video, audio-visual and entertainment lighting control apparatus for professional use. Part 1: Emission Electromagnetic Compatibility – Product family standard for audio,
	Electromagnetic compatibility – Requirements and tests.	(excluding Annex A3)	ricetroniagnetic Companionity – Froduct fainify standard for addito- video, audio-visual and entertainment lighting control professional use. Part 2: Immunity
European Union Basic EMC Standards EN 61000-4-2: 1995, 1999, 2001	Electromagnetic compatibility (EMC). Part 4: Testing and	EN 61326 1998	Electrical equipment for measurement, control and laboratory use – EMC requirements
	measurement techniques. Section 2: Electrostatic discharge immunity test – Basic EMC Publication	EN 61547 1996	Equipment for general lighting purposes – EMC immunity requirements
EN 61000-4-3:1997, 1998, 2002 AS/NZS 61000.4.3 1999	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 3: Radiated, radio-frequency, electromagnetic field immunity test	EN 50130-4 1996	Alarm Systems. Part 4: Electromagnetic compatibility. Product family standard: Immunity requirements for components of fire, intruder and social alarm systems.
EN 61000-4-4 1995	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 4: Electrical fast	EN 55104 1995	Electromagnetic compatibility immunity – requirements for household appliances, tools and similar apparatus. Product family standard.
EN 61000-4-5 1995	transient/burst immunity test – Basic EMC publication (EMC) Part 4: Testing and measurement techniques. Section 5:	EN 50083-2 1995	Cabled distribution systems for television and sound signals. Part 2: Electromagnetic compatibility for equipment.
AS/NZS 61000.4.5 1999 EN 61000-4-6 1996	Surge immunity test. Electromagnetic compatibility (EMC). Part 4: Testing	EN 60601-1-2: 1993, 2002	Medical electrical equipment Part 1: general requirements for safety Section 2: Collateral standard: Electromagnetic compatibility –
AS/NZS 61000.4.6 1999	and measurement techniques. Section 6: Immunity to conducted disturbances, induce by radio-frequency fields.	IEC 1800-3 1995	requirements and tests Adjustable speed electrical power drive systems. Part 3: EMC product
EN 61000-4-8 1994	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 8: Power frequency magnetic field impunity test	EN 60555 Part 2 1987	standard including specific test methods. Disturbances in supply systems caused by household appliances and similar electrical equipment. Part 2: Harmonics.
EN 61000-4-11 1994 11:	field immunity test. (EMC) Part 4: Testing and measurement techniques. Section Voltage dips, short interruptions and voltage Variations	EN 60555 Part 3 1987	similar electrical equipment. Part 2: Harmonics Disturbances in supply systems caused by household appliances and similar electrical equipment. Part 3: Voltage fluctuations.
ENV 61000-2-2 1993	immunity tests. Electromagnetic compatibility (EMC). Part 2: Environment, Section 2: Compatibility levels for low-frequency conducted disturbances and signaling in public low-voltage power supply	EN 61000-3-2: 1995, 2000 Limits AS/NZS 61000.3.2 1998 EN 61000-3-3 1995 AS/NZS 61000.3.3 1999	Electromagnetic compatibility (EMC). Part 3: Limits Section 2: for harmonic current emissions Electromagnetic compatibility (EMC). Part 3: Limits Section 2: Limitation of voltage fluctuations and flicker in low-voltage supply
EU Product Family Standards	systems (IEC 1000-2-2:1990) Electromagnetic capability – Generic emission standard. Part 1:	ETS 300 386-1 1994	systems. Equipment Engineering (EE); Public telecommunication network equipment electro-magnetic compatibility (EMC) requirements Part 1: Product family overview, compliance criteria and test levels
EN 50081-1 1992	Residential, commercial and light industry. (I.S.)		riounci iamily overview, compilance criteria and test levels
EN 50081-2 1993 Part	Electromagnetic compatibility – Generic emission standard. 2: Industrial environment		
EN 50082-1 1992, 1998 Part EN 50082-2 1995	Electromagnetic compatibility – Generic emission standard. 1: Residential, commercial and light industry Electromagnetic compatibility – Generic immunity Standard. Part 2: Industrial environment		
(A2LA Cert. No. 1627-01) 1/31/06	Page 3 of 11	(A2LA Cert. No. 1627-01) 1/31/06	Page 4 of 11

EETS 200 330 v1.2.1: 1998, 1999 Electromagnetic compatibility and Radio spectrum matters (EEM); Electromagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment (ETS) Electromagnetic compatibility and Radio spectrum matters (EEM); Short range devices (SRD); Technical characteristics and test methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 to 30 MHz Radio Equipment and Systems (RES); Wideband transmission Radio Equipment and Systems (RES); Wideband systems; Technical characteristics and test conditions for data transmission equipment operating in the 2,4 GHz ISM band using spread spectrum modulation techniques Electromagnetic compatibility and Radio spectrum matters (EEM); Short range devices; Technical characteristics and methods for radio equipment to be used in the 1 Ghz to 40 frequency range ETS 300 836-1:1998 Broadband Radio Access Networks (BRAN); 5 GHz (draft) high performance RLAN; Harmonized EN covering Essential requirements of article 3.2 of the R&TTE Directive 47 CFR FCC low operating on frequency range 47 CFR FCC low operating on frequen	
ETS EN 300 386 2000 v1 2.1, 2001 v1.3.1 ETS S00 132-1 1996 ETS 300 132-1 1996 Equipment Engineering (EE), rower supply interface at the input to telecommunications equipment, Part 2. Operated by alternating current (as) devired from direct current (a) Expiration for direct current (a) Expiration from direct current (b) Expiration from direct (b) Expiration from direct (b) Expiration from direct (b) Expiration from direct (b) Expi	01 Electromagnetic compatibility and Radio spectrum Matters (ERM);
ETS 300 132-1 1996 ETS 300 132-1 1996 ETTS 300 132-2 1996 Equipment Engineering (EE), Power supply interface at the direct current (School and Control and Control and Control and Control (EE), Power supply interface at the direct current (School and Control and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Control (EE), Power supply interface at the direct current (School and Contro	Wideband Transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using spread spectrum
ETS 300 132-1 1996 Equipment Engineering (EE): Power supply interface at the injunt to nebecommunications equipment. Part 1: Operated by sharmating current (e.) derived from direct current (e.) ETS 300 132-2 1996 ETR 285 1997 A strainformer (EE): Power supply interface at the injunt to nebecommunications equipment. Part 2: Operated by direct current (EC): Power of the injunction of the i	modulation techniques; Part 2: Harmonized EN covering essential
alemaning current (a) derived from direct current (dc) ETTS 200 332-21996 Equipment Engineering (EE): Proves upply interface at the direct current (dc) Equipment Engineering (EE): Proves upply interface at the direct current (dc) ETTR 283 1997 Equipment Engineering (EE): Proves upply interface at the direct current (dc) ETTR 283 1997 Equipment Engineering (EE): Proves upply interface at the direct current (dc) ETTR 283 1997 Equipment Engineering (EE): Transient voltages at Interface on telecommunications direct current (DC) power ETTR 283 1997 ELECTROMAGEN (EE): Transient voltages at Interface on telecommunications direct current (DC) power ELECTROMAGEN (EE): Transient voltages at Interface on telecommunications (EEM): Short Current (EEM): Short Engineering (EEM): Electromagnetic compatibility (EMO) standard for fixed and in light and test methods for ratio equipment (ETS) manufacts (EEM): Short Engineering (EEM): Short	requirements under article 3.2 of the R&TTE Directive 102 Electromagnetic compatibility and Radio spectrum Matters (ERM);
EFE 283 1997 A distributions. EV role annual residence in the large to telecommunications equipment. Part 2 Operated by distributions. EV role annual residence in the large to telecommunications of the large transmission on telecommunications direct current (DC) power on telecommunications. EV role annual residence in the large transmission of the large transmission of the large transmission. EV role annual residence in the large devices. (ERM): Electromagnetic compatibility and Radio spectrum muters. (ERM): Electromagnetic compatibility of Radio spectrum muters. (ERM): Electromagnetic compatibility and electrical safety—electromagnetic residence of radio noise emissions from industrial, sequence	Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
imput to telecommunications equipment; Pan 2: Operated by direct current (cb) Equipment Engineering (EE): Transient voltages at Interface to relecommunications direct current (OC) power (Canadian RL-16 (Can	O2 Switches for household and similar fixed electrical installations Part
ERY 281 1997 distributions. Electromagnetic compatibility and Radio spectrum matters (EM). Electromagnetic solution for data spiness in the frequency range 9 to 30 MHz. ETS 300 328 1996 transmission ETS EN 300 440 v1.2.1 1999 Electromagnetic compatibility and Radio spectrum matters (EM). Sino trange devices: Technical characteristics and nethods for radio equipment to be used in the 1 Ghz to 40 the	2-1: Particular requirements – Electronic switches
and internations. EU ratio standards (ETS) EN 300 858 v1.21: 1998, 1999 (Electromagnetic compatibility and Radio spectrum matters (EBM). Electromagnetic compatibility and Radio spectrum matters (EBM). Soft ratio equipment in the range 9 k1 k1 to 25 to 30 MHz. ETS 300 328 1996 ETS EN 300 328 1996 ETS EN 300 440 v1.2.1 1999 ETS EN 300 893-2002 v1.2.1 Broadband Radio Acces Networks (BAN); 5 GHz (draft) high performance to be used in the 15th to 40 frequency range EN 301 893-2002 v1.2.1 Broadband Radio Acces Networks (BAN); 5 GHz (draft) high performance (BAM). Soft range devices. Technical characteristics and methods for radio equipment and services (BAN). The service of the RAFTE (BAN) and the services (BAN). Electromagnetic compatibility and Radio Acces Networks (BAN); 5 GHz (draft) high performance (BAN). Electromagnetic compatibility and Radio Acces Networks (BAN); 5 GHz (draft) high performance (BAN). Soft range devices. Technical characteristics and methods for radio equipment and services; Pan 17: Specific conditions for 24 GHz wideband transmission systems and 5 GHz high performance (BAN). Soft Radio Type approval and Radio Frequency (RF) conformance test specification and Radio Perspective material and soft and	
EU radio standards (ETS) EN 300 385 v1.2.1: 1998, 1999 Electromagnetic compatibility and Radio spectrum matters (ERM), Electromagnetic Compatibility (EMC) standard for Electromagnetic compatibility and Radio spectrum matters (ERM), Electromagnetic compa	2400 – 2483.5 MHz band.
EERTOMAGENCE (EMM). Electromagenic compatibility and Radio spectrum matters (EMM). Electromagenic compatibility (EMC) standard for fixed radio links and ancillary equipment (ETS) Electromagenic compatibility and Radio spectrum matters (EMM). Solar and lext methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop systems in the frequency range 5 to 30 MHz. ETS 300 328 1996 transmission ETS EN 300 440 v1 2.1 1999 Electromagenic compatibility and Radio spectrum matters (EMM). Solar range device reclaims of the conditions for data transmission equipment of the submitted in the 1 Ghz to 40 file. Electromagenic compatibility and Radio spectrum matters (EMM). Solar range devices reclaims a specific device of frequency range and spectrum standard (EMM). Solar range devices reclaims of the 1 Ghz to 40 file. Electromagenic compatibility and Radio spectrum matters (EMM). Solar range devices range (EMM) and the 1 Ghz to 40 file. Electromagenic compatibility and Radio spectrum matters (EMM). Solar range devices range and spectrum standard (EMM) and the 1 Ghz to 40 file. Electromagenic compatibility and Radio spectrum matters (EMM). Solar range for range and spectrum standard requipment and services the specification for the 1 Ghz to 40 Ghz. Electromagenic compatibility and Radio spectrum matters of radio noise emissions from industrial, and medical equipment. Electromagenic compatibility and spectrum spectrum recommendations for 24 GHz wideband transmission systems and 5 GHz high performance RLAN equipment and services the spectrum compatibility and spectrum matters and spectrum recommendations for the 1 Ghz to 40 GHz. Andrea Annual spectrum recompatibility and electrical and equipment in the range of black to 40 GHz. Annual spectrum recompatibility and spectrum recompatibility and spectrum recompatibility and spec	receivers, 27.41 to 960.0 MHz
Fixed radio links and ancillary equipment (ETS)	34 1996 & 2000, Issue 1 Industry Canada – 900 MHz narrowband personal communications services
Electromagnetic compatibility and Radio spectrum matters (RRM); Short range devices (SRD); Technical characteristics and test methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop yeasens in the frequency range 9 kHz to 25 MHz and inductive loop yeasens in the requester, range 9 kHz to 25 MHz and inductive loop yeasens in the requester, range 9 kHz to 25 MHz and inductive loop yeasens in the requester, range 9 kHz to 25 MHz and inductive loop yeasens in the requester, range 9 kHz to 25 MHz and inductive loop yeasens in the requester radios and saystems. Technical characteristics and test conditions for data vansing spread spectrum motaters (GRM); Short range devices, Technical characteristics and test conditions for data vansing spread spectrum motaters (GRM); Short range devices, Technical characteristics and test conditions for fine percept yrange. Electromagnetic compatibility and Radio spectrum matters (GRM); Short range devices, Technical characteristics and test conditions for fine percept yrange. The performance of the performance test specification of produce performance performance test specification of produce performance performance performance performance performance pe	10 2000 Issue 3, Industry Canada – Low power license-exempt radio 2001 Issue 5 communication devices
and test methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop yearsm in the frequery range 9 to 30 MHz Radio Equipment and Systems (RES); Widebaud radional experiments of the systems of the recompanion of the systems of the recompanion of the systems (RES); Widebaud ETS EN 300 440 v1.2.1 1999 Electromagnetic compatibility and Radio spectrum matters (FRM); Short range devices; Technical characteristics and methods for radio equipment to be used in the 1 Clin to 40 frequency range EN 91 893-2002 EN 91893-2002 BY 12.1 BY 1980 ETS 300 836-1:1998 ETS 300 836-	Specification for Restricted Radiation Radio Apparatus (New Zealand)
ETS 300 328 1996 transmission Radio Equipment and Systems (RES); Wideband systems (RES) and transmission equipment operating in the 2.4 GHE ISM band transmission equipment operating in the 2.4 GHE ISM band using spread spectrum modulation techniques Electromagnetic compability and Radio Spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and sing spread spectrum modulation techniques Electromagnetic compability and Radio Spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum matters (ERA); Short range devices, Technical characteristics, and spectrum range devices, Technical characteristics, and spectrum range devices, Technical spectrum range devices, Technical characteristics, Technical spectrum range (
systems. Technical characteristics and test conditions for data transmission equipment operating in the 24 GHz ISM band using spread spectrum modulation techniques Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and methods for radio equipment to be used in the 1 Ghz to 40 frequency range in the 1 Shadio Local Area Network (HIPERLAN) Type 1; 2 from power transmission on the 1 Shadio Local Area Network (HIPERLAN) Type 1; 2 from power from ance 2 from power range in the 1 Ghz to 40 frequency (RP); conformance test specification in specifications represent the 1 from power transmission on the 1 from the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency (RP); conformance test specification of the 1 Ghz to 40 frequency	power transmitters Scope A1 uencies below 1 GHz,
transmission equipment operating in the 2.4 GHL ISM band using spread spectrum modulation techniques ellectromagnetic compatibility and Radio spectrum matters (BRN); Short range devices; Technical characteristics and methods for radio equipment to be used in the 1 Ghz to 40 frequency range and methods for radio equipment to be used in the 1 Ghz to 40 frequency range and methods for radio equipment to be used in the 1 Ghz to 40 frequency range and methods for radio equipment of the solid property of the pr	systems, unintentional 1 devices.
ETS EN 300 440 v1.2.1 1999 Electromagnetic compatibility and Radio spectrum matters (ERM): Short range devices; Technical characteristics and methods for radio equipment to be used in the 1 Ghz to 40 frequency range EN 301 893:2002 With the exception of frequency range EN 301 893:2002 ETS 300 836-1:1998 ETS 300 836-1:1998 Performance Conformance Conformance Radio Local Aran Network (HIPERLAN) Type 1: testing specification: Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification or Part 1: Radio Type approval testing testing approval testing testing approval testing testing approval testing testing and testing t	power transmitters Scope A2
methods for radio equipment to be used in the 1 Ghz to 40 frequency range EN 301 893:2002 EN 301 893:2003 EN 3	n of spread spectrum
FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment in the range of 9 Hz to 4 GOHz. 1 January 2003 ANSI EMC Standards ANSI C63.1 1998, 1999, 2001, 2003 American National Standard for faction on the ministrial and equipment in the range of 9 Hz to 4 GOHz. 1 January 2003 ANSI C63.1 1998, 1999, 2001, 2003 American National Standard for fower circuits of the faction of ministrial and equipment in the range of 9 Hz to 4 GOHz. 1 January 2003 ANSI C63.1 1992, 1999, 2001, 2003 American National Standard for feetcomagnetic material equipment in the range of 9 Hz to 4 GOHz. 1 January 2003 ANSI C63.1 1992, 1999, 2001, 2003 American National Standard for feetcomagnetic material equipment in the range of 9 Hz to 4 GOHz. 2 AS/ACIF S016-2 AS/ACIF S016-2 AS/ACIF S018-2 South African EMC standards BEEE ECS Lit. 1980, 1991 BEEE C62.41: 1980, 1991 BEEE	licensed Personal Scope A3
high performance RLAN; Harmonized EN covering Essential requirements of article 3.2 of the RetTE Directive Broadband Radio Access Networks (BRAN); High Radio Local Area Network (HIPELA) Type 1; testing specification; Part 1: Radio Type approval and Radio Frequency (RF) conformance testing; Specification, Part 1: Radio Type approval and Radio Frequency (RF) conformance testing; Specification and Services; Part 17: Specific conditions for 2.4 dFR; Electromagnetic Compatibility and Radio spectrum Matters (FRM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for 2.4 dFR; EMC Standards (FRM); Electromagnetic Compatibility and Radio Services in Rule Parts 2.2, 24 dFR PCC Mrs. Scope Radio-Services and medical equipment and services; Part 17: Specific conditions for 3.4 dFR PCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods of measurement of radio-noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods of measurement of radio-noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods of measurement of radio-noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods of measurement of radio-noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods of measurement of radio-noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods	System (PCS) devices licensed National Scope A4
ETS 300 83-61:1998 Performance Conformance Radio Local Area Network (HIPELA) Type 1: testing specification; Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for 2.4 d FIR wideband transmission systems and 5 GHz high performance RLAN equipment FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (ST MP-5 1986 FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Standards ANSI EMC Standards ANSI EMC Standards ANSI EMC Standards ANSI EMC Standards ANSI C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 Hz to 40GHz. American National Standard for electromagnetic interference (EMI) control – calibration of antennas. IEEE ECC Standards IEEE CG2.4: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 Selectromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. Swedish EMC Standards BAKOM 3336.3 1995 Selectromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization for Gaming equipment. Part 1: Casino equipment. Impanese VCCI Standards SAS (17: S03.2- AS/ACIF	structure devices and
Radio Local Area Network (HIPERLAN) Type 1:	ues.
Frequency (RF) conformance test specification Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic compatibility (EMC) standard for 2.4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment FCC (Federal Communications Sommission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. ANSI EMC Standards ANSI C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. Ansi C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electromagnetic radiated emissions measurements in electromagnetic radiated emissions measurements of electromagnetic radiated emissions for low-voltage electrical and equipment. EEEE EMC Standards FECE C42.4: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. FULT G.703 AS/ACIF S03-2- AS/ACIF S03-2- AS/ACIF S03-2- AS/ACIF S03-2- AS/ACIF S0	sonal mobile Scope B1
(AZLA Cert. No. 1627-01) 1/31/06 FCC (Federal Communications Scope Services: and a services; Part 17. Specific conditions for 2,4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment FCCOST MP-5 1986 FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. ANSI EMC Standards RESE CS 24: 1997, 1999 issue 2/ Generic criteria for network telecommunications equipment. ANSI CS 34: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions from industrial, and medical equipment in terrange for 9 kHz to 40 GHz. American National Standard for rethods of measurement of radio-noise emissions for low-voltage electrical and equipment in terrange for 9 kHz to 40 GHz. American National Standard for electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE CS 24: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards IEEE CS 24: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. AS/ACIF S013-2 AS/ACIF S013-2 AS/ACIF S013-2 AS/ACIF S013-2 Telecommunications Tille Tille Tille Tille Til	, 25, 27.
2,4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment 47 CFR FCC Marco 80 and 87 47 CFR FCC Marco 90 and 97 40 and 97	the following FCC
Read of Communications Registration; Read	ritime and Aviation B3
47 CFR PCC Mic Scope in 47 CFR	ices in 47 CFR Parts
FCC/OST MP-5 1986 FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. Bellcore electromagnetic compatibility and electrical safety—Generic criteria for network telecommunications equipment. ANSI CG3.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI CG3.5: 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE CG2.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African EMC standards SABS 1718-1: 1996 Telecommunications Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing: Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. TELECOM Telecommunications Title Tit	crowave Radio Services B4 Parts 21, 74 and 101.
FCC/OST MP-5 1986	1627-01) 1/31/06 Page 6 of 11
FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, and medical equipment. Bellcore electromagnetic compatibility and electrical safety—Generic criteria for network telecommunications equipment. ANSI C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.5 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards IEEC C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards South African EMC standards other than CISPR equivalents South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99,05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test TU-T G.703 HKTA 2029 TElecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. TELecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. TBR 1: 1995 TELecommunications Title TCC 47 CFR Part 68 Telephone	1027-01) 1/31/00 Fage 0 01 11
measurement of radio noise emissions from industrial, and medical equipment. GR-1089-CORE: 1997, 1999 issue 2/ 2002 Issue 3 Generic criteria for network telecommunications equipment. ANSI C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.4: 1982, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.5: 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic canada VDSL IEEE EMC Standards IEEE C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards Swedish EMC Standards South African EMC standards other than CISPR equivalents South African EMC standards other than CISPR equivalents South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements ITU-T G.703 HKTA 2028 HKTA 2029 Telecommunications Telecommunications Registration; General test methods; Lightning surge: Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecommunications Telecommunications Telecommunications Title Telecomentications Title	
measurement of radio noise emissions from industrial, and medical equipment. GR-1089-CORE: 1997, 1999 issue 2/ Bellcore electromagnetic compatibility and electrical safety— Generic criteria for network telecommunications equipment. ANSI C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.5: 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE EMC Standards IEEE EMC Standards IEEE EAC Standards BAKOM 3336.3: 1995 Seedish EMC Standards South African EMC standards other than CISPR equivalents South African EMC standards other than CISPR equivalents South African EMC standards VCCI V-3/99.05: 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Telecommunications Telecommunications Registration: General test methods; Lightning surge: Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecommunications Telecommunications Telecom Standards Title	
GR-1089-CORE: 1997, 1999 issue 2/ 2002 Issue 3 Generic criteria for network telecommunications equipment. ANSI EGAS 4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.5 1988 American National Standard for nethods of measurement of radio-noise emissions for low-voltage electronal and equipment in the range of 9 kHz to 40GHz. ANSI C63.5 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic canada VDSL IEEE EMC Standards IEEE EAC Standards BAKOM 3336.3 1995 Seedish EMC Standards South African EMC Standards other than CISPR equivalents South African EMC standards other than CISPR equivalents South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecommunications Telecommunications Telecommunications Title Tit	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone
ANSI EMC Standards ANSI CS3.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. AMSI CS3.5 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 Electromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-399,05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Telecom Standards Title Telecomounications Telecomounications Telecomounications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. TBR 2: 1997 Telecom Standards Title Telecomounications Registration; Connection of terminal equipment to the telephone Terminal Equipment TCB	Network Telecommunications Telephone Terminal Equipment Supplemental
ANSI C63.4: 1992, 1999, 2001, 2003 American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.5 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 Electromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. TBR 2: 1997 TBR 2: 1997 TBR 2: 1997	Technical Requirements for Connection of Stutter Dial Tone Detection
electronic radio-noise emissions for low-voltage electrical and equipment in the range of 9 kHz to 40GHz. ANSI C63.5 1988 American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE ECG 2.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 Electromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements PCCI V-4/99.05 1999 Technical Requirements Telecommunications Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Telecom Standards Title TBR 2: 1997 TBR 2: 1997	Devices and ADSL Modems to the Telephone Network Telecommunications Telephone Terminal Equipment Technical
electronic equipment in the range of 9 kHz to 40GHz. American National Standard for electromagnetic radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 Electromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3.99.05 1999 Technical Requirements NCCI V-4.99.05 1999 Technical Requirements Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Telecom Standards Title Tonnection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Requirements for Connection of Terminal Equipment to the Telephone Network
compatibility — radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas. IEEE EMC Standards IEEE C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 Electromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3:99.05 1999 Technical Requirements VCCI V-4:99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TBR 2: 1997 TBR 2: 1997 TBR 2: 1997	Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone
1 January 2003	Network Industry
IEEE C62.41: 1980, 1991 IEEE recommended practice on surge voltages in low-voltage AC power circuits AS/ACIF S002-2 AS/ACIF S016-2 AS/ACIF S016-2 AS/ACIF S016-2 AS/ACIF S016-2 AS/ACIF S018-2 AS/ACIF	Terminal Attachment Program Requirements and Test Methods for Issue Very-High-Bit-Rate Digital Subscriber Line (VDSL) Terminal
AC power circuits Swedish EMC Standards BAKOM 3336.3 1995 BOUTH African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japaneses VCCI Standards VCCI V-3.99.05 1999 Technical Requirements NCCI V-4.99.05 1999 Telecommunications Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TBR 2: 1997 TBR 2: 1997 TBR 2: 1997	Equipment O01 Analogue interworking and non-interference requirements for
BAKOM 3336.3 1995 Electromagnetic compatibility and electrical safety (EMC & for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test HKTA 2028 HKTA 2029 Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Tonnection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Customer Equipment for connection to the Public Switched Telephone Network
S) for wired terminal equipment. Harmonization document information over the OFCOM requirements. South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Telecom Standards Title Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	001 Requirements for Customer Equipment for connection to hierarchical
South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99,05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TBR 2: 1997 TBR 2: 1997	
South African EMC standards other than CISPR equivalents SABS 1718-1: 1996 South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test HKTA 2028 HCTA 2029 Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TER 2: 1997 TBR 2: 1997 TBR 2: 1997	
equipment. Part 1: Casino equipment. Japanese VCCI Standards VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test HKTA 2028 HKTA 2029 Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TER 2: 1997 TBR 2: 1997	Local Loop Interface of a Telecommunications Network — Part 1: General
VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test HKTA 2028 HKTA 2029 Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Part 2: Broadband
VCCI V-3/99.05 1999 Technical Requirements Instruction for Test Conditions for Requirement under Test HKTA 2028 HKTA 2029 Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Part 3: DC, Low Frequency AC and Voiceband Physical/electrical characteristics of hierarchical Digital interfaces
Telecommunications Telecommunications (General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Haaring Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 1544 kbit/s
Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Network connection specification for connection of CPE to the PTNs in
power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TBR 2: 1997 FCC 47 CFR Part 68 Telephone Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	Hong Kong using digital leased circuits at data rate of 2048 kbit/s Attachment requirements for terminal equipment to be connected to
testing; Hearing Aid Compatibility testing (excluding volume control); Protocol analysis and Jitter testing. Telecom Standards Title TBR 2 : 1997 FCC 47 CFR Part 68 Telephone Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	circuit switched data networks and leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically,
FCC 47 CFR Part 68 Telephone Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signaling rate up to, and including,
FCC 47 CFR Part 68 Telephone Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB	1 984 kbit/s Attachment requirements for Data Terminal Equipment (DTE) to
	connect to Packet Switched Public Data Networks (PSPDNs) for CCITT
	Recommendation X.25 interfaces at data signaling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations
C1. CS-03 Issue 8 1996 through amendment 5 Specification for terminal equipment, terminal systems,	X.21 and X.21 bit
Network protection devices, connection arrangements and hearing aids compatibility.	
TIA/EIA TSB31-B 1998 Bulletin Part 68 Rationale and Measurement Guidelines (Feb	
	1627-01) 1/31/06 Page 8 of 11
(A2LA Cert. No. 1627-01) 1/31/06 Page 7 of 11	

Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN IEC 60950 2000 EN 60950 1997, 1998, 2000 IEC 60950-1 2001 TBR 3: 1995 + Amdt: 1997 Safety of information technology equipment Safety of information technology equipment, including using ISDN basic access Electrical business equipment. TBR 4: 1995 + Amdt: 1997 Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access UL 60950-1 2003 CSA C22.2 No. 60950-00 CSA C22.2 No. 60950-1 03 AS/NZS 3260 1993 TBR 012: 1993 + Amdt: 1996 Business Telecommunications (BT); Open Network Provision Approval and test specification - Safety of information technology Approval and test specification – Safety of information technology equipment including electrical business Equipment. Approval and test specification – Safety of information technology equipment including electrical business equipment – Alphabetical reference index to IEC 950 (Supplement to ASIVES 3260:1993) Australian Communications Authority – Safety requirements for (ONP) technical requirements: 2 048 kbit/s digital unstructured leased line (D2048U) Attachment requirements for terminal AS/NZS 3260 Supp 1 1996 equipment
Business TeleCommunications (BTC); 2 048 kbit/s digital
structured leased lines (D2048S); Attachment requirements for TBR 013: 1996 ACA TS 001 1997 structure reiseu into It/2004-85), Atlactiment requirements for terminal equipment interface. Terminal Equipment (TE), Attachment requirements for pan-European approval for connection to the analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Australiar Colliminations Authority – Safety requirements for customer equipment. Telephone Equipment Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements. Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements. TBR 21: 1998 UL 1459 1995 IEC 1010-1 1990 IEC 61010-1 1993 EN 61010-1 1993, 2001 IEC 61010-1 2001 Frequency (DTMF) signaling Business TeleCommunications (BTC); 34 Mbit/s digital UL 61010B-1 2003 TBR 24: 1997 UL 3101-1 1993 Electrical equipment for laboratory use Part 1: General requirements. UL 3121-1 1995

UL 3121-1 1995

UL 3195

UL 3195

UL 3195

UL 3195 Unstructured and structured leased lines (D34U and D34S); Attachment requirements for terminal equipment interface Electrical measuring and test equipment. Part 1: General requirements Medical electrical equipment. Part 1: General requirements for safety. Medical electrical equipment. Fart 1: General requirements of saccy. Medical electrical equipment Medical electrical equipment Medical electrical equipment Part 1: General Requirements for safety. Audio/video and similar electronic apparatus – Safety requirements Audio/video and musical instrument apparatus for Household, commercial and similar general use Australian/New Zealand Standard – Approval and test Securification. A Mains constructed electronics and related Equipment for Analogue Interworking and Non interference Requirements for Customer Equipment Connected to the Public Switched Telephone Network General Requirements for Customer Equipment Connected to Hierarchical Digital Interfaces Requirements for ISDN Basic Access Interface TS 002: 1997 EN 60601-1 1995 (Including AM 2) UL 2601-1 1997 IEC 60065 1998, 2000 ANSI/UL 6500: 1998 CAN/CSA 60065-00 AS/NZS 3250 1995 TS 016: 1997 TS 031 : 1997 Australiam/New Zealand Standard – Approval and test Specification – Mains operated electronic and related Equipment for household and similar general use Audio, video and similar electronic equipment. Consumer and 1994, commercial products Safety requirements for main operated electronic and related apparatus Requirements for ISDN Primary Rate Access Interface Requirements for Customer Equipment for connection to a metallic loop interface of a Telecommunications Network -TS 038: 1997 AS/NZS 60065 2000 AS/ACIF S043.2:2001 Canadian C22.2 No. 1-94 (1-98) 1998 EN 60065 1994 for household and similar general use.
Radiation safety of laser products, equipment Classification, requirements and user's guide Safety of laser products Part 1: equipment Classification, requirements. Product Safety
General test methods; Input tests; Electric strength tests; Impulse tests; Permanency of marking tests; IEC 60825 1990 Accessibility tests; Energy Hazard measurements; Capacitor discharge tests; Humidity conditioning; Earthing tests; Limited power source measurements; Stability tests; Steel ball tests; Lithium Battery Reverse Current measurements; Leakage current tests; Transformer abnormal tests; Telecom leakage tests; Over voltage/power EN 60825-1 1994 IEC 60825-1 2001 IEC 60825-2 2000-5 Safety of laser products – Part 2: Safety of optical communication cross tests (excluding x-ray tests). IEC 60825-4 1997-11 Safety of laser products – Part 4: Laser guards
IEC 60335-1 1995 Safety of household and similar electrical appliances
(Including AMZ – 1997 & AM 12 – 1997) Part 1: General requirements
EN 60335-1 2001
UL 60335-1 1998
CANUCSA E227 CONTRACT RESIDENT RESIDENT CONTRACT RESIDENT RESI Product Safety Standards Title Specific Product Safety Standards IEC 950 1991 Safety of information technology equipment including Includes Amendments 1, 2, 3, and 4 electrical business equipment. Safety of information technology equipment, including UL 1950 1998 CAN/CSA E335-1 1994 Safety of information Technology Equipment, including lectrical business equipment.

Safety of Information Technology Equipment (UL 1950)

Safety of information technology equipment CSA C22.2 No.950-95 UL 60950 2000 (A2LA Cert. No. 1627.01) 1/31/06 Page 9 of 11 (A2LA Cert. No. 1627.01) 1/31/06 Page 10 of 11 UL 61010A-1 : 2002 Electrical equipment for laboratory use; part 1: General Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements Safety information technology equipment EN 61010-1:2001 AS/NZS 60950 : 2000 Environmental Environmental Standards GR-63-CORE ETS 300 019 (vibration up to 1000Hz) Environmental testing is performed at the satellite facility located at 168 Ayer Rd, Littleton, MA 01460 (A2LA Cert. No. 1627.01) 1/31/06 Page 11 of 11

Curtis-Straus LLC • 527 Great Road • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828