

# Maximum Permissive Exposure

FCC ID: U6OG0S02

IC: 9982A-G0S02

Product Name: HP Prime Wireless Dongle

Model No: G0S02-60001

## SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and $\leq 50$ mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances  $\leq 50$  mm* are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$$

$[\sqrt{f_{\text{GHz}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where


$f_{\text{GHz}}$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation


The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**EUT Side:**



**EUT Lie:**



**[Maximum measured transmitter power]**

Mode	Frequency	Peak Output Power (dBm)
1.	2402MHz	-14.39
2.	2440MHz	-12.37
3.	2480MHz	-11.76

The max output power E.I.R.P=-11.76dBm=0.0667mW

Per KDB 447498 clarifies "When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.", this device has output power 0.00064mW < threshold 10 mW thus this device is exempt from SAR test.

Sincerely Yours,

A handwritten signature in blue ink that reads "Ben Cheng".

---

Mr. Ben Cheng  
Manager  
AUDIX Technology Corporation