

RF Exposure MPE Exhibit

WARNING. This is NOT a CONSUMER device. It is designed for an installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENSE or express consent of an FCC licensee to operate this device. Unauthorized use may result in significant forfeiture penalties, including penalties of \$100,000 for each continuing violation

Limits for Occupational /Controlled Exposure

Maximum permissible exposure : MPE(mW/cm²) = Freq(MHz)/1500

894 MHz/1500 = 0.596 mW/cm²

The following calculations determine at what distance from the antenna the power density is equal to = 0.596 mW/cm²

TX Output Power = 25dBm

Antenna Gain = 18dBi

EIRP of TX and Antenna = 43dBm

43dBm = 20W = 20000mW

MPE Calculation

$$\text{Power Density} = P_d(\text{ mW/cm}^2) = \frac{EIRP}{4\pi d^2}$$

$$d = \sqrt{\frac{EIRP}{4\pi P_d}}$$

FCC ID: UDIRBB850
IC: 5842A-RBB850

Telcosat Inc.

$$d = \sqrt{\frac{20000}{4\pi \times 0.596 mW/cm^2}}$$

d = 51.6cm

The minimum safe distance for Occupational/Controlled exposure is 51.6cm for the Telcosat RBB-850 with installed antenna. This is the worst case for both Uplink and Downlink. The maximum antenna gain stated for both Uplink and downlink. This product is installed by trained professionals .