

Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band II Mid-Touch Left (RMC)

DUT: Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty

Cycle:1:1;Conv.F=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 41.21$; $\rho = 1000$ kg/m³ ;

Phantom section: Left Section

Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:

Probe:SSE5; Calibrated: 12/09/2011


- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band II Mid Touch-Left/Area Scan: Measurement grid: dx=20mm, dy=20mm

Configuration/ WCDMA Band II Mid Touch-Left/Zoom Scan: Measurement grid:



dx=8mm,dy=8mm,dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Left head
Device Position	Cheek
Band	WCDMA Band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=-46.00, Y=-41.00

SAR 10g (W/Kg)	0.271369
SAR 1g (W/Kg)	0.382977



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band II Mid-Tilt-Left (RMC)

DUT:Mobile Phone; Type: AM62

C Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty

Cycle:1:1;Conv.F=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 41.21$; $\rho = 1000$ kg/m³ ; Phantom section: Left Section

Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:


- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band II Mid Tilt-Left/Area Scan: Measurement grid: dx=20mm, dy=20mm


Configuration/ WCDMA Band II Mid Tilt-Left/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Left head
Device Position	Tilt
Band	WCDMA Band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)

SURFACE SAR





VOLUME SAR



Maximum location: X=-29.00, Y=-23.00

SAR 10g (W/Kg)	0.235548
SAR 1g (W/Kg)	0.326467



Test Laboratory: AGC Lab**Date: Sep.24,2012****WCDMA band II Mid-Touch Right (RMC)****DUT:Mobile Phone; Type: AM62**

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty

Cycle:1:1;Conv.F=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 41.21$; $\rho = 1000$ kg/m³ ;

Phantom section: Right Section


Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:

- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01



Configuration/ WCDMA band II Mid Touch-Right/Area Scan: Measurement grid: dx=20mm, dy=20mm**Configuration/ WCDMA band II Touch-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;**

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Right head
Device Position	Cheek
Band	WCDMA band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=-57.00, Y=-38.00

SAR 10g (W/Kg)	0.291573
SAR 1g (W/Kg)	0.479437



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA band II Mid-Tilt Right <RMC>

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty

Cycle:1:1;Conv.F=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 41.21$; $\rho = 1000$ kg/m³ ;

Phantom section: Right Section


Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:

- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01



Configuration/PCS1900 Mid Tilt-Right/Area Scan: Measurement grid: dx=20mm, dy=20mm**Configuration/PCS1900 Mid Tilt-Right/Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Right head
Device Position	Tilt
Band	WCDMA band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=-8.00, Y=22.00

SAR 10g (W/Kg)	0.072354
SAR 1g (W/Kg)	0.122738



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA band II Mid-Body-towards grounds (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1;
 convF=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 53.36$;
 $\rho = 1000$ kg/m³ ;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21


Satimo Configuration:

- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA band II Mid Body-back/Area Scan: Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA band II Mid Body-back/Zoom Scan: Measurement grid: dx=8mm,
 dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=1.00, Y=9.00

SAR 10g (W/Kg)	0.462046
SAR 1g (W/Kg)	0.635459



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA band II Mid-Body-towards phantom (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty

Cycle:1:1;Conv.F=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 53.36$; $\rho = 1000$ kg/m³ ;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21


Satimo Configuration:

- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA band II Mid Body-Front/Area Scan: Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA band II Mid Body-Front/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Front
Band	WCDMA band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=1.00, Y=9.00

SAR 10g (W/Kg)	0.307287
SAR 1g (W/Kg)	0.452764



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA band II Mid-Body-towards ground (HSDPA)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1;

convF=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 53.36$; $\rho = 1000$ kg/m³ ;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21



Satimo Configuration:

- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA band II Mid Body-back/Area Scan: Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA band II Mid Body-back/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)

SURFACE SAR**VOLUME SAR**

Maximum location: X=0.00, Y=15.00

SAR 10g (W/Kg)	0.302572
SAR 1g (W/Kg)	0.420374



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA band II Mid-Body-towards ground (RMC with earphone)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1;

convF=6.42 Frequency: 1880 MHz; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 53.36$; $\rho = 1000$ kg/m³ ;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21



Satimo Configuration:

- Probe:SSE5; Calibrated: 12/09/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA band II Mid Body-back/Area Scan: Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA band II Mid Body-back/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA band II
Channels	Middle
Signal	TDMA (Crest factor: 1.0)

SURFACE SAR**VOLUME SAR**

Maximum location: X=2.00, Y=7.00

SAR 10g (W/Kg)	0.294324
SAR 1g (W/Kg)	0.432758



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Middle-touch-Left (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;
Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: f = 835 MHz; σ =0.92 mho/m; ϵ_r =41.73;
 ρ = 1000 kg/m³ ;

Phantom section: Left Section

Ambient temperature (°C): 21, Liquid temperature (°C): 21

Satimo Configuration:


Probe:SSE5; Calibrated: 12/09/2011

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Touch-Left/Area Scan (6x8x1): Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA Band V Mid Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Left head
Device Position	Cheek
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=-40.00, Y=-25.00

SAR 10g (W/Kg)	0.367346
SAR 1g (W/Kg)	0.526278



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Mid Tilt-left (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;
Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 41.73$;
 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Left Section

Ambient temperature (°C): 21, Liquid temperature (°C): 21


Satimo Configuration:

Probe:SSE5; Calibrated: 12/09/2011

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01



Configuration/ WCDMA Band V Mid Tilt-Left/Area Scan (6x8x1): Measurement grid: dx=20mm, dy=20mm
Configuration/ WCDMA Band V Mid Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Left head
Device Position	Tilt
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=-23.00, Y=-9.00

SAR 10g (W/Kg)	0.125775
SAR 1g (W/Kg)	0.200573



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Middle touch-Right (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;
Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 41.73$;
 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature (°C): 21, Liquid temperature (°C): 21

Satimo Configuration:


Probe:SSE5; Calibrated: 12/09/2011

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Touch-Right/Area Scan: Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$



Configuration/ WCDMA Band V Mid Touch-Right/Zoom Scan: Measurement grid: $dx=8\text{mm}$,
 $dy=8\text{mm}$, $dz=5\text{mm}$;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Right head
Device Position	Cheek
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=-49.00, Y=-43.00

SAR 10g (W/Kg)	0.342836
SAR 1g (W/Kg)	0.501747



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Mid-tilt-Right (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;
 Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: $f = 835$ MHz; $\sigma = 0.92$ mho/m; $\epsilon_r = 41.73$;
 $\rho = 1000$ kg/m³ ;

Phantom section: Right Section

Ambient temperature (°C): 21, Liquid temperature (°C): 21

Satimo Configuration:


Probe:SSE5; Calibrated: 12/09/2011

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Tilt-Right/Area Scan: Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA Band V Mid Tilt-Right/Zoom Scan: Measurement grid: dx=8mm,
 dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Right head
Device Position	Tilt
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=8.00, Y=8.00

SAR 10g (W/Kg)	0.205537
SAR 1g (W/Kg)	0.287158



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Mid-Body-Towards Grounds (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD; DutyCycle:1: 1;
Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: f = 835 MHz; σ =1.01 mho/m; ϵ_r =55.13;
 ρ = 1000 kg/m³ ;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:


Probe:SSE5; Calibrated: 12/09/2011

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Body-Front/Area Scan (6x8x1): Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA Band V Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)



Maximum location: X=3.00, Y=34.00

SAR 10g (W/Kg)	0.160237
SAR 1g (W/Kg)	0.245946



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Mid-body- Towards Phantom (RMC)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;

Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: $f = 835$ MHz; $\sigma = 1.01$ mho/m; $\epsilon_r = 55.13$; $\rho = 1000\text{kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:

Probe:SSE5; Calibrated: 12/09/2011


- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Body- Back /Area Scan (6x8x1): Measurement grid: dx=20mm, dy=20mm


Configuration/ WCDMA Band V Mid Body- Back /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Front
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)

SURFACE SAR





VOLUME SAR



Maximum location: X=8.00, Y=49.00

SAR 10g (W/Kg)	0.104039
SAR 1g (W/Kg)	0.157382



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Mid-body- Towards Grounds(HSPA)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;

Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ mho/m}$; $\epsilon_r = 55.13$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C):21, Liquid temperature (°C):21

Satimo Configuration:

Probe:SSE5; Calibrated: 12/09/2011


- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Body- Back /Area Scan (6x8x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$


Configuration/ WCDMA Band V Mid Body- Back /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)

SURFACE SAR





VOLUME SAR



Maximum location: X=8.00, Y=36.00

SAR 10g (W/Kg)	0.127567
SAR 1g (W/Kg)	0.213575



Test Laboratory: AGC Lab

Date: Sep.24,2012

WCDMA Band V Mid-body- Towards Grounds(with earphone)(HSPA)

DUT:Mobile Phone; Type: AM62

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; DutyCycle:1: 1;

Conv.F=6.79 Frequency: 835 MHz; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ mho/m}$; $\epsilon_r = 55.13$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}\text{C}$):21, Liquid temperature ($^{\circ}\text{C}$):21

Satimo Configuration:


Probe:SSE5; Calibrated: 12/09/2011

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM1; Type: SAM
- Measurement SW: OpenSAR V4_02_01

Configuration/ WCDMA Band V Mid Body- Back /Area Scan (6x8x1): Measurement grid: dx=20mm, dy=20mm



Configuration/ WCDMA Band V Mid Body- Back /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Very fast
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA Band V
Channels	Middle
Signal	TDMA (Crest factor: 1.0)




Maximum location: X=2.00, Y=35.00


SAR 10g (W/Kg)	0.167286
SAR 1g (W/Kg)	0.262876




Appendix C. TEST SETUP PHOTOGRAPHS & EUT PHOTOGRAPHS
Test Setup Photographs
LEFT-CHECK TOUCH




LEFT-TILT 15°




RIGHT-CHECK TOUCH




RIGHT-TILT 15⁰



Body Back15mm



Body Front15mm



Body back with Headset



DEPTH OF THE LIQUID IN THE PHANTOM—ZOOM IN

Note : The position used in the measurement were according to IEEE 1528-2003



EUT PHOTOGRAPHS
TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT





LEFT VIEW OF EUT



RIGHT VIEW OF EUT






OPEN VIEW OF EUT-3



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2

