

RF Exposure Evaluation Report

Product : RC Tirex - Remote controlled smoke
spitting dinosaur

Trade mark : LEXIBOOK

Model/Type reference : DINO02 (wrist remote)

Serial Number : N/A

Report Number : EED32P80824604

FCC ID : UU8-DINO02A

Date of Issue : Aug. 22, 2023

Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1091
47 CFR Part 2.1093
447498 D04 Interim General RF
Exposure Guidance v01

Test result : PASS

Prepared for:

Lexibook America

**C/O Pramex International 1251 Avenue of the Americas, 3rd Fl., New
York, 10020, United States**

Prepared by:

**Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Frazer Li

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Aug. 22, 2023



Check No.: 9836050623

2 Version

Version No.	Date	Description
00	Aug. 22, 2023	Original

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
4.4 TEST LOCATION	5
4.5 DEVIATION FROM STANDARDS	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5 SAR EVALUATION	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
5.1.1 Limits	6
5.1.2 Test Procedure	6
5.1.3 EUT RF Exposure Evaluation	7

4 General Information

4.1 Client Information

Applicant:	Lexibook America
Address of Applicant:	C/O Pramex International 1251 Avenue of the Americas,3rd Fl., New York,10020,United States
Manufacturer:	Lexibook America
Address of Manufacturer:	C/O Pramex International 1251 Avenue of the Americas,3rd Fl., New York,10020,United States

4.2 General Description of EUT

Product Name:	RC Tirez - Remote controlled smoke spitting dinosaur
Model No.(EUT):	DINO02 (wrist remote)
Trade mark:	LEXIBOOK

4.3 Product Specification subjective to this standard

Frequency Range:	TX & RX: 2405MHz ~2475MHz
Modulation Type:	GFSK
Test Power Grade:	Default
Test Software of EUT:	RF Test
Antenna Type:	Internal Antenna
Antenna Gain:	0.59dBi
Power Supply:	DC 3.0V LITHIUM BATTERY
Sample Received Date:	Jun. 07, 2023
Sample tested Date:	Jun. 07, 2023 to Aug. 22, 2023
Remark: Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5.1.3 EUT RF Exposure Evaluation

For Watch:

Mode	Field strength of the fundamental signal (dBuV/m@3m)	ERP (dBm)	ERP (mW)	Limit (mW)	Result
2475MHz	80.92	-16.46	0.023	≤2.722	PASS

Note:

- ① EIRP=conducted power+antenna gain;
 - ② ERP=EIRP-2.15;
 - ③ $\text{EIRP(dBm)} = \text{Field strength of the fundamental signal(dBuV/m@3m)} - 95.23$;
 - ④ $\text{ERP(mW)} = 10^{(\text{ERP (dBm)}/10)}$;
 - ⑤ The estimation distance is 0.5cm;
 - ⑥ The test data please refer to the report of EED32P80824602.
- Only the worst case data was recorded in the report.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***