RF EXPOSURE REPORT

REPORT NO.:	SA121019C06
MODEL NO.:	MBR1400v2
FCC ID:	UXX-MBR1400V2
RECEIVED:	Oct. 19, 2012
TESTED:	Oct. 23 ~ Nov. 16, 2012
ISSUED:	Nov. 21, 2012

APPLICANT:	CradlePoint, Inc.
ADDRESS:	805W Franklin Street, Boise ID 83702, USA

ISSUED BY:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
LAB ADDRESS:	No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.
TEST LOCATION:	No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

TABLE OF CONTENTS

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA121019C06	Original release	Nov. 21, 2012

1. CERTIFICATION

PRODUCT:	Dual band Router
MODEL NO.:	MBR1400v2
BRAND:	CradlePoint, Inc.
APPLICANT:	CradlePoint, Inc.
TESTED:	Oct. 23 ~ Nov. 16, 2012
TEST SAMPLE:	ENGINEERING SAMPLE
STANDARDS:	**FCC Part 2 (Section 2.1091)**
	FCC OET Bulletin 65, Supplement C (01-01)
	IEEE C95.1

The above equipment (model: MBR1400v2) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Pettie Chen / Senior Specialist , **DATE :** Nov. 21, 2012

APPROVED BY : Ken Liu / Manager , **DATE :** Nov. 21, 2012

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm^2)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	…	…	F/1500	30
1500-100,000	…	…	1.0	30

F = Frequency in MHz

2.2 MPE calculation Formula

$Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm^2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Calculation result of maximum conducted power

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm^2)	LIMIT (mW/cm^2)
2412-2462	27.13	5	20	0.325	1
5180-5240	16.04	5	20	0.025	1
5745-5825	18.88	5	20	0.049	1