

# SUBMITTAL APPLICATION REPORT

## FOR GRANT OF CERTIFICATION

FOR

**MODEL: WMR200**  
**2412-2472 MHz**  
**Broadband Wireless Data Transmitter**

FOR

**LIGOWAVE LLC.**  
**1440 Dutch Valley Place, Suite 1155**  
**Atlanta, GA 30324**


Test Report Number: 080824

Authorized Signatory: *Scot D Rogers*  
Scot D. Rogers

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 1 of 39  
Date: August 25, 2008

**ROGERS LABS, INC.**

4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Phone / Fax (913) 837-3214

**ENGINEERING TEST REPORT  
For APPLICATION of  
GRANT of CERTIFICATION**

FOR  
**CFR 47, PART 15C - INTENTIONAL RADIATORS**  
**CFR47 Paragraph 15.247**  
**License Exempt Intentional Radiator**

For

**LIGOWAVE LLC.**  
1440 Dutch Valley Place, Suite 1155  
Atlanta, GA 30324

**BROADBAND WIRELESS DATA TRANSMITTER**  
Model: WMR200  
Frequency Range 2412-2472 MHz  
FCC ID#: VKV-WMR200  
IC: 7607A-WBD500

Test Date: August 24, 2008

Certifying Engineer: *Scot D Rogers*  
Scot D. Rogers  
Rogers Labs, Inc.  
4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Phone: (913) 837-3214  
Fax: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.  
This report must not be used by the client to claim product endorsement by NVLAP, NIST, or  
any agency of the U.S. Government.

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 2 of 39  
Date: August 25, 2008

## Table Of Contents

<b>TABLE OF CONTENTS.....</b>	<b>3</b>
<b>FORWARD .....</b>	<b>5</b>
<b>OPINION / INTERPRETATION OF RESULTS .....</b>	<b>5</b>
<b>ENVIRONMENTAL CONDITIONS.....</b>	<b>5</b>
<b>EQUIPMENT TESTED.....</b>	<b>5</b>
<b>2.1033(B) APPLICATION FOR CERTIFICATION.....</b>	<b>6</b>
<b>APPLICABLE STANDARDS &amp; TEST PROCEDURES .....</b>	<b>6</b>
<b>EQUIPMENT FUNCTION AND TESTING PROCEDURES .....</b>	<b>7</b>
<b>EQUIPMENT AND CABLE CONFIGURATIONS .....</b>	<b>7</b>
AC Line Conducted Emission Test Procedure.....	7
Radiated Emission Test Procedure.....	8
<b>UNITS OF MEASUREMENTS .....</b>	<b>8</b>
<b>TEST SITE LOCATIONS .....</b>	<b>8</b>
<b>LIST OF TEST EQUIPMENT .....</b>	<b>9</b>
<b>SUBPART B – UNINTENTIONAL RADIATORS .....</b>	<b>10</b>
AC Line Conducted EMI .....	10
Figure 1 AC Line Conducted Emissions Line 1 .....	11
Figure 2 AC Line Conducted Emissions Line 2 .....	11
Radiated EMI.....	12
Figure three General Radiated Emissions taken at 1 meter in screen room. ....	13
Figure four General Radiated Emissions taken at 1 meter in screen room. ....	13
Figure five General Radiated Emissions taken at 1 meter in screen room. ....	14
Figure six General Radiated Emissions taken at 1 meter in screen room. ....	14
Figure seven General Radiated Emissions taken at 1 meter in screen room. ....	15
Figure eight General Radiated Emissions taken at 1 meter in screen room. ....	15
AC Line Conducted Emissions Data (7 Highest Emissions).....	16
General Radiated Emissions Data from EUT (Highest Emissions).....	16
Summary of Results for AC Line Conducted Emissions.....	17
Summary of Results for General Radiated Emissions.....	17
Statement of Modifications and Deviations .....	17
<b>SUBPART C - INTENTIONAL RADIATORS .....</b>	<b>17</b>
<b>15.203 Antenna Requirements .....</b>	<b>17</b>

<b>15.205 Restricted Bands of Operation.....</b>	<b>17</b>
Radiated Emissions in Restricted Bands Data (worst-case) .....	18
<b>Summary of Results for Radiated Emissions in Restricted Bands.....</b>	<b>18</b>
<b>Statement of Modifications and Deviations .....</b>	<b>19</b>
<b>15.209 Radiated Emissions Limits; General Requirements .....</b>	<b>19</b>
General Radiated Emissions from EUT Data (Highest Emissions).....	20
<b>Summary of Results for General Radiated Emissions.....</b>	<b>20</b>
<b>15.247 Operation in the Band 2412-2472 MHz .....</b>	<b>21</b>
Figure 9 Operations at three frequencies in band .....	21
Figure 10 Maximum output power at three frequencies in band .....	22
Figure 11 6dB Band width Requirement plot taken in screen room .....	22
Figure 12 6dB Band width Requirement plot taken in screen room .....	23
Figure 13 6dB Band width Requirement plot taken in screen room .....	23
Figure 14 6dB Band width Requirement plot taken in screen room .....	24
Figure 15 6dB Band width Requirement plot taken in screen room .....	24
Figure 16 6dB Band width Requirement plot taken in screen room .....	25
Figure 17 Power Spectral Density plot taken in screen room.....	25
Figure 18 Power Spectral Density plot taken in screen room.....	26
Figure 19 Power Spectral Density plot taken in screen room.....	26
Figure 20 Antenna Conducted Emission plot taken in screen room.....	27
Figure 21 Antenna Conducted Emission plot taken in screen room.....	27
Figure 22 Antenna Conducted Emission plot taken in screen room.....	28
Figure 23 Antenna Conducted Emission plot taken in screen room.....	28
Figure 24 Antenna Conducted Emission plot taken in screen room.....	29
Transmitter Information and Data .....	29
Radiated Emissions from EUT Data (19 dBi Panel) .....	31
Radiated Emissions from EUT Data (24 dBi Grid) .....	32
<b>Summary of Results for Radiated Emissions of Intentional Radiator .....</b>	<b>33</b>
<b>Statement of Modifications and Deviations .....</b>	<b>33</b>
<b>ANNEX.....</b>	<b>34</b>
<b>Annex A Measurement Uncertainty Calculations.....</b>	<b>35</b>
<b>Annex B Test Equipment List For Rogers Labs, Inc.....</b>	<b>37</b>
<b>Annex C Qualifications.....</b>	<b>38</b>
<b>Annex D FCC Site Registration Letter .....</b>	<b>39</b>



NVLAP Lab Code 200087-0

## Forward

The following information is submitted for consideration in obtaining a Grant of Certification for a License Exempt Intentional Radiator operating under CFR47 Paragraph 15.247.

Name of Applicant:  
LIGOWAVE LLC  
1440 Dutch Valley Place, Suite 1155  
Atlanta, GA 30324

Model: WMR200

FCC I.D.: VKV-WMR200 FRN: 0017 41 6041  
Frequency Range: 2412-2472MHz.

Operating Power: 0.5 W conducted power

## Opinion / Interpretation of Results

Tests Performed	Results
Emissions Tests	
Emissions as per CFR47 paragraphs 2 and 15.205	Complies
Emissions as per CFR47 paragraphs 2 and 15.209	Complies
Emissions as per CFR47 paragraphs 2 and 15.247	Complies

## Environmental Conditions

Ambient Temperature 25.6° C  
Relative Humidity 38%  
Atmospheric Pressure 29.89 in Hg

## Equipment Tested

Equipment	Model	FCC I.D.#
EUT	WMR200	VKV-WMR200
Interface support board	Proto	N/A

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 5 of 39  
Date: August 25, 2008

## 2.1033(b) Application for Certification

(1) Manufacturer: LIGOWAVE LLC.  
1440 Dutch Valley Place, Suite 1155  
Atlanta, GA 30324

(2) Identification: Model: WMR200  
FCC I.D.: VKV-WMR200 IC: 7607A-WMR200

(3) Instruction Book:  
Refer to Exhibit for Instruction Manual.

(4) Description of Circuit Functions:  
Refer to Exhibit of Operational Description.

(5) Block Diagram with Frequencies:  
Refer to Exhibit of Operational Description.

(6) Report of Measurements:  
Report of measurements follows in this Report.

(7) Photographs: Construction, Component Placement, etc.:  
Refer to Exhibit for photographs of equipment.

(8) No Peripheral Equipment was Necessary for operation. A laptop computer was used for testing purposes.

(9) Transition Provisions of 15.37 are not being requested.

(10) Not Applicable. The unit is not a scanning receiver.

(11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.

## Applicable Standards & Test Procedures

In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2007, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247, and RSS-210 the following information is submitted.

Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in the ANSI 63.4-2003 Document FCC, documents DA00-1407 and DA00-705 and/or TIA/EIA 603-1. Testing for the line-conducted emissions were performed as defined in sections

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 6 of 39  
Date: August 25, 2008

8 and 13.1.3, testing of the radiated emissions was performed as defined in sections 8 and 13.1.4 of ANSI C63.4. Testing of the intentional radiated emissions was performed as defined in section 13 of ANSI C63.4.

## **Equipment Function and Testing Procedures**

The EUT is a 2412-2472 MHz radio transmitter module used to transmit data in applications offering broadband wireless connectivity. The unit is marketed for use to incorporate a wireless link to exchange data information from one point to another. For testing purposes the WMR200 transceiver attached to the interface which was connected to the computer and placed on a wooden table. The equipment receives power from the support host only and offers no provision to connect to utility AC power. The support card required 3.3 volts DC to operate the EUT. The DC power was supplied by a DC power supply. The WMR200 design incorporates modulation limiting, power regulation, shielding, mini card slot connector, and a MMCX antenna connection point. No other interfacing options are provided on the design. For testing purposes WMR200 was powered from the support interface card inserted in the computer. The AC lines of the computers AC/DC power adapter was tested for line conducted emissions. The EUT was to transmit in all maximum data modes available during testing. The device is marketed for professionally installed use and the antenna connection complies with the unique antenna connection requirements. Radiated emissions testing for this equipment was performed using the supplied antenna options, Omni directional, panel, and grid.

## **Equipment and Cable Configurations**

### **AC Line Conducted Emission Test Procedure**

The WMR200 operates from DC power only and must be used with the compliant equipment offering DC power and interface capability. The WMR200 was operated using the manufacturer supplied interface board and computer AC/DC power supply. Testing for the AC line-conducted emissions testing was performed as defined in sections 8 and 13.1.3 of ANSI C63.4. The test setup including the EUT was arranged in a typical equipment configuration and placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50  $\mu$ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor internal to the LISN. The LISN

was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table.

### **Radiated Emission Test Procedure**

The EUT was placed on a rotating 1 x 1.5-meter wooden platform, 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. Testing for the radiated emissions was performed as defined in sections 8 and 13.1.4 of ANSI C63.4. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. Refer to photographs in the test setup exhibits for EUT placement during testing.

### **Units of Measurements**

Conducted EMI      Data is in dB $\mu$ V; dB referenced to one microvolt.

Radiated EMI      Data is in dB $\mu$ V/m; dB/m referenced to one microvolt per meter.

### **Test Site Locations**

Conducted EMI      The AC power line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 W. 259<sup>th</sup> Terrace, Louisburg, KS.

Radiated EMI      The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259<sup>th</sup> Terrace, Louisburg, KS.

Site Approval      Refer to Annex for FCC Site Registration Letter, # 90910, Industry Canada Site Registration IC3041A-1

## List of Test Equipment

A Hewlett Packard 8591EM Spectrum Analyzer was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

HP 8591 EM ANALYZER SETTINGS		
CONDUCTED EMISSIONS		
RBW	AVG. BW	DETECTOR FUNCTION
9 kHz	30 kHz	Peak / Quasi Peak
RADIATED EMISSIONS		
RBW	AVG. BW	DETECTOR FUNCTION
120 kHz	300 kHz	Peak / Quasi Peak
HP 8562A ANALYZER SETTINGS		
RBW	VIDEO BW	DETECTOR FUNCTION
100 kHz	100 kHz	PEAK
1 MHz	1 MHz	Peak / Average

EQUIPMENT	MFG.	MODEL	CAL. DATE	DUE.
LISN	Comp. Design	FCC-LISN-2-MOD.CD	10/07	10/08
LISN	Comp. Design	1762	2/08	2/09
Antenna	ARA	BCD-235-B	10/07	10/08
Antenna	EMCO	3147	10/07	10/08
Antenna	EMCO	3143	5/08	5/09
Analyzer	HP	8591EM	5/08	5/09
Analyzer	HP	8562A	5/08	5/09

## **Subpart B – Unintentional Radiators**

### ***AC Line Conducted EMI***


The EUT was arranged in a typical equipment configuration and placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. The manufacturer supplied AC power adapter for the computer was connected to the LISN. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the computer/EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor, internal to the LISN. Power line conducted emissions testing were carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground.

Preliminary testing was performed to identify the frequency of each radio frequency emission displaying the highest amplitude. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then the data was recorded with maximum conducted emissions levels. Refer to figures one and two for plots of the AC Line conducted emissions.

MARKER  
400 kHz  
60.38 dB $\mu$ V

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 400 kHz  
60.38 dB $\mu$ V

REF OFFSET 17.Ø dB  
LOG REF 95.Ø dBµV



START 150 kHz #IF BW 9.0 kHz AVG BW 30 kHz STOP 30.00 MHz SWP 1.40 sec

**Figure 1 AC Line Conducted Emissions Line 1**

MARKER  
180 kHz  
68.59 dBuV

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 180 KHz  
68.59 dB<sub>UV</sub>

REF OFFSET 17.Ø dB  
LOG REF 95.Ø dBµV




Figure 2 AC Line Conducted Emissions Line 2

## Radiated EMI

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. The antenna port was connected to a 50-ohm load and operated through all available modes for general radiated emissions testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Plots were made of the radiated frequency spectrum from 30 MHz to 22,000 MHz for the preliminary testing. Refer to figures three through eight for plots of the general radiated emissions spectrum taken in a screen room. The highest radiated emission was then re-maximized at the OATS location before final radiated emissions measurements were performed.

Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 30 MHz to 22,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 5 GHz and or, pyramidal horns and mixers from 4 GHz to 40 GHz, notch filters and appropriate amplifiers were utilized.

### Sample Calculations:

$$\begin{aligned} \text{RFS} &= \text{Radiated Field Strength} \\ \text{dB}\mu\text{V/m} @ 3\text{m} &= \text{dB}\mu\text{V} + \text{A.F.} - \text{Amplifier Gain} \\ \text{dB}\mu\text{V/m} @ 3\text{m} &= 62.8 + 7.3 - 30 \\ &= 40.1 \end{aligned}$$

MARKER  
 100.0 MHz  
 51.38 dB $\mu$ V

ACTV DET: PEAK  
 MEAS DET: PEAK QP  
 MKR 100.0 MHz  
 51.38 dB $\mu$ V




Figure three General Radiated Emissions taken at 1 meter in screen room.

MARKER  
 303 MHz  
 39.95 dB $\mu$ V

ACTV DET: PEAK  
 MEAS DET: PEAK QP  
 MKR 303 MHz  
 39.95 dB $\mu$ V






Figure four General Radiated Emissions taken at 1 meter in screen room.



**Figure five General Radiated Emissions taken at 1 meter in screen room.**



**Figure six General Radiated Emissions taken at 1 meter in screen room.**


Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 14 of 39  
Date: August 25, 2008

NVLAP®

NVLAP Lab Code 200087-0



**Figure seven General Radiated Emissions taken at 1 meter in screen room.**




Figure eight General Radiated Emissions taken at 1 meter in screen room.

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 15 of 39  
Date: August 25, 2008

**AC Line Conducted Emissions Data (7 Highest Emissions)**

Frequency band (MHz)	L1 Level (dB $\mu$ V)			L2 Level (dB $\mu$ V)			CISPR 22 Limit Q.P. Ave(dB $\mu$ V)
	Peak	Q.P.	AVE	Peak	Q.P.	AVE	
0.15 – 0.5	60.4	40.6	18.9	68.6	42.5	24.1	65 / 55
0.5 – 5	47.3	42.1	24.5	44.2	34.7	13.8	56 / 46
5 – 10	31.5	27.2	20.8	32.6	27.3	21.2	60 / 50
10 – 15	32.5	26.4	20.1	33.0	26.3	20.0	60 / 50
15 – 20	30.8	26.0	19.7	33.0	27.0	19.7	60 / 50
20 – 25	35.33	27.2	19.5	38.4	29.7	19.4	60 / 50
25 – 30	38.5	28.0	18.4	33.1	30.8	18.9	60 / 50

Other emissions present had amplitudes at least 10 dB below the limit.

**General Radiated Emissions Data from EUT (Highest Emissions)**

Frequency in MHz	FSM Horz. (dB $\mu$ V)	FSM Vert. (dB $\mu$ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dB $\mu$ V/m)	RFS Vert. @ 3m (dB $\mu$ V/m)	FCC Class B Limit @ 3m (dB $\mu$ V/m)
100.0	62.8	65.4	7.3	30	40.1	42.7	43.5
133.5	48.5	54.9	8.5	30	27.0	33.4	43.5
166.2	61.1	60.6	8.7	30	39.8	39.3	43.5
232.7	59.2	43.4	11.3	30	40.5	24.7	46.0
266.4	48.5	43.5	12.9	30	31.4	26.4	46.0
281.2	45.9	38.0	12.9	30	28.8	20.9	46.0
281.4	45.8	38.1	12.9	30	28.7	21.0	46.0
300.4	53.5	48.7	14.0	30	37.5	32.7	46.0
352.0	45.3	43.8	15.3	30	30.6	29.1	46.0
432.0	44.6	44.6	16.8	30	31.4	31.4	46.0
498.4	40.9	43.1	18.3	30	29.2	31.4	46.0

Other emissions present had amplitudes at least 20 dB below the limit.

***Summary of Results for AC Line Conducted Emissions***

The conducted emissions for the EUT meet the requirements for CISPR 22 and FCC Part 15B CLASS B Digital Devices. The EUT had a 13.9 dB minimum margin below the Quasi-Peak limit, and a 20.5 dB minimum margin below the CISPR average limit. Measurements were taken using the peak, quasi peak, and average, measurement function for each emissions amplitude and were below the limits stated in the specification. Other emissions were present with recorded data representing worst-case amplitudes.

***Summary of Results for General Radiated Emissions***

The general radiated emissions for the EUT meet the requirements for CISPR 22 and FCC Part 15B CLASS B Digital Devices. The EUT had a 0.8 dB minimum margin below the quasi-peak limit. Other emissions were present with amplitudes at least 20 dB below the limit.

***Statement of Modifications and Deviations***

No modifications to the EUT were required for the unit to meet the CISPR 22 or FCC Part 15B CLASS B emissions standards. There were no deviations or exceptions to the specifications.

***Subpart C - Intentional Radiators***

As per CFR47, Subpart C, paragraph 15.247 the following information is submitted.

***15.203 Antenna Requirements***

The design utilizes a unique surface mount connector offering a connection for a coaxial cable. The end product is marketed and sold for professional installation only. The antenna connection point complies with the unique antenna connection requirements. The requirements of 15.203 are fulfilled and there are no deviations or exceptions to the specification.

***15.205 Restricted Bands of Operation***

Spurious emissions falling in the restricted frequency bands of operation were measured at a distance of three meters at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were checked at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. No other significant emission was observed which fell into the restricted bands of operation.

## Sample Calculation:

$$\begin{aligned}
 \text{RFS (dB}\mu\text{V/m @ 3m)} &= \text{FSM(dB}\mu\text{V)} + \text{A.F.(dB)} - \text{Gain(dB)} \\
 &= 48.5 + 8.5 - 30 \\
 &= 27.0
 \end{aligned}$$

**Radiated Emissions in Restricted Bands Data (worst-case)**

Frequency in MHz	FSM Horz. (dB $\mu$ V)	FSM Vert. (dB $\mu$ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dB $\mu$ V/m)	RFS Vert. @ 3m (dB $\mu$ V/m)	FCC Class B Limit @ 3m (dB $\mu$ V/m)
133.5	48.5	54.9	8.5	30	27.0	33.4	43.5
166.2	61.1	60.6	8.7	30	39.8	39.3	43.5
240.0	39.1	38.9	11.7	30	20.8	20.6	46.0
266.4	48.5	43.5	12.9	30	31.4	26.4	46.0
4824.0	22.8	31.7	41.4	30	34.2	43.1	54.0
4884.0	29.1	35.5	41.2	30	40.3	46.7	54.0
4944.0	22.1	32.7	42.1	30	34.2	44.8	54.0
7236.0	21.0	23.0	36.0	30	27.0	29.0	54.0
7326.0	22.8	23.1	36.3	30	29.1	29.4	54.0
7416.0	22.0	22.3	36.6	30	28.6	28.9	54.0
12060.0	18.8	23.0	40.0	30	28.8	33.0	54.0
12210.0	20.3	20.7	40.2	30	30.5	30.9	54.0
12360.0	21.0	22.0	40.4	30	31.4	32.4	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

**Summary of Results for Radiated Emissions in Restricted Bands**

The radiated emissions for the EUT meet the requirements for FCC Part 15C Intentional Radiators. The EUT had a 3.7 dB minimum margin below the limits. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. No other emissions were found in the restricted frequency bands. Other emissions were present with amplitudes at least 20 dB below the FCC Limits.

***Statement of Modifications and Deviations***

No modifications to the EUT were required for the unit to meet the FCC Part 15C paragraph 15.205 emissions requirements. There were no deviations or exceptions to the specifications.

***15.209 Radiated Emissions Limits; General Requirements***

The EUT was arranged in a typical equipment configuration and operated through all of its various modes. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Radiated emissions were observed in the screen room from 30 to 18,000 MHz and plots were made of the radiated emissions frequency spectrum from 30 MHz to 18,000 MHz for the preliminary testing. The highest radiated emission was then re-maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the open area test site at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 30 MHz to 25,000 MHz was searched for radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna polarization between horizontal and vertical. Antennas used were Broadband Biconical from 30 MHz to 200 MHz, Biconilog from 30 MHz to 1000 MHz, Log Periodic from 200 MHz to 5 GHz, and/or Pyramidal Horns from 4 GHz to 40 GHz.

Sample Calculations:

$$\begin{aligned} \text{RFS} &= \text{Radiated Field Strength} \\ \text{dB}\mu\text{V/m} @ 3\text{m} &= \text{dB}\mu\text{V} + \text{A.F.} - \text{Amplifier Gain} \\ \text{dB}\mu\text{V/m} @ 3\text{m} &= 62.8 + 7.3 - 30 \\ &= 40.1 \end{aligned}$$

**General Radiated Emissions from EUT Data (Highest Emissions)**

Frequency in MHz	FSM Horz. (dB $\mu$ V)	FSM Vert. (dB $\mu$ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dB $\mu$ V/m)	RFS Vert. @ 3m (dB $\mu$ V/m)	FCC Class B Limit @ 3m (dB $\mu$ V/m)
100.0	62.8	65.4	7.3	30	40.1	42.7	43.5
133.5	48.5	54.9	8.5	30	27.0	33.4	43.5
166.2	61.1	60.6	8.7	30	39.8	39.3	43.5
232.7	59.2	43.4	11.3	30	40.5	24.7	46.0
266.4	48.5	43.5	12.9	30	31.4	26.4	46.0
281.2	45.9	38.0	12.9	30	28.8	20.9	46.0
281.4	45.8	38.1	12.9	30	28.7	21.0	46.0
300.4	53.5	48.7	14.0	30	37.5	32.7	46.0
352.0	45.3	43.8	15.3	30	30.6	29.1	46.0
432.0	44.6	44.6	16.8	30	31.4	31.4	46.0
498.4	40.9	43.1	18.3	30	29.2	31.4	46.0


Other emissions present had amplitudes at least 20 dB below the limit.

**Summary of Results for General Radiated Emissions**

The radiated emissions for the EUT meet the requirements for FCC Part 15C paragraph 15.209 Intentional Radiators. The EUT had a 0.8 dB minimum margin below the limits. Other emissions were present with amplitudes at least 20 dB below the FCC Limits.

### 15.247 Operation in the Band 2412-2472 MHz

The power output was measured both at the antenna connection and at the open area test site at a three-meter distance. Three antenna configurations were offered and tested for certification. The panel offers gain of 19 dBi, the Grid offers gain of 24 dBi, and the Omni offers gain of 12 dBi. Data was taken per Paragraph 2.1046(a) and 15.247. Figures nine and ten demonstrate compliance with frequencies of operation and maximum output power requirements of 15.247(a)(2) across the band. Figures eleven through sixteen demonstrate compliance with the minimum 6 db bandwidth requirements of 15.247(A)(2). Figures seventeen through nineteen demonstrate compliance to power spectral density per 15.247(d). Figures nineteen through twenty-four demonstrate antenna conducted emissions and compliance with the requirements of 15.247(c) for emission limitations. Compliance to band edge requirements per 15.209 and 15.247 are demonstrated in radiated emissions tables for each antenna configuration. Antenna option configurations tested for compliance ranged in gain from 12 dBi to 24 dBi with worst case emissions presented in this document.




**Figure 9 Operations at three frequencies in band**

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214


Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 21 of 39  
Date: August 25, 2008



**Figure 10 Maximum output power at three frequencies in band**




**Figure 11 6dB Band width Requirement plot taken in screen room**


Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 22 of 39  
Date: August 25, 2008



**Figure 12 6dB Band width Requirement plot taken in screen room**



**Figure 13 6dB Band width Requirement plot taken in screen room**

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 23 of 39  
Date: August 25, 2008




Figure 14 6dB Band width Requirement plot taken in screen room




Figure 15 6dB Band width Requirement plot taken in screen room

Rogers Labs, Inc.  
 4405 W. 259th Terrace  
 Louisburg, KS 66053  
 Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
 Model: WMR200  
 Test #: 080824  
 Test to: FCC (15.247), RSS-210  
 File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
 IC: 7607A-WMR200  
 SN: ENG1  
 Page 24 of 39  
 Date: August 25, 2008




Figure 16 6dB Band width Requirement plot taken in screen room






Figure 17 Power Spectral Density plot taken in screen room



**Figure 18 Power Spectral Density plot taken in screen room**




**Figure 19 Power Spectral Density plot taken in screen room**


Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210


FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 26 of 39  
Date: August 25, 2008




**Figure 20** Antenna Conducted Emission plot taken in screen room




**Figure 21 Antenna Conducted Emission plot taken in screen room**



**Figure 22 Antenna Conducted Emission plot taken in screen room**



**Figure 23 Antenna Conducted Emission plot taken in screen room**



**Figure 24 Antenna Conducted Emission plot taken in screen room**

## Transmitter Information and Data

The antenna conducted output power, power spectral density, and 20-dB bandwidth were measured at three frequencies in the band of operation. The data reported below represents the worst-case operational conditions.

Frequency MHz	Antenna Conducted Output Power dBm (mW)	Occupied Bandwidth MHz	Power Spectral Density dBm
2412	26.67 (465 mW)	16.54	1.67
2442	26.83 (482 mW)	16.67	0.67
2472	26.50 (447 mW)	16.54	-1.67



NVLAP Lab Code 200087-0

Radiated Emissions from EUT Data (12 dBi Omni)

Frequency in MHz	FSM Horz. (dB $\mu$ V)	FSM Vert. (dB $\mu$ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dB $\mu$ V/m)	RFS Vert. @ 3m (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2412.0	72.0	83.3	32.8	0	104.8	116.1	--
4824.0	21.6	21.8	41.4	30	33.0	33.2	54.0
7236.0	20.5	21.6	36.0	30	26.5	27.6	54.0
9648.0	19.5	21.8	38.1	30	27.6	29.9	54.0
12060.0	19.5	19.9	40.0	30	29.5	29.9	54.0
2442.0	70.3	82.3	33.2	0	103.5	115.5	--
4884.0	19.3	20.8	41.2	30	30.5	32.0	54.0
7326.0	19.2	22.5	36.3	30	25.5	28.8	54.0
9768.0	20.5	21.6	38.2	30	28.7	29.8	54.0
12210.0	20.6	21.5	40.2	30	30.8	31.7	54.0
2472.0	69.9	81.7	33.4	0	103.3	115.1	--
4944.0	18.2	23.0	42.1	30	30.3	35.1	54.0
7416.0	19.6	21.0	36.6	30	26.2	27.6	54.0
9888.0	20.9	20.8	38.3	30	29.2	29.1	54.0
12360.0	19.3	21.1	40.4	30	29.7	31.5	54.0
Band Edge Compliance							
2400.0	46.0	49.8	32.9	30	48.9	52.7	54.0
2483.5	47.2	47.9	33.3	30	50.5	51.2	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 30 of 39  
Date: August 25, 2008

**Radiated Emissions from EUT Data (19 dBi Panel)**

Frequency in MHz	FSM Horz. (dB $\mu$ V)	FSM Vert. (dB $\mu$ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dB $\mu$ V/m)	RFS Vert. @ 3m (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2412.0	88.7	93.7	32.8	0	121.5	126.5	--
4824.0	23.3	31.7	41.4	30	34.7	43.1	54.0
7236.0	21.1	23.3	36.0	30	27.1	29.3	54.0
9648.0	20.5	21.8	38.1	30	28.6	29.9	54.0
12060.0	19.5	21.3	40.0	30	29.5	31.3	54.0
2442.0	87.3	92.3	33.2	0	120.5	125.5	--
4884.0	23.5	32.0	41.2	30	34.7	43.2	54.0
7326.0	22.1	22.3	36.3	30	28.4	28.6	54.0
9768.0	20.1	21.3	38.2	30	28.3	29.5	54.0
12210.0	19.0	21.6	40.2	30	29.2	31.8	54.0
2472.0	87.1	92.3	33.4	0	120.5	125.7	--
4944.0	21.5	31.1	42.1	30	33.6	43.2	54.0
7416.0	21.3	23.5	36.6	30	27.9	30.1	54.0
9888.0	19.5	22.5	38.3	30	27.8	30.8	54.0
12360.0	18.0	22.0	40.4	30	28.4	32.4	54.0
<b>Band Edge Compliance</b>							
2400.0	46.4	50.1	32.9	30	49.3	53.0	54.0
2483.5	47.2	48.4	33.3	30	50.5	51.7	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

**Radiated Emissions from EUT Data (24 dBi Grid)**

Frequency in MHz	FSM Horz. (dB $\mu$ V)	FSM Vert. (dB $\mu$ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dB $\mu$ V/m)	RFS Vert. @ 3m (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2412.0	84.7	94.5	32.8	0	117.5	127.3	--
4824.0	22.8	31.7	41.4	30	34.2	43.1	54.0
7236.0	21.0	23.0	36.0	30	27.0	29.0	54.0
9648.0	19.3	22.7	38.1	30	27.4	30.8	54.0
12060.0	18.8	23.0	40.0	30	28.8	33.0	54.0
2442.0	83.7	94.7	33.2	0	116.9	127.9	--
4884.0	29.1	35.5	41.2	30	40.3	46.7	54.0
7326.0	22.8	23.1	36.3	30	29.1	29.4	54.0
9768.0	19.3	20.0	38.2	30	27.5	28.2	54.0
12210.0	20.3	20.7	40.2	30	30.5	30.9	54.0
2472.0	82.0	94.5	33.4	0	115.4	127.9	--
4944.0	22.1	32.7	42.1	30	34.2	44.8	54.0
7416.0	22.0	22.3	36.6	30	28.6	28.9	54.0
9888.0	21.0	21.3	38.3	30	29.3	29.6	54.0
12360.0	21.0	22.0	40.4	30	31.4	32.4	54.0
<b>Band Edge Compliance</b>							
2400.0	48.2	50.0	32.9	30	51.1	52.9	54.0
2483.5	47.1	48.4	33.3	30	50.4	51.7	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

***Summary of Results for Radiated Emissions of Intentional Radiator***

The EUT had the highest radiated emission of 127.9 dB $\mu$ V/m at 3 meters at the fundamental frequency of operation utilizing the dish antenna. The EUT had a worst-case of 7.3 dB margin below the limit for the harmonic emissions. The EUT had a worst-case of 1.0 dB margin below the limit at band edges. The radiated emissions for the EUT meet the requirements for FCC Part 15.247 Intentional Radiators. There are no measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the FCC Limits. The specifications of 15.247 were met; there are no deviations or exceptions to the requirements.

***Statement of Modifications and Deviations***

No modifications to the EUT were required for the unit to meet the FCC Part 15C emissions standards. There were no deviations to the specifications.



NVLAP Lab Code 200087-0

## Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment List.
- Annex C Rogers Qualifications.
- Annex D FCC Site Registration Letter.

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 34 of 39  
Date: August 25, 2008

## Annex A Measurement Uncertainty Calculations

### Radiated Emissions Measurement Uncertainty Calculation

Measurement of vertically polarized radiated field strength over the frequency range 30 MHz to 1 GHz on an open area test site at 3m and 10m includes following uncertainty:

Contribution	Probability	Uncertainty
	Distribution	(dB)
Antenna factor calibration	normal (k = 2)	±0.58
Cable loss calibration	normal (k = 2)	±0.2
Receiver specification	rectangular	±1.0
Antenna directivity	rectangular	±0.1
Antenna factor variation with height	rectangular	±2.0
Antenna factor frequency interpolation	rectangular	±0.1
Measurement distance variation	rectangular	±0.2
Site Imperfections	rectangular	±1.5

Combined standard uncertainty  $u_c(y)$  is

$$U_c(y) = \pm \sqrt{\left[\frac{1.0}{2}\right]^2 + \left[\frac{0.2}{2}\right]^2 + \left[\frac{1.0^2 + 0.1^2 + 2.0^2 + 0.1^2 + 0.2^2 + 1.5^2}{3}\right]}$$

$$U_c(y) = \pm 1.6 \text{ dB}$$

It is probable that  $u_c(y) / s(q_k) > 3$ , where  $s(q_k)$  is estimated standard deviation from a sample of  $n$  readings unless the repeatability of the EUT is particularly poor, and a coverage factor of  $k = 2$  will ensure that the level of confidence will be approximately 95%, therefore:

$$s(q_k) = \sqrt{\frac{1}{(n-1)} \sum_{k=1}^n (q_k - \bar{q})^2}$$

$$U = 2 U_c(y) = 2 \times \pm 1.6 \text{ dB} = \pm 3.2 \text{ dB}$$

Notes:

- 1.1 Uncertainties for the antenna and cable were estimated, based on a normal probability distribution with  $k = 2$ .
- 1.2 The receiver uncertainty was obtained from the manufacturer's specification for which a rectangular distribution was assumed.
- 1.3 The antenna factor uncertainty does not take account of antenna directivity.
- 1.4 The antenna factor varies with height and since the height was not always the same in use as when the antenna was calibrated an additional uncertainty is added.
- 1.5 The uncertainty in the measurement distance is relatively small but has some effect on the received signal strength. The increase in measurement distance as the antenna height is increased is an inevitable consequence of the test method and is therefore not considered a contribution to uncertainty.
- 1.6 Site imperfections are difficult to quantify but may include the following contributions:
  - Unwanted reflections from adjacent objects.
  - Ground plane imperfections: reflection coefficient, flatness, and edge effects.
  - Losses or reflections from "transparent" cabins for the EUT or site coverings.
  - Earth currents in antenna cable (mainly effect biconical antennas).

The specified limits for the difference between measured site attenuation and the theoretical value ( $\pm 4$  dB) were not included in total since the measurement of site attenuation includes uncertainty contributions already allowed for in this budget, such as antenna factor.



NVLAP Lab Code 200087-0

### Conducted Measurements Uncertainty Calculation

Measurement of conducted emissions over the frequency range 9 kHz to 30 MHz includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Receiver specification	rectangular	±1.5
LISN coupling specification	rectangular	±1.5
Cable and input attenuator calibration	normal (k=2)	±0.5

Combined standard uncertainty  $u_c(y)$  is

$$U_c(y) = \pm \sqrt{\left[\frac{0.5}{2}\right]^2 + \frac{1.5^2 + 1.5^2}{3}}$$

$$U_c(y) = \pm 1.2 \text{ dB}$$

As with radiated field strength uncertainty, it is probable that  $u_c(y) / s(qk) > 3$  and a coverage factor of  $k = 2$  will suffice, therefore:

$$U = 2 U_c(y) = 2 \times \pm 1.2 \text{ dB} = \pm 2.4 \text{ dB}$$

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 36 of 39  
Date: August 25, 2008



NVLAP Lab Code 200087-0

## **Annex B Test Equipment List For Rogers Labs, Inc.**

The test equipment used is maintained in calibration and good operating condition. Use of this calibrated equipment ensures measurements are traceable to national standards.

List of Test Equipment	Calibration Date
Oscilloscope Scope: Tektronix 2230	2/08
Wattmeter: Bird 43 with Load Bird 8085	2/08
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140	2/08
H/V Power Supply: Fluke Model: 408B (SN: 573)	2/08
R.F. Generator: HP 606A	2/08
R.F. Generator: HP 8614A	2/08
R.F. Generator: HP 8640B	2/08
Spectrum Analyzer: HP 8562A,	5/08
Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W	
HP Adapters: 11518, 11519, 11520	
Spectrum Analyzer: HP 8591EM	5/08
Frequency Counter: Leader LDC825	2/08
Antenna: EMCO Biconilog Model: 3143	5/08
Antenna: EMCO Log Periodic Model: 3147	10/07
Antenna: Antenna Research Biconical Model: BCD 235	10/07
Antenna: EMCO Dipole Set 3121C	2/08
Antenna: C.D. B-101	2/08
Antenna: Solar 9229-1 & 9230-1	2/08
Antenna: EMCO 6509	2/08
Audio Oscillator: H.P. 201CD	2/08
R.F. Power Amp 65W Model: 470-A-1010	2/08
R.F. Power Amp 50W M185- 10-501	2/08
R.F. PreAmp CPPA-102	2/08
LISN 50 $\mu$ Hy/50 ohm/0.1 $\mu$ f	10/07
LISN Compliance Eng. 240/20	2/08
LISN Fischer Custom Communications FCC-LISN-50-16-2-08	2/08
Peavey Power Amp Model: IPS 801	2/08
Power Amp A.R. Model: 10W 1010M7	2/08
Power Amp EIN Model: A301	2/08
ELGAR Model: 1751	2/08
ELGAR Model: TG 704A-3D	2/08
ESD Test Set 2010i	2/08
Fast Transient Burst Generator Model: EFT/B-101	2/08
Current Probe: Singer CP-105	2/08
Current Probe: Solar 9108-1N	2/08
Field Intensity Meter: EFM-018	2/08
KEYTEK Ecat Surge Generator	2/08
Shielded Room 5 M x 3 M x 3.0 M	

**Annex C Qualifications****SCOT D. ROGERS, ENGINEER****ROGERS LABS, INC.**

Mr. Rogers has approximately 17 years experience in the field of electronics. Six years working in the automated controls industry and 6 years working with the design, development and testing of radio communications and electronic equipment.

**POSITIONS HELD:**


Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

**EDUCATIONAL BACKGROUND:**

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

  
Scot D. Rogers



NVLAP Lab Code 200087-0

**Annex D FCC Site Registration Letter**

**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

June 18, 2008

Registration Number: 90910

Rogers Labs, Inc.  
4405 West 259th Terrace,  
Louisburg, KS 66053


Attention: Scot Rogers

Re: Measurement facility located at Louisburg  
3 & 10 meter site  
Date of Renewal: June 18, 2008

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,  
  
Phyllis Parish  
Industry Analyst

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214

Revision 1

LigoWave LLC  
Model: WMR200  
Test #: 080824  
Test to: FCC (15.247), RSS-210  
File: LigoWave WMR200 TestRpt

FCC ID#: VKV-WMR200  
IC: 7607A-WMR200  
SN: ENG1  
Page 39 of 39  
Date: August 25, 2008