



[www.nemko.com](http://www.nemko.com)



**Test Report:** 88001-1TRFWL

**Applicant:** Riga Dev.Com Inc  
30 Kern Rd. Suite 202  
Toroton, ON  
M3B 1T1 Canada

**Apparatus:** WiSE250

**FCC ID:** VFH-WISE250

**In Accordance With:** FCC Part 15 Subpart C, 15.247  
FHSS System and Digitally Modulated Radiators  
902-928MHz, 2400 - 2483.5 MHz, 5725-5850MHz

**Tested By:** Nemko Canada Inc.  
303 River Road  
Ottawa, Ontario  
K1V 1H2

**Authorized By:**   
Jin Xu, Wireless Specialist

**Date:** September 11, 2007

**Total Number of Pages:** 30

## Report Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

The assessment summary is as follows:

<b>Apparatus Assessed:</b>	WiSE250
<b>Specification:</b>	FCC Part 15 Subpart C, 15.247
<b>Compliance Status:</b>	Complies
<b>Exclusions:</b>	None
<b>Non-compliances:</b>	None
<b>Report Release History:</b>	Original Release

Author: Heng Lin    EMC / Wireless Specialist

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025.

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

---

## TABLE OF CONTENTS

<b>Report Summary</b> .....	<b>2</b>
<b>Section 1 : Equipment Under Test</b> .....	<b>4</b>
1.1 Product Identification .....	4
1.2 Samples Submitted for Assessment.....	4
1.3 Technical Specifications of the EUT .....	4
1.4 Block Diagram of Test Setup .....	5
<b>Section 2 : Test Conditions</b> .....	<b>6</b>
2.1 Specifications .....	6
2.2 Deviations From Laboratory Test Procedures .....	6
2.3 Test Environment .....	6
2.4 Test Equipment.....	6
<b>Section 3 : Observations</b> .....	<b>7</b>
3.1 Modifications Performed During Assessment .....	7
3.2 Record Of Technical Judgements .....	7
3.3 EUT Parameters Affecting Compliance .....	7
3.4 Test Deleted.....	7
3.5 Additional Observations .....	7
<b>Section 4 : Results Summary</b> .....	<b>8</b>
4.1 FCC Part 15 Subpart C : Test Results .....	9
<b>Appendix A : Test Results</b> .....	<b>10</b>
Clause 15.207(a) Powerline Conducted Emissions .....	10
Clause 15.209(a) Radiated Emissions within Restricted Bands .....	12
Clause 15.247(a)(2) Systems using digital modulation techniques .....	16
Clause 15.247(b)(3) Maximum peak output power of systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands .....	19
Clause 15.247(d) Radiated Emissions Not in Restricted Bands .....	23
Clause 15.247(e) Power Spectral Density for Digitally Modulated Devices.....	26
<b>Appendix B : Setup Photographs</b> .....	<b>28</b>
<b>Appendix C : Block Diagram of Test Setups</b> .....	<b>30</b>

## Section 1 : Equipment Under Test

### 1.1 Product Identification

The Equipment Under Test was identified as follows:

WiSE250

### 1.2 Samples Submitted for Assessment

The following samples of the apparatus have been submitted for type assessment:


Sample No.	Description	Serial No.
1	WiSE250	None
3	WiSE250	None
	IBM Laptop (Type: 2647-9NU)	78-1VRMP
	AC Adaptor for IBM Laptop (P/N: 02K6657)	None

The first samples were received on: June 21, 2007

### 1.3 Technical Specifications of the EUT

<b>Operating Frequency:</b>	2405 MHz – 2480 MHz	
<b>Peak Output Power:</b>	3.62 dBm	
<b>Emission Designator</b>	G1D	
<b>Modulation:</b>	O-QPSK	
<b>Antenna Data:</b>	MMCX plug Whip Monopole:	0 dBi
	MMCX to RP-SMA Dipole:	3.2 dBi
<b>Antenna Connector:</b>	Detachable Antenna MMCX plug Whip Monopole & MMCX to RP-SMA Dipole	
<b>Power Source</b>	3.3VDC	

### 1.4 Block Diagram of Test Setup



## Section 2 : Test Conditions

### 2.1 Specifications

The apparatus was assessed against the following specifications:

FCC Part 15 Subpart C, 15.247

FHSS System and Digitally Modulated Radiators  
902-928MHz, 2400 - 2483.5 MHz, 5725-5850MHz

### 2.2 Deviations From Laboratory Test Procedures

No deviations were made from laboratory test procedures.

### 2.3 Test Environment

All tests were performed under the following environmental conditions:

Temperature range : 15 – 30 °C  
Humidity range : 20 - 75 %  
Pressure range : 86 - 106 kPa  
Power supply range : +/- 5% of rated voltages

### 2.4 Test Equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Next Cal.
Receiver/Spectrum Analyzer	Rohde & Schwarz	ESU	FA002043	Oct. 24/07
LISN	Rohde & Schwarz	ENV216	FA002023	Sep. 04/08
Spectrum Analyzer	Rohde & Schwarz	FSU	FA001877	Jan. 16/08
Receiver	Rohde & Schwarz	ESVS-30	FA001445	July 14/07
Biconical (2) Antenna	EMCO	3109	FA000904	Sept. 12/07
Log Periodic Antenna #1	EMCO	LPA-25	FA000477	Sept. 12/07
Horn Antenna #1	EMCO	3115	FA000649	Feb. 26/08
Horn Antenna #2	EMCO	3115	FA000825	Jan. 30/08
Horn 18 – 26.5 GHz	Electro-Metrics	SH-50/60-1	FA000479	COU
1.0 – 2.0 GHz Amplifier	JCA	12-400	FA001498	Aug. 02/07
2.0 – 4.0 GHz Amplifier	JCA	24-600	FA001496	Aug. 02/07
4.0 – 8.0 GHz Amplifier	JCA	48-600	FA001497	Aug. 02/07
5.0 – 18.0 GHz Amplifier	NARDA	DWT-186N23U40	FA001409	COU
18.0 – 26.0 GHz Amplifier	NARDA	BBS-1826N612	FA001550	COU

COU – Calibrate on Use

NCR – No Calibration Required

## **Section 3 : Observations**

### **3.1 Modifications Performed During Assessment**

No modifications were performed during assessment.

### **3.2 Record Of Technical Judgements**

No technical judgements were made during the assessment.

### **3.3 EUT Parameters Affecting Compliance**

The user of the apparatus could not alter parameters that would affect compliance.

### **3.4 Test Deleted**

No Tests were deleted from this assessment.

### **3.5 Additional Observations**

There were no additional observations made during this assessment.

## **Section 4 : Results Summary**

This section contains the following:

FCC Part 15 Subpart C : Test Results

The column headed 'Required' indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

- N No : not applicable / not relevant.
- Y Yes : Mandatory i.e. the apparatus shall conform to these tests.
- N/T Not Tested, mandatory but not assessed. (See section 3.4 Test deleted)

The results contained in this section are representative of the operation of the apparatus as originally submitted.

**4.1 FCC Part 15 Subpart C : Test Results**

Part 15	Test Description	Required	Result
15.31(e)	Variation of power supply	Y	PASS
15.207(a)	Powerline Conducted Emissions	Y	PASS
15.209(a)	Radiated Emissions within Restricted Bands	Y	PASS
15.247(a)(1)	Frequency hopping systems	N	
15.247(a)(1)(i)	Frequency hopping systems operating in the 902-928 MHz band	N	
15.247(a)(1)(ii)	Frequency hopping systems operating in the 5725-5850 MHz band	N	
15.247(a)(1)(iii)	Frequency hopping systems operating in the 2400-2483.5 MHz band	N	
15.247(a)(2)	Systems using digital modulation techniques	Y	PASS
15.247(b)(1)	Maximum peak output power of Frequency hopping systems operating in the 2400-2483.5 MHz band and 5725-5850 MHz band	N	
15.247(b)(2)	Maximum peak output power of Frequency hopping systems operating in the 902-928 MHz band	N	
15.247(b)(3)	Maximum peak output power of systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands	Y	PASS
15.247(b)(4)	Maximum peak output power	Y	PASS
15.247(c)(1)	Fixed point-to-point Operation with directional antenna gains greater than 6 dBi	N	
15.247(c)(2)	Transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams	N	
15.247(d)	Radiated Emissions Not in Restricted Bands	Y	PASS
15.247(e)	Power Spectral Density for Digitally Modulated Devices	Y	PASS
15.247(f)	Time of Occupancy for Hybrid Systems	N	

Notes:

## Appendix A : Test Results

### Clause 15.207(a) Powerline Conducted Emissions

Frequency of Conducted limit (dBuV)		
Emission (MHz)	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### Test Conditions:


<b>Sample Number:</b>	1, 3	<b>Temperature:</b>	20 °C
<b>Date:</b>	September 11, 2007	<b>Humidity:</b>	40 %
<b>Modification State:</b>	0	<b>Tester:</b>	Heng Lin
		<b>Laboratory:</b>	Ottawa

**Test Results:** See Attached Plots.


### Additional Observations:

All measurements for conducted emissions were performed using a Peak detector, Average detector and Quasi-Peak detector with 9 kHz RBW.

AC Mains Phase Line – 120VAC, 60Hz



AC Mains Neutral Line – 120VAC, 60Hz



**Clause 15.209(a) Radiated Emissions within Restricted Bands**

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvoltmeter)	Measurement Distance (meters)
0.009-0.490	2400/F (kHz)	300
0.490-1.705	24000/F (kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**Test Conditions:**

<b>Sample Number:</b>	3	<b>Temperature (°C):</b>	20
<b>Date:</b>	June 29, 2007	<b>Humidity (%):</b>	40
<b>Modification State:</b>	0	<b>Tester:</b>	Heng Lin
		<b>Laboratory:</b>	Ottawa

**Test Results:**

See Attached Table for Results

**Additional Observations:**


The Spectrum was searched from 30MHz to the 10<sup>th</sup> Harmonic.

These results apply to emissions found in the Restricted Bands defined in FCC Part 15 Subpart C, 15.205.


All measurements for radiated emissions within the restricted bands were performed using a Peak detector with 100 kHz RBW / VBW below 1 GHz and a Peak Detector with 1 MHz RBW / VBW above 1 GHz.

Frequency (MHz)	Ant	Pol. V/H	RCVD Signal (dBµV/m)	Ant. Factor (dB)	Amp. Gain (dB)	Duty Cycle Corr.	Cable Loss (dB)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
4810.0000	Horn2	H	69.7	33.3	55.5	-11.4	8.3	55.8	74.0	18.2	Peak
							8.3	44.4	54.0	9.6	Average
4810.0000	Horn2	V	72.2	33.4	55.5	-11.4	8.3	58.4	74.0	15.6	Peak
							8.3	47.0	54.0	7.0	Average
4890.0000	Horn2	H	69.2	33.3	55.3	-11.4	8.5	55.7	74.0	18.3	Peak
							8.5	44.3	54.0	9.7	Average
4890.0000	Horn2	V	70.9	33.4	55.3	-11.4	8.5	57.5	74.0	16.5	Peak
							8.5	46.1	54.0	7.9	Average
4960.0000	Horn2	H	67.3	33.3	55.0	-11.4	8.6	54.2	74.0	19.8	Peak
							8.6	42.8	54.0	11.2	Average
4960.0000	Horn2	V	68.2	33.4	55.0	-11.4	8.6	55.2	74.0	18.8	Peak
							8.6	43.8	54.0	10.2	Average

Duty Cycle:




Date: 24.AUG.2007 10:07:04



Date: 24.AUG.2007 10:07:56

This is representative of normal operation. The maximum theoretical duty cycle is 27%. Therefore peak emissions were averaged using a duty cycle of 27% (-11.4dB).

**Delta Marker Measurement for 2.4835MHz Band Edge**



Date: 29.JUN.2007 10:00:07

Measured Field Strength for High Channel in 1 MHz RBW = 100.7 dBμV/m

Delta Marker = -35.84 dB

Therefore, Peak Field Strength = 100.7 dBμV/m – 35.84 dB = 64.86 dBμV/m

Limit = 74 dBμV/m

Average Field Strength = 64.86 dBμV/m – 11.4dB (Duty Cycle) = 53.46 dBμV/m

Limit = 54 dBμV/m

**Clause 15.247(a)(2) Systems using digital modulation techniques**

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

**Test Conditions:**


<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	20
<b>Date:</b>	June 28, 2007	<b>Humidity (%):</b>	45
<b>Modification State:</b>	0	<b>Tester:</b>	Heng Lin
		<b>Laboratory:</b>	Ottawa

**Test Results:**

**6dB Bandwidth:**


Channel (MHz)	Low 2405	Mid 2445	High 2480
<b>Bandwidth (MHz)</b>	1.78	1.58	1.66

**Low Channel**



Date: 28.JUN.2007 15:07:25

Mid Channel




Date: 28.JUN.2007 15:06:36

High Channel



Date: 28.JUN.2007 15:08:48

99% Occupied Bandwidth:



Date: 29.JUN.2007 13:36:46

**Clause 15.247(b)(3) Maximum peak output power of systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands**

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

**Test Conditions:**

<b>Sample Number:</b>	1, 3	<b>Temperature (°C):</b>	20
<b>Date:</b>	June 28, 2007	<b>Humidity (%):</b>	45
<b>Modification State:</b>	0	<b>Tester:</b>	Heng Lin
		<b>Laboratory:</b>	Ottawa

**Test Results:**

See Attached Table and Plots.

**Conducted Output Power:**

The output power was measured at +/-15% of the supply voltage and found that there was no change.

Note: The EUT was modified by the manufacturer to perform conducted measurements.

Channel Range	Measured Output Power	
	dBm	(W)
Low (2405 MHz)	3.04	0.0020
Mid (2445 MHz)	3.62	0.0023
High (2480 MHz)	2.68	0.0019


For Monopole antenna:

Measured output power = 3.62 dBm  
 Maximum output power = 3.62 dBm + 0 dBi = 3.62 dBm (EIRP)  
 Limit = 36 dBm (EIRP)

For Dipole antenna:


Measured output power = 3.62 dBm  
 Maximum output power = 3.62 dBm + 3.2 dBi = 6.82 dBm (EIRP)  
 Limit = 36 dBm (EIRP)

Low Channel:




Date: 28.JUN.2007 15:05:03

Mid Channel:



Date: 28.JUN.2007 15:05:39

High Channel:



Date: 28.JUN.2007 15:04:28

**Radiated Output Power:**

With Monopole Antenna:

Ch.	Freq.	Pol V/H	ANT.	Rx dBuV	Cable loss dB	Ant Factor dB/m	F.S. dBuV/m
low	2405.0000	Horn2	V	66.2	5.4	28.4	98.9
	2405.0000	Horn2	H	58.2	5.4	28.5	95.8
mid	2445.0000	Horn2	V	66.9	5.4	28.4	97.9
	2445.0000	Horn2	H	58.7	5.4	28.5	94.0
hi	2480.0000	Horn2	V	67.2	5.5	28.4	98.6
	2480.0000	Horn2	H	56.2	5.5	28.5	95.2

With Dipole Antenna:

Ch.	Freq.	Pol V/H	ANT.	Rx dBuV	Cable loss dB	Ant Factor dB/m	F.S. dBuV/m
low	2405.0000	Horn2	V	66.2	5.4	28.4	100.0
	2405.0000	Horn2	H	58.2	5.4	28.5	92.1
mid	2445.0000	Horn2	V	66.9	5.4	28.4	100.7
	2445.0000	Horn2	H	58.7	5.4	28.5	92.6
hi	2480.0000	Horn2	V	67.2	5.5	28.4	101.1
	2480.0000	Horn2	H	56.2	5.5	28.5	90.2

Measured value (V/m) =  $10^{(FS/20)} = 0.1135$  V/m

Antenna Gain (numeric) =  $10^{(Ag/10)} = 2.0893$

Output Power (W) =  $\frac{E^2 R^2}{30G} = 0.00184$  W

E = Measured Value (V/m)

R = Measurement distance

G = Antenna Gain (numeric)

**Additional Observations:**

All Measurements were performed at 3m using a 3MHz RBW/VBW.

**Clause 15.247(d) Radiated Emissions Not in Restricted Bands**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	22
<b>Date:</b>	June 28, 2007	<b>Humidity (%):</b>	45
<b>Modification State:</b>	0	<b>Tester:</b>	Heng Lin
		<b>Laboratory:</b>	Ottawa

**Test Results:**


See Attached Plots.

**Lower Band Edge:**




Date: 28.JUN.2007 15:18:36

Upper Band Edge:




Date: 28.JUN.2007 15:16:59

Conducted Emissions  
Low Channel: (2405 MHz)




Date: 28.JUN.2007 15:36:09

Mid Channel: (2445 MHz)



Date: 28.JUN.2007 15:33:35

High Channel: (2480MHz)



Date: 28.JUN.2007 15:32:10

**Clause 15.247(e) Power Spectral Density for Digitally Modulated Devices**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	22
<b>Date:</b>	June 29, 2007	<b>Humidity (%):</b>	45
<b>Modification State:</b>	0	<b>Tester:</b>	Heng Lin
		<b>Laboratory:</b>	Ottawa

**Test Results:**


See Attached Plots.

**Power Spectral Density  
Low Channel: (2405 MHz)**




Date: 3.JUL.2007 15:18:01

Mid Channel: (2445 MHz)



Date: 3.JUL.2007 15:53:11

High Channel: (2480 MHz)



Date: 3.JUL.2007 16:44:23


## Appendix B : Setup Photographs

### Conducted Emissions Setup:



### Spurious Emissions Setup:

With RP-SMA Dipole antenna




With Whip Monopole antenna



### Appendix C : Block Diagram of Test Setups

#### Test Site For Radiated Emissions



#### Conducted Emissions

