

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666
Fax: +86 (0) 21 6191 5678
ee.shanghai@sgs.comReport No.: SHEMA180700569104
Page: 1 of 13

1 Cover Page

RF MPE REPORT

Application No.:	SHEMA1807005691CR
Applicant:	Voxx Accessories Corporation
FCC ID:	VIXHSDB2
IC:	21578-HSDB2
Equipment Under Test (EUT):	
NOTE: The following sample(s) was/were submitted and identified by the client as	
Product Name:	Video Doorbell
Model No.(EUT):	HSDB2
Standards:	FCC Rules 47 CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v06 RSS-102 Issue 5 (March 2015)
Date of Receipt:	2018-07-13
Date of Test:	2018-08-08 to 2018-08-09
Date of Issue:	2018-08-10
Test Result:	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.




Parlam Zhan
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2018-08-13	/

Authorized for issue by:			
		 _____ Vincent Zhu / Project Engineer	
		 _____ Parlam Zhan /Reviewer	

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.1 GENERAL DESCRIPTION OF E.U.T.....	4
3.2 TECHNICAL SPECIFICATIONS.....	4
3.3 TEST LOCATION	7
3.4 TEST FACILITY	7
4 TEST STANDARDS AND LIMITS	8
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:.....	8
4.2 IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:.....	8
5 MEASUREMENT AND CALCULATION	9
5.1 MAXIMUM TRANSMIT POWER	9
5.2 MPE CALCULATION	13

3 General Information

3.1 Client Information

Applicant:	Voxx Accessories Corporation
Address of Applicant:	3502 Woodview Trace, Suite 220, Indianapolis, Indiana 46268
Manufacturer:	Voxx Accessories Corporation
Address of Manufacturer:	3502 Woodview Trace, Suite 220, Indianapolis, Indiana 46268

3.1 General Description of E.U.T.

Power supply:	AC 8~24V
Test voltage:	AC 12V

3.2 Technical Specifications

2.4G:

Antenna Gain	0.5 dBi
Antenna Type	Integral
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz

5G:

Antenna Gain	1 dBi
Antenna Type	Integral Antenna
DFS Function	Slave without Radar detection
TPC Function	Not Support

Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	UNII Band I	802.11a/n(HT20)/ac(HT20)	5180-5240	4
		802.11n(HT40)/ac(HT40)	5190-5230	2
		802.11ac(HT80)	5210	1
	UNII Band II-A	802.11a/n(HT20)/ac(HT20)	5260-5320	4
		802.11n(HT40)/ac(HT40)	5270-5310	2
		802.11ac(HT80)	5290	1
	UNII Band II-C	802.11a/n(HT20)/ac(HT20)	5500-5700	11
		802.11n(HT40)/ac(HT40)	5510-5670	5
		802.11ac(HT80)	5530~5610	2
	UNII Band III	802.11a/n(HT20)/ac(HT20)	5745-5825	5
		802.11n(HT40)/ac(HT40)	5755-5795	2
		802.11ac(HT80)	5775	1
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)			
Channel Spacing:	802.11a/n(HT20)/ac(HT20): 20MHz 802.11n(HT40)/ac(HT40): 40MHz 802.11ac(HT80): 80MHz			
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0-15 802.11ac: MCS0-9			

Selected Test Channel for 802.11a/n(HT20)/ac(HT20)		
Band	Channel	Frequency
U-NII Band I	The lowest channel (CH36)	5180MHz
	The middle channel (CH40)	5200MHz
	The highest channel (CH48)	5240MHz
U-NII Band II-A	The lowest channel (CH52)	5260MHz
	The middle channel (CH60)	5300MHz
	The highest channel (CH64)	5320MHz
U-NII Band II-C	The lowest channel (CH100)	5500MHz
	The middle channel (CH120)	5600MHz
	The highest channel (CH140)	5700MHz
U-NII Band III	The lowest channel (CH149)	5745MHz
	The middle channel (CH157)	5785MHz
	The highest channel (CH165)	5825MHz

Selected Test Channel for 802.11n(HT40)/ac(HT40)		
Band	Channel	Frequency
U-NII Band I	The lowest channel (CH38)	5190MHz
	The highest channel (CH46)	5230MHz
U-NII Band II-A	The lowest channel (CH54)	5270MHz
	The highest channel (CH62)	5310MHz
U-NII Band II-C	The lowest channel (CH102)	5510MHz
	The middle channel (CH118)	5590MHz
	The highest channel (CH134)	5670MHz
U-NII Band III	The lowest channel (CH151)	5755MHz
	The highest channel (CH159)	5795MHz

Selected Test Channel for 802.11ac(HT80)		
Band	Channel	Frequency
U-NII Band I	One channel (CH42)	5210MHz
U-NII Band II-A	One channel (CH58)	5290MHz
U-NII Band II-C	The lowest channel (CH106)	5530MHz
	The middle channel (CH122)	5610MHz
U-NII Band III	One channel (CH155)	5775MHz

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868,C-4336,T-12221,G-10830 respectively.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

4.2 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W

For 5G device, the limit of worse case is 4.53W

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM180700569101-2.4GHz.

Test mode	Test Frequency (MHz)	Average Power (dBm)	Average Power (mW)
802.11b	2412	17.22	52.72
	2437	17.10	51.29
	2462	17.02	50.35
802.11g	2412	16.15	41.21
	2437	15.35	34.28
	2462	15.59	36.22
802.11 n(HT20)	2412	16.22	41.88
	2437	17.36	54.45
	2462	17.08	51.05
802.11 n(HT40)	2422	15.67	36.90
	2437	15.56	35.97
	2452	15.45	35.08

The Power Data is based on the RF Test Report SHEM180700569102-5GHz.

FCC

Test Mode	Test Channel	Level [dBm]	Power [dBm]	Power [mW]
11A	5180	17.06	17.44	55.46
11A	5220	16.14	16.52	44.87
11A	5240	16.24	16.61	45.81
11A	5260	16.32	16.69	46.67
11A	5280	16.55	16.92	49.20
11A	5320	16.53	16.91	49.09
11A	5500	16.31	16.68	46.56
11A	5600	16.11	16.48	44.46
11A	5700	15.66	16.04	40.18
11A	5745	15.83	16.20	41.69
11A	5785	15.69	16.07	40.46
11A	5825	15.74	16.12	40.93
11N20	5180	15.94	17.12	51.52
11N20	5220	15.12	16.30	42.66
11N20	5240	15.09	16.28	42.46
11N20	5260	15.21	16.39	43.55

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

11N20	5280	15.36	16.55	45.19
11N20	5320	15.54	16.73	47.10
11N20	5500	14.99	16.17	41.40
11N20	5600	15.09	16.28	42.46
11N20	5700	14.54	15.73	37.41
11N20	5745	14.7	15.88	38.73
11N20	5785	14.71	15.90	38.90
11N20	5825	14.54	15.72	37.33
11N40	5190	13.96	17.03	50.47
11N40	5230	13.78	16.86	48.53
11N40	5270	14.11	17.19	52.36
11N40	5310	14.4	17.48	55.98
11N40	5510	13.56	16.64	46.13
11N40	5590	13.54	16.61	45.81
11N40	5670	13.43	16.51	44.77
11N40	5755	13.51	16.59	45.60
11N40	5795	13.43	16.72	46.99
11AC20	5180	14.95	17.19	52.36
11AC20	5220	13.97	16.22	41.88
11AC20	5240	14.08	16.33	42.95
11AC20	5260	14.17	16.42	43.85
11AC20	5280	14.31	16.56	45.29
11AC20	5320	14.43	16.68	46.56
11AC20	5500	14.03	16.28	42.46
11AC20	5600	14.05	16.30	42.66
11AC20	5700	13.52	15.77	37.76
11AC20	5745	13.69	16.06	40.36
11AC20	5785	13.51	15.76	37.67
11AC20	5825	13.62	15.87	38.64
11AC40	5190	14.07	16.89	48.87
11AC40	5230	14.19	17.02	50.35
11AC40	5270	14.17	16.99	50.00
11AC40	5310	14.6	17.44	55.46
11AC40	5510	13.77	16.59	45.60
11AC40	5590	13.8	16.64	46.13

11AC40	5670	13.65	16.47	44.36
11AC40	5755	13.74	16.58	45.50
11AC40	5795	13.66	16.49	44.57
11AC80	5210	13.51	13.57	22.75
11AC80	5290	14.05	14.16	26.06
11AC80	5530	12.68	12.80	19.05
11AC80	5610	12.39	12.49	17.74
11AC80	5775	12.84	12.97	19.82

ISED

Test Mode	Test Channel	Conducted Power [dBm]	EIRP Power [dBm]	EIRP Power [mW]
11A	5180	17.44	18.44	69.82
11A	5220	16.52	17.52	56.49
11A	5240	16.61	17.61	57.68
11A	5260	16.69	17.69	58.75
11A	5280	16.92	17.92	61.94
11A	5320	16.91	17.91	61.80
11A	5500	16.68	17.68	58.61
11A	5600	16.48	17.48	55.98
11A	5700	16.04	17.04	50.58
11A	5745	16.20	17.2	52.48
11A	5785	16.07	17.07	50.93
11A	5825	16.12	17.12	51.52
11N20	5180	17.12	18.12	64.86
11N20	5220	16.30	17.3	53.70
11N20	5240	16.28	17.28	53.46
11N20	5260	16.39	17.39	54.83
11N20	5280	16.55	17.55	56.89
11N20	5320	16.73	17.73	59.29
11N20	5500	16.17	17.17	52.12
11N20	5600	16.28	17.28	53.46
11N20	5700	15.73	16.73	47.10
11N20	5745	15.88	16.88	48.75
11N20	5785	15.90	16.9	48.98
11N20	5825	15.72	16.72	46.99

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

11N40	5190	17.03	18.03	63.53
11N40	5230	16.86	17.86	61.09
11N40	5270	17.19	18.19	65.92
11N40	5310	17.48	18.48	70.47
11N40	5510	16.64	17.64	58.08
11N40	5590	16.61	17.61	57.68
11N40	5670	16.51	17.51	56.36
11N40	5755	16.59	17.59	57.41
11N40	5795	16.72	17.72	59.16
11AC20	5180	17.19	18.19	65.92
11AC20	5220	16.22	17.22	52.72
11AC20	5240	16.33	17.33	54.08
11AC20	5260	16.42	17.42	55.21
11AC20	5280	16.56	17.56	57.02
11AC20	5320	16.68	17.68	58.61
11AC20	5500	16.28	17.28	53.46
11AC20	5600	16.30	17.3	53.70
11AC20	5700	15.77	16.77	47.53
11AC20	5745	16.06	17.06	50.82
11AC20	5785	15.76	16.76	47.42
11AC20	5825	15.87	16.87	48.64
11AC40	5190	16.89	17.89	61.52
11AC40	5230	17.02	18.02	63.39
11AC40	5270	16.99	17.99	62.95
11AC40	5310	17.44	18.44	69.82
11AC40	5510	16.59	17.59	57.41
11AC40	5590	16.64	17.64	58.08
11AC40	5670	16.47	17.47	55.85
11AC40	5755	16.58	17.58	57.28
11AC40	5795	16.49	17.49	56.10
11AC80	5210	13.57	14.57	28.64
11AC80	5290	14.16	15.16	32.81
11AC80	5530	12.80	13.8	23.99
11AC80	5610	12.49	13.49	22.34
11AC80	5775	12.97	13.97	24.95

5.2 MPE Calculation

For 2.4G: The best case gain of the antenna is 0.5dBi. 0.5dB logarithmic terms convert to numeric result is nearly 1.12.

For 5G: The best case gain of the antenna is 1dBi. 1dB logarithmic terms convert to numeric result is nearly 1.26.

For 2.4GHz WiFi:

The Max Conducted average Output Power is 17.36dBm (54.45 mW)

For 5GHz WiFi:

The Max Conducted average Output Power is 17.48dBm (55.98 mW)

The Max EIRP Output Power is 18.48dBm (70.47 mW)

For FCC:

According to the formula $S = \frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note:

1) P (Watts) = Power Input to antenna = $10^{\frac{dBm}{10}} / 1000$

2) G (Antenna gain in numeric) = $10^{\frac{Antenna gain in dBi}{10}}$

3) R = distance to the center of radiation of antenna (in meter) = 20cm

4) MPE limit = 1mW/cm²

For 2.4GHz WiFi:

$$S = \frac{PG}{4R^2\pi} = \frac{54.45 \times 1.12}{4 \times 400 \times 3.14} = 0.012 \text{ mW/cm}^2$$

For 5GHz WiFi:

$$S = \frac{PG}{4R^2\pi} = \frac{55.98 \times 1.26}{4 \times 400 \times 3.14} = 0.014 \text{ mW/cm}^2$$

For IC:

For 2.4GHz WiFi:

$$E.I.R.P. = P \cdot G = 0.05445 \times 1.12 = 0.0609 \text{ W} < 2.68 \text{ W}$$

For 5GHz WiFi:

$$E.I.R.P. = 0.07047 \text{ W} < 4.5 \text{ W}$$

2.4GHz and 5GHz WiFi modules can't simultaneous transmitting, So, the device is exclusion from SAR test.

--End of the Report--