

FCC Test Report

Report No. : 1812C50319612501

Applicant : Ad Hoc Electronics, LLC

Address : 115 South State Street, Suite B, Lindon, Utah,
United States, 84042

Product Name : Wireless Switch

Report Date : 2025-07-11

Shenzhen Anbotek Compliance Laboratory Limited

Contents

| | |
|---|----|
| 1. General Information | 5 |
| 1.1. Client Information | 5 |
| 1.2. Description of Device (EUT) | 5 |
| 1.3. Auxiliary Equipment Used During Test | 6 |
| 1.4. Description of Test Configuration | 6 |
| 1.5. Additional Instructions | 6 |
| 1.5. Description of Test Setup | 6 |
| 1.6. Test Equipment List | 7 |
| 1.7. Measurement Uncertainty | 8 |
| 1.8. Description of Test Facility | 8 |
| 1.9. Disclaimer | 9 |
| 2. Summary of Test Results | 10 |
| 3. Conducted Emission Test | 11 |
| 3.1. Test Standard and Limit | 11 |
| 3.2. Test Setup | 11 |
| 3.3. Test Procedure | 11 |
| 3.4. Test Data | 11 |
| 4. Radiated Emission and Band Edge | 12 |
| 4.1. Test Standard and Limit | 12 |
| 4.2. Test Setup | 13 |
| 4.3. Test Procedure | 14 |
| 4.4. Test Data | 15 |
| 5. 20dB Bandwidth Test | 20 |
| 5.1. Test Standard and Limit | 20 |
| 5.2. Test Setup | 20 |
| 5.3. Test Procedure | 20 |
| 5.4. Test Data | 20 |
| 6. Antenna Requirement | 22 |
| 6.1. Test Standard and Requirement | 22 |
| 6.2. Antenna Connected Construction | 22 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH | 23 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH | 23 |
| APPENDIX III -- INTERNAL PHOTOGRAPH | 23 |

TEST REPORT

Applicant : Ad Hoc Electronics, LLC
Manufacturer : Ad Hoc Electronics, LLC
Product Name : Wireless Switch
Model No. : E9T-CDR
Trade Mark : N/A
Rating(s) : Input:3.3V== 20mA


Test Standard(s) : 47 CFR Part 15.249
Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15.249 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-06-07

Date of Test 2025-06-07 to 2025-07-03

Prepared by 

(Macy Ling)

Approved & Authorized Signer 

(Hugo Chen)

Revision History

| Report Version | Description | Issued Date |
|----------------|-----------------|-------------|
| R00 | Original Issue. | 2025-07-11 |
| | | |
| | | |

1. General Information

1.1. Client Information

| | | |
|--------------|---|--|
| Applicant | : | Ad Hoc Electronics, LLC |
| Address | : | 115 South State Street, Suite B, Lindon, Utah, United States |
| Manufacturer | : | Ad Hoc Electronics, LLC |
| Address | : | 115 South State Street, Suite B, Lindon, Utah, United States |

1.2. Description of Device (EUT)

| | | |
|--|---|---|
| Product Name | : | Wireless Switch |
| Model No. | : | E9T-CDR |
| Trade Mark | : | N/A |
| Test Power Supply | : | Self-generated when switch is pressed |
| Test Sample No. | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample) |
| Adapter | : | N/A |
| RF Specification | | |
| Operation Frequency | : | 902.875MHz |
| Number of Channel | : | 1 Channels |
| Modulation Type | : | FSK |
| Antenna Type | : | Single-stage antenna |
| Antenna Gain(Peak): | : | -1.72dBi |
| Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. | | |

1.3. Auxiliary Equipment Used During Test

| Title | Manufacturer | Model No. | Serial No. |
|-------|--------------|-----------|------------|
| / | / | / | / |

1.4. Description of Test Configuration

The engineering test program was provided and the EUT was programmed to be in transmitting mode.

| Channel | Freq.(MHz) |
|---------|------------|
| 01 | 902.875 |

1.5. Additional Instructions


Power level setup in software

By pressing to fire

Operation Band:

| Mode | Channel(MHz) | Power level | Transmitting type |
|------|--------------|-------------|-------------------|
| SRD | 902.875 | default | data pack TX |

1.5. Description of Test Setup



1.6. Test Equipment List

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|---|-----------------|-------------------|------------------|------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | Rohde & Schwarz | ENV216 | 100055 | 2024-09-09 | 1 Year |
| 2. | Three Phase V-type Artificial Power Network | CYBERTEK | EM5040DT | E215040DT00 1 | 2025-01-13 | 1 Year |
| 3. | EMI Test Receiver | Rohde & Schwarz | ESCI | 100627 | 2025-01-13 | 1 Year |
| 4. | EMI Test Receiver | Rohde & Schwarz | ESR26 | 101481 | 2025-01-14 | 1 Year |
| 5. | MXA Spectrum Analysis | Agilent | N9020A | MY51170037 | 2024-09-09 | 1 Year |
| 6. | EMI Preamplifier | SKET Electronic | LNPA-0118G- 45 | SKET-PA-002 | 2025-01-13 | 1 Year |
| 7. | Double Ridged Horn Antenna | SCHWARZBECK | BBHA 9120D | 02555 | 2022-10-16 | 3 Year |
| 8. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | 345 | 2022-10-23 | 3 Year |
| 9. | Loop Antenna(9K-30M) | Schwarzbeck | FMZB1519B | 00053 | 2024-09-12 | 1 Year |
| 10. | Horn Antenna | A-INFO | LB-180400-KF | J211060628 | 2024-01-22 | 3 Year |
| 11. | Pre-amplifier | SONOMA | 310N | 186860 | 2025-01-14 | 1 Year |
| 12. | EMI Test Software EZ-EMC | SHURPLE | N/A | N/A | N/A | N/A |
| 13. | MXA Spectrum Analysis | KEYSIGHT | N9020A | MY53280032 | 2024-09-09 | 1 Year |
| 14. | MXG RF Vector Signal Generator | Agilent | N5182A | MY47420647 | 2025-01-14 | 1 Year |
| 15. | Signal Generator | Agilent | E4421B | MY41000743 | 2025-02-21 | 1 Year |
| 16. | DC Power Supply | IVYTECH | IV3605 | 1804D360510 | 2024-09-09 | 1 Year |
| 17. | Constant Temperature Humidity Chamber | ZHONGJIAN | ZJ-KHWS80B | N/A | 2024-10-14 | 1 Year |
| 18. | Spectrum Analyzer | Rohde & Schwarz | FSV40-N | 102150 | 2025-04-25 | 1 Year |

1.7. Measurement Uncertainty

| Parameter | Uncertainty |
|---|--|
| Conducted emissions (AMN 150kHz~30MHz) | 3.2dB |
| Occupied Bandwidth | 925Hz |
| Radiated spurious emissions (Below 30MHz) | 3.26dB |
| Radiated spurious emissions (30MHz~1GHz) | Horizontal: 3.70dB; Vertical: 4.42dB |
| Radiated spurious emissions (above 1GHz) | 1G-6GHz: 4.64dB 6G-18GHz: 4.82dB 18G-40GHz: 5.62dB |
| <p>The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.</p> | |

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



2. Summary of Test Results


| Standard Section | Test Item | Result |
|---|---------------------|--------|
| 15.203 | Antenna Requirement | PASS |
| 15.207 | Conducted Emission | N/A |
| 15.249 | Radiated Emission | PASS |
| 15.215(c) | 20dB Bandwidth | PASS |
| 15.249(c) | Band Edge | PASS |
| Remark: "N/A" is an abbreviation for Not Applicable. | | |

3. Conducted Emission Test

3.1. Test Standard and Limit

| | | | |
|--|---------------------------|--------------------------------|---------------|
| Test Standard | FCC Part15 Section 15.207 | | |
| Test Limit | Frequency | Maximum RF Line Voltage (dBuV) | |
| | | Quasi-peak Level | Average Level |
| | 150kHz~500kHz | 66 ~ 56 * | 56 ~ 46 * |
| | 500kHz~5MHz | 56 | 46 |
| | 5MHz~30MHz | 60 | 50 |
| Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency. | | | |

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Not applicable.

4. Radiated Emission and Band Edge

4.1. Test Standard and Limit

| Test Standard | | | | | |
|--|-------------------|----------------------------------|----------------|------------|--------------------------|
| FCC Part15 C Section 15.209 and 15.205 | | | | | |
| Test Limit | Frequency (MHz) | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz~0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz~88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz~216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz~960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz~1000MHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1000MHz | 500 | 54.0 | Average | 3 |
| - | | 74.0 | Peak | 3 | |

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

| Test Standard | | | | | | |
|-----------------------------|-----------------|--|--|----------------|---------|--------------------------|
| FCC Part15 C Section 15.249 | | | | | | |
| Test Limit | Frequency (MHz) | Field Strength of fundamental ((millivolts /meter) | Field Strength of Harmonics (microvolts/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 902~928 | 50 | - | 94.0 | QP | 3 |
| | 902~928 | - | 500 | 74.0 | Peak | 3 |
| | 902~928 | - | 500 | 54.0 | Average | 3 |
| | 2400~2483.5 | 50 | - | 114.0 | Peak | 3 |
| | 2400~2483.5 | 50 | - | 94.0 | Average | 3 |
| | 2400~2483.5 | - | 500 | 74.0 | Peak | 3 |
| | 2400~2483.5 | - | 500 | 54.0 | Average | 3 |

Remark:

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.



Test Results (30~1000MHz)

Test Mode: CH01
 Power Source: Self-generated when switch is pressed
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 22.5°C/55%RH
 Fundamental




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|--------|
| 1 | 46.1779 | 31.55 | -16.78 | 14.77 | 40.00 | -25.23 | QP | |
| 2 | 53.5052 | 31.77 | -17.60 | 14.17 | 40.00 | -25.83 | QP | |
| 3 | 107.8876 | 33.56 | -19.01 | 14.55 | 43.50 | -28.95 | QP | |
| 4 | 209.3129 | 34.59 | -19.80 | 14.79 | 43.50 | -28.71 | QP | |
| 5 | 483.9094 | 32.26 | -12.59 | 19.67 | 46.00 | -26.33 | QP | |
| 6 | 900.1471 | 56.29 | -6.70 | 49.59 | | | | |

Note: Result = Reading + Factor Over Limit = Result - Limit

Test Results (30~1000MHz)

Test Mode: CH01
 Power Source: Self-generated when switch is pressed
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 22.5°C/55%RH
 Fundamental



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|--------|
| 1 | 38.8878 | 31.82 | -16.49 | 15.33 | 40.00 | -24.67 | QP | |
| 2 | 52.7599 | 33.28 | -17.54 | 15.74 | 40.00 | -24.26 | QP | |
| 3 | 106.3850 | 34.25 | -18.93 | 15.32 | 43.50 | -28.18 | QP | |
| 4 | 207.8497 | 36.81 | -19.79 | 17.02 | 43.50 | -26.48 | QP | |
| 5 | 554.8251 | 33.90 | -11.94 | 21.96 | 46.00 | -24.04 | QP | |
| 6 | 906.4823 | 56.07 | -6.61 | 49.46 | | | | |

Note: Result = Reading + Factor Over Limit = Result - Limit


Test Results (1GHz-25GHz)

| Peak value: | | | | | | |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 1805.75 | 28.52 | 15.27 | 43.79 | 74.00 | -30.21 | Vertical |
| 2708.63 | 28.58 | 18.09 | 46.67 | 74.00 | -27.33 | Vertical |
| 3611.50 | 29.45 | 23.76 | 53.21 | 74.00 | -20.79 | Vertical |
| 4514.38 | * | | | 74.00 | | Vertical |
| 5417.25 | * | | | 74.00 | | Vertical |
| 1805.75 | 28.19 | 15.27 | 43.46 | 74.00 | -30.54 | Horizontal |
| 2708.63 | 29.13 | 18.09 | 47.22 | 74.00 | -26.78 | Horizontal |
| 3611.50 | 28.14 | 23.76 | 51.90 | 74.00 | -22.10 | Horizontal |
| 4514.38 | * | | | 74.00 | | Horizontal |
| 5417.25 | * | | | 74.00 | | Horizontal |
| Average value: | | | | | | |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 1805.75 | 16.79 | 15.27 | 32.06 | 54.00 | -21.94 | Vertical |
| 2708.63 | 17.63 | 18.09 | 35.72 | 54.00 | -18.28 | Vertical |
| 3611.50 | 18.92 | 23.76 | 42.68 | 54.00 | -11.32 | Vertical |
| 4514.38 | * | | | 54.00 | | Vertical |
| 5417.25 | * | | | 54.00 | | Vertical |
| 1805.75 | 16.52 | 15.27 | 31.79 | 54.00 | -22.21 | Horizontal |
| 2708.63 | 18.16 | 18.09 | 36.25 | 54.00 | -17.75 | Horizontal |
| 3611.50 | 17.65 | 23.76 | 41.41 | 54.00 | -12.59 | Horizontal |
| 4514.38 | * | | | 54.00 | | Horizontal |
| 5417.25 | * | | | 54.00 | | Horizontal |

Note:

1. Result=Reading + Factor
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:




5. 20dB Bandwidth Test

5.1. Test Standard and Limit

| | |
|---------------|-----------------------------|
| Test Standard | FCC Part15 C Section 15.249 |
|---------------|-----------------------------|

5.2. Test Setup




5.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 10kHz, VBW≥3*RBW =30kHz,
Detector= Average
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

5.4. Test Data

| | | | | | |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 25.3 °C | Humidity: | 48 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

| Frequency (MHz) | Bandwidth (kHz) | Result |
|-----------------|-----------------|--------|
| 902.875 | 353.1 | PASS |



6. Antenna Requirement

6.1. Test Standard and Requirement

| | |
|---------------|--|
| Test Standard | FCC Part15 Section 15.203 |
| Requirement | 1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |

6.2. Antenna Connected Construction

The antenna is a Single-stage antenna which permanently attached, and the best case gain of the antenna is -1.72dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----