

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Spyderx operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 X 3.7V rechargeable battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 2dBi.

The normal radiated output power (e.i.r.p) is: -22.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -24.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 73.8dB $\mu$ V/m at 3m in the frequency 2431MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -21.43dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 72.3dB $\mu$ V/m at 3m in the frequency 2472MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -22.93dBm  
which is within the production variation.

The maximum conducted output power specified is -21.0dBm =0.008mW

The source- based time-averaging conducted output power  
=0. 008\* Duty cycle mW <0.008 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} &= 3.0 * (\text{min. test separation distance, mm}) / \text{sqrt(freq. in GHz)} \\ &= 3.0 * 5 / \text{sqrt}(2.472) \text{ mW} \\ &= 9.54 \text{ mW} \end{aligned}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 6.0435ms

Effective period of the cycle = 0.4783ms

DC = 0.4783ms / 6.0435ms = 0.0791 or 7.91%