



Prüfbericht-Nr.: <i>Test report No.:</i>	50049137 002	Auftrags-Nr.: <i>Order No.:</i>	164063836	Seite 1 von 21 <i>Page 1 of 21</i>
Kunden-Referenz-Nr.: <i>Client reference No.:</i>	N/A	Auftragsdatum: <i>Order date.:</i>	17.05.2016	
Auftraggeber: <i>Client:</i>	Binatone Electronics International Ltd. Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong			
Prüfgegenstand: <i>Test item:</i>	Wi-Fi Baby Monitor System			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	BabyNursery7 BU (motorola)			
Auftrags-Inhalt: <i>Order content:</i>	FCC and IC approval			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 RSS-247 Issue 1 May 2015 RSS-Gen Issue 4 November 2014			
Wareneingangsdatum: <i>Date of receipt:</i>	24.05.2016	Please refer to photo documents		
Prüfmuster-Nr.: <i>Test sample No.:</i>	1601078			
Prüfzeitraum: <i>Testing period:</i>	12.06.2016 - 30.06.2016			
Ort der Prüfung: <i>Place of testing:</i>	Accurate Technology Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
 03.08.2016 Ryan Yang / Senior Project Engineer		 05.08.2016 Owen Tian / Technical Certifier		
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>
Sonstiges / Other:				
Only evaluate the 2.4GHz Wi-Fi 802.11 b/g/n(HT20) function in this test report. FCC ID: VLJ-BN7BU IC: 4522A-BN7BU HVIN: BabyNursery7 BU				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.				
<i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

VD4

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 6dB BANDWIDTH

RESULT: Pass

5.1.5 99% BANDWIDTH

RESULT: Pass

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.8 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

Contents

1	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY.....	6
2.6	LOCATION OF ORIGINAL DATA.....	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	6
3	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE.....	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	8
3.5	SUBMITTED DOCUMENTS.....	8
4	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION	9
4.2	TEST OPERATION AND TEST SOFTWARE.....	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	9
4.5	TEST SETUP DIAGRAM	10
5	TEST RESULTS	12
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	12
5.1.1	<i>Antenna Requirement</i>	<i>12</i>
5.1.2	<i>Maximum Peak Conducted Output Power</i>	<i>13</i>
5.1.3	<i>Conducted Power Spectral Density</i>	<i>14</i>
5.1.4	<i>6dB Bandwidth</i>	<i>15</i>
5.1.5	<i>99% Bandwidth</i>	<i>16</i>
5.1.6	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>17</i>
5.1.7	<i>Radiated Spurious Emission</i>	<i>18</i>
5.1.8	<i>Conducted Emission on AC Mains.....</i>	<i>19</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	20
7	LIST OF TABLES.....	21
8	LIST OF PHOTOGRAPHS	21

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix C: Test Results of Wi-Fi 802.11b/g/n(HT20) of Conducted Testing

Appendix D: Test Results of Wi-Fi 802.11b/g/n(HT20) of Radiated Testing

2 Test Sites

2.1 Test Facilities

Accurate Technology Co., Ltd.

F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan Shenzhen, 518057, P.R. China

FCC Registration No.: 752051

Test site Industry Canada No.: 5077A-2

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Accurate Technology Co., Ltd.

Radio Spectrum Test				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Spectrum Analyzer	R&S	ESPI3	100396/003	09.01.2017
Spectrum Analyzer	Agilent	E7405A	MY45115511	09.01.2017
Temp. & Humid. Chamber	Gongwen	HSD-500	0109	09.01.2017
Spurious Emission				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Spectrum Analyzer	R&S	FSV40	101495	01.01.2017
Test Receiver	R&S	ESCS30	100307	01.01.2017
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	01.01.2017
Loop Antenna	Schwarzbeck	FMZB1516	1516131	01.01.2017
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	01.01.2017
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	01.01.2017
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	01.01.2017
Pre-Amplifier	R&S	CBLU11835 40-01	3791	01.01.2017
50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	01.01.2017
RF Coaxial Cable	SUHNER	N-3m	No.8	01.01.2017
RF Coaxial Cable	RESENBERGER	N-3.5m	No.9	01.01.2017
RF Coaxial Cable	SUHNER	N-6m	No.10	01.01.2017
RF Coaxial Cable	RESENBERGER	N-12m	No.11	01.01.2017
50_ Coaxial Switch	Anritsu Corp	MP59B	6200283933	09.01.2017
Conducted Emission on AC Mains				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Test Receiver	R&S	ESCI	26115-010-0027	17.05.2017
L.I.S.N.	R&S	ENV216	101161	17.05.2017
50Ω Coaxial Switch	Anritsu	MP59B	6100175589	17.05.2017

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Item		Extended Uncertainty
Conducted Emission		± 2.0 dB
Radiated Emission (9kHz-30MHz)	Field strength (dB μ V/m)	U=3.08dB, k=2, σ =95%
Radiated Emission (30-1000MHz)	Field strength (dB μ V/m)	U=4.42dB, k=2, σ =95%
Radiated Emission (above 1000MHz)	Field strength (dB μ V/m)	U=4.06dB, k=2, σ =95%
Radio Spectrum		± 0.60 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix C & D of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The Accurate Technology Co., Ltd. Test facility located at F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan Shenzhen, 518057, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Wi-Fi Baby Monitor System (BabyNursery7) device, it contains a parent unit(BabyNursery7 PU) and a baby unit(BabyNursery7 BU). The BU supports general 2.4GHz and Wi-Fi 802.11 b/g/n(HT20) wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Wi-Fi Baby Monitor System
Type Designation	BabyNursery7 BU
Trade Mark	motorola
FCC ID	VLJ-BN7BU
IC / HVIN	4522A-BN7BU / BabyNursery7 BU
Operating Temperature Range	0 °C ~ +45 °C
Operating Voltage	DC 5.0V 1500mA input via AC/DC adapter DC 3.7V via internal rechargeable lithium battery
Testing Voltage	AC 120V, 60Hz
AC/DC Adapter	Model: S012BEU0500150 Input: AC 100-240V~50/60Hz, 500mA Output: DC 5.0V~1500mA
Technical Specification of general 2.4GHz wireless	
Operating Frequency	2402 - 2477 MHz
Type of Modulation	GFSK
Channel Number	22 channels
Channel Separation	2 MHz / 5 MHz
Antenna Type / Gain	Integral Antenna / 0 dBi
Technical Specification of Wi-Fi 802.11 b/g/n(HT20)	
Operating Frequency	2412 - 2462 MHz for 802.11b/g/n(HT20)
Type of Modulation	DSSS(DBPSK/DQPSK/CCK) OFDM(BPSK/QPSK/16QAM/64QAM)
Data Rate	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 Mbps for 802.11n(HT20)
Channel Number	11 channels for 802.11b/g/n(HT20)
Channel Separation	5 MHz
Antenna Type / Gain	Integral Antenna / 0 dBi

Table 3: RF Channel and Frequency of Wi-Fi 802.11 b/g/n(HT20)

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	/	/

Remark:

Test frequencies are lowest channel: 2412 MHz, middle channel: 2437 MHz and highest channel: 2462 MHz for 802.11b/g/n(HT20)

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Wi-Fi transmitting
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. On, Wi-Fi transmitting with AD/DC adapter
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- Block Diagram
- FCC/IC Label and Location Info
- Operation Description
- User Manual
- Parts List
- PCB Layout
- Photo Document
- Schematics

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all tests were performed on model BabyNursery7 BU in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Notebook PC	Lenovo	ThinkPad X240	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(b)(3)
 RSS-247 Clause 5.4(4)
 Basic standard : ANSI C63.10: 2013
 Limits : < 1.0 Watts
 Kind of test site : Shielded Room

Test Setup

Date of testing : 28.06.2016
 Input voltage : AC 120V, 60Hz
 Operation mode : A
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 5: Test Result of Maximum Peak Conducted Output Power, BU Unit

Test Mode	Data Rate	Frequency (MHz)	Measured Power		Limit
			dBm	W	
802.11b	1 Mbps	2412	14.30	0.02692	< 1W(30dBm)
		2437	12.70	0.01862	
		2462	12.10	0.01622	
802.11g	6 Mbps	2412	14.10	0.02570	
		2437	12.70	0.01862	
		2462	12.00	0.01585	
802.11n (HT20)	MCS0 Mbps	2412	14.20	0.02630	
		2437	12.70	0.01862	
		2462	12.10	0.01622	
Maximum Measured Value			14.30	0.02692	

Note: The cable loss is taken into account in results.

5.1.3 Conducted Power Spectral Density

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(e) RSS-247 Clause 5.2(2)
Basic standard	: ANSI C63.10: 2013
Limits	: 8 dBm / 3kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 28.06.2016
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.

Table 6: Test Result of Power Spectral Density, BU Unit

Test Mode	Data Rate	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/3KHz)
802.11b	1 Mbps	2412	-7.13
		2437	-6.95
		2462	-6.1
802.11g	6 Mbps	2412	-10.50
		2437	-10.32
		2462	-10.49
802.11n (HT20)	MCS0 Mbps	2412	-11.21
		2437	-11.37
		2462	-10.51
Maximum Measured Value			-6.100

Note: The cable loss is taken into account in results.

For the measurement records, refer to the appendix C.

5.1.4 6dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(2)
 RSS-247 Clause 5.2(1)
 Basic standard : ANSI C63.10: 2013
 Limits : > 500 KHz
 Kind of test site : Shielded Room

Test Setup

Date of testing : 30.06.2016
 Input voltage : AC 120V, 60Hz
 Operation mode : A
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 7: Test Result of 6dB Bandwidth, BU Unit

Test Mode	Data Rate	Frequency (MHz)	-6dB Bandwidth (MHz)	Limit (kHz)
802.11b	1 Mbps	2412	7.989	> 500
		2437	7.988	
		2462	7.945	
802.11g	6 Mbps	2412	16.411	
		2437	16.411	
		2462	16.324	
802.11n (HT20)	MCS0 Mbps	2412	17.670	
		2437	17.584	
		2462	17.366	
Minimum Measured Value			7.95	

Note: The cable loss is taken into account in results.

For the measurement records, refer to the appendix C.

5.1.5 99% Bandwidth

RESULT:
Pass
Test Specification

Test standard : RSS-Gen Clause 6.6
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 28.06.2016
Input voltage : AC 120V, 60Hz
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 25 °C
Relative humidity : 56 %
Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 8: Test Result of 99% Bandwidth, BU Unit

Test Mode	Data Rate	Frequency (MHz)	99% Bandwidth (MHz)	Limit (kHz)
802.11b	1 Mbps	2412	12.200	/
		2437	12.200	
		2462	12.069	
802.11g	6 Mbps	2412	16.368	
		2437	16.281	
		2462	16.324	
802.11n (HT20)	MCS0 Mbps	2412	17.496	
		2437	17.496	
		2462	17.496	
Maximum Measured Value			17.50	

Note: The cable loss is taken into account in results.

For the measurement records, refer to the appendix C.

5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 28.06.2016
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to following test plot, and compliance is achieved as well.

For the measurement records, refer to the appendix C.

5.1.7 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	: ANSI C63.10: 2013
Limits	: Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 4 & Table 5
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 27.06.2016 & 28.06.2016
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24 °C
Relative humidity	: 48 %
Atmospheric pressure	: 101 kPa

Remark:

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test set-up photos.

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to following test plot, and compliance is achieved as well.

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For the measurement records, refer to the appendix D.

5.1.8 Conducted Emission on AC Mains

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.207(a) RSS-Gen Clause 8.8
Basic standard	: ANSI C63.10: 2013
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.207(a) RSS-Gen Table 3
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 29.06.2016
Input voltage	: AC 120V, 60Hz
Operation mode	: B
Earthing	: Not connected
Ambient temperature	: 24 °C
Relative humidity	: 53 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix D.

6 Photographs of the Test Set-Up

Photograph 1: Set-up for Radio Spectrum Test

Please refer to TÜV Rheinland report 50049137 001 for more details.

Photograph 2: Set-up for Radiated Spurious Emission (9kHz ~ 30MHz)

Please refer to TÜV Rheinland report 50049137 001 for more details.

Photograph 3: Set-up for Radiated Spurious Emission (30MHz~1GHz)

Please refer to TÜV Rheinland report 50049137 001 for more details.

Photograph 4: Set-up for Radiated Spurious Emission (1GHz ~ 18GHz)

Please refer to TÜV Rheinland report 50049137 001 for more details.

Photograph 5: Set-up for Radiated Spurious Emission (18GHz ~ 26GHz)

Please refer to TÜV Rheinland report 50049137 001 for more details.

Photograph 6: Set-up for Conducted Emission on AC Mains

Please refer to TÜV Rheinland report 50049137 001 for more details.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Technical Specification of EUT	7
Table 3: RF Channel and Frequency of Wi-Fi 802.11 b/g/n(HT20)	8
Table 4: List of Accessories and Auxiliary Equipment.....	9
Table 5: Test Result of Maximum Peak Conducted Output Power, BU Unit	13
Table 6: Test Result of Power Spectral Density, BU Unit.....	14
Table 7: Test Result of 6dB Bandwidth, BU Unit.....	15
Table 8: Test Result of 99% Bandwidth, BU Unit.....	16

8 List of Photographs

Photograph 1: Set-up for Radio Spectrum Test	20
Photograph 2: Set-up for Radiated Spurious Emission (9kHz ~ 30MHz)	20
Photograph 3: Set-up for Radiated Spurious Emission (30MHz~1GHz)	20
Photograph 4: Set-up for Radiated Spurious Emission (1GHz ~ 18GHz).....	20
Photograph 5: Set-up for Radiated Spurious Emission (18GHz ~ 26GHz).....	20
Photograph 6: Set-up for Conducted Emission on AC Mains.....	20


Appendix C

Test Results of Wi-Fi 802.11b/g/n(HT20) of Conducted Testing


APPENDIX C	1
APPENDIX C.1: CONDUCTED POWER SPECTRAL DENSITY	2
<i>Wi-Fi 802.11 b mode, 1 Mbps</i>	2
<i>Wi-Fi 802.11 g mode, 6 Mbps</i>	3
<i>Wi-Fi 802.11 n(HT) mode, MCS0 Mbps</i>	5
APPENDIX C.2: 6dB BANDWIDTH	7
<i>Wi-Fi 802.11 b mode, 1 Mbps</i>	7
<i>Wi-Fi 802.11 g mode, 6 Mbps</i>	8
<i>Wi-Fi 802.11 n(HT) mode, MCS0 Mbps</i>	10
APPENDIX C.3: 99% BANDWIDTH	12
<i>Wi-Fi 802.11 b mode, 1 Mbps</i>	12
<i>Wi-Fi 802.11 g mode, 6 Mbps</i>	13
<i>Wi-Fi 802.11 n(HT) mode, MCS0 Mbps</i>	15
APPENDIX C.4: CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH	17
<i>Wi-Fi 802.11 b mode, 1 Mbps</i>	17
<i>Wi-Fi 802.11 g mode, 6 Mbps</i>	18
<i>Wi-Fi 802.11 n(HT) mode, MCS0 Mbps</i>	20
<i>Wi-Fi 802.11 b mode, Band Edge</i>	22
<i>Wi-Fi 802.11 g mode, Band Edge</i>	23
<i>Wi-Fi 802.11 n(HT20) mode, Band Edge</i>	24

Appendix C.1: Conducted Power Spectral Density


Wi-Fi 802.11 b mode, 1 Mbps



Date: 28.JUN.2016 16:17:27




Date: 28.JUN.2016 16:18:08




Date: 28.JUN.2016 16:18:44


Wi-Fi 802.11 g mode, 6 Mbps



Date: 28.JUN.2016 16:20:26




Date: 28.JUN.2016 16:21:42




Date: 28.JUN.2016 16:22:19


Wi-Fi 802.11 n(HT) mode, MCS0 Mbps



Date: 28.JUN.2016 17:06:45




Date: 28.JUN.2016 17:05:44




Date: 28.JUN.2016 17:04:57

Appendix C.2: 6dB Bandwidth


Wi-Fi 802.11 b mode, 1 Mbps



Date: 28.JUN.2016 15:57:06




Date: 28.JUN.2016 16:00:42




Date: 28.JUN.2016 16:02:44


Wi-Fi 802.11 g mode, 6 Mbps



Date: 28.JUN.2016 16:37:11




Date: 28.JUN.2016 16:39:07




Date: 28.JUN.2016 16:40:59


Wi-Fi 802.11 n(HT) mode, MCS0 Mbps



Date: 28.JUN.2016 16:55:09




Date: 28.JUN.2016 16:49:42




Date: 28.JUN.2016 16:52:28

Appendix C.3: 99% Bandwidth


Wi-Fi 802.11 b mode, 1 Mbps



Date: 28.JUN.2016 16:05:57




Date: 28.JUN.2016 16:05:08




Date: 28.JUN.2016 16:04:11


Wi-Fi 802.11 g mode, 6 Mbps



Date: 28.JUN.2016 16:33:34




Date: 28.JUN.2016 16:32:59




Date: 28.JUN.2016 16:32:02


Wi-Fi 802.11 n(HT) mode, MCS0 Mbps



Date: 28.JUN.2016 16:56:24




Date: 28.JUN.2016 16:57:04




Date: 28.JUN.2016 16:57:45

Appendix C.4: Conducted Spurious Emissions Measured in 100 kHz Bandwidth


Wi-Fi 802.11 b mode, 1 Mbps



Date: 28.JUN.2016 16:13:56




Date: 28.JUN.2016 16:12:55




Date: 28.JUN.2016 16:11:22


Wi-Fi 802.11 g mode, 6 Mbps



Date: 28.JUN.2016 16:27:25




Date: 28.JUN.2016 16:25:52




Date: 28.JUN.2016 16:26:46


Wi-Fi 802.11 n(HT) mode, MCS0 Mbps



Date: 28.JUN.2016 17:02:10




Date: 28.JUN.2016 17:03:05




Date: 28.JUN.2016 17:03:48

Wi-Fi 802.11 b mode, Band Edge




Date: 28.JUN.2016 16:07:45



Date: 28.JUN.2016 16:09:50

Wi-Fi 802.11 g mode, Band Edge




Date: 28.JUN.2016 16:29:01



Date: 28.JUN.2016 16:30:18

Wi-Fi 802.11 n(HT20) mode, Band Edge



Date: 28.JUN.2016 17:00:51



Date: 28.JUN.2016 16:59:33

Appendix D

Test Results of Wi-Fi 802.11b/g/n(HT20) of Radiated Testing

APPENDIX D.....	1
APPENDIX D.1: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	2
<i>BU Unit, Wi-Fi 802.11 b mode, 1 Mbps</i>	<i>2</i>
<i>BU Unit, Wi-Fi 802.11 g mode, 6 Mbps</i>	<i>23</i>
<i>BU Unit, Wi-Fi 802.11 n(HT20) mode, MCS0 Mbps</i>	<i>43</i>
APPENDIX D.2: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	63
<i>BU Unit, Wi-Fi 802.11 b mode, 1 Mbps</i>	<i>63</i>
<i>BU Unit, Wi-Fi 802.11 g mode, 6 Mbps</i>	<i>67</i>
<i>BU Unit, Wi-Fi 802.11 n(HT20) mode, MCS0 Mbps</i>	<i>71</i>
APPENDIX D.3: TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS	75
<i>BU Unit, B mode.....</i>	<i>75</i>

NOTE

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test set-up photos.

Appendix D.1: Test Results of Radiated Spurious Emissions

BU Unit, Wi-Fi 802.11 b mode, 1 Mbps

9KHz - 30MHz


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2412MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-28 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2437MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-28 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2462MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-28 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



30MHz - 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2760

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	285.9778	53.08	-9.65	43.43	46.00	-2.57	QP			
2	330.1949	49.36	-8.34	41.02	46.00	-4.98	QP			
3	595.1327	41.22	-3.02	38.20	46.00	-7.80	QP			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2761
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	46.18	-8.34	37.84	46.00	-8.16	QP			
2	440.1963	43.68	-5.90	37.78	46.00	-8.22	QP			
3	506.4791	42.26	-4.63	37.63	46.00	-8.37	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2762
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	46.23	-8.34	37.89	46.00	-8.11	QP			
2	440.1963	43.55	-5.90	37.65	46.00	-8.35	QP			
3	506.4791	42.16	-4.63	37.53	46.00	-8.47	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2763

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	285.9778	53.09	-9.65	43.44	46.00	-2.56	QP			
2	330.1949	49.11	-8.34	40.77	46.00	-5.23	QP			
3	595.1327	41.40	-3.02	38.38	46.00	-7.62	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2764
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	285.9778	52.86	-9.65	43.21	46.00	-2.79	QP			
2	330.1949	49.14	-8.34	40.80	46.00	-5.20	QP			
3	595.1327	41.08	-3.02	38.06	46.00	-7.94	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2765
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	46.35	-8.34	38.01	46.00	-7.99	QP			
2	440.1963	43.62	-5.90	37.72	46.00	-8.28	QP			
3	506.4791	41.97	-4.63	37.34	46.00	-8.66	QP			

1GHz - 18GHz




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2880
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2412.000	103.98	-7.43	96.55	/	/	peak			
2	4824.167	48.94	-0.19	48.75	74.00	-25.25	peak			
3	4824.167	40.54	-0.19	40.35	54.00	-13.65	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2881

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2412.000	102.44	-7.43	95.01	/	/	peak			
2	4824.203	49.19	-0.19	49.00	74.00	-25.00	peak			
3	4824.203	41.42	-0.19	41.23	54.00	-12.77	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2884

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	104.56	-7.36	97.20	/	/	peak			
2	4874.211	49.18	0.09	49.27	74.00	-24.73	peak			
3	4874.211	41.44	0.09	41.53	54.00	-12.47	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2885

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	103.67	-7.36	96.31	/	/	peak			
2	4874.220	49.11	0.09	49.20	74.00	-24.80	peak			
3	4874.220	41.23	0.09	41.32	54.00	-12.68	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2886

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2462.000	100.90	-7.35	93.55	/	/	peak			
2	4924.235	45.71	0.34	46.05	74.00	-27.95	peak			
3	4924.235	37.95	0.34	38.29	54.00	-15.71	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2887

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2462.000	104.48	-7.35	97.13	/	/	peak			
2	4924.240	49.02	0.34	49.36	74.00	-24.64	peak			
3	4924.240	40.67	0.34	41.01	54.00	-12.99	AVG			

18GHz - 26GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2890

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26072.999	33.49	17.18	50.67	74.00	-23.33	peak			
2	26072.999	23.07	17.18	40.25	54.00	-13.75	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2891
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26204.426	34.16	16.50	50.66	74.00	-23.34	peak			
2	26204.426	23.70	16.50	40.20	54.00	-13.80	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2892
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26265.307	34.18	16.50	50.68	74.00	-23.32	peak			
2	26265.307	23.71	16.50	40.21	54.00	-13.79	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2893
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25982.398	33.65	17.24	50.89	74.00	-23.11	peak			
2	25982.398	22.88	17.24	40.12	54.00	-13.88	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2894

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26255.151	33.32	17.06	50.38	74.00	-23.62	peak			
2	26255.151	23.07	17.06	40.13	54.00	-13.87	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2895
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26174.038	34.07	16.50	50.57	74.00	-23.43	peak			
2	26174.038	23.85	16.50	40.35	54.00	-13.65	AVG			

**BU Unit, Wi-Fi 802.11 g mode, 6 Mbps
9KHz - 30MHz**


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2412MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-28 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2437MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-28 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2462MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-28 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



30MHz - 1GHz




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2766
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	45.05	-8.34	36.71	46.00	-9.29	QP			
2	419.1080	43.27	-6.19	37.08	46.00	-8.92	QP			
3	550.9479	41.62	-3.59	38.03	46.00	-7.97	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2767

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	285.9778	52.04	-9.65	42.39	46.00	-3.61	QP			
2	330.1949	48.37	-8.34	40.03	46.00	-5.97	QP			
3	595.1327	39.01	-3.02	35.99	46.00	-10.01	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2768

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	285.9778	51.89	-9.65	42.24	46.00	-3.76	QP			
2	330.1949	48.38	-8.34	40.04	46.00	-5.96	QP			
3	595.1327	38.79	-3.02	35.77	46.00	-10.23	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2769
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	45.02	-8.34	36.68	46.00	-9.32	QP			
2	419.1080	43.06	-6.19	36.87	46.00	-9.13	QP			
3	550.9479	41.26	-3.59	37.67	46.00	-8.33	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2770

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	44.93	-8.34	36.59	46.00	-9.41	QP			
2	419.1080	43.11	-6.19	36.92	46.00	-9.08	QP			
3	550.9479	41.02	-3.59	37.43	46.00	-8.57	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2771

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	241.6761	45.84	-10.84	35.00	46.00	-11.00	QP			
2	285.9778	51.95	-9.65	42.30	46.00	-3.70	QP			
3	330.1949	48.51	-8.34	40.17	46.00	-5.83	QP			

1GHz - 18GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2897

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2412.000	99.60	-7.43	92.17	/	/	peak			
2	4824.000	49.43	-0.19	49.24	74.00	-24.76	peak			
3	4824.000	41.77	-0.19	41.58	54.00	-12.42	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2900

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	101.67	-7.36	94.31	/	/	peak			
2	4874.000	47.33	0.09	47.42	74.00	-26.58	peak			
3	4874.000	39.42	0.09	39.51	54.00	-14.49	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2901
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	100.86	-7.36	93.50	/	/	peak			
2	4874.000	46.49	0.09	46.58	74.00	-27.42	peak			
3	4874.000	38.14	0.09	38.23	54.00	-15.77	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2902

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2462.000	98.24	-7.35	90.89	/	/	peak			
2	4924.000	45.74	0.34	46.08	74.00	-27.92	peak			
3	4924.000	37.91	0.34	38.25	54.00	-15.75	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2903

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2462.000	102.22	-7.35	94.87	/	/	peak			
2	4924.000	48.73	0.34	49.07	74.00	-24.93	peak			
3	4924.000	40.91	0.34	41.25	54.00	-12.75	AVG			

18GHz - 26GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2906

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26275.468	33.81	17.05	50.86	74.00	-23.14	peak			
2	26275.468	23.29	17.05	40.34	54.00	-13.66	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2907

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26093.176	33.98	16.50	50.48	74.00	-23.52	peak			
2	26093.176	23.84	16.50	40.34	54.00	-13.66	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2908
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26356.895	33.89	16.50	50.39	74.00	-23.61	peak			
2	26356.895	24.46	16.50	40.96	54.00	-13.04	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2909
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26316.150	33.71	17.02	50.73	74.00	-23.27	peak			
2	26316.150	23.80	17.02	40.82	54.00	-13.18	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2910
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26305.974	33.91	17.03	50.94	74.00	-23.06	peak			
2	26305.974	23.59	17.03	40.62	54.00	-13.38	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2911
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26214.563	33.96	16.50	50.46	74.00	-23.54	peak			
2	26214.563	23.51	16.50	40.01	54.00	-13.99	AVG			

**BU Unit, Wi-Fi 802.11 n(HT20) mode, MCS0 Mbps
9KHz - 30MHz**


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2412MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: X
 Start of Test: 2016-6-29 /

SCAN TABLE: "LFRE Fin"

Short Description:		SUB STD VTERM2 1.70				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2437MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: Y
 Start of Test: 2016-6-29 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: TX 2462MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: AC 120V/60Hz
 Comment: Z
 Start of Test: 2016-6-29 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



30MHz - 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2772

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	241.6762	45.72	-10.84	34.88	46.00	-11.12	QP			
2	285.9778	52.71	-9.65	43.06	46.00	-2.94	QP			
3	351.7078	44.64	-7.73	36.91	46.00	-9.09	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2773

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	374.6225	41.95	-7.44	34.51	46.00	-11.49	QP			
2	419.1080	44.11	-6.19	37.92	46.00	-8.08	QP			
3	506.4791	42.71	-4.63	38.08	46.00	-7.92	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2774
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	285.9778	43.88	-9.65	34.23	46.00	-11.77	QP			
2	419.1080	44.04	-6.19	37.85	46.00	-8.15	QP			
3	506.4791	42.76	-4.63	38.13	46.00	-7.87	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2775

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	241.6761	45.50	-10.84	34.66	46.00	-11.34	QP			
2	285.9778	52.58	-9.65	42.93	46.00	-3.07	QP			
3	351.7078	44.70	-7.73	36.97	46.00	-9.03	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2776

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/06/27/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	241.6761	45.46	-10.84	34.62	46.00	-11.38	QP			
2	285.9778	52.69	-9.65	43.04	46.00	-2.96	QP			
3	351.7078	44.55	-7.73	36.82	46.00	-9.18	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2777
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/06/27/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	42.72	-8.34	34.38	46.00	-11.62	QP			
2	419.1080	44.35	-6.19	38.16	46.00	-7.84	QP			
3	506.4791	43.00	-4.63	38.37	46.00	-7.63	QP			

1GHz - 18GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2913

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2412.000	99.38	-7.43	91.95	/	/	peak			
2	4824.227	46.31	-0.19	46.12	74.00	-27.88	peak			
3	4824.227	38.75	-0.19	38.56	54.00	-15.44	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2916
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	101.61	-7.36	94.25	/	/	peak			
2	4874.240	47.73	0.09	47.82	74.00	-26.18	peak			
3	4874.240	39.52	0.09	39.61	54.00	-14.39	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2917

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2437MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	99.22	-7.36	91.86	/	/	peak			
2	4874.255	44.70	0.09	44.79	74.00	-29.21	peak			
3	4874.255	36.15	0.09	36.24	54.00	-17.76	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2918

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2462.000	96.50	-7.35	89.15	/	/	peak			
2	4924.230	43.28	0.34	43.62	74.00	-30.38	peak			
3	4924.230	35.29	0.34	35.63	54.00	-18.37	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2919

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2462.000	100.86	-7.35	93.51	/	/	peak			
2	4924.238	49.78	0.34	50.12	74.00	-23.88	peak			
3	4924.238	40.18	0.34	40.52	54.00	-13.48	AVG			

18GHz - 26GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2922

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26032.693	33.25	17.21	50.46	74.00	-23.54	peak			
2	26032.693	23.37	17.21	40.58	54.00	-13.42	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2923
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25992.449	33.78	16.50	50.28	74.00	-23.72	peak			
2	25992.449	24.03	16.50	40.53	54.00	-13.47	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2924
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26305.974	34.27	16.50	50.77	74.00	-23.23	peak			
2	26305.974	23.73	16.50	40.23	54.00	-13.77	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2925
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2437MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26387.495	33.17	16.97	50.14	74.00	-23.86	peak			
2	26387.495	23.38	16.97	40.35	54.00	-13.65	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2926
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26032.693	33.23	17.21	50.44	74.00	-23.56	peak			
2	26032.693	23.38	17.21	40.59	54.00	-13.41	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2927
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25992.449	34.41	16.50	50.91	74.00	-23.09	peak			
2	25992.449	23.70	16.50	40.20	54.00	-13.80	AVG			

Appendix D.2: Test Results of Radiated Emissions in Restricted Bands

BU Unit, Wi-Fi 802.11 b mode, 1 Mbps
Low channel




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2882	Polarization: Vertical
Standard: FCC (Band Edge)	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2016/06/29
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Wifi Baby monitor system	Engineer Signature: LGWADE
Mode: TX 2412MHz	Distance: 3m
Model: BabyNursery7 BU	
Manufacturer: Binatone Electronics International Limited	
Note: 802.11b	



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2385.680	50.77	-7.56	43.21	74.00	-30.79	peak			
2	2385.680	40.12	-7.56	32.56	54.00	-21.44	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2883
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2385.840	53.68	-7.56	46.12	74.00	-27.88	peak			
2	2385.840	43.54	-7.56	35.98	54.00	-18.02	AVG			

High channel



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2888
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.599	53.28	-7.37	45.91	74.00	-28.09	peak			
2	2483.599	42.99	-7.37	35.62	54.00	-18.38	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2889
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited


Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.912	46.63	-7.38	39.25	74.00	-34.75	peak			
2	2483.912	36.94	-7.38	29.56	54.00	-24.44	AVG			

**BU Unit, Wi-Fi 802.11 g mode, 6 Mbps
Low channel**





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2899

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2412MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2389.680	62.52	-7.53	54.99	74.00	-19.01	peak			
2	2389.680	51.63	-7.53	44.10	54.00	-9.90	AVG			

High channel



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2904

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.912	64.05	-7.38	56.67	74.00	-17.33	peak			
2	2483.912	53.76	-7.38	46.38	54.00	-7.62	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2905
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2462MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited


Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.599	55.21	-7.37	47.84	74.00	-26.16	peak			
2	2483.599	45.02	-7.37	37.65	54.00	-16.35	AVG			

**BU Unit, Wi-Fi 802.11 n(HT20) mode, MCS0 Mbps
Low channel**





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2915
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wifi Baby monitor system
Mode: TX 2412MHz
Model: BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/06/29
Time:
Engineer Signature: LGWADE
Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	62.26	-7.53	54.73	74.00	-19.27	peak			
2	2390.000	52.03	-7.53	44.50	54.00	-9.50	AVG			

High channel



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2920

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.550	64.00	-7.37	56.63	74.00	-17.37	peak			
2	2483.550	53.65	-7.37	46.28	54.00	-7.72	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2921

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wifi Baby monitor system

Mode: TX 2462MHz

Model: BabyNursery7 BU

Manufacturer: Binatone Electronics International Limited

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/06/29

Time:

Engineer Signature: LGWADE

Distance: 3m

Note: 802.11n HT20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.747	53.81	-7.37	46.44	74.00	-27.56	peak			
2	2483.747	44.09	-7.37	36.72	54.00	-17.28	AVG			

Appendix D.3: Test Results of Conducted Emission on AC Mains BU Unit, B mode


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
Manufacturer: Binatone Electronics International Limited
Operating Condition: B
Test Site: 1#Shielding Room
Operator: LGMADE
Test Specification: L 120V/60Hz
Comment: Mains Port
Start of Test: 6/30/2016 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
Average
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
Average



MEASUREMENT RESULT: "TUV-0630-9_fin"

6/30/2016

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.165000	41.70	10.5	65	23.5	QP	L1	GND
0.485000	44.10	10.7	56	12.2	QP	L1	GND
0.970000	35.20	10.8	56	20.8	QP	L1	GND
10.090000	31.70	11.3	60	28.3	QP	L1	GND

MEASUREMENT RESULT: "TUV-0630-9_fin2"

6/30/2016

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.385000	26.60	10.7	48	21.6	AV	L1	GND
0.490000	34.70	10.7	46	11.5	AV	L1	GND
1.055000	23.40	10.9	46	22.6	AV	L1	GND
10.240000	20.80	11.3	50	29.2	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: Wifi Baby monitor system M/N:BabyNursery7 BU
 Manufacturer: Binatone Electronics International Limited
 Operating Condition: B
 Test Site: 1#Shielding Room
 Operator: LGWADE
 Test Specification: N 120V/60Hz
 Comment: Mains Port
 Start of Test: 6/30/2016 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TUV-0630-10_fin"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.160000	36.10	10.5	66	29.4	QP	N	GND
0.490000	42.60	10.7	56	13.6	QP	N	GND
0.965000	29.30	10.8	56	26.7	QP	N	GND
5.540000	26.40	11.2	60	33.6	QP	N	GND

MEASUREMENT RESULT: "TUV-0630-10_fin2"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.380000	29.00	10.7	48	19.3	AV	N	GND
0.495000	36.20	10.7	46	9.9	AV	N	GND
1.060000	24.40	10.9	46	21.6	AV	N	GND
5.170000	21.00	11.2	50	29.0	AV	N	GND