



TEST REPORT

Date: 2014-04-21

Report No.: 60.870.14.003.02F

Applicant: Binatone Electronics International Ltd.
Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong

Description of Samples: Model name: Video Baby Monitor (Parent Unit)
Brand name: motorola
Model no.: MBP36SPU, SCOUT36SPU, FOCUS36SPU
FCCID: VLJ-MBP36SPU

Date Samples Received: 2014-02-19

Date Tested: 2014-02-20 to 2014-04-12

Investigation Requested: FCC Part 15 Subpart C, Section 15.247

Conclusions: The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remarks: ---

Checked by: Approved by:-

Ray Cheung
Project Engineer
Wireless & Telecom Department

Jeff Pong
Operation Manager
Wireless & Telecom Department



CONTENT:

Cover	Page 1 of 29
Content	Page 2-3 of 29
<u>1.0 General Details</u>	
1.1 Test Laboratory	Page 4 of 29
1.2 Applicant Details	Page 4 of 29
1.3 Equipment Under Test [EUT]	Page 5 of 29
1.4 Related Submittal(s) Grants	Page 5 of 29
<u>2.0 Technical Details</u>	
2.1 Investigations Requested	Page 6 of 29
2.2 Test Standards and Results Summary	Page 6 of 29
<u>3.0 Test Methodology</u>	
3.1 Radiated Emission	Page 7 of 29
3.2 Field Strength Calculation	Page 7 of 29
3.3 Conducted Emission	Page 7 of 29
<u>4.0 Test Results</u>	
4.1 Number of Frequency Hopping	Page 8 of 29
4.2 20dB Bandwidth Measurement	Page 9-10 of 29
4.3 Hopping Channel Carrier Frequency Separation	Page 11 of 29
4.4 Average Time of Occupancy	Page 12-14 of 29
4.5 Pseudorandom Hopping Algorithm	Page 15 of 29
4.6 Band Edge Measurement	Page 16-17 of 29
4.7 Maximum Output Power	Page 18-20 of 29
4.8 Out of Band Emissions and Emissions in Restricted Bands	Page 21-25 of 29
4.9 Conducted Emission on AC Mains	Page 26-28 of 29



5.0 List of Measurement Equipments

Page 29 of 29

Appendix A

Photos of Test Setup

Appendix B

External EUT Photos

Appendix C

Internal EUT Photos



1.0 General Details

1.1 Test Laboratory

Attestation of Global Compliance SZ Co Ltd.
2/F, Building 2, No.1-No.4, Chaxi Sanwei, Technical
Industrial Park, Gushu, Xixiang, Shenzhen, China.
Registration Number: 259865

Tested by:

A blue ink signature of the name "John Zhi".

John Zhi

1.2 Applicant Details

Applicant

Binatone Electronics International Ltd.
Floor 23A, 9 Des Voeux Road West, Sheung Wan Hong
Kong

Manufacturer

VTech(Dongguan) Telecommunications Limited
VTech Science Park, Xia Ling Bei Management Zone,
Liaobu, Dongguan, Guangdong, China



1.3 Equipment Under Test [EUT]

Description of EUT

Product Description:	Video Baby Monitor (Parent Unit)
Model No.:	MBP36SPU, SCOUT36SPU, FOCUS36SPU
Brand Name:	motorola
FCCID:	VLJ-MBP36SPU
Rating:	DC 5.0V, 600mA powered by AC/DC power adaptor Or DC 3.6V 900mAh (Ni-MH package rechargeable battery)
Operated Frequency:	2402– 2479 MHz
No. of Operated Channel:	23
Accessories and Auxiliary Equipments:	AC/DC Switching Adaptor
Antenna Type:	Integral
Manufacture of Antenna:	Cvision HK Limited
Antenna Gain:	0 dBi
Antenna Model:	N/A

General Operation of EUT

The Equipment Under Test (EUT) is a Monitor of Wireless Monitoring System.

As per Client Declaration, the circuit design, PCB Layout, shielding and interface of MBP36SPU, SCOUT36SPU & FOCUS36SPU are identical. So we use MBP36SPU as a representative model to perform all testing.

FHSS Operation Principle:

This module is controlled by microchip to generate Pseudorandom Frequency Hopping Sequence, this module support 23 hopping channels. Refer to section 4.5 of this report to have more detail of Pseudorandom Hopping Algorithm.

1.4 Related Submittal(s) Grants

This is a signal application subjected to Certificate Authorization.



2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15:2012 and ANSI C63.4: 2009

2.2 Test Standards and Results Summary Tables

Test Condition	Test Requirement	Test Result	
		Pass	N/A
Number of Frequency Hopping	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20dB Bandwidth Measurement	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Hopping Channel Carrier Frequency Separation	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Average Time of Occupancy	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Pseudorandom Hopping Algorithm	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band Edge Measurement	Section 15.247	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Maximum Output Power	Section 15.247 (b1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Out of Band Emission	Section 15.247 (d)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission in Restricted Band	Section 15.247 (d)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Conducted Emission on AC Mains	Section 15.207	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Antenna Requirement	Section 15.203	<input checked="" type="checkbox"/>	<input type="checkbox"/>
		See note 1	

Note 1 : The EUT uses a permanently attached antenna, which in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

Remark: N/A - Not Applicable



3.0 Test Methodology

3.1 Radiated Emission

The sample was placed 0.8m above the ground plane on a standard emission test site *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

3.2 Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$\begin{aligned} \text{FS} &= \text{R} + \text{System Factor} \\ \text{System Factor} &= \text{AF} + \text{CF} + \text{FA} - \text{PA} \end{aligned}$$

Where FS = Net Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer / Test Receiver in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

3.3 Conducted Emissions

The test was performed in accordance with ANSI C63.4: 2009, with the following: initial measurements were performed in peak and average detection modes on the live line of personal computer, any emissions recorded within 30dB of the relevant limit lines were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.



4.0 Test Results

4.1 Number of Hopping Frequency

Test Requirement: FCC part 15 section 15.247 (a1)(iii)
 Test Date: 2014-03-19
 Mode of Operation: Transmitting mode.
 Detector Function: Max Hold

Result: PASS

Measured Result :


Operating Channel Frequency in sequence (MHz):

Channels list		
CH1=2402MHz	CH2=2404MHz	CH3=2406MHz
CH4=2408MHz	CH5=2410MHz	CH6=2415MHz
CH7=2420MHz	CH8=2425MHz	CH9=2430MHz
CH10=2435MHz	CH11=2440MHz	CH12=2445MHz
CH13=2450MHz	CH14=2455MHz	CH15=2460MHz
CH16=2465MHz	CH17=2467MHz	CH18=2469MHz
CH19=2471MHz	CH20=2473MHz	CH21=2475MHz
CH22=2477MHz	CH23=2479MHz	

Limit for Number of Hopping Channel [Section 15.247 (a1)(iii)]

At least 15 non-overlapping channels of each sequence for 2400-2483.5MHz.

Result data graph shows the number of operation channels:





4.2 20dB Bandwidth Measurement

Test Requirement: FCC part 15 section 15.247 (a1)
 Test Date: 2014-03-19
 Mode of Operation: Transmitting mode.
 Detector Function: Max Hold


Test Setup:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Channel	Measured frequency (MHz)	20dB Bandwidth (MHz)
Lowest	2402	2.166
Middle	2440	2.165
Highest	2475	2.206


This result is used for checking the hopping channel carrier frequencies separation.

Result data graph shows 20 dB bandwidth, CF = 2402MHz, BW = 2.166MHz






Result data graph shows 20 dB bandwidth, CF = 2440MHz, BW = 2.165MHz



Result data graph shows 20 dB bandwidth, CF = 2479MHz, BW = 2.206MHz





4.3 Hopping Channel Carrier Frequency Separation

Test Requirement: FCC part 15 section 15.247 (a1)
 Test Date: 2014-03-19
 Mode of Operation: Transmitting mode.
 Detector Function: Max Hold

Result: PASS


Measured Result :

Refer to the delta marker, the frequency separation between two adjacent channels is 1.998 MHz, therefore, the requirement of channel separated by a minimum of 25kHz of the hopping channel is applied.

Limits for Hopping Channel Separation [Section 15.247 (a1)]:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25KHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

Result data graph shows the channel separation:





4.4 Average Time of Channel Occupancy

Test Requirement: FCC part 15 section 15.247 (a1)(iii)
Test Date: 2014-03-19
Mode of Operation: Transmitting mode.
Detector Function: Zero span, Sweep time 1s

Result : PASS

Measured Result :

Each transmission only 23 channels will be used.

Observe time = 23 channels \times 0.4s = 9.2s

There are 14 pulses within 880 ms

And one set of pulses = 147us

Therefore, the average channel occupancy times (ms)

= 147us \times 14 \times 9.2/880ms


So, total transmitting time is 0.022s. (<0.4s).

Limits for Average Time of Occupancy [Section 15.247 (a1)(iii)]:


The average time of occupancy on any channel shall not be greater than 0.4 second within a period of 0.4 seconds multiplied by the number of hopping channels employed.



Result data graph shows total 23 channels are used.




Result data graph shows total 14 pulses with 880 ms.





Result data graph zooms into detail, one pulse period is 147us.





4.5 Pseudorandom Hopping Algorithm

Pseudorandom Frequency Hopping

MBP36SPU uses FHSS technology the frequency range of the system is operating from 2402MHz to 2479MHz. There are totally 23 channels with 2MHz (the worst) channel separation. A single data frame is transmitted on each frequency location before skipping to the next hopping frequency in the list.

Channels list		
CH1=2402MHz	CH2=2404MHz	CH3=2406MHz
CH4=2408MHz	CH5=2410MHz	CH6=2415MHz
CH7=2420MHz	CH8=2425MHz	CH9=2430MHz
CH10=2435MHz	CH11=2440MHz	CH12=2445MHz
CH13=2450MHz	CH14=2455MHz	CH15=2460MHz
CH16=2465MHz	CH17=2467MHz	CH18=2469MHz
CH19=2471MHz	CH20=2473MHz	CH21=2475MHz
CH22=2477MHz	CH23=2479MHz	

Requirement for Pseudorandom Hopping Algorithm [Section 15.247 (a1)]:

The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on average by the transmitter.



4.6 Band Edge Measurement

Test Requirement: FCC part 15 section 15.247
 Test Date: 2014-03-19
 Mode of Operation: Transmitting mode.
 Detector Function: Max Hold

Result: PASS


Measured Result :

Refer to the figure, it shows the frequency of lower band edge and upper band edge separately.

Limits of Band Edge for Carrier Frequencies Operated within the Bands [Section 15.247]:


The carrier frequencies should operate within 2400-2483.5MHz.

Result data graph shows the frequency of lowest channel.





Result data graph shows the frequency of highest channel.





4.7 Maximum Output Power

Test Requirement: FCC part 15 section 15.247 (a1)
 Test Method: ANSI C63.4:2009
 Test Date: 2014-03-19
 Mode of Operation: Transmitting mode.
 Detector Function: Peak
 Measurement BW: RBW 1MHz ; VBW 1MHz

Test Setup:



Result : PASS


Frequency (MHz)	Peak Output Power		Limit	
	(dBm)	(W)	(dBm)	(W)
Lowest Channel : 2402	16.76	0.047	21	0.125
Middle Channel : 2440	16.56	0.045	21	0.125
Highest Channel : 2479	16.58	0.045	21	0.125

Limits for Maximum Output Power [Section 15.247 (a1)(iii)]:


For frequency hopping systems employing at least 75 hopping channels: 1 Watt
 For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts



Result data graph shows the frequency of lowest channel




Result data graph shows the frequency of middle channel





Result data graph shows the frequency of highest channel






4.8 Out of Band Emissions and Emissions in Restricted Bands

Test Requirement: FCC part 15 section 15.247 (d)
Test Method: ANSI C63.4:2009
Test Date: 2014-03-19
Mode of Operation: Transmitting mode.
Detector Function: Peak
Measurement BW: RBW 100KHz ; VBW 300KHz

Test Setup:



**Result : PASS****Out of Frequency Band Emissions:**

For out of band emissions that are close to or exceed 20dB attenuation requirement, and emission falls into restricted band, radiated emission was performed in order to show compliance with the general radiated emission requirement.

Result Summary:

Refer to the emission data graph, result shows that the significant emissions detected are with more than 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Limits for Out of Frequency Band Emission [Section 15.247 (d)]:

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. Attenuation below the general limits specified in Section 15.209(a) is not required.

Limit for Radiated Emission Falling in Restricted Bands [Section 15.209]:

Frequency (MHz)	Field Strength [μ V/m]	Field Strength [dB μ V/m]
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.



Result : PASS

All Emission and Emissions Fall into Restricted Band were recorded as below:

Radiated Emissions							
	Emissions Frequency	E-Field Polarity	Reading	System Factor	Field strength at 3m	Limit	Delta to Limit
	MHz		dBuV/m	dB	dBuV/m	dBuV/m	dBuV/m
Lowest Channel							
PK	4808.00	V	46.88	8.30	55.18	74.00	-18.82
PK	4808.00	H	47.68	8.30	55.98	74.00	-18.02
Middle Channel							
PK	4880.00	V	46.92	8.40	55.32	74.00	-18.68
PK	48880.00	H	45.28	8.40	53.68	74.00	-20.32
Highest Channel							
PK	4958.00	V	44.82	8.46	53.28	74.00	-20.72
PK	4958.00	H	44.01	8.46	52.47	74.00	-21.53
Spurious Emissions							
QP	39.70	V	25.62	8.51	34.13	40.00	-5.87
QP	135.08	V	24.22	13.15	37.37	43.50	-6.13
QP	319.38	V	22.93	16.70	39.63	46.00	-6.37
QP	384.05	V	19.13	18.96	38.09	46.00	-7.91
QP	400.22	V	20.40	19.08	39.48	46.00	-6.52
QP	479.43	V	17.64	20.91	38.55	46.00	-7.45
QP	46.17	H	11.22	11.49	22.71	40.00	-17.29
QP	117.30	H	25.18	11.67	36.85	43.50	-6.65
QP	202.98	H	17.65	12.11	29.76	43.50	-13.74
QP	319.38	H	23.95	16.70	40.65	46.00	-5.35
QP	384.05	H	21.11	18.96	40.07	46.00	-5.93
QP	479.43	H	19.77	20.91	40.68	46.00	-5.32

Refer to Figures shows the worst case channel's emission data graph from 30MHz-26GHz.



Result Summary:


- 1) Communication mode: All other emissions are more than 20dB below FCC part 15.209 limit.
- 2) No further spurious emissions found between 30 MHz and lowest internal used/generated frequency and from 30MHz to 1GHz.

Remarks:


1. “*” Radiated emissions which fall in the restricted bands as defined in Section 15.205(a).
2. Emission level with more than 20dB below the FCC required limit is not mentioned in table.
3. Delta to Limit = Field strength (dB μ V/m) – Limit (dB μ V/m).
4. Calculated measurement uncertainty: 9kHz -30MHz: 1.8dB.
30MHz -1GHz: 5.2dB.
1GHz -18GHz: 5.1dB.



Radiated emission data graph (Vertical polarization, 30MHz-1GHz)



Radiated emission data graph (Horizontal polarization, 30MHz-1GHz)






4.9 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC part 15 Section 15.207 Class B
 Test Method: ANSI C63.4:2009
 Test Date: 2014-03-19
 Mode of Operation: -Transmitting mode
 Detector Function: CISPR Quasi Peak
 Measurement BW: 100 kHz
 Worst Case Channel: 1

Test Setup:



Results: PASS

- Refer Figures and tables for the result.

Limits for Conducted Emission [Section 15.207]:

Frequency Range [MHz]	Quasi-Peak Limit [dB μ V]	Average Limit [dB μ V]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50


* Decreases with the logarithm of the frequency.

Remarks:

Calculated measurement uncertainty: ± 2.8 dB



Result data graph shows the conducted emission (Live).




Refer to the following table for the result details:

Conducted Emission					
Frequency (MHz)	Detector (QP/AV)	Phase	Result (dB μ V)	Limit (dB μ V)	Margin
0.158	QP	L	54.10	65.56	-11.46
0.182	QP	L	51.71	64.39	-12.68
0.218	QP	L	50.56	62.89	-12.33
0.370	QP	L	39.87	58.50	-18.63
1.066	QP	L	33.58	56.00	-22.42
3.714	QP	L	34.91	56.00	-21.09



Result data graph shows the conducted emission (Neutral).



Refer to the following table for the result details:

Conducted Emission					
Frequency (MHz)	Detector (QP/AV)	Phase	Result (dB μ V)	Limit (dB μ V)	Margin
0.166	QP	N	54.11	65.15	-11.04
0.206	QP	N	51.88	63.36	-11.48
0.242	QP	N	49.27	62.02	-12.75
0.818	QP	N	38.29	56.00	-17.71
2.106	QP	N	35.83	56.00	-20.17
6.840	QP	N	37.20	60.00	-22.80



5.0 List of Measurement Equipment

Radiated Emission and Bandwidth Emissions

Description	Manufacturer	Model no.	Serial no.	CAL due
N/A	3m Semi- Anechoic Chamber	9.0(L)*6.0(W)* 6.0(H)	N/A	Jul. 16 2014
Agilent	Spectrum Analyzer	E4440A	US41421290	Jul. 16 2014
R&S	EMI Test Receiver	ESCI	100694	Jul. 16 2014
A.H.	Wideband Antenna	SAS-521-4	26	Jul. 16 2014
EMCO	Antenna	3142C	60447	Jul. 16 2014
EM	Horn Antenna	EM-AH-10180	67	Jul. 16 2014
EM	Power Amplifier	EM30180	0607030	Jul. 16 2014
MF	Position Controller	MF-7802	MF780208138	N/A

Conducted Emissions

Description	Manufacturer	Model no.	Serial no.	CAL due
N/A	Shielding Room	7.(L)x4(W)x3(H)	N/A	Jul. 16 2014
R&S	EMI Test Receiver	ESCI	100694	Jul. 16 2014
R&S	LISN	ESH3-Z5	8389791009	Jul. 16 2014

N/A Not Applicable or Not Available