

RF Exposure Report

Report No.: SA160428C07-2 R1

FCC ID: VPYLB1KD

Test Model: LBEE6ZZ1KD

Received Date: Apr. 28, 2016

Test Date: May 19 ~ Jul. 13, 2016

Issued Date: Jul. 25, 2016

Applicant: Murata Manufacturing Co., Ltd.

Address: 10-1, Higashikotari 1-chome, Nagaokakyo-shi, Kyoto 617-8555, Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA160428C07-2	Original release.	May 27, 2016
SA160428C07-2 R1	1. Revised product name 2. BT EDR/LE function: The EUT changed Bluetooth Config File (hcd file) to BCM4349B1_002.002.014.0077.0092.hcd test, the RF exposure was re-calculation	Jul. 25, 2016

1 Certificate of Conformity

Product: Communication Module

Brand: MURATA

Test Model: LBEE6ZZ1KD

Sample Status: Engineering sample

Applicant: Murata Manufacturing Co., Ltd.

Test Date: May 19 ~ Jul. 13, 2016

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 (October 23, 2015)
IEEE C95.1


The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Pettie Chen / Senior Specialist

Date: Jul. 25, 2016

Approved by :


Ken Liu / Senior Manager

Date: Jul. 25, 2016

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	1TX	22.65	2.37	20	0.0632	1
5180-5240	1TX	9.36	2.93	20	0.0034	1
	2TX	12.15	5.94	20	0.0128	1
5260-5320	1TX	9.39	2.93	20	0.0034	1
	2TX	12.14	5.94	20	0.0128	1
5500-5720	1TX	9.82	2.93	20	0.0037	1
	2TX	12.95	5.94	20	0.0154	1
5745-5825	1TX	10.12	2.93	20	0.0040	1
	2TX	12.73	5.94	20	0.0146	1
BT EDR	-	8.99	2.37	20	0.0027	1
BT LE	-	5.72	2.37	20	0.0013	1

Note:

WLAN: 5GHz Band: 2TX: Directional gain = 2.93dBi + 10log(2) = 5.94dBi

CONCLUSION:

Only WLAN 2.4G (1TX) & WLAN 5G (1TX) can transmit simultaneously (declared by client), the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4G (1TX) + WLAN 5G (1TX) = 0.0632 + 0.0154 = 0.00786

Therefore, the maximum calculation of this situation is 0.00786, which is less than the "1" limit.

---END---