

EMV TESTHAUS

test report

EMV TESTHAUS

Customer:
Xylem Analytics Germany GmbH

Dr. Karl-Slevogt-Straße 1
82362 Weilheim
Germany Tel.: +49 881 183-0
Fax: +49 881 183-420

RF test report

170586-AU01+W05



Industry
Canada

Xylem Analytics Germany GmbH

RFID module

NFC-Module1



The test result refers exclusively to the
model tested.

This test report may not be copied or published
in extracts without the written authorization of
the accreditation agency and/or
EMV TESTHAUS GmbH



Deutsche
Akkreditierungsstelle
D-PL-12155-01-00

EMV **TESTHAUS** GmbH

Gustav-Hertz-Straße 35
94315 Straubing
Germany
Tel.: +49 9421 56868-0
Fax: +49 9421 56868-100
Email: info@emv-testhaus.com

Accreditation:



Test Firm Type "accredited": Valid until 2019-05-06
MRA US-EU, FCC designation number: DE0010
BNetzA-CAB-02/21-02/04 Valid until 2018-11-27

Industry Canada test site numbers with registration expiry date:
3472A-1, expiring 2018-11-09
3472A-2, expiring 2018-11-12

Test laboratory:

EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

The technical accuracy is guaranteed through the quality management of
EMV **TESTHAUS** GmbH.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

Table of contents

1	Summary of test results	6
2	Referenced publications	8
3	Equipment under test (EUT)	9
3.1	General information	9
3.2	Radio specifications	10
3.3	Photo documentation	10
4	Test configuration and mode of operation	11
4.1	Test configuration	11
4.2	Mode of operation	11
5	Test procedures	12
5.1	General specifications	12
5.2	Radiated emissions below 30 MHz	12
5.3	Radiated emissions from 30 MHz to 1 GHz	14
5.4	Radiated emissions above 1 GHz	16
5.5	Bandwidth measurements	20
5.6	Operation within the band 13.110 MHz - 14.010 MHz	20
5.7	Carrier frequency stability	21
6	Test results	22
6.1	20 dB bandwidth	23
6.2	Occupied bandwidth	27
6.3	Operation within the band 13.110 MHz – 14.010 MHz	30
6.4	Carrier frequency stability	34
6.5	Emissions outside the operating frequency band(s) specified	38
6.6	Band-edge compliance (radiated)	51
7	Equipment calibration status	53
8	Measurement uncertainties	54
9	Revision history	55



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

List of figures

Figure 1: Setup for radiated emissions test below 30 MHz	14
Figure 2: Setup for radiated emissions test from 30 MHz to 1 GHz	16
Figure 3: Setup for radiated emissions test above 1 GHz	19
Figure 4: Test setup for carrier frequency stability measurement.....	21
Figure 5: Chart of 20 dB bandwidth on channel 01	25
Figure 6: Chart of occupied bandwidth test.....	29
Figure 7: Spektrum mask of 13.56 MHz @ 3m distance	32
Figure 8: Chart of emissions test below 30 MHz without tag in position 2, antenna parallel @ 3 m.....	40
Figure 9: Chart of emissions test from 30 MHz to 1 GHz with tag in position 1	44
Figure 10: Chart of radiated disturbance test 1 GHz – 18 GHz, with tag, EUT position 1, horizontal polarization of antenna	49
Figure 11: Final results of radiated disturbance test1 GHz – 18 GHz, with tag, EUT position 1, horizontal polarization of antenna.....	49
Figure 12: Chart of radiated disturbance test 18 GHz – 25 GHZ – exploratory measurement- polarization vertical + horizontal	50
Figure 13: Chart of radiated emission – Band edge compliance	52
Figure 14: Final results of radiated emission measurement – Band edge compliance	52



List of tables

Table 1: Devices used for testing	11
Table 2: Recalculation factors for extrapolation	13
Table 3: Bandwidth and detector type for radiated emissions test below 30 MHz	13
Table 4: Bandwidth and detector type for radiated emissions test from 30 MHz to 1 GHz	15
Table 5: Bandwidth and trace settings for exploratory radiated emissions test above 1 GHz.....	17
Table 6: Bandwidth and detector type for final radiated emissions test above 1 GHz	17
Table 7: Results of 20 dB bandwidth tests.....	25
Table 8: Results of occupied bandwidth test.....	29
Table 9: Results of emission within the band 13.110 MHz to 14.010 MHz	32
Table 10: General radiated emission limits up to 30 MHz according to §15.209	39
Table 11: Final results of emission below 30 MHz, without tag in position 2, antenna parallel @ 3 m	41
Table 12: General radiated emission limits \geq 30 MHz according to §15.209	43
Table 13: Final results of emissions test from 30 MHz to 1 GHz with tag in position 1	45
Table 14: General radiated emission limits above 960 MHz according to §15.209	47



1 Summary of test results

System type: RFID Reader

47 CFR part and section	Test	Equivalent to IC radio standard(s)	Page	Result	Note(s)
15.207	AC power line conducted emissions 150 kHz to 30 MHz	RSS-210, section 3.1 RSS-Gen, section 8.8	---	Not applicable	1
15.215(c)	20 dB bandwidth	---	23	For information only	---
2.202(a) ANSI C63.10	Occupied bandwidth (99 %)	RSS-Gen, section 6.7	27	For information only	---
15.225 (a) – (d)	Operation within the band 13.110 – 14.010 MHz	RSS-210 section B.6	30	Passed	---
15.225(e)	Carrier frequency stability	RSS-210, section B.6 RSS-Gen, section 6.11	34	Passed	---
15.247(d) ANSI C63.10	Band-edge measurements	RSS-247, Section 5.5	51	Passed	---
15.209	Emissions outside the operating frequency band(s) specified 9 kHz to 10 th harmonic 9 kHz to 30 MHz 30 MHz to 1 GHz 1 GHz to 10 th harmonic	RSS-Gen, section 6.13 RSS-Gen, section 8.9	38 42 46	Passed Passed Passed	--- --- 3

Notes (for information about EUT see clause 3):

- 1 Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.
- 2 Not applicable if the 10th harmonic of the intentional transmitter is beyond 1 GHz (please see 47 CFR Part 15, section 15.33(a)(1), and RSS-Gen, section 6.13)
- 3 According to 47 CFR Part 15, §15.33, the frequency range of investigation for the digital device shall be used if the range of investigation determined by the highest internal frequency of the digital device is higher than the 10th harmonic of the intentional radiator



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

Straubing, September 13, 2018

Andreas Menacher

Andreas Menacher
Test engineer
EMV **TESTHAUS** GmbH

Konrad Graßl

Konrad Graßl
Head of radio department
EMV **TESTHAUS** GmbH



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

2 Referenced publications

Publication	Title
CFR 47 Part 2 October 2017	Code of Federal Regulations, Title 47 (Telecommunication), Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)
CFR 47 Part 15 October 2017	Code of Federal Regulations, Title 47 (Telecommunication), Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)
ANSI C63.10 June 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB Publication no. 558074 April 02, 2019	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
RSS-Gen, Issue 5 April 2018	Spectrum Management and Telecommunications - Radio Standards Specification - General Requirements for Compliance of Radio Apparatus
RSS-210 Issue 9, August 2016	Spectrum Management and Telecommunications Radio Standards Specification Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment
RSS-247, Issue 2 February 2017	Spectrum Management and Telecommunications - Radio Standards Specification - Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

3 Equipment under test (EUT)

All Information in this clause is declared by customer.

3.1 General information

Product type: RFID module
Model name: NFC-Module1
HMN: TLC 750 NFC
Serial number Host: DUT_4
Applicant: Xylem Analytics Germany GmbH
Manufacturer: Xylem Analytics Germany GmbH
Version: Hardware: 1.00
Software: 1.00
Additional modifications: For carrier frequency stability test the battery of the device was removed, to connect a DC-power supply to the device.
FCC ID: VQ5-NFCMODULE1
Power supply: Battery supply
Nominal voltage: 3.7 V
Minimum voltage: 3.0 V
Maximum voltage: 4.2 V
Nominal frequency: ---
Temperature range: -25 °C to +50 °C (customer defined)
Device type: Portable Mobile Fixed



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

3.2 Radio specifications

System type:	RFID Reader		
Application frequency band:	13.110 MHz – 14.010 MHz		
Frequency range used:	13.273237 MHz – 13.865325 MHz		
Operating frequencies:	13.56 MHz		
Short description:	The EUT is a RFID module which works at 13.56 MHz and is tested in a handheld temperature measuring device which employs also Bluetooth low energy and wireless power transfer (receiver). In this test report only the RFID module is the subject of matter.		
Number of RF channels	1		
Modulation	ASK		
Antenna:	Type:	PCB antenna	
	Gain:	n/a	
	Connector:	<input type="checkbox"/> external <input type="checkbox"/> temporary	<input type="checkbox"/> internal <input checked="" type="checkbox"/> none (integral antenna)

3.3 Photo documentation

For external photos of the EUT see annex B, for internal ones see annex C.

Photos taken during testing including EUT positions can be found in annex A.

For radiated emission measurements, premeasurements were performed in 3 orthogonal positions, the positions are shown in annex A.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

4 Test configuration and mode of operation

4.1 Test configuration

Device	Type designation	Serial or inventory no.	Manufacturer
<i>EUT</i>			
TLC 750 NFC	Handheld temperature measuring device with NFC, BLE and WPT.	DUT_4	Xylem Analytics Germany GmbH
<i>Support equipment</i>			
RFID-tag	13.56 MHz	---	---
DC-Power supply	Statron 3231.1	E01235	Statron Gerätetechnik GmbH

Table 1: Devices used for testing

4.2 Mode of operation

4.2.1 Test software used for all tests

Manufacturer programmed all EUT's to "continuous-tag-reading-mode".

4.2.2 Test modes applied

During the pre-tests it was observed that the "continuous-tag-reading-mode" is the respective worst- case. Therefore this mode was selected for final testing. The device was configured by manufacturer to activate the RFID reader for continuous transmission via RFID card.

The information if a tag was used or not used has been noted at the respective test.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

5 Test procedures

5.1 General specifications

5.1.1 Test setups

Tabletop devices are placed on a non-conductive table with a height of 0.8 m. In case of AC power-line conducted emissions test, the rear of the EUT is located 40 cm to the vertical wall of the RF-shielded (screened) room which is used as vertical conducting plane. For radiated emission measurements above 1 GHz, tabletop devices are placed at a height of 1.5 m above the floor using a support made of styrene placed on top of the non-conductive table.

Floor-standing devices are placed either directly on the reference ground-plane or on insulating material (see clause 6.3.3 of ANSI C63.4-2014 for more details).

All other surfaces of tabletop or floor-standing EUTs are at least 80 cm from any other grounded conducting surface. This includes the case or cases of one or more LISNs when performing an AC power-line conducted emissions test.

Radiated emission measurements of equipment that can be used in multiple orientations (e.g. portable or handheld devices) are performed with the EUT in each of three orthogonal axis positions.

5.2 Radiated emissions below 30 MHz

Radiated emissions below 30 MHz are measured according to clause 6.4 of ANSI C63.10 using an inductive shielded loop antenna. As this antenna measures the magnetic field only, its antenna factors are converted to electric field strength values assuming a free space impedance of 377Ω as described in clause 4.3.1 of ANSI C63.10. This results in an additional correction of 51.53 dB.

According to clause 6.4.3 of ANSI C63.10, at frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the requirements. In this case, the results are extrapolated to the specified distance by using a recalculation factor determined according to one of the methods described in clause 6.4.4 of ANSI C63.10, provided that the maximum dimension of the device is equal to or less than 0.625 times the wavelength at the frequency being measured. As the minimum wavelength is 10 meters corresponding to the maximum frequency of 30 MHz, this requirement is fulfilled if the maximum dimension of the device is equal to or less than 6.25 meters.

Unless otherwise stated, the recalculation factor is determined according to clause 6.4.4.2 "Extrapolation from the measurement of a single point" of ANSI C63.10:



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

$$\begin{aligned}
 d_{\text{near field}} &= 47.77 / f_{\text{MHz}}, \text{ or} \\
 f_{\text{MHz}} &= 47.77 / d_{\text{near field}}
 \end{aligned}$$

The frequency f_{MHz} at which the near field distance is equal to the limit and/or test distance is important for selection of the right formula to determine the recalculation factor:

$$\begin{aligned}
 f_{\text{MHz}}(300 \text{ m}) &\approx 0.159 \text{ MHz} \\
 f_{\text{MHz}}(30 \text{ m}) &\approx 1.592 \text{ MHz} \\
 f_{\text{MHz}}(3 \text{ m}) &\approx 15.923 \text{ MHz}
 \end{aligned}$$

Based on the test distances for the general radiated emission limits as specified in §15.209 of 47 CFR Part 15, the following formulas are used to determine the recalculation factor:

Frequency (f)	d_{limit}	d_{measure}	Formula for recalculation factor
9 kHz \leq f \leq 159 kHz 490 kHz $<$ f \leq 1.592 MHz	300 m 30 m	3 m	$-40 \log(d_{\text{limit}} / d_{\text{measure}})$
159 kHz $<$ f \leq 490 kHz 1.592 MHz $<$ f \leq 15.923 MHz	300 m 30 m	3 m	$-40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$
f $>$ 15.923 MHz	30 m	3 m	$-20 \log(d_{\text{limit}} / d_{\text{measure}})$

Table 2: Recalculation factors for extrapolation

Prescans for radiated measurements below 30 MHz are performed in a fully anechoic room (called "CDC"). The measurement distance is 3 meters. The emissions of the EUT are recorded with an EMI test receiver configured as described in table 3.

Frequency (f)	Measurement receiver bandwidth	Step size	Detector type		
			Prescan	Prescan with FFT	Final scan
9 kHz \leq f $<$ 150 kHz	200 Hz	\leq 100 Hz	Peak, Average	Peak Quasi-peak, Average	Peak Quasi-peak, Average
150 kHz \leq f $<$ 30 MHz	9 kHz	\leq 4.5 kHz	Peak, Average	Peak Quasi-peak, Average	Peak Quasi-peak, Average

Table 3: Bandwidth and detector type for radiated emissions test below 30 MHz

Prescans are performed with all detectors activated at the same time. If the test receiver is capable of FFT analysis, it is used for prescans, but not for final scans. If no limit is specified for certain detectors, final scan measurement with these detectors may be omitted.

The radiated emissions test below 30 MHz is performed in the following steps:

- The loop antenna is positioned with its plane perpendicular to the ground with the lowest height of the antenna 1 m above the ground.
- The EUT is placed in its standard position on a turntable capable of rotation through 360° in the horizontal plane and arranged as tabletop or floor-standing equipment, as applicable. The EUT is switched on.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

- c) The measurement equipment is connected to the loop antenna and set-up according to the specifications of the test (see table 3).
- d) The EUT is turned to a position likely to get the maximum and the test antenna is rotated to detect the maximum of the fundamental in this EUT position.
- e) Then the EUT is rotated in a horizontal plane through 360° in steps of 45°. Starting at 0°, at each table position the spectrum for the full frequency range is recorded. If the emission at a certain frequency is higher than the levels already recorded, the current table position is noted as the maximum position.
- f) After the last prescan, the significant maximum emissions and their table positions are determined and collected in a list.
- g) With the test receiver set to the first frequency of the list, the EUT is rotated by $\pm 45^\circ$ around the table position found during prescans while measuring the emission level continuously. For final scan, the worst-case table position is set and the maximum emission level is recorded.
- h) Step g) is repeated for all other frequencies in the list.
- i) Finally, for frequencies with critical emissions the loop antenna is rotated again to find the maximum of emission. At least, frequency and level of the six highest emissions relative to the limit have to be recorded. However, emissions more than 20 dB below the limit do not need to be reported.

If the EUT may be used in various positions, steps a) to i) are repeated in two other orthogonal positions. If the EUT may be used in one position only, steps a) to i) are repeated in one orthogonal position.




Figure 1: Setup for radiated emissions test below 30 MHz

5.3 Radiated emissions from 30 MHz to 1 GHz

Radiated emissions in the frequency range 30 MHz to 1 GHz are measured according to clause 6.5 of ANSI C63.10 using a semi-anechoic chamber (SAC) with a ground plane on the floor. The measurement distance is 3 meters. The emissions of the EUT are recorded with an EMI test receiver configured as described in table 4.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

Frequency (f)	Measurement receiver bandwidth	Step size	Detector type		
			Prescan	Prescan with FFT	Final scan
30 MHz ≤ f ≤ 1 GHz	120 kHz	≤ 60 kHz	Peak	Quasi-peak	Quasi-peak

Table 4: Bandwidth and detector type for radiated emissions test from 30 MHz to 1 GHz

The measurement antenna is a combination of a biconical antenna and a logarithmic-periodic dipole array antenna. It is mounted on a support capable of allowing the antenna to be used in either horizontal or vertical polarization and in a height between 1 m and 4 m above the ground plane.

If the test receiver is capable of FFT analysis, it is used for prescans, but not for final scans.

The radiated emissions test from 30 MHz to 1 GHz is performed in the following steps:

- a) The measurement antenna is oriented initially for vertical polarization.
- b) The EUT is placed in its standard position on a turntable capable of rotation through 360° in the horizontal plane and arranged as tabletop or floor-standing equipment, as applicable. The EUT is switched on.
- c) The measurement equipment is connected to the measurement antenna and set-up according to the specifications of the test (see table 4).
- d) The table position is set to 0°.
- e) The antenna height is set to 1 m.
- f) The spectrum for the full frequency range is recorded. If the emission at a certain frequency is higher than the levels already recorded, the polarization and height of the measurement antenna as well as the current table position are noted as the maximum position.
- g) The antenna height is increased to 4 m in steps of 50 cm. At each height, step f) is repeated.
- h) The polarization of the measurement antenna is changed to horizontal.
- i) The antenna height is decreased from 4 m to 1 m in steps of 50 cm. At each height, step f) is repeated.
- j) The EUT is rotated in a horizontal plane through 360° in steps of 60°. At each table position, steps e) to i) are repeated.
- k) After the last prescan, the significant maximum emissions with their polarizations and heights of the measurement antenna as well as their table positions are determined and collected in a list.
- l) With the test receiver set to the first frequency of the list, the measurement antenna is set to the polarization and height and the table is moved to the position as determined during prescans.
- m) The antenna is moved by ±50 cm around this height and the EUT is rotated by ±60° around this table position while measuring the emission level continuously.
- n) For final scan, the worst-case positions of antenna and table are set and the maximum emission level is recorded.
- o) Steps l) to n) are repeated for all other frequencies in the list. At least, frequency and level of the six highest emissions relative to the limit have to be recorded. However, emissions more than 20 dB below the limit do not need to be reported.

If the EUT may be used in various positions, steps a) to o) are repeated in two other orthogonal positions.






Figure 2: Setup for radiated emissions test from 30 MHz to 1 GHz

5.4 Radiated emissions above 1 GHz

Radiated emissions above 1 GHz are measured according to clause 6.6 of ANSI C63.10 by conducting exploratory and final radiated emission tests. According to clause 6.6.4.1 of ANSI C63.10, measurements may be performed at a distance closer than that specified in the requirements. However, an attempt shall be made to avoid making final measurements in the near field of both the measurement antenna and the EUT.

For measurement of radiated emissions above 1 GHz, horn antennas are used.

Sample calculation:

Frequency (MHz)	Reading value (dB μ V)	Antenna correction (dB/m)	Correction pre- amplifier (dB)	Cable attenuation (dB)	Correction factor (Corr.) (dB/m)	Level (dB μ V/m)
2400	50.00	27.76	-34.57	3.51	-3.30	46.70

Correction factor = Antenna correction + Correction pre-amplifier + Cable attenuation

Level = Reading value + Correction factor = 50.00 dB μ V - 3.30 dB/m = 46.70 dB μ V/m

5.4.1 Exploratory radiated emissions measurements

Exploratory radiated emissions above 1 GHz are measured in a semi-anechoic chamber with RF absorbing material on the floor or a fully anechoic room. They are performed by moving the receiving antenna over all sides of the EUT at a closer distance (e.g. 0.5 or 1 m) while observing the display of the test receiver to find the emissions to be re-tested during final radiated emission measurements.

According to clause 5.3.3 of ANSI C63.10, when performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade of distance (inverse of linear distance for field-strength measurements). To simplify testing and documentation, the limits are increased accordingly instead of decreasing the results.

The emissions of the EUT are displayed and recorded with an EMI test receiver operating in the spectrum analyzer mode using the settings as described in table 5.

Frequency (f)	Resolution bandwidth	Video bandwidth	Sweep time	Trace detector(s)	Trace mode(s)	Test
f ≥ 1 GHz	1 MHz	3 MHz	AUTO	Max Peak, Average	Clear Write	Searching
					Max Hold	Recording

Table 5: Bandwidth and trace settings for exploratory radiated emissions test above 1 GHz

If during exploratory radiated emissions measurements no levels to be re-tested are found, the final radiated emissions measurement may be omitted. In this case, the chart of the exploratory radiated emissions measurements has to be reported.

5.4.2 Final radiated emissions measurements

Final radiated emissions above 1 GHz are measured in a semi-anechoic chamber (SAC) with RF absorbing material on the floor between measurement antenna and EUT. The measurement distance is 3 meters. The emissions of the EUT are recorded with an EMI test receiver configured as described in table 6.

Frequency (f)	Measurement receiver bandwidth	Step size	Detector type	
			Prescan	Final scan
f ≥ 1 GHz	1 MHz	≤ 500 kHz	Peak, Average	Peak, Average

Table 6: Bandwidth and detector type for final radiated emissions test above 1 GHz

Prescans are performed with both detectors activated at the same time. If the test receiver is capable of FFT analysis, it is used for prescans, but not for final scans.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

The horn antenna is mounted on a support capable of allowing the antenna to be used in either horizontal or vertical polarization and to be moved in a scan height range between 1 m and the scan height upper range defined in clause 6.6.3.3 of ANSI C63.10. When the EUT is manipulated through three different orientations, the scan height upper range for the measurement antenna is limited to 2.5 m above the ground plane or 0.5 m above the top of the EUT, whichever is higher. Otherwise, the scan height upper range is 4 m above the ground plane.

To keep the emission signal within the illumination area of the 3 dB beamwidth of the measurement antenna, the automatic tilt function of the antenna support device is used to point the antenna at an angle toward the source of the emission.

The final radiated emissions test above 1 GHz is performed in the following steps:

- a) The measurement antenna is oriented initially for vertical polarization.
- b) The EUT is placed in its standard position on a turntable capable of rotation through 360° in the horizontal plane and arranged as tabletop or floor-standing equipment, as applicable. The EUT is switched on.
- c) The measurement equipment is connected to the measurement antenna and set-up according to the specifications of the test (see table 6).
- d) The table position is set to 0°.
- e) The antenna height is set to 1 m.
- f) The spectrum for the full frequency range is recorded. If the emission at a certain frequency is higher than the levels already recorded, the polarization and height of the measurement antenna as well as the current table position are noted as the maximum position.
 - g) The antenna height is increased to the scan height upper range in steps of 50 cm. At each height, step f) is repeated.
- h) The polarization of the measurement antenna is changed to horizontal.
- i) The antenna height is decreased from the scan height upper range to 1 m in steps of 50 cm. At each height, step f) is repeated.
- j) The EUT is rotated in a horizontal plane through 360° in steps of 30°. At each table position, steps e) to i) are repeated.
- k) After the last prescan, the significant maximum emissions with their polarizations and heights of the measurement antenna as well as their table positions are determined and collected in a list.
- l) With the test receiver set to the first frequency of the list, the measurement antenna is set to the polarization and height and the table is moved to the position as determined during prescans.
- m) The antenna is moved by ± 50 cm around this height and the EUT is rotated by ± 30 ° around this table position while measuring the emission level continuously.
- n) For final scan, the worst-case positions of antenna and table are set and the maximum emission level is recorded.
- o) Steps l) to n) are repeated for all other frequencies in the list. At least, frequency and level of the six highest emissions relative to the limit have to be recorded. However, emissions more than 20 dB below the limit do not need to be reported.

If the EUT may be used in various positions, steps a) to o) are repeated in two other orthogonal positions.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1




Figure 3: Setup for radiated emissions test above 1 GHz

5.5 Bandwidth measurements

5.5.1 20 dB bandwidth of the emission

The 20 dB bandwidth of the emission is measured according to clause 6.9.2 of ANSI C63.10 as the width of the spectral envelope of the modulated signal, at an amplitude level reduced by a ratio of 20 dB down from the reference value.

The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer is between two times and five times the 20 dB bandwidth. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 % to 5 % of the 20 dB bandwidth and the video bandwidth (VBW) shall be approximately three times RBW.

The reference level of the instrument is set as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (20 \text{ dB bandwidth}/\text{RBW})]$ below the reference level.

5.5.2 99 % occupied bandwidth

According to section 6.7 of RSS-Gen, the occupied bandwidth (OBW) is defined as the 99 % emission bandwidth.

The span of the spectrum analyzer is set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

The resolution bandwidth is in the range of 1 % to 5 % of the occupied bandwidth and the video bandwidth is not smaller than three times the resolution bandwidth. Video averaging is not permitted.

If possible, the detector of the spectrum analyzer is set to "Sample". However, if the device is not transmitting continuously, a peak, or peak hold is used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement).

To measure the 99 % emission bandwidth, the OBW function of the test receiver is used with the power bandwidth set to 99 %. This function indicates the lowest frequency (starting from the left side of the span) and the highest frequency (starting from the right side of the span) where 0.5% of the total sum is reached. The difference between the two frequencies is the 99 % occupied bandwidth.

5.6 Operation within the band 13.110 MHz - 14.010 MHz

The EUT was placed in a fully anechoic chamber and the testing was performed in accordance with ANSI C63.10 and 47 CFR Part 15, section 15.225 (a) to (d). The measurement distance was 3



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

m. To find the closest margin of the spectrum to the limit mask adapted to the test distance the EUT was rotated by 360 degrees with detector of the test receiver set to peak. The loop antenna placed in a fixed height of 1 meter was rotated by 360 degrees to get the maximum of emission. In case of exceeding the limits the detector is switched to quasi peak for final testing in position of maximum emission.

5.7 Carrier frequency stability

1. If possible EUT is operating providing an unmodulated carrier. The peak detector of the spectrum analyzer is selected and resolution as well as video bandwidth are set to values appropriate to the shape of the spectrum of the EUT. The frequency counter mode of the spectrum analyzer is used to maximize the accuracy of the measured frequency tolerance. If an unmodulated carrier is not available a significant and stable point on the spectrum is selected and the span is reduced to a value that delivers an accuracy which shall be better than 1% of the maximum frequency tolerance allowed for the carrier signal. This method may be performed as long as the margin to the frequency tolerance allowed is larger than the uncertainty of the measured frequency tolerance.
2. The carrier frequency is measured depending on the variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment an external supply voltage can be used and set at the battery nominal voltage, and again at the battery operating end point voltage which must be specified by the equipment manufacturer. Alternatively, tests shall be performed using a new battery.
3. The carrier frequency is measured over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage.




Figure 4: Test setup for carrier frequency stability measurement

6 Test results

This clause gives details about the test results as collected in the summary of test results on page 6.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.1 20 dB bandwidth

Performed by:	Andreas Menacher	Date(s) of test:	June 28, 2018
Climatic conditions:	Ambient temperature 24 °C	Relative humidity 36 %	Barometric pressure 976 hPa
Result ¹ :	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.1.1 Test equipment

	Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/>	EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00552
<input type="checkbox"/>	EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/>	EMI test receiver	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/>	EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/>	EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/>	Field probe	RF-R 400-1	Langer EMV-Technik	E00270

¹ For information about measurement uncertainties see page 92.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

170586-AU01+W05

Page 23 of 55

6.1.1 Limits

According to §15.215(c), intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.1.2 Test procedure

The 20 dB bandwidth is measured using the test procedure as described in clause 5.5.1.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.1.3 Test results

Remark: The 20 dB bandwidth measurement was performed without tag, because this was the worst case.




Figure 5: Chart of 20 dB bandwidth on channel 01

20 dB bandwidth [kHz]	Band edge left		Band edge right		Result
	Frequency [MHz]	Limit [MHz]	Frequency [MHz]	Limit [MHz]	
426.600	13.348388	13.110	13.774988	14.010	Recorded

Table 7: Results of 20 dB bandwidth tests

f_{assigned} (MHz)	Index	f_{-20dB} (MHz)	Δf_T (kHz)	Δf_U (kHz)	$f_{-20dB(T, U)}$ (MHz)	Limit (MHz)	Margin (kHz)	Result
13.560000	low	13.543912	0.125	0.038	13.543749	13.110000	433.749	Passed
	high	13.573837	4.375	0.187	13.578399	14.010000	431.601	Passed
	Bandwidth	29.925 kHz			34.650 kHz			

with:

- $f_{-20dB(\text{low})}$ = lower frequency in MHz where emission is at least 20 dB below the carrier
- $f_{-20dB(\text{high})}$ = upper frequency in MHz where emission is at least 20 dB below the carrier
- f_{assigned} = assigned frequency in kHz
- $\Delta f_{T(\text{low})}$ = maximum absolute value of negative frequency offset to frequency at nominal conditions caused by temperature variation in kHz
- $\Delta f_{U(\text{low})}$ = maximum absolute value of negative frequency offset to frequency at nominal conditions caused by voltage variation in kHz
- $\Delta f_{T(\text{high})}$ = maximum absolute value of positive frequency offset to frequency at nominal conditions caused by temperature variation in kHz
- $\Delta f_{U(\text{high})}$ = maximum absolute value of positive frequency offset to frequency at nominal conditions caused by voltage variation in kHz
- $\Delta f_{\text{volt}(\text{high})}$ = maximum absolute value of positive frequency offset to frequency at nominal conditions caused by voltage variation in kHz
- $f_{-20dB(T, U)}$ = frequency in MHz where emission is at least 20 dB below the carrier, including offset caused by variations of temperature and supply voltage as recorded in clause 5.7

Measured -20 dB emission bandwidth:

At nominal conditions: 29.925 kHz

Including variations in temperature and supply voltage: 34.650 kHz



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.2 Occupied bandwidth

Section(s) in 47 CFR Part 15:	Requirement(s): Reference(s):	2.202(a) ANSI C63.10, clause 6.9
Section(s) in RSS:	Requirement(s): Reference(s):	RSS-Gen, section 6.7 ANSI C63.10, clause 6.9

Performed by:	Andreas Menacher	Date(s) of test:	June 28, 2018
Climatic conditions:	Ambient temperature 24 °C	Relative humidity 36 %	Barometric pressure 976 hPa
Result ² :	<input checked="" type="checkbox"/> Test passed <input type="checkbox"/> Test not passed		

6.2.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00552
<input type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Field probe	RF-R 400-1	Langer EMV-Technik	E00270

² For information about measurement uncertainties see page 76.



6.2.2 Limits

Although there is no limit specified, the occupied bandwidth has to be recorded and reported.

6.2.3 Test procedure

The occupied bandwidth is measured using the test procedure as described in clause 5.5.2.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.2.4 Test results

Remark: The occupied bandwidth measurement was performed with tag, because this was the worst case.




Figure 6: Chart of occupied bandwidth test

99% bandwidth [kHz]	Band edge left		Band edge right		Result
	Frequency [MHz]	Limit [MHz]	Frequency [MHz]	Limit [MHz]	
592.087	13.273237	13.110	13.865325	14.010	Recorded

Table 8: Results of occupied bandwidth test

6.3 Operation within the band 13.110 MHz – 14.010 MHz

Section(s) in 47 CFR Part 15:	Requirement(s):	15.225 (a)-(e)
	Reference(s):	ANSI C63.10, section 6.4
Section(s) in RSS:	Requirement(s):	RSS-210, section B.6
	Reference(s):	ANSI C63.10, section 6.4

Performed by:	Andreas Menacher	Date(s) of test:	June 28, 2018
Climatic conditions:	Ambient temperature 24 °C	Relative humidity 36 %	Barometric pressure 976 hPa
Result ³ :	<input checked="" type="checkbox"/> Test passed <input type="checkbox"/> Test not passed		

6.3.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Compact Diagnostic Chamber (CDC)	VK041.0174	Albatross Projects	E00026
<input type="checkbox"/> Open area test site (OATS)	---	EMV TESTHAUS	E00354
<input type="checkbox"/> Semi-anechoic chamber (SAC)	SAC3	Albatross Projects	E00716
<input checked="" type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00552
<input type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input type="checkbox"/> Field probe	RF-R 400-1	Langer EMV-Technik	E00270
<input checked="" type="checkbox"/> Loop antenna	HFH2-Z2	Rohde & Schwarz	E00060
<input type="checkbox"/> Cable set CDC	RF cable(s)	Huber + Suhner AME HF-Technik AME HF-Technik Stabo	E00446 E00920 E00921 E01215
<input type="checkbox"/> Test software	EMC32-EB (V10.35)	Rohde & Schwarz	E00777
<input type="checkbox"/> Test software	EMC32-MEB (V10.35)	Rohde & Schwarz	E00778
<input type="checkbox"/> Test software	EMC32-MEB (V10.35)	Rohde & Schwarz	E01073

³ For information about measurement uncertainties see page 76.

6.3.2 Limits

As specified in section 15.225(a)-(d) of 47 CFR Part 15:

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

In case of measurements are performed at other distances than that specified in the requirements, the limits in the charts and tables reported with the test results are derived from the general radiated emission limits as listed above using the recalculation factor as described in clause 5.2.

6.3.3 Test procedure

The emission within the band 13.110 MHz – 14.010 MHz is measured using the test procedure as described in clause 5.6.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.3.4 Test results




Figure 7: Spektrum mask of 13.56 MHz @ 3m distance

Frequency [MHz]	Measured value [dB μ V/m]	Detector	Recalculation factor [dB]	Field strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	BW [kHz]
13.559775	45.43	PK	-21.40	24.03	84.00	59.97	10

Table 9: Results of emission within the band 13.110 MHz to 14.010 MHz

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 “Extrapolation from the measurement of a single point”:

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}$$

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$

f_{MHz} [MHz]	$d_{\text{near field}}$ [m]	d_{measure} [m]	d_{limit} [m]	Recalculation factor [dB]
13.559775	3.523	3.000	30.000	-21.40



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.4 Carrier frequency stability

Section(s) in 47 CFR Part 15: Requirement(s): 15.225(e)
Reference(s): 15.225(e)

Section(s) in RSS: Requirement(s): RSS-210, annex B6,
RSS-Gen, section 6.11
Reference(s): RSS-Gen, section 6.11

Performed by:	Andreas Menacher	Date(s) of test:	July 2, 2018
Climatic conditions:	Ambient temperature 27 °C	Relative humidity 34%	Barometric pressure 977 hPa
Result ⁴ :	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.4.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Climatic chamber 990 l	VC4100	Vötsch Industrietechnik	C00014
<input checked="" type="checkbox"/> Climatic chamber 340 l	VC ³ 4034	Vötsch Industrietechnik	C00015
<input checked="" type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00552
<input type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Field probe	RF-R 400-1	Langer EMV-Technik	E00270

⁴ For information about measurement uncertainties see page 92.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.4.2 Limits

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ (100 ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

For battery operated equipment, the equipment tests shall be performed using a new battery. Alternatively, an external supply voltage can be used and set at the battery nominal voltage, and again at the battery operating end point voltage which must be specified by the equipment manufacturer.

6.4.3 Test procedure

The carrier frequency stability is measured using the test procedure as described in clause 5.7.




EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.4.4 Test results

Carrier frequency stability vs. temperature



Supply voltage: 5 V Frequency under nominal conditions: 13.5599625 MHz


Temperature (°C)	Frequency (MHz)	Frequency Tolerance (Hz)	Frequency Tolerance (ppm)	Upper Limit (ppm)	Lower Limit (ppm)	Margin (ppm)
-20	13.560038	75	5.5	+100.0	-100.0	94.5
-10	13.560438	475	35.0	+100.0	-100.0	65.0
±0	13.560250	288	21.2	+100.0	-100.0	78.8
+10	13.560325	363	26.7	+100.0	-100.0	73.3
+20	13.559963	0	0.0	+100.0	-100.0	100.0
+30	13.560063	100	7.4	+100.0	-100.0	92.6
+40	13.560038	75	5.5	+100.0	-100.0	94.5
+50	13.559875	-87	-6.5	+100.0	-100.0	93.5



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

Carrier frequency stability vs. supply voltage



Temperature:	+20 °C	Battery End Point:	3.00 V
Frequency under nominal conditions:	13.56 MHz		

Supply Voltage (V)	Frequency (MHz)	Frequency Tolerance (Hz)	Frequency Tolerance (ppm)	Upper Limit (ppm)	Lower Limit (ppm)	Margin (ppm)
4.20	13.560163	163	12.0	+100.0	-100.0	88.0
3.70	13.559963	-38	-2.8	+100.0	-100.0	97.2
3.00	13.560188	187	13.8	+100.0	-100.0	86.2



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.5 Emissions outside the operating frequency band(s) specified

6.5.1 Emissions below 30 MHz

Section(s) in 47 CFR Part 15:	Requirement(s):	15.209
	Reference(s):	ANSI C63.10, clause 6.4
Section(s) in RSS:	Requirement(s):	RSS-Gen, section 6.13
	Reference(s):	ANSI C63.10, clause 6.4

Result⁵: Test passed Test not passed

6.5.1.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Compact Diagnostic Chamber (CDC)	VK041.0174	Albatross Projects	E00026
<input type="checkbox"/> Open area test site (OATS)	---	EMV TESTHAUS	E00354
<input type="checkbox"/> Semi-anechoic chamber (SAC)	SAC3	Albatross Projects	E00716
<input type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00552
<input type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00001
<input checked="" type="checkbox"/> EMI test receiver	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input type="checkbox"/> Field probe	RF-R 400-1	Langer EMV-Technik	E00270
<input checked="" type="checkbox"/> Loop antenna	HFH2-Z2	Rohde & Schwarz	E00060
<input type="checkbox"/> Cable set CDC	RF cable(s)	Huber + Suhner AME HF-Technik AME HF-Technik Stabo	E00446 E00920 E00921 E01215
<input type="checkbox"/> Test software	EMC32-EB (V10.35)	Rohde & Schwarz	E00777
<input checked="" type="checkbox"/> Test software	EMC32-MEB (V10.35)	Rohde & Schwarz	E00778
<input type="checkbox"/> Test software	EMC32-MEB (V10.35)	Rohde & Schwarz	E01073

⁵ For information about measurement uncertainties see page 92.



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.5.1.2 Limits

Frequency [MHz]	Field strength [μ V/m]	Field strength [dB μ V/m]	Measurement distance [m]
0.009 – 0.490	2400/F(kHz) (266.67 – 4.90)	48.52 – 13.80	300
0.490 – 1.705	24000/F(kHz) (48.98 – 14.08)	33.80 – 22.97	30
1.705 – 30	30	29.54	30

Table 10: General radiated emission limits up to 30 MHz according to §15.209

In case of measurements are performed at other distances than that specified in the requirements, the limits in the charts and tables reported with the test results are derived from the general radiated emission limits as listed in table 10 using the recalculation factor as described in clause 5.2.

6.5.1.3 Test procedure

The emissions below 30 MHz are measured using the

- test procedure for radiated measurements as described in clause 5.2.



6.5.1.4 Test results

Performed by:	Andreas Menacher	Date(s) of test:	June 28, 2018
Climatic conditions:	Ambient temperature 24 °C	Relative humidity 36 %	Barometric pressure 976 hPa
Test distance:	<input checked="" type="checkbox"/> 3 m	<input type="checkbox"/> 10 m	<input type="checkbox"/> m
Antenna alignment:	<input checked="" type="checkbox"/> in parallel	<input type="checkbox"/> in line	<input type="checkbox"/> angle °
EUT position ⁶ :	<input checked="" type="checkbox"/> Position 1	<input checked="" type="checkbox"/> Position 2	<input checked="" type="checkbox"/> Position 3

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
9 kHz – 150 kHz	50 Hz	200 Hz	QP, PK, CAV	QP, PK, AV	2 s	1 s	Off
150 kHz – 30 MHz	2.25 kHz	9 kHz	QP, PK, CAV	QP, PK, AV	2 s	1 s	Off




Figure 8: Chart of emissions test below 30 MHz without tag in position 2, antenna parallel @ 3 m

⁶ Exploratory measurements are performed in all positions as indicated. However, the figures and result tables within this test report show the worst case position, only.

Frequency (MHz)	Measured value QuasiPeak (dB μ V/m)	Recalculation factor (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (deg)	Result
13.560000	37.04	-21.40	15.64	84.00	68.36	173.0	Pass

Table 11: Final results of emission below 30 MHz, without tag in position 2, antenna parallel @ 3 m

Note: The frequency 13.56 MHz is the carrier frequency and doesn't fall under the limit of CFR 47 15.209.

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 "Extrapolation from the measurement of a single point":

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}$$

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$

f_{MHz} [MHz]	$d_{\text{near field}}$ [m]	d_{measure} [m]	d_{limit} [m]	Recalculation factor [dB]
13.560	3.523	3.000	30.000	-21.40



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.5.2 Emissions from 30 MHz to 1 GHz

Section(s) in 47 CFR Part 15:	Requirement(s): Reference(s):	15.209 ANSI C63.10, clause 6.5
Section(s) in RSS:	Requirement(s): Reference(s):	RSS-Gen, section 6.13 ANSI C63.10, clause 6.5

Result⁷: Test passed Test not passed

6.5.2.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Semi-anechoic chamber (SAC)	SAC3	Albatross Projects	E00716
<input type="checkbox"/> Free space semi-anechoic chamber (FS-SAC)	FS-SAC	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00552
<input type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00001
<input checked="" type="checkbox"/> EMI test receiver	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input type="checkbox"/> Preamplifier (1 GHz - 18 GHz)	ALS05749	Aldetec	W01007
<input type="checkbox"/> TRILOG broadband antenna (CDC)	VULB 9160	Schwarzbeck	E00011
<input type="checkbox"/> TRILOG broadband antenna (OATS)	VULB 9163	Schwarzbeck	E00013
<input checked="" type="checkbox"/> TRILOG broadband antenna (SAC)	VULB 9162	Schwarzbeck	E00643
<input type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052
<input type="checkbox"/> Horn antenna	BBHA 9170	Schwarzbeck	W00054
<input checked="" type="checkbox"/> Cable set SAC	RF cable(s)	Huber + Suhner	E00755 E01033 E01034
<input type="checkbox"/> Cable set FS-SAC	RF cable(s)	Teledyne Reynolds Huber + Suhner Teledyne Reynolds	E00435 E00307 E00433
<input checked="" type="checkbox"/> Test software	EMC32-EB (V10.35)	Rohde & Schwarz	E00777
<input type="checkbox"/> Test software	EMC32-MEB (V10.35)	Rohde & Schwarz	E00778
<input type="checkbox"/> Test software	EMC32-MEB (V10.35)	Rohde & Schwarz	E01073

⁷ For information about measurement uncertainties see page 92.



6.5.2.2 Limits

Frequency [MHz]	[μ V/m]	Field strength [dB μ V/m]	Measurement distance [m]
30 – 88	100	40.00	3
88 – 216	150	43.52	3
216 - 960	200	46.02	3
Above 960	500	53.98	3

Table 12: General radiated emission limits \geq 30 MHz according to §15.209

6.5.2.3 Test procedure

The emissions from 30 MHz to 1 GHz are measured using the

- test procedure for radiated measurements as described in clause 5.3.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.5.2.4 Test results

Performed by:	Andreas Menacher	Date(s) of test:	June 27, 2018
Climatic conditions:	Ambient temperature 25 °C	Relative humidity 33%	Barometric pressure 978 hPa
Test distance:	<input checked="" type="checkbox"/> 3 m	<input type="checkbox"/> 10 m	<input type="checkbox"/> m
EUT position ⁸ :	<input checked="" type="checkbox"/> Position 1	<input checked="" type="checkbox"/> Position 2	<input checked="" type="checkbox"/> Position 3

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
30 MHz – 1 GHz	30 kHz	120 kHz	QP	QP	1 s	1 s	20 dB




Figure 9: Chart of emissions test from 30 MHz to 1 GHz with tag in position 1

⁸ Exploratory measurements are performed in all positions as indicated. However, the figures and result tables within this test report show the worst case position, only.

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
176.280000	29.86	43.50	13.64	190.0	H	52.0
583.080000	32.90	46.00	13.10	146.0	H	283.0

Table 13: Final results of emissions test from 30 MHz to 1 GHz with tag in position 1



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.5.3 Emissions from 1 GHz to 25 GHz

Result⁹: Test passed Test not passed

6.5.3.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Semi Anechoic Chamber (SAC)	---	Albatross Projects	E00716
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Preamplifier	ALS05749	Aldetec	W01007
<input checked="" type="checkbox"/> Preamplifier	BBV 9721	Schwarzbeck	W01350
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120	Schwarzbeck	W00052
<input checked="" type="checkbox"/> Horn antenna	BBHA 9170	Schwarzbeck	W00055
<input checked="" type="checkbox"/> Measurement software	EMC 32	Rohde & Schwarz	---

⁹ For information about measurement uncertainties see page 92.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

170586-AIJ01+W05

Page 46 of 55

6.5.3.2 Limits

Frequency [MHz]	Field strength [μ V/m]	Field strength [dB μ V/m]	Measurement distance [m]
Above 960	500	53.98	3

Table 14: General radiated emission limits above 960 MHz according to §15.209

6.5.3.3 Test procedure

The emissions from 1 GHz to 25 GHz are measured using the

- test procedure for radiated measurements as described in clause 5.4.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.5.3.4 Test results

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Pre-amplifier	Distance
			Prescan	Final scan	Prescan	Final scan		
1 GHz – 18 GHz	250 kHz	1 MHz	PK + AV	PK + AV	1.5 s	0.1 s	External	3.0 m

Note 1: The measurements from 1 GHz to 17 GHz are made at a measurement distance of 3.0 m.

Frequency range	Resolution bandwidth	Video bandwidth	Sweep time	Trace detector(s)	Trace mode(s)	Test	Pre-amplifier	Distance
18 GHz – 25 GHz	1 MHz	3 MHz	AUTO	Max Peak	Clear Write	Searching	20 dB	0.5 m

Note 2: The exploratory measurements from 18 GHz to 25 GHz are made at a measurement distance of 0.5 m. The limit lines for these tests are converted and calculated from the limit lines at a measurement distance of 3 m.

Remark: Premeasurements were carried out to find the worst case position of EUT and antenna.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1




Figure 10: Chart of radiated disturbance test 1 GHz – 18 GHz, with tag, EUT position 1, horizontal polarization of antenna

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Pol
2401.568000	88.96	---	74.00	-14.96	161.0	121.0	-15.8	H
2402.000000	---	40.40	54.00	13.60	161.0	121.0	-15.8	H
2426.000000	---	39.00	54.00	15.00	161.0	121.0	-15.8	H
2426.767000	87.37	---	74.00	-13.37	159.0	119.0	-15.8	H
2480.000000	---	36.66	54.00	17.34	161.0	121.0	-15.8	H
2480.948000	84.51	---	74.00	-10.51	157.0	118.0	-15.8	H
4803.068000	59.22	---	74.00	14.78	161.0	117.0	-7.9	H
4851.318000	58.00	---	74.00	16.00	159.0	116.0	-7.9	H
4960.318000	51.59	---	74.00	22.41	159.0	120.0	-7.6	H
17987.500000	---	48.27	54.00	5.73	161.0	121.0	17.4	H

Figure 11: Final results of radiated disturbance test 1 GHz – 18 GHz, with tag, EUT position 1, horizontal polarization of antenna

Note: Emissions at 2401.568 MHz, 2426.767 MHz and 2480.948 MHz are carrier frequencies the BLE part of the device, which have to be estimated under the limit of 15.247 and RSS-247.




Figure 12: Chart of radiated disturbance test 18 GHz – 25 GHZ – exploratory measurement- polarization vertical + horizontal

Remark: No assessable emissions could be detected.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

6.6 Band-edge compliance (radiated)

Section(s) in 47 CFR Part 15:	Requirement(s): Reference(s):	15.247(d) KDB 558074 D01, section 13
Section(s) in RSS:	Requirement(s): Reference(s):	RSS-247, section 5.5 ANSI C63.10, clause 6.10

Performed by:	Andreas Menacher	Date of test:	August 24, 2018
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

Remark: Result of band-edge compliance measurement was gained by using the result of the radiated emission measurement from 1 GHz to 18 GHz.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1




Figure 13: Chart of radiated emission – Band edge compliance

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
2401.568000	88.96	---	74.00	-14.96	161.0	H	121.0
2402.000000	---	40.40	54.00	13.60	161.0	H	121.0
2426.767000	87.37	---	74.00	-13.37	159.0	H	119.0
2426.000000	---	39.00	54.00	15.00	161.0	H	121.0
2480.948000	84.51	---	74.00	-10.51	157.0	H	118.0
2480.000000	---	36.66	54.00	17.34	161.0	H	121.0

Figure 14: Final results of radiated emission measurement – Band edge compliance

7 Equipment calibration status

Description	Modell number	Serial number	Inventory number(s)	Last calibration	Next calibration
EMI test receiver	ESR7	101059	E00739	2018-05	2019-05
EMI test receiver	ESCI 3	100328	E00552	2018-10	2019-10
EMI test receiver	ESW44	101538	E00895	2017-07	2018-07
Loop antenna	HFH2-Z2	871398/0050	E00060	2016-09	2018-09
Magnetic field probe	RF-R 400-1	02.2030	E00270	N/A (see note 3)	
TRILOG broadband antenna (SAC3)	VULB 9162	9162-041	E00643	2018-03	2021-03
Horn antenna	BBHA 9120D	9120D-592	W00052	2017-04	2020-04
Horn antenna	BBHA 9170	9170-331	W00055	2016-06	2019-06
Preamplifier (1 GHz - 18 GHz)	ALS05749	001	W01007	2017-10	2018-10
Preamplifier (18 GHz - 40 GHz)	BBV 9721	43	W01350	2017-11	2018-11
Compact diagnostic chamber (CDC)	VK041.0174	D62128-A502-A69-2-0006	E00026	N/A	
Semi-anechoic chamber (SAC)	SAC3	C62128-A520-A643-x-0006	E00716	2018-03	2021-03
Cable set CDC	RG214/U	---	E00446	2018-04	2019-04
	LCF12-50J	---	E01215	2018-04	2019-04
	LMR400	1718020006	E00920	2018-01	2019-01
	RG214 Hiflex	171802007	E00921	2018-01	2019-01
Cable set of semi-anechoic chamber SAC3	SF104EA/11PC35/11PC35/10000MM	501347/4EA	E00755	2017-12	2018-12
	SF104E/11PC35/11PC35/2000MM	507410/4E	E01033	2017-12	2018-12
	SF104E/11PC35/11PC35/2000MM	507411/4E	E01034	2017-09	2018-09

Note 1: Industry Canada (test sites number 3472A-1 and 3472A-2): 2018-11

Note 2: Expiration date of test firm accreditation for SAC:

FCC test firm type "accredited": 2019-05

Note 3: Used for relative measurements only (see test instruments for clause 6.1, 6.2 and 6.4)



8 Measurement uncertainties

Description	Uncertainty	k=
AC power line conducted emission	± 4.1 dB	2
Carrier frequency separation Number of hopping frequencies Time of occupancy (dwell time)	± 5.0 %	2
Bandwidth tests	± 2.0 %	
Maximum conducted output power (conducted)	± 1.5 dB	
Power spectral density (conducted)	± 2.9 dB	
Conducted spurious emissions	± 2.9 dB	
Radiated emissions in semi-anechoic chamber		
9 kHz to 30 MHz	± 4.8 dB	2
30 MHz to 300 MHz	± 5.4 dB	2
300MHz to 1 GHz	± 4.7 dB	2
Radiated emissions in semi-anechoic chamber with RF absorbing material on the floor or fully anechoic room		
1 GHz to 25 GHz	± 4.5 dB	2

Comment: The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k. For a confidence level of 95 % the coverage factor k is 2.

Test related measurement uncertainties have to be taken into consideration when evaluating the test results. All used test instrument as well as the test accessories are calibrated at regular intervals.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1

9 Revision history

<i>Revision</i>	<i>Date</i>	<i>Issued by</i>	<i>Description of modifications</i>
0	2018-09-13	Andreas Menacher	First edition



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Xylem Analytics Germany GmbH
RFID module
NFC-Module1