

YEONHWA M TECH CO.,LTD
36, Jeonpa-ro 44beon-gil Manan-gu, Gyeonggi-do,
Anyang-si, South Korea

September 4, 2025

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046

FCC ID: VSOXR-R1400
Model Number: XR-R1400, MDR-504

Dear Sir/Madam,

We, YEONHWA M TECH CO.,LTD, acknowledge that this device will not be marketed to USA users with the frequency band which is not allowed by rule part 90. and it is a violation of FCC rules if this device is operated on unauthorized frequencies inside the U.S.A.

This equipment meets the requirements of the FCC Rules, Parts 90.203(e) and (g), as applicable. Programming of this products transmit frequencies can be performed ONLY by the manufacturer or by service or by maintenance personal.

The operator can't program transmit frequencies using the equipment's external operation controls. This is to certify that the requirements of 47 CFR Part 90.203(j)(4) and (5) spectrum efficiency are met by the YEONHWA M TECH CO.,LTD as demonstrated by the tests conducted on the sample radio provided.

The tests show that the 4FSK data rate is in accordance with ETSI TS 102 361-1, that is 9600 bits per second in a 12.5 kHz bandwidth to satisfy the data rate requirement of 4800 bits per second per 6.25 kHz of channel bandwidth (7K62F1D emissions). Additionally the Repeater uses the AMBE+2 half-rate vocoder to compress 60 ms of normal bursts are sent in alternate 30 ms TDMA slots and so comply with the equivalence of one voice channel per 6.25 kHz bandwidth (7K74F1W emission). Additionally the radio also meets the requirement of one voice channel per 12.5kHz of channel bandwidth for analogue speech (10K0F3E emission).

Sincerely,



HWAN-DAE KIM
Vice President
Tel: 82-31-444-7270
Fax: 82-31-444-7271
Email: hdkim@xradio.co.kr